

Profile Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type	Sample No.	SPT Values (blows/6 in)	Cu (tsf)	Moisture Content (%)	Profile Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type	Sample No.	SPT Values (blows/6 in)	Cu (tsf)	Moisture Content (%)
879.44	5-inch thick ASPHALT over 5.6-inch CONCRETE --PAVEMENT--	0						879.44		0					
878.1	Very stiff to stiff, brown SANDY CLAY LOAM, trace gravel --FILL--	1	X	4	4	2.00	11	878.1		1	X	11	4	3.03	12
873.9	Medium stiff, black CLAY LOAM, trace organic matter	2	X	2	2	1.00	16	873.9		2	X	12	6	3.53	9
872.1	Very soft, brown SANDY CLAY LOAM	3	X	1	1	0.50	28	872.1		3	X	13	9	4.76	10
869.2	Loose, brown SANDY LOAM	4	X	1	1	<0.25	18	869.2		4	X	14	4	2.95	11
868.9	Hard, brown SILTY CLAY, trace gravel	5	X	1	1	NP	15	842.9	Very stiff, gray CLAY LOAM	5	X	15	5	2.25	15
864.2	Medium dense, brown SILT	6	X	3	3	4.26	11	839.4	Boring terminated at 40.00 ft	6	X	16	4	3.61	11
861.4	Very stiff to hard, brown SILTY CLAY, trace gravel	7	X	6	6	NP	15			7	X	17	4	4.35	12
		8	X	5	5	4.18	11			8	X	18	3	3.53	12
		9	X	5	5	3.94	11			9	X	19	5	3.77	11
		10	X	5	5	3.85	11			10	X	20	4	3.61	11

GENERAL NOTES			WATER LEVEL DATA		
Begin Drilling	11-25-2009	Complete Drilling	11-25-2009	While Drilling	9.00 ft
Drilling Contractor	WTS	Drill Rig	Mobile B-57 TMR	At Completion of Drilling	21.00 ft
Driller	K&J	Logger	F.Bozga	Time After Drilling	NA
Checked by	N. Davis	Depth to Water	NA	The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.	
Drilling Method	3.25 IDA HSA; 140# Mobile Automatic Hammer				

Profile Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type	Sample No.	SPT Values (blows/6 in)	Cu (tsf)	Moisture Content (%)	Profile Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type	Sample No.	SPT Values (blows/6 in)	Cu (tsf)	Moisture Content (%)
878.84	4.5-inch thick ASPHALT over 7.5-inch thick CONCRETE --PAVEMENT--	0						878.84		0					
878.1	Loose, brown SANDY LOAM, trace gravel --BASE COURSE--	1	X	5	5	NP	9	878.1		1	X	11	3	3.28	10
873.3	Loose, brown SAND, trace gravel --FILL--	2	X	2	2	NP	13	873.3		2	X	12	6	3.20	11
871.9	Soft, brown SANDY CLAY LOAM	3	X	2	2	0.25	16	871.9		3	X	13	5	3.20	11
867.8	Loose, brown GRAVELLY SAND	4	X	3	3	NP	13	867.8		4	X	14	4	1.48	11
842.3	Medium dense, brown SAND, trace gravel	5	X	5	5	2.25	15	842.3	Stiff, gray CLAY LOAM	5	X	15	4	1.48	11
839.4	Stiff to hard, brown SILTY CLAY, trace gravel	6	X	2	2	2.25	13	839.4	Boring terminated at 40.00 ft	6	X	16	4	3.61	11
		7	X	4	4	4.35	12			7	X	17	4	4.35	12
		8	X	3	3	3.53	12			8	X	18	3	3.53	12
		9	X	5	5	3.77	11			9	X	19	5	3.77	11
		10	X	4	4	3.61	11			10	X	20	4	3.61	11

GENERAL NOTES			WATER LEVEL DATA		
Begin Drilling	11-25-2009	Complete Drilling	11-25-2009	While Drilling	8.50 ft
Drilling Contractor	WTS	Drill Rig	Mobile B-57 TMR	At Completion of Drilling	10.00 ft
Driller	K&J	Logger	F.Bozga	Time After Drilling	NA
Checked by	N. Davis	Depth to Water	NA	The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.	
Drilling Method	3.25 IDA HSA; 140# Mobile Automatic Hammer				

FILE NAME = 95-Project\2102155_0023\road\structure\0560276_60M53_002_Borings.dgn