

PAVEMENT/SHOULDERS												
LOCATION			31100500	35101500	40600100	40601005	42400200	42400800	44000600	44002200E	44201833	48101202
			SUBBASE GRANULAR MATERIAL, TYPE B, 6"	AGGREGATE BASE COURSE, TYPE B	BITUMINOUS MATERIALS (PRIME COAT)	HOT-MIX ASPHALT REPLACEMENT OVER PATCHES	PORTLAND CEMENT CONCRETE SIDEWALK, 5 INCH	DETECTABLE WARNINGS	SIDEWALK REMOVAL	HOT-MIX ASPHALT REMOVAL OVER PATCHES, 1 1/2"	CLASS D PATCHES, TYPE IV, 15 INCH	AGGREGATE SHOULDERS, TYPE B
			SQ YD	CU YD	GALLON	TON	SQ FT	SQ FT	SQ FT	SQ YD	SQ YD	CU YD
STA. 19+55 TO STA. 20+44	JOLIET	RT/LT	720		504	61				720	720	
STA. 58+02 TO STA. 58+11	WILSON	RT		61			549		549			
STA. 58+08 TO STA. 58+10	WILSON	RT						8				
STA. 58+11 TO STA. 58+39	WILSON	RT										
STA. 20+25 TO STA. 20+66	JOLIET	LT										2
STA. 19+35 TO STA. 19+60	JOLIET	RT										3
TOTAL			720	61	504	61	549	8	549	720	720	5

GUARDRAIL			
LOCATION			63000025
			STEEL PLATE BEAM GUARDRAIL, ATTACHED TO STRUCTURES
			FOOT
STA. 19+40 TO STA. 19+58	JOLIET	RT	25
STA. 20+39 TO STA. 20+57	JOLIET	LT	25
TOTAL			50

LANDSCAPING/EROSION CONTROL											
LOCATION			20101400	20101500	20101600	21101505	25000110	25000312	25100115	25100630	28000400
			NITROGEN FERTILIZER NUTRIENT	PHOSPHORUS FERTILIZER NUTRIENT	POTASSIUM FERTILIZER NUTRIENT	TOPSOIL EXCAVATION AND PLACEMENT	SEEDING, CLASS 1A	SEEDING, CLASS 4A	MULCH, METHOD 2	EROSION CONTROL BLANKET	PERIMETER EROSION BARRIER
			POUND	POUND	POUND	CU YD	ACRE	ACRE	ACRE	SQ YD	FOOT
STA. 19+10 TO STA. 19+76	JOLIET	RT	23	23	23	15.9	0.032	0.007	0.032	32.8	69
STA. 20+56 TO STA. 20+85	JOLIET	LT	23	23	23	22.8	0.023	0.01	0.023	49.6	86
TOTAL			45	45	45	38.7	0.055	0.017	0.055	82.4	155
ROUNDED TOTAL			45	45	45	39	0.25	0.25	0.25	83	155

78000200			
LOCATION			THERMOPLASTIC PAVEMENT MARKING - LINE
			FOOT
STA. 57+84 TO STA. 58+22	JOLIET	RT	61
STA. 57+02 TO STA. 57+38	JOLIET	LT	79
STA. 19+90 TO STA. 20+75	JOLIET	RT	120
TOTAL			260

IDOT DISTRICT ONE

HOT-MIX ASPHALT MIXTURE REQUIREMENTS

MIXTURE TYPE	AIR VOIDS @ NDES
PATCHING	
CLASS D PATCHES (HMA BINDER IL-19.0MM), 15" (IN 5 LIFTS)	4% @ 70 GYR
HMA REPLACEMENT OVER PATCHES (HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70, (IL-9.5MM); 1.5")	4% @ 70 GYR

NOTES:

THE UNIT WEIGHT USED TO CALCULATE HOT-MIX ASPHALT SURFACE MIXTURES IS 112 LBS/SQ YD/IN

THE "AC TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 70-22" AND FOR NON-POLYMERIZED HMA THE "AC TYPE" SHALL BE "PG 64-22" UNLESS MODIFIED BY DISTRICT ONE SPECIAL PROVISIONS FOR "PERCENT OF RAP" SEE DISTRICT SPECIAL PROVISIONS. (BMPR)


BITUMINOUS MATERIALS (PRIME COAT) APPLICATION RATES

SURFACE TYPE	APPLICATION RATE (GAL/SQ YD)
HOT-MIX ASPHALT SURFACE & BINDER COURSES	0.05
AGGREGATE SUBGRADE	0.25

NOTES:

THE UNIT VOLUME USED TO CALCULATE BITUMINOUS MATERIALS (PRIME COAT) QUANTITIES WAS THE MAXIMUM APPLICATION RATES SHOWN.

FILE NAME = S:\JOLI\62200-62391\62353\016\MicroStation\Sheets\DI-ahh-schedule.dgn



USER NAME = brianf	DESIGNED - -	REVISED -
PLOT SCALE = 50.0000' / IN.	DRAWN - -	REVISED -
PLOT DATE = 2/19/2007	CHECKED - -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SCHEDULE OF QUANTITIES

F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
2534	02-00068-00-BR	DUPAGE	15	3
CONTRACT NO. 63561				