



SOIL BORING LOG

Page 1 of 1 Date 1/24/05

Table with columns for depth, soil type, and test results. Includes data for boring B47-1 at 47th Street.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by @-Blows, S-Shear, P-Penetrometer. The SPT (N) value is the sum of the last two blow values in each sampling zone (ASTM D 1586).

BBS, from 137 Rev. 8-99



SOIL BORING LOG

Page 1 of 1 Date 1/24/05

Table with columns for depth, soil type, and test results. Includes data for boring B47-3 at 47th Street.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by @-Blows, S-Shear, P-Penetrometer. The SPT (N) value is the sum of the last two blow values in each sampling zone (ASTM D 1586).

BBS, from 137 Rev. 8-99



SOIL BORING LOG

Page 1 of 1 Date 1/25/05

Table with columns for depth, soil type, and test results. Includes data for boring B47-5 at 47th Street.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by @-Blows, S-Shear, P-Penetrometer. The SPT (N) value is the sum of the last two blow values in each sampling zone (ASTM D 1586).

BBS, from 137 Rev. 8-99



SOIL BORING LOG

Page 1 of 1 Date 1/25/05

Table with columns for depth, soil type, and test results. Includes data for boring B47-7 at 47th Street.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by @-Blows, S-Shear, P-Penetrometer. The SPT (N) value is the sum of the last two blow values in each sampling zone (ASTM D 1586).

BBS, from 137 Rev. 8-99



SOIL BORING LOG

Page 1 of 1 Date 1/25/05

Table with columns for depth, soil type, and test results. Includes data for boring B35-2 at 35th Street.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by @-Blows, S-Shear, P-Penetrometer. The SPT (N) value is the sum of the last two blow values in each sampling zone (ASTM D 1586).

BBS, from 137 Rev. 8-99



SOIL BORING LOG

Page 1 of 1 Date 1/25/05

Table with columns for depth, soil type, and test results. Includes data for boring B35-4 at 35th Street.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by @-Blows, S-Shear, P-Penetrometer. The SPT (N) value is the sum of the last two blow values in each sampling zone (ASTM D 1586).

BBS, from 137 Rev. 8-99

Summary table with columns: F.A.I. RTE., SECTION, COUNTY, TOTAL SHEETS, SHEET NO., STA., TO STA., FED. ROAD DIST. NO. 1, ILLINOIS FED. AID PROJECT, 1818, ETC. 2324.6-1P1R-8, 62300.

ADDED SHEET SB-07 logo with CTE and AECOM branding.

REVISIONS table with columns: NAME, DATE. Includes entry: ADDENDUM #2, 9-16-05.

ILLINOIS DEPARTMENT OF TRANSPORTATION F.A.I. 90/94 (DAN RYAN EXPRESSWAY) 71ST STREET TO 31ST STREET (NB EXPRESS LANES) SCALE: NONE DRAWN BY: LAM DATE: September 16, 2005 CHECKED BY: JAL

Vertical text on the right margin: F:\94065\CTE\71-31\SOIL BORING\04\SB14002A.SW 9/16/2005 9:26:28 AM