



SOIL BORING LOG

Page 1 of 1

Date 6/24/05

Table with columns for SOIL BORING LOG, including ROUTE, SECTION, COUNTY, and SOIL BORING LOG data with various soil types and elevations.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by @-Bulge, S-Shear, P-Penetrometer. The SPT (N) value is the sum of the last two blow values in each sampling zone (MSD10 T286) BBS, Form 137 (Rev. 8-99)



SOIL BORING LOG

Page 1 of 1

Date 6/24/05

Table with columns for SOIL BORING LOG, including ROUTE, SECTION, COUNTY, and SOIL BORING LOG data with various soil types and elevations.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by @-Bulge, S-Shear, P-Penetrometer. The SPT (N) value is the sum of the last two blow values in each sampling zone (MSD10 T286) BBS, Form 137 (Rev. 8-99)



SOIL BORING LOG

Page 1 of 1

Date 6/24/05

Table with columns for SOIL BORING LOG, including ROUTE, SECTION, COUNTY, and SOIL BORING LOG data with various soil types and elevations.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by @-Bulge, S-Shear, P-Penetrometer. The SPT (N) value is the sum of the last two blow values in each sampling zone (MSD10 T286) BBS, Form 137 (Rev. 8-99)



SOIL BORING LOG

Page 1 of 1

Date 6/23/05

Table with columns for SOIL BORING LOG, including ROUTE, SECTION, COUNTY, and SOIL BORING LOG data with various soil types and elevations.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by @-Bulge, S-Shear, P-Penetrometer. The SPT (N) value is the sum of the last two blow values in each sampling zone (MSD10 T286) BBS, Form 137 (Rev. 8-99)



SOIL BORING LOG

Page 1 of 1

Date 6/23/05

Table with columns for SOIL BORING LOG, including ROUTE, SECTION, COUNTY, and SOIL BORING LOG data with various soil types and elevations.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by @-Bulge, S-Shear, P-Penetrometer. The SPT (N) value is the sum of the last two blow values in each sampling zone (MSD10 T286) BBS, Form 137 (Rev. 8-99)



SOIL BORING LOG

Page 1 of 1

Date 6/23/05

Table with columns for SOIL BORING LOG, including ROUTE, SECTION, COUNTY, and SOIL BORING LOG data with various soil types and elevations.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by @-Bulge, S-Shear, P-Penetrometer. The SPT (N) value is the sum of the last two blow values in each sampling zone (MSD10 T286) BBS, Form 137 (Rev. 8-99)

Table with columns: F.A.I. INTL., SECTION, COUNTY, TOTAL SHEETS, SHEET NO., STA., TO STA., FED. ROAD DIST. NO., ILLINOIS FED. AID PROJECT, 62302



Table with columns: REVISIONS (NAME, DATE), ILLINOIS DEPARTMENT OF TRANSPORTATION (F.A.I. 90/94 DAN RYAN EXPRESSWAY), 71ST STREET TO 31ST STREET (SB EXPRESS LANES), SOIL BORING LOGS, SCALE: NONE, DRAWN BY: PHP, CHECKED BY: JAL, DATE: September 16, 2005