



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

November 3, 2010

SUBJECT: FAS Route 1279 (IL 178)
Project ACRS-ACTE-1279 (111)
Section 6R, B
LaSalle County
Contract No. 66547
Item No. 53, November 5, 2010 Letting
Addendum B

NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

1. Revised page iii of the Table of Contents to the Special Provisions.
2. Added pages 193 - 194 to the Special Provisions.

Prime contractors must utilize the enclosed material when preparing their bid and must include any Schedule of Prices changes in their bidding proposal.

Bidders using computer-generated bids are cautioned to reflect any and all Schedule of Prices changes, if involved, into their computer programs.

Very truly yours,

Scott E. Stitt, P.E.
Acting Engineer of Design and Environment

A handwritten signature in black ink, appearing to read 'Ted B. Walschleger P.E.'.

By: Ted B. Walschleger, P. E.
Engineer of Project Management

cc: George F. Ryan, Region 2, District 3; Mike Renner; Estimates

TBW:DB:jc

FLAGGER AT SIDE ROADS AND ENTRANCES (BDE) 105

FRAMES AND GRATES (BDE) 105

HOT-MIX ASPHALT – ANTI-STRIPPING ADDITIVE (BDE) 106

HOT-MIX ASPHALT – DROP-OFFS (BDE) 106

HOT-MIX ASPHALT - FINE AGGREGATE (BDE) 106

HOT-MIX ASPHALT – PLANT TEST FREQUENCY (BDE) 107

HOT-MIX ASPHALT – QC/QA ACCEPTANCE CRITERIA (BDE) 108

HOT-MIX ASPHALT – TRANSPORTATION (BDE) 108

LIQUIDATED DAMAGES (BDE) 109

METAL HARDWARE CAST INTO CONCRETE (BDE) 109

MULCH (BDE) 110

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM / EROSION AND SEDIMENT CONTROL DEFICIENCY DEDUCTION (BDE) 112

PAVEMENT MARKING REMOVAL (BDE) 113

PAVEMENT PATCHING (BDE) 113

PAYMENTS TO SUBCONTRACTORS (BDE) 114

PERSONAL PROTECTIVE EQUIPMENT (BDE) 115

PRECAST CONCRETE HANDLING HOLES (BDE) 115

PRISMATIC CURB REFLECTORS (BDE) 116

RAISED REFLECTIVE PAVEMENT MARKERS (BDE) 117

RECLAIMED ASPHALT PAVEMENT (RAP) (BDE) 117

REFLECTIVE SHEETING ON CHANNELIZING DEVICES (BDE) 124

REINFORCEMENT BARS - STORAGE AND PROTECTION (BDE) 124

SEEDING (BDE) 125

SELF-CONSOLIDATING CONCRETE FOR CAST-IN-PLACE CONSTRUCTION (BDE) 127

SELF-CONSOLIDATING CONCRETE FOR PRECAST PRODUCTS (BDE) 131

SUBCONTRACTOR MOBILIZATION PAYMENTS (BDE) 132

TEMPORARY EROSION CONTROL (BDE) 133

BITUMINOUS MATERIALS COST ADJUSTMENTS (BDE) (RETURN FORM WITH BID) 134

FUEL COST ADJUSTMENT (BDE) (RETURN FORM WITH BID) 137

STEEL COST ADJUSTMENT (BDE) (RETURN FORM WITH BID) 141

STORM WATER POLLUTION PREVENTION PLAN 145

404 PERMIT 154

NATIONWIDE PERMITS AND CONDITIONS 158

IEPA REGIONAL CONDITIONS 171

IDNR PERMIT 189

NON-SPECIAL WASTE WORKING CONDITIONS 193

NON-SPECIAL WASTE WORKING CONDITIONS

NON-SPECIAL WASTE WORKING CONDITIONS

This work shall be according to Article 669 of the Standard Specifications for Road and Bridge Construction adopted January 1, 2002 and the following:

Revise Article 669.01 of the Standard Specifications to read:

" 669.01 Description. This work shall consist of the excavation, removal, and proper disposal of contaminated soil, water, and underground storage tanks (UST), their content, and associated underground piping to the point where the piping is above the ground, including determining the content types and estimated quantities."

Qualifications. The term environmental firm shall mean an environmental firm with at least five (5) documented leaking underground storage tank (LUST) cleanups or that is pre-qualified in hazardous waste by the Department. Documentation includes but not limited to verifying remediation and special waste operations for sites contaminated with gasoline, diesel, or waste oil in accordance with all Federal, State, or local regulatory requirements and shall be provided to the Engineer for approval. The environmental firm selected shall not be a former or current consultant or have any ties with any of the properties contained within and/or adjacent to this construction project.

General. Implementation of this Special Provision will likely require the Contractor to subcontract for the execution of certain activities. It will be the Contractor's responsibility to assess the working conditions and adjust anticipated production rates accordingly.

The Contractor shall manage all contaminated materials as non-special waste as previously identified. This work shall include monitoring and potential sampling, analytical testing, and management of petroleum contaminated material. During the PSI an Underground Storage Tank (UST) was discovered between Station 18+10 and Station 18+70, 0 to 40 feet offset RT.

The Contractor shall excavate and dispose of any soil classified as a non-special waste or groundwater classified as a special waste as directed by this project or the Engineer. Any excavation or disposal beyond what is required by this project or the Engineer shall be at the Contractor's expense. The preliminary site investigation (PSI) report, available through the District's Environmental Studies Unit, estimated the excavation quantity of non-special waste at the following location. The information available at the time of plan preparation determined the limits of the contamination and the quantities estimated were based on soil and or groundwater excavation for construction purposes only. The lateral distance is measured from centerline and the farthest distance is the offset distance or construction limit which ever is less. The Environmental Firm shall continuously monitor for worker protection and the Contractor shall manage and dispose of all soils excavated within the following areas as classified below. Any soil samples or analysis without the approval of the Engineer shall be at the Contractor's expense.

1. Station 176+70 to Station 177+80 0 to 80 feet LT and RT (Morrissy Residence Property, Site 1544-1/1544A-6, 230 Canal Street). Contaminants of concern sampling parameters: PNAs and Arsenic.
2. Station 177+80 to Station 179+00 0 to 80 feet LT and RT (Village of Utica Parking Lot, Site 1544A-8, southwest corner of Canal Street and IL 178). Contaminants of concern sampling parameters: PNAs and TCLP Lead.

Backfill pugs shall be place within the following locations.

1. Station 43+00 to Station 44+80 0 to 40 feet) RT (SBC, Site 1544A-5, 221 Church Street) – non-special waste. Contaminants of concern sampling parameters: BETX, SVOCs, and Lead.
2. Station 43+90 to Station 44+20 0 to 30 feet LT (Vacant Lot #7, Site 1544A-3, 224 Church Street) – non-special waste. Contaminants of concern sampling parameters: BETX, SVOCs, and Lead.

Revise the first paragraph of Article 669.15 of the Standard Specifications to read:

^^ 669.15 Method of Measurement. Non-special waste, special waste, and hazardous waste soil disposal will be measured for payment according to either Article 202.07(b) when performing earth excavation, Article 502.14(b) when excavating for structures, or by computing the volume of the trench using the maximum trench width permitted and the actual depth of the trench.”

Revise the second paragraph of Article 669.16 of the Standard Specifications to read:

^^ The excavation, transportation, and disposal of soil and other materials from an excavation determined to be contaminated will be paid for at the contract unit price per cubic yard (cubic meter) for NON-SPECIAL WASTE DISPOSAL, SPECIAL WASTE DISPOSAL, or HAZARDOUS WASTE DISPOSAL.”