

CULVERT AND STORM SEWER SCHEDULE

LOCATION	TYPE	PIPE CULVERT REMOVAL	STORM SEWER, RUBBER GASKET, CLASS A			RESTRICTED DEPTH MANHOLES, 5' DIAMETER		INLETS, TYPE B, TYPE 8 GRATE	REMOVING MANHOLES	TRENCH BACKFILL	REINFORCED CONCRETE PIPE TEE, 18" PIPE WITH 12" RISER
			TYPE 1, 36"	TYPE 2, 12"	TYPE 2, 18"	TYPE 1 FRAME, OPEN LID	TYPE 8 GRATE				
		FOOT	FOOT	FOOT	FOOT	EACH	EACH	EACH	EACH	CU YD	EACH
ITEP SHARED-USE FACILITY											
STA 11+23.66	LT 20.28'	TO STA 12+23.57	LT 8.64'	RCP	99.44						
STA 13+60.37	LT 5.96'	TO STA 13+75.32	LT 6.95'	RCP	14.98						
STA 11+23.70	LT 19.30'	TO STA 12+10.00	LT 13.27'			85.42					
STA 12+10.00	LT 13.27'	TO STA 13+27.13	LT 10.70'			117.93					
STA 13+74.97	LT 11.95'	TO STA 13+75.32	LT 6.95'								
STA 13+75.32	LT 6.95'	TO STA 13+52.98	LT 5.44'								
STA 11+23.70	LT 19.30'										
STA 12+10.00	LT 13.27'						1				
STA 13+74.97	LT 11.95'							1			
STA 13+75.32	LT 6.95'									1	
STA 11+23.67	LT 20.29'								1		
STA 13+55.95	LT 5.64'	TO STA 13+75.32	LT 6.95'							24.30	
STA 13+75.11	LT 9.96'	TO STA 13+75.32	LT 6.95'							5.90	
TOTAL					114.42	203.35	5.01	16.39	1	1	1
USE					115	204	6	17	1	1	1
										30.2	
										31	

DITCH SCHEDULE

LOCATION	DITCH ELEVATION
FEET	
ITEP SHARED-USE FACILITY	
TRAPEZOIDAL DITCH WITH 2' BTM	
STA 11+25.00 20.29' LT	441.79
STA 11+50.00 11.97' LT	441.50
STA 11+75.00 13.58' LT	441.33
STA 12+00.00 14.52' LT	441.03
STA 12+10.00 13.27' LT	440.94
TRAPEZOIDAL DITCH WITH 2' BTM	
STA 13+40.00 11.08' LT	442.74
STA 13+25.00 10.38' LT	442.59
STA 13+00.00 10.83' LT	441.86
STA 12+75.00 10.93' LT	441.68
STA 12+50.00 11.94' LT	441.42
STA 12+25.00 13.57' LT	441.12
STA 12+10.00 13.27' LT	440.94
TRAPEZOIDAL DITCH WITH 2' BTM	
STA 13+50.00 11.55' LT	442.42
STA 13+74.98 12.45' LT	441.62
TRAPEZOIDAL DITCH WITH 2' BTM	
STA 15+75.00 16.82' LT	443.36
STA 15+50.00 16.18' LT	443.12
STA 15+25.00 14.47' LT	443.00
STA 15+00.00 12.80' LT	442.87
STA 14+75.00 12.99' LT	442.62
STA 14+50.00 11.15' LT	442.37
STA 14+25.00 9.69' LT	442.09
STA 14+00.00 10.77' LT	441.88
STA 13+74.98 12.45' LT	441.62

PAVING SCHEDULE

LOCATION	COMBINATION CURB AND GUTTER REMOVAL	COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.24	GUTTER REMOVAL	CONCRETE GUTTER	DETECTABLE WARNINGS	PAINT PAVEMENT MARKING, LINE 12"	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH	PROTECTIVE COAT
ITEP SHARED-USE FACILITY								
RT 10+77.77	8.00'	TO LT 10+75.55	8.00'					
RT 11+08.13	8.00'	TO LT 11+08.58	8.00'		16.18	16.18		9.67
LT 11+11.80	17.43'	TO LT 11+22.26	19.47'		16.19	16.19		
LT 17+88.01	13.00'	TO RT 17+68.52	13.00'	33.46	10.66	10.66		11.17
STA 10+71.37	TO STA 12+00.00						785.28	87.25
STA 12+00.00	TO STA 13+00.00						800.00	88.89
STA 13+00.00	TO STA 14+00.00						985.76	109.53
STA 14+00.00	TO STA 15+00.00						800.00	88.89
STA 15+00.00	TO STA 16+00.00						800.00	88.89
STA 16+00.00	TO STA 17+00.00						800.00	88.89
STA 17+00.00	TO STA 17+82.18						649.56	72.17
RT STA 10+73.23						4.0		
LT STA 11+10.99						4.0		
RT STA 17+76.32						4.0		
LT STA 10+78.43	TO STA 11+05.92					27.5		
RT STA 10+79.39	TO STA 11+05.67					26.3		
STA 10+75.13						15.00		
STA 11+09.04						15.00		
STA 17+77.42						15.00		
TOTAL	33.46	33.46	43.03	43.03	45.00	65.8	5,620.60	645.35
USE	33.5	33.5	43.5	43.5	45	66	5,621	646

EXTRA BARS FOR TEST SAMPLES

BAR	NO.	SIZE	LENGTH	SHAPE
+ (E)	1	#4	7'-5"	—
v ₃ (E)	1	#5	8'-3"	—
n (E)	1	#6	5'-7"	—
a ₁ (E)	1	#7	12'-0"	—
h ₁₁ (E)	1	#8	25'-0"	—
TOTAL WEIGHT				120 lb.

NOTES:

THESE BARS SHALL BE IDENTICAL TO AND DELIVERED WITH THE BARS OF THE SAME MARK LISTED IN THE STRUCTURE SHEETS. ONE BAR OF EACH OF THESE MARKS WILL BE SELECTED BY THE ENGINEER TO BE USED AS A TEST SAMPLE.

THIS CHART ASSUMES THAT ALL BARS OF THE SAME SIZE ON THE JOB WILL HAVE THE SAME HEAT NUMBER. IF BARS OF THE SAME SIZE ON THE JOB HAVE DIFFERENT HEAT NUMBERS, THEN THE CONTRACTOR SHALL SUPPLY ADDITIONAL BARS FROM OTHER HEAT NUMBERS FOR SAMPLING BY THE ENGINEER AT NO ADDITIONAL COST.