

SUMMARY OF QUANTITIES					PAVEMENT	
S.I.	CODE NO.	PAY ITEM	UNIT	QUAN	CONSTRUCTION TYPE CODE	
					1000	
	40600100	BITUMINOUS MATERIALS (PRIME COAT)	GALLON	1400	1400	
	40600300	AGGREGATE (PRIME COAT)	TON	42	42	
	40600895	CONSTRUCTING TEST STRIP	EACH	1	1	
	40600982	HOT-MIX ASPHALT SURFACE REMOVAL -- BUTT JOINT	SQ YD	580	580	
	40603310	HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50	TON	1171	1171	
	44000155	HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"	SQ YD	13350	13350	
	48102100	AGGREGATE WEDGE SHOULDER, TYPE B	TON	368	368	
	60255500	MANHOLES TO BE ADJUSTED	EACH	1	1	
	67100100	MOBILIZATION	L SUM	1	1	
	70101800	TRAFFIC CONTROL AND PROTECTION, (SPECIAL)	L SUM	1	1	
*	70300100	SHORT TERM PAVEMENT MARKING	FOOT	2000	2000	
*	78000200	THERMOPLASTIC PAVEMENT MARKING -- LINE 4"	FOOT	14332	14332	
*	78000600	THERMOPLASTIC PAVEMENT MARKING -- LINE 12"	FOOT	140	140	
*	78000650	THERMOPLASTIC PAVEMENT MARKING -- LINE 24"	FOOT	135	135	
*	78300200	RAISED REFLECTIVE PAVEMENT MARKER REMOVAL	EACH	62	62	
	X4067107	POLYMERIZED LEVELING BINDER (MACHINE METHOD), IL-4.75, N50	TON	536	536	
	X4420452	CLASS D PATCHES, TYPE II, 4 INCH	SQ YD	30	30	
	X4420454	CLASS D PATCHES, TYPE III, 4 INCH	SQ YD	200	200	
	X4420456	CLASS D PATCHES, TYPE IV, 4 INCH	SQ YD	320	320	

* SPECIALTY ITEMS

- BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "J.U.L.I.E." AT (800) 892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS UTILITIES. (48 HOUR NOTIFICATION IS REQUIRED).
- UTILITIES INDICATED ON THE PLANS ARE PROVIDED FOR THE CONTRACTORS USE AND ARE BASED UPON INFORMATION AVAILABLE AT THE TIME OF THE ADVERTISEMENT FOR BIDS. THE OWNER AND ENGINEER DO NOT GUARANTEE THE ACCURACY OF UTILITIES INFORMATION.
- IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS.
- EXACT LOCATIONS FOR PATCHING SHALL BE DETERMINED IN THE FIELD BY THE ENGINEER.
- ANY REFERENCE TO STANDARDS THROUGHOUT THE PLANS OR SPECIAL PROVISIONS SHALL BE INTERPRETED TO BE THE LATEST STANDARDS OF THE ILLINOIS DEPARTMENT OF TRANSPORTATION.
- THE THICKNESS OF HOT-MIX ASPHALT MIXTURE STATED IN THE SPECIFICATIONS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE HOT-MIX ASPHALT SURFACE IS PLACED.

* - INDICATES SPECIALTY ITEMS

FILE NAME = 09267-QUAN-01 - 001	USER NAME =	DESIGNED -- HLG/TG	REVISED --	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	SAUK TRAIL RESURFACING 80TH AVENUE TO HARLEM AVENUE SUMMARY OF QUANTITIES		F.A.U. RTE. 3753	SECTION 09-00041-00-RS	COUNTY WILL	TOTAL SHEETS 8	SHEET NO. 2	
	PLOT SCALE =	DRAWN -- RG/LTL	REVISED --		SCALE: NONE	SHEET NO. 2 OF 8 SHEETS	STA. TO STA.	CONTRACT NO. 63247				
	PLOT DATE = 07-27-09	CHECKED --	REVISED --		FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT ARA-9003-(363)							