

SUMMARY OF QUANTITIES					PAVEMENT	MARKINGS	LANDSCAPE
S.I.	CODE NO.	PAY ITEM	UNIT	QUAN	CONSTRUCTION TYPE CODE		
					1000	SFTY-1D	Y003
	20101700	SUPPLEMENTAL WATERING	UNIT	4			4
	20200100	EARTH EXCAVATION	CU YD	73	73		
	20800150	TRENCH BACKFILL	CU YD	8	8		
	21101615	TOPSOIL, FURNISH AND PLACE, 4"	SQ YD	121			121
	25000400	NITROGEN FERTILIZER NUTRIENTS	POUND	2			2
	25000500	PHOSPHORUS FERTILIZER NUTRIENTS	POUND	2			2
	25000600	POTASSIUM FERTILIZER NUTRIENTS	POUND	2			2
	25200110	SODDING, SALT TOLERANT	SQ YD	121			121
	40201000	AGGREGATE FOR TEMPORARY ACCESS	TON	100	100		
	40600100	BITUMINOUS MATERIALS (PRIME COAT)	GALLON	5565	5565		
	40600300	AGGREGATE (PRIME COAT)	TON	25	25		
	40600625	LEVELING BINDER (MACHINE METHOD), N50	TON	1168	1168		
	40600982	HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT	SQ YD	152	152		
	40603335	HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50	TON	2407	2407		
	42300300	PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT, 7 INCH	SQ YD	156	156		
	42400200	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH	SQ FT	537	537		
	42400800	DETECTABLE WARNINGS	SQ FT	24	24		
	44000156	HOT-MIX ASPHALT SURFACE REMOVAL, 1 3/4"	SQ YD	26387	26387		
	44000200	DRIVEWAY PAVEMENT REMOVAL	SQ YD	473	473		
	44000300	CURB REMOVAL	FOOT	31	31		
	44000500	COMBINATION CURB AND GUTTER REMOVAL	FOOT	576	576		
	44000600	SIDEWALK REMOVAL	SQ FT	537	537		
	44001700	COMBINATION CURB AND GUTTER REMOVAL AND REPLACEMENT	FOOT	3525	3525		
	44002020	CONCRETE MEDIAN SURFACE REMOVAL	SQ FT	1180	1180		
	44201725	CLASS D PATCHES, TYPE I, 7 INCHES	SQ YD	199	199		
	44201729	CLASS D PATCHES, TYPE II, 7 INCH	SQ YD	125	125		
	44201733	CLASS D PATCHES, TYPE III, 7 INCH	SQ YD	47	47		
	44201735	CLASS D PATCHES, TYPE IV, 7 INCH	SQ YD	1003	1003		
	44201759	CLASS D PATCHES, TYPE IV, 9 INCH	SQ YD	1436	1436		
	550A0330	STORM SEWERS, CLASS A, TYPE 2 10"	FOOT	14	14		
	550A0340	STORM SEWERS, CLASS A, TYPE 2 12"	FOOT	7	7		
	60202705	CATCH BASINS, TYPE A, 4'-DIAMETER, WITH SALVAGED FRAME AND GRATE	EACH	2	2		
	60250200	CATCH BASINS TO BE ADJUSTED	EACH	15	15		
	60252800	CATCH BASINS TO BE RECONSTRUCTED	EACH	3	3		
	60255500	MANHOLES TO BE ADJUSTED	EACH	1	1		
	60300310	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)	EACH	6	6		
	60500050	REMOVING CATCH BASINS	EACH	2	2		
	60619200	CONCRETE MEDIAN, TYPE SB-6.06	SQ FT	1180	1180		
	67100100	MOBILIZATION	L SUM	1	1		
	70101700	TRAFFIC CONTROL AND PROTECTION	L SUM	1	1		
	70300100	SHORT-TERM PAVEMENT MARKING	FOOT	2904		2904	
*	78000200	THERMOPLASTIC PAVEMENT MARKING - LINE 4"	FOOT	12754		12754	
*	78000600	THERMOPLASTIC PAVEMENT MARKING - LINE 12"	FOOT	15		15	
*	78000650	THERMOPLASTIC PAVEMENT MARKING - LINE 24"	FOOT	89		89	
*	78100100	RAISED REFLECTIVE PAVEMENT MARKER	EACH	400		400	
*	88600600	DETECTOR LOOP REPLACEMENT	FOOT	160	160		
	X0325702	NIGHTTIME WORK ZONE LIGHTING	L SUM	1	1		
	X4400220	CURB REMOVAL AND REPLACEMENT	FOOT	79	79		
	XX006806	HOT-MIX ASPHALT DRIVEWAY PAVEMENT	SQ YD	296	296		

**GENERAL NOTES:**

- BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "J.U.L.I.E." AT (800) 892-0123 AND (312) 744-7000 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS UTILITIES. (48 HOUR NOTIFICATION IS REQUIRED).
- UTILITIES INDICATED ON THE PLANS ARE PROVIDED FOR THE CONTRACTORS USE AND ARE BASED UPON INFORMATION AVAILABLE AT THE TIME OF THE ADVERTISEMENT FOR BIDS. THE OWNER AND ENGINEER DO NOT GUARANTEE THE ACCURACY OF UTILITIES INFORMATION.
- IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS.
- SCHEDULES INCLUDED IN THE PLANS HAVE BEEN PREPARED FROM FIELD NOTES. EXACT LOCATIONS FOR PATCHING SHALL BE DETERMINED IN THE FIELD BY THE ENGINEER.
- ANY REFERENCE TO STANDARDS THROUGHOUT THE PLANS OR SPECIAL PROVISIONS SHALL BE INTERPRETED TO BE THE LATEST STANDARDS OF THE ILLINOIS DEPARTMENT OF TRANSPORTATION.
- THE THICKNESS OF HMA MIXTURE STATED IN THE SPECIFICATIONS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE HMA SURFACE IS PLACED.
- ACCESS TO DRIVEWAYS SHALL BE MAINTAINED AT ALL TIMES BY LIMITING CURB AND GUTTER REPAIR TO ONE-HALF THE DRIVEWAY WIDTH AT ONE TIME AS WELL AS TEMPORARY AGGREGATE.

\* - INDICATES SPECIALTY ITEMS

FILE NAME = 08214-QUAN-01 - P01	USER NAME =	DESIGNED -- TRL	REVISIONS --	<b>STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION</b>	76TH AVENUE STREET RESURFACING 95TH STREET(FAP 29) TO 103RD STREET(FAU 1573) SUMMARY OF QUANTITIES AND GENERAL NOTES			F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.		
		CHECKED -- TRL	REVISIONS --		SCALE: NONE	SHEET NO. 2	OF 15 SHEETS	STA.	TO STA.	1029	09-00058-00-RS	COOK	15	2
	PLOT SCALE =	DRAWN -- PS	REVISIONS --		CONTRACT NO. 63259									
	PLOT DATE = 7/17/09	CHECKED -- AG	REVISIONS --		FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT M-9003 (339)									