

## **SOIL BORING LOG**

Page <u>1</u> of <u>1</u>

Date	3/22/10
------	---------

ROUTE FA 308	_ DESC	RIPTIO	P92 N	-057-0	8 Bridge over Apple River, IL 84, 100' S. of S. Hanover Hill Road LOGGED BY W. Garza
SECTION 103 BR-4		LOCA	TION _	Hanov	er Twp 9SW, <b>SEC. , TWP.</b> 26N, <b>RNG.</b> 1W
COUNTY JoDaviess DF	RILLING M	ETHOL			HAMMER TYPE CME-45 Automatic
STRUCT. NO.	— E P T H	L O W	U C S Qu (tsf)	M O I S T (%)	Surface Water Elev.         ft           Stream Bed Elev.         76.50           Groundwater Elev.:         ft           First Encounter         ft           Upon Completion         ft           After         Hrs.         ft
VERY STIFF dark brown LOAM	97.00	1 7 8	2.5 P	16.0	
STIFF gray SILTY CLAY LOAM	93.00	5 3 2 4	1.9 B	32.0	
MEDIUM tan SILTY LOAM	90.50	1 3 3	0.7 B	27.0	
STIFF tan SILTY CLAY LOAM with LIMESTONE fragments	88.00	0 3 5 6	1.0 P	28.0	
HARD tan CLAY		3 5 8	5.6 B	18.0	
VERY DENSE tan weathered LIMESTONE	85.00 				
Auger Refusal at 16' Borehole continued with rock coring.	83.00	-			

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



## **ROCK CORE LOG**

Page <u>1</u> of <u>1</u>

Date 3/22/10

ROUTE	FA 308		Bridge over Apple River, 5. of S. Hanover Hill Road	IL 84	, 100	_ LO	GGED	BY W.	Garza
		R-4 LOCATION Hanover							
		CORING METHOD				R E	R	CORE	S T
Station BORING NO.	B-2 318+30 9.00ft Lt	Core Diameter Top of Rock Elev	2 in 85.00 ft	D E P T H	CORE	C O > E R >	Q D	T M E	R E N G T
Offset Ground Sui	9.00ft Lt of face Elev. 9	<u>CL</u> 9.00 <b>ft</b>		(ft)	(#)	(%)	(%)	(min/ft)	
t.s.f.: 80.8 to	80.3	ense & mostly aphanitic.	83.00	-20	1	90	33	2.2	886.0
t.s.f.: 75.5 to		assively bedded, some pitting is appare	ent. 73.00	-25	2	100	72	2.2	663.0
Dolomite: as t.s.f.: 70.1 to				-30	3	100	52	1.2	1003.0
End of Boring	3		68.00	-35					

Color	pictures	of the	COTES

Cores will be stored for examination until

The "Strength" column represents the uniaxial compressive strength of the core sample (ASTM D-2938)

BBS, form 138 (Rev. 8-99)



	USER NAME =	DESIGNED -	REVISED	
		CHECKED -	REVISED	
	PLOT SCALE =	DRAWN -	REVISED	
C	PLOT DATE =	CHECKED -	REVISED	