STORM SEWER (CONTINUED)

STATION	OFFSET	TYPE	PRECAST REINFORCED CONCRETE FLARED END SECTIONS						TRENCH BACKFILL	STORM SEWERS, CLASS A																STORM SEWER (WATER MAIN REQUIREMENTS)					PIPE CULVERTS, CLASS D, TYPE 1 15"	METAL END SECTION 15"
										TYPE 1								TYPE 2														
			12"	15"	18"	24"	30"	48"		12"	15"	18"	24"	30"	36"	42"	48"	12"	15"	18"	24"	30"	36"	42"	48"	12"	15"	18"	24"	30"		
			EACH	EACH	EACH	EACH	EACH	EACH	CU YD	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	EACH
6048+00.13	64.57 LT.	INLET																														
		SS							1																	12						
6047+87.63	71.07 LT.	INLET																														
		SS							2																	30						
6047+60.00	56.00 LT.	INLET																														
		SS							7																	57						
6048+15.00	9.00 RT.	INLET																														
		SS							2									13														
6048+00.00	9.00 RT.	INLET																														
		SS							8									43														
6048+00.00	54.00 RT.	INLET																														
		SS																17														
6048+00.00	71.20 RT.	END SECTION	1																													
6048+35.6	67.40 LT.	INLET																														
		SS																		35												
6048+70.00	56.00 LT.	M.H.																														
		SS							27												106											
6048+70.00	54.00 RT.	M.H.																														
		SS																			19											
6048+70.00	74.00 RT.	END SECTION				1																										
6049+50.00	56.00 LT.	INLET																														
		SS							9									78														
6049+50.00	54.00 RT.	INLET																														
		SS																16														
6049+50.00	69.40 RT.	END SECTION	1																													
6050+65.00	54.00 LT.	INLET																														
		SS							16									105														
6050+65.00	54.00 RT.	INLET																														
		SS																18														
6050+65.00	72.40 RT.	END SECTION	1																													
6052+00.00	64.50 LT.	INLET																														
		SS																	10													
6052+00.00	54.00 LT.	INLET																														
		SS							9										51													
6052+00.00	C.L.	INLET																														
		SS							8										51													
6052+00.00	54.00 RT.	INLET																														
		SS																		20												
6052+00.00	74.10 RT.	END SECTION			1																											
6053+35.00	54.00 LT.	INLET																														
		SS							15									105														
6053+35.00	54.00 RT.	INLET																														
		SS																18														
6053+35.00	72.40 RT.	END SECTION	1																													
6054+70.00	54.00 LT.	INLET																														
		SS							15									105														
6054+70.00	54.00 RT.	INLET																														
		SS																18														
6054+70.00	70.70 RT.	END SECTION	1																													
6055+70.00	71.50 LT.	INLET																														
		SS																		26												
6055+90.00	54.00 LT.	INLET																														
		SS							12											47												
6055+90.00	4.90 LT.	M.H.																														
		SS							22											56												
6055+90.00	54.00 RT.	INLET																														
		SS																			24											
6055+90.00	78.30 RT.	END SECTION				1																										
6056+15.00	2.00 RT.	INLET																														
		SS							4									24														
6056+90.00	54.00 LT.	INLET																														
		SS							8									49														
6056+90.00	3.77 LT.	INLET																														
		SS							13									55														
6056+90.00	54.00 RT.	INLET																														
		SS																20														