

BEAM #1

Location	Station	*Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abutment	6117+58.41	-36.00	573.05	573.05
CL Brg. S. Abut.	6117+60.52	-36.00	573.07	573.07
A	6117+70.52	-36.00	573.19	573.22
B	6117+80.52	-36.00	573.31	573.36
C	6117+90.52	-36.00	573.43	573.50
D	6118+00.52	-36.00	573.54	573.62
E	6118+10.52	-36.00	573.66	573.75
F	6118+20.52	-36.00	573.78	573.86
G	6118+30.52	-36.00	573.89	573.97
H	6118+40.52	-36.00	574.01	574.06
I	6118+50.52	-36.00	574.13	574.15
CL Brg. N. Abut.	6118+59.44	-36.00	574.23	574.23
Bk. N. Abutment	6118+61.56	-36.00	574.26	574.26

BEAM #2

Location	Station	*Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abutment	6117+63.03	-28.00	573.30	573.30
CL Brg. S. Abut.	6117+65.14	-28.00	573.33	573.33
A	6117+75.14	-28.00	573.45	573.47
B	6117+85.14	-28.00	573.56	573.62
C	6117+95.14	-28.00	573.68	573.76
D	6118+05.14	-28.00	573.80	573.89
E	6118+15.14	-28.00	573.91	574.01
F	6118+25.14	-28.00	574.03	574.12
G	6118+35.14	-28.00	574.15	574.22
H	6118+45.14	-28.00	574.27	574.32
I	6118+55.14	-28.00	574.38	574.41
CL Brg. N. Abut.	6118+64.06	-28.00	574.49	574.49
Bk. N. Abutment	6118+66.18	-28.00	574.51	574.51

BEAM #3

Location	Station	*Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abutment	6117+67.65	-20.00	573.54	573.54
CL Brg. S. Abut.	6117+69.76	-20.00	573.56	573.56
A	6117+79.76	-20.00	573.68	573.71
B	6117+89.76	-20.00	573.80	573.85
C	6117+99.76	-20.00	573.91	573.99
D	6118+09.76	-20.00	574.03	574.12
E	6118+19.76	-20.00	574.15	574.24
F	6118+29.76	-20.00	574.27	574.35
G	6118+39.76	-20.00	574.38	574.45
H	6118+49.76	-20.00	574.50	574.55
I	6118+59.76	-20.00	574.62	574.64
CL Brg. N. Abut.	6118+68.68	-20.00	574.72	574.72
Bk. N. Abutment	6118+70.80	-20.00	574.75	574.75

BEAM #4

Location	Station	*Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abutment	6117+72.26	-12.00	573.75	573.75
CL Brg. S. Abut.	6117+74.38	-12.00	573.78	573.78
A	6117+84.38	-12.00	573.89	573.92
B	6117+94.38	-12.00	574.01	574.07
C	6118+04.38	-12.00	574.13	574.20
D	6118+14.38	-12.00	574.25	574.33
E	6118+24.38	-12.00	574.36	574.45
F	6118+34.38	-12.00	574.48	574.57
G	6118+44.38	-12.00	574.60	574.67
H	6118+54.38	-12.00	574.71	574.77
I	6118+64.38	-12.00	574.83	574.86
CL Brg. N. Abut.	6118+73.30	-12.00	574.94	574.94
Bk. N. Abutment	6118+75.41	-12.00	574.96	574.96

BEAM #5

Location	Station	*Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abutment	6117+76.88	-4.00	573.97	573.97
CL Brg. S. Abut.	6117+79.00	-4.00	573.99	573.99
A	6117+89.00	-4.00	574.11	574.14
B	6117+99.00	-4.00	574.22	574.28
C	6118+09.00	-4.00	574.34	574.42
D	6118+19.00	-4.00	574.46	574.55
E	6118+29.00	-4.00	574.58	574.67
F	6118+39.00	-4.00	574.69	574.78
G	6118+49.00	-4.00	574.81	574.88
H	6118+59.00	-4.00	574.93	574.98
I	6118+69.00	-4.00	575.05	575.07
CL Brg. N. Abut.	6118+77.92	-4.00	575.15	575.15
Bk. N. Abutment	6118+80.03	-4.00	575.17	575.17

SOUTHBOUND P.G.

Location	Station	*Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abutment	6117+79.19	0.00	574.07	574.07
CL Brg. S. Abut.	6117+81.31	0.00	574.10	574.10
A	6117+91.31	0.00	574.21	574.24
B	6118+01.31	0.00	574.33	574.39
C	6118+11.31	0.00	574.45	574.52
D	6118+21.31	0.00	574.57	574.65
E	6118+31.31	0.00	574.68	574.78
F	6118+41.31	0.00	574.80	574.89
G	6118+51.31	0.00	574.92	574.99
H	6118+61.31	0.00	575.04	575.09
I	6118+71.31	0.00	575.15	575.18
CL Brg. N. Abut.	6118+80.23	0.00	575.26	575.26
Bk. N. Abutment	6118+82.34	0.00	575.28	575.28