PART "B" SHEET 67 OF 136


NOTES


Inserts for ${}^3\!4''$ ϕ threaded dowel rods, when specified, are to be two strut, ferrule type for interior beams and single ferrule, flared loop type for exterior beams. Prestressing steel shall be uncoated high strength, low relaxation 7-wire strand, Grade 270. The nominal diameter shall be $^{\rm l}_2$ " and the nominal cross-sectional area shall be 0.153 sq. in.

A minimum $2\frac{1}{2}$ " ϕ lifting pin shall be used to engage the lifting loops during handling. The top and bottom plates shall be AASHTO M270 Grade 50.

The bottom plates shall be galvanized according to AASHTO M111. Top plates and threaded rods need not be galvanized.

Threaded rods shall be ASTM F 1554 Grade 55.





BOTTOM PLATE See bearing details for pintle

hole locations when required.


LIFTING LOOP DETAIL


-3'' Radius


-Top of Beam

270 ksi strands

-1^l₄′′ ¢ Conduit







BAR Gi

BAR G2

BAR G4


All material for bracing shall be hot dip galvanized according to AASHTO M111 unless otherwise noted. Two hardened washers are required for each set of oversized holes.

All holes shall be 15 ₁₆ " ϕ unless otherwise noted. 5 _{l6} " x 3" x 3" plate washers are required over all slotted holes.

All bolts shall be galvanized according to AASHTO M232. Bracing shall be installed as beams are erected and tightened as soon as possible during erection.

Permanent bracing shall not be paid for separately, but shall be included in the cost of Furnishing and Erecting Precast Prestressed Concrete I-Beams.

- * Fabricator shall locate to miss strands within permissible tolerances.
- ** Alternate C12x30 channels are permitted to facilitate material acquisition.



PERMANENT BRACING DETAILS FOR 36" PPC I-BEAMS

BILL OF MATERIAL

| Item | Unit | Total |
|---|------|-------|
| Furnishing and Erecting Precast Prestressed Concrete I-Beams, 36" | Ft. | 370.0 |

COUNTY

SANGAMON 194 125

PI-4-36D

1-28-11

| REVISED - | |
|-----------|------------------------|
| REVISED - | |
| REVISED - | |
| REVISED - | |
| | REVISED - REVISED - |

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

36" PPC I-BEAM DETAILS MECHANICSBURG RD. OVER F.A.I.-72 - S.N. 084-0150 • (84-10-1RS-3, 84-10-2RS-R)BR,I | CONTRACT NO. 72C90 SHEET NO. 13 OF 27 SHEETS FED. ROAD DIST, NO. 6 ILLINOIS FED. AID PROJECT