

STAGE II CONSTRUCTION LINE

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Appr. Bent	298+51.38	6.75	604.62	604.62
A	298+61.38	6.75	604.72	604.72
B	298+71.38	6.75	604.82	604.82
Bk. N. Abut.	298+80.34	6.75	604.89	604.89
⊕ Brg N. Abut.	298+81.13	6.75	604.90	604.90
C	298+91.13	6.75	604.98	605.00
D	299+01.13	6.75	605.05	605.10
E	299+11.13	6.75	605.11	605.18
F	299+21.13	6.75	605.16	605.24
G	299+31.13	6.75	605.20	605.27
H	299+41.13	6.75	605.24	605.30
I	299+51.13	6.75	605.27	605.31
J	299+61.13	6.75	605.29	605.31
K	299+71.13	6.75	605.30	605.31
⊕ Exist. Pier	299+80.30	6.75	605.31	605.31
L	299+90.30	6.75	605.31	605.32
M	300+00.30	6.75	605.29	605.31
N	300+10.30	6.75	605.27	605.31
O	300+20.30	6.75	605.24	605.30
P	300+30.30	6.75	605.21	605.28
Q	300+40.30	6.75	605.16	605.24
R	300+50.30	6.75	605.11	605.18
S	300+60.30	6.75	605.04	605.09
T	300+70.30	6.75	604.98	605.00
⊕ Brg S. Abut.	300+79.47	6.75	604.90	604.90
Bk. S. Abut.	300+80.26	6.75	604.89	604.89
U	300+90.26	6.75	604.81	604.81
V	301+00.26	6.75	604.71	604.71
Bk. S. Appr. Bent	301+09.22	6.75	604.62	604.62

BEAM 6 (BEAM 5*)

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Appr. Bent	298+51.38	7.94	604.61	604.61
A	298+61.38	7.94	604.70	604.70
B	298+71.38	7.94	604.80	604.80
Bk. N. Abut.	298+80.34	7.94	604.87	604.87
⊕ Brg N. Abut.	298+81.13	7.75	604.89	604.89
C	298+91.13	7.75	604.96	604.98
D	299+01.13	7.75	605.03	605.08
E	299+11.13	7.75	605.09	605.16
F	299+21.13	7.75	605.15	605.23
G	299+31.13	7.75	605.19	605.26
H	299+41.13	7.75	605.23	605.29
I	299+51.13	7.75	605.25	605.29
J	299+61.13	7.75	605.28	605.29
K	299+71.13	7.75	605.28	605.29
⊕ Exist. Pier	299+80.30	7.75	605.29	605.29
L	299+90.30	7.75	605.29	605.29
M	300+00.30	7.75	605.27	605.29
N	300+10.30	7.75	605.26	605.29
O	300+20.30	7.75	605.22	605.28
P	300+30.30	7.75	605.19	605.26
Q	300+40.30	7.75	605.14	605.22
R	300+50.30	7.75	605.09	605.16
S	300+60.30	7.75	605.03	605.08
T	300+70.30	7.75	604.96	604.98
⊕ Brg S. Abut.	300+79.47	7.75	604.89	604.89
Bk. S. Abut.	300+80.26	7.94	604.87	604.87
U	300+90.26	7.94	604.79	604.79
V	301+00.26	7.94	604.69	604.69
Bk. S. Appr. Bent	301+09.22	7.94	604.61	604.61

BEAM 7 (BEAM 6*)

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Appr. Bent	298+51.38	15.88	604.48	604.48
A	298+61.38	15.88	604.58	604.58
B	298+71.38	15.88	604.68	604.68
Bk. N. Abut.	298+80.34	15.88	604.75	604.75
⊕ Brg N. Abut.	298+81.13	15.50	604.77	604.77
C	298+91.13	15.50	604.84	604.86
D	299+01.13	15.50	604.91	604.96
E	299+11.13	15.50	604.97	605.04
F	299+21.13	15.50	605.03	605.11
G	299+31.13	15.50	605.07	605.14
H	299+41.13	15.50	605.11	605.17
I	299+51.13	15.50	605.13	605.17
J	299+61.13	15.50	605.16	605.17
K	299+71.13	15.50	605.16	605.17
⊕ Exist. Pier	299+80.30	15.50	605.17	605.17
L	299+90.30	15.50	605.17	605.17
M	300+00.30	15.50	605.15	605.17
N	300+10.30	15.50	605.14	605.17
O	300+20.30	15.50	605.10	605.16
P	300+30.30	15.50	605.07	605.14
Q	300+40.30	15.50	605.02	605.10
R	300+50.30	15.50	604.97	605.04
S	300+60.30	15.50	604.90	604.95
T	300+70.30	15.50	604.84	604.86
⊕ Brg S. Abut.	300+79.47	15.50	604.77	604.77
Bk. S. Abut.	300+80.26	15.88	604.75	604.75
U	300+90.26	15.88	604.67	604.67
V	301+00.26	15.88	604.57	604.57
Bk. S. Appr. Bent	301+09.22	15.88	604.48	604.48

BEAM 8 (BEAM 7*)

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Appr. Bent	298+51.38	23.81	604.35	604.35
A	298+61.38	23.81	604.45	604.45
B	298+71.38	23.81	604.55	604.55
Bk. N. Abut.	298+80.34	23.81	604.62	604.62
⊕ Brg N. Abut.	298+81.13	23.25	604.64	604.64
C	298+91.13	23.25	604.72	604.74
D	299+01.13	23.25	604.79	604.84
E	299+11.13	23.25	604.85	604.92
F	299+21.13	23.25	604.90	604.98
G	299+31.13	23.25	604.94	605.01
H	299+41.13	23.25	604.98	605.04
I	299+51.13	23.25	605.01	605.05
J	299+61.13	23.25	605.03	605.05
K	299+71.13	23.25	605.04	605.05
⊕ Exist. Pier	299+80.30	23.25	605.05	605.05
L	299+90.30	23.25	605.05	605.05
M	300+00.30	23.25	605.03	605.05
N	300+10.30	23.25	605.01	605.05
O	300+20.30	23.25	604.98	605.04
P	300+30.30	23.25	604.95	605.02
Q	300+40.30	23.25	604.90	604.98
R	300+50.30	23.25	604.85	604.92
S	300+60.30	23.25	604.78	604.83
T	300+70.30	23.25	604.72	604.74
⊕ Brg S. Abut.	300+79.47	23.25	604.64	604.64
Bk. S. Abut.	300+80.26	23.81	604.62	604.62
U	300+90.26	23.81	604.54	604.54
V	301+00.26	23.81	604.44	604.44
Bk. S. Appr. Bent	301+09.22	23.81	604.35	604.35

BEAM 9 (W. CURTAIN WALL *)

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Appr. Bent	298+51.38	31.75	604.19	604.19
A	298+61.38	31.75	604.28	604.28
B	298+71.38	31.75	604.38	604.38
Bk. N. Abut.	298+80.34	31.75	604.46	604.46
⊕ Brg N. Abut.	298+81.13	31.00	604.48	604.48
C	298+91.13	31.00	604.55	604.57
D	299+01.13	31.00	604.63	604.68
E	299+11.13	31.00	604.68	604.75
F	299+21.13	31.00	604.74	604.82
G	299+31.13	31.00	604.78	604.85
H	299+41.13	31.00	604.82	604.88
I	299+51.13	31.00	604.85	604.89
J	299+61.13	31.00	604.87	604.89
K	299+71.13	31.00	604.88	604.89
⊕ Exist. Pier	299+80.30	31.00	604.88	604.88
L	299+90.30	31.00	604.88	604.89
M	300+00.30	31.00	604.87	604.89
N	300+10.30	31.00	604.85	604.89
O	300+20.30	31.00	604.82	604.88
P	300+30.30	31.00	604.79	604.86
Q	300+40.30	31.00	604.74	604.82
R	300+50.30	31.00	604.69	604.76
S	300+60.30	31.00	604.62	604.67
T	300+70.30	31.00	604.56	604.58
⊕ Brg S. Abut.	300+79.47	31.00	604.48	604.48
Bk. S. Abut.	300+80.26	31.75	604.46	604.46
U	300+90.26	31.75	604.37	604.37
V	301+00.26	31.75	604.28	604.28
Bk. S. Appr. Bent	301+09.22	31.75	604.19	604.19

* Denotes description variations for Approach Spans associated with Main Span callouts.