

PATCHING SCHEDULE

LOCATION	CLASS A PATCHES				CLASS A PATCHES			SAW	TIE	PATCH	
	LENGTH (FT)	WIDTH	SQ YD		11 IN	11 IN	11 IN	CUTS	BARS	REINF	
					TY II	TY III	TY IV	FOOT	EACH	SQ YD	
WESTBOUND 72	PASS.	CENT.	DRIV.								
WEST OF 55											
STA 650+59			6.0	12.0	8.0	8.0		60.0		8.0	
STA 545+35	10.0			12.0	13.3	13.3		68.0		13.3	
STA 462+89			6.0	12.0	8.0	8.0		60.0		8.0	
STA 433+75			6.0	12.0	8.0	8.0		60.0		8.0	
STA 408+90			6.0	12.0	8.0	8.0		60.0		8.0	
STA 407+50			12.0	12.0	16.0		16.0	72.0		16.0	
STA 402+40			20.0	12.0	26.7			88.0		26.7	
STA 1368+05			8.0	12.0	10.7	10.7		64.0		10.7	
STA 1368+05	8.0			12.0	10.7	10.7		64.0		10.7	
STA 1365+95			10.0	12.0	13.3	13.3		68.0		13.3	
STA 486+00			8.0	12.0	10.7	10.7		64.0		10.7	
STA 400+50			50.0	12.0	66.7		66.7	148.0	26	66.7	
TOTAL W.B.					200.0	90.7	16.0	93.4	876.0	26.0	200.0
EASTBOUND 72											
MORGAN C.L.											
STA 12+90			6.0	12.0	8.0	8.0		60.0		8.0	
STA 63+04			10.0	12.0	13.3	13.3		68.0		13.3	
STA 405+50			20.0	12.0	26.7		26.7	88.0		26.7	
STA 514+37		6.0		12.0	8.0	8.0		60.0		8.0	
STA 665+10			8.0	12.0	10.7	10.7		64.0		10.7	
STA 665+10	8.0			12.0	10.7	10.7		64.0		10.7	
STA 681+20			20.0	12.0	26.7		26.7	88.0		26.7	
STA 682+27			10.0	12.0	13.3	13.3		68.0		13.3	
STA 693+22			8.0	12.0	10.7	10.7		64.0		10.7	
STA 693+22	8.0			12.0	10.7	10.7		64.0		10.7	
TOTAL W.B.					138.7	85.4	0.0	53.4	688.0	0.0	138.7
TOTALS					338.7	176.1	16.0	146.8	1564.0	26.0	338.7

MIXTURE REQUIREMENTS

THE FOLLOWING MIXTURE REQUIREMENTS

ARE APPLICABLE FOR THIS PROJECT

MIXTURE USE(S)	H.M.A. SHOULDER REM & REPL SURF	H.M.A. SHOULDER REM & REPL LOWER LIFTS
AC/PG	PG 64-22	PG 64-22
DESIGN AIR VOIDS	4.0% @ N DESIGN = 50	4.0% @ N DESIGN = 50
MIXTURE COMP	IL 9.5	IL 19.0
FRICITION AGG	MIX "C"	N/A