# STANDARD BAR SPLICER ASSEMBLY

Minimum Lap Lengths							
Bar size to be spliced	Table 1	Table 2	Table 3	Table 4	Table 5	Table 6	
3, 4	1'-5''	1'-11''	2'-1''	2'-4''	2'-7"	2'-11''	
5	1'-9''	2'-5"	2'-7''	2'-11''	3'-3''	3′-8′′	
6	2'-1''	2'-11''	3'-1''	3′-6′′	3'-10''	4'-5''	
7	2'-9''	3′-10′′	4'-2''	4'-8''	5′-2′′	5′-10′′	
8	3′-8′′	5'-1''	5′-5′′	6'-2''	6'-9''	7′-8′′	
9	4'-7''	6′-5′′	6'-10''	7′-9′′	8'-7''	9′-8′′	

Table 1: Black bar, 0.8 Class C

Table 2: Black bar, Top bar lap, 0.8 Class C

Table 3: Epoxy bar, 0.8 Class C

Table 4: Epoxy bar, Top bar lap, 0.8 Class C


Table 5: Epoxy bar, Class C

Table 6: Epoxy bar, Top bar top, Class C

Threaded splicer bar length = min. lap length +  $1^{l_2}$ " + thread length

\* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.


Location	Bar size	No. assemblies required	Table for minimum lap length
Top Slab	#6	40	3
Bott. Slab	#5	36	3
Walls	#6	21	3



### INSTALLATION AND SETTING METHODS


"A": Set bar splicer assembly by means of a template bolt.
"B": Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E) : Indicates epoxy coating.



## STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required



# BAR SPLICER ASSEMBLY FOR #5 BAR ON INTEGRAL OR SEMI-INTEGRAL ABUTMENTS

No. required =

# Abutment Approach slab Threaded couplers (E) BAR SPLICER ASSEMBLY FOR #5 BAR ON STUB ABUTMENTS No. required = Threaded splicer bar (E)

# <u>NOTES</u>

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

COUNTY

ST. CLAIR 38 25

CONTRACT NO. 76E21

All reinforcement shall be lapped and tied to the splicer bars.

Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications.

See approved list of bar splicer assemblies and mechanical splicers for alternatives.

BSD-1

1-27-12

_

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

			_
BAR SPLICER ASSEMBLY AND MECHANICAL SPLICER DETAILS		SECTION	
STRUCTURE NO. 082-2046	103	23BR-1	l
	STA. 674+45		ſ
SHEET NO, 6 OF 8 SHEETS	ILLINOIS FED.		ă