



### DESIGNER NOTES

- 1) CLASS A3 OR A4 CAN BE USED FOR DITCH LINING. USE A4 FOR VELOCITIES GREATER THAN 12 FPS. A3 MAY BE USED AS AN ALTERNATE TO FIBERMAT.
- 2) INCLUDE PAY ITEM FOR FILTER FABRIC FOR USE WITH RIPRAP. NOTE THE SPECIFICATION BOOK DOES NOT REQUIRE FABRIC ON A3 BUT INCLUDE IT WHEN USING THIS STANDARD.
- 3) EXAMPLE: CLASS A4 MEANS A QUALITY AND GRADATION RR 3. SEE ARTICLE 1005.01 FOR SIZE.
- 4) REMEMBER TO FILL IN THE DIMENSIONS ON THE DITCH SECTION ABOVE.
- 5) ADD THE CLASS A3 OR A4 TO THE NOTE ON THE BOTTOM RIGHT.
- 6) USE PAY ITEM 28300470 AGGREGATE DITCH 12"

CLASS \_\_\_\_\_ WILL BE REQUIRED ON THIS PROJECT AT THE LOCATION SHOWN ON THE PLANS.

THIS WORK SHALL BE DONE ACCORDING TO SECTION 283 OF THE STANDARD SPECIFICATION. AGGREGATE DITCH WILL BE MEASURED FOR PAYMENT IN PLACE AND THE AREA COMPUTED IN SQUARE YARD OF ACTUAL SURFACE AREA. AGGREGATE DITCH WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQUARE YARD FOR AGGREGATE DITCH, 12".

**283-1**

## AGGREGATE DITCH FOR FLEXIBLE DITCH LINING