

35600

356.00

Designer Note: Fill the HMA and PCC depths as the same depth. Use the HMA depth for the pay item name and calculation of the Earth Excavation for Widening quantity. Method of payment is described in the last paragraph of Section 356 of the Standard Specifications.

Use this item when the Contractor may need to construct widening for staging and the type of payment is not required to be as specific material. Make sure there will be adequate coverage with final overlay.

TEMPORARY BASE COURSE WIDENING [REDACTED]"

Effective April 26, 2013

This item shall include all materials, labor and equipment necessary to construct base course widening in accordance with Section 356 of the Standard Specifications except as herein specified.

The Contractor shall have the option of constructing temporary pavement made of [REDACTED]" Hot-Mix Asphalt base course or [REDACTED]" PCC base course.

Hot-Mix Asphalt base course shall be placed in accordance with applicable portions of Section 356 of the Standard Specifications. Material for Hot-Mix Asphalt base course shall be Hot-Mix Asphalt Binder Course IL-19.0 in accordance with Sections 406 and 407 of the Standard Specifications. PCC base course shall be in accordance with Section 354 of the Standard Specifications.

This work will be paid for at the contract unit price per Square Yard (Square Meter) for BASE COURSE WIDENING [REDACTED]", which price shall be payment in full for all materials, labor and equipment including bituminous and aggregate prime coat necessary to perform the work as herein specified.