

Designer Note: Use when requiring a solid concrete island to be constructed on an existing pavement. Also include a detail in the plans showing cross sections and any anchor bolts if so required. If anchor bolts are required, include last sentence of special. Otherwise, be sure to remove last sentence for typing. Existing CADD drawing 606301 can be used as an example.

### **ISLAND PAVEMENT CONSTRUCTED ON EXISTING PAVEMENT**

Effective January 1, 1997

Revised January 1, 2007

This work shall consist of constructing a solid concrete island on the existing pavement as shown on the details included in the plans and shall be done in accordance with the applicable portions of Section 606 of the Standard Specifications and the following provisions:

1. All references to Concrete Median shall be interpreted to mean Island Pavement.
2. Add the following to Article 606.09:

Transverse expansion joints shall be installed in the Island Pavement producing a vertical prolongation of the joints in the underlying pavement. In no case shall the joints be spaced more than 100' (30 m) apart. The expansion joint shall be constructed of 3/4" (20 mm) preformed joint material.

3. Add the following to Article 606.15:

This work will be paid for at the contract unit price per Square Foot (Square Meter), measured as specified, for ISLAND PAVEMENT, which shall include payment for furnishing and installing all joints as required. Anchor bolts will be paid for at the contract unit price per Each for ANCHOR BOLTS of the size specified.