
THIS DISTRICT 5 DETAIL SHOULD BE USED CHECK SHEET #15 AND SHALL ALSO APPLY PAVEMENT. NOTE: DESIGNER

FILE NAME =


c:\pw_work\PWIDOT\CRAI


USER NAME = craigre

RESURFACED PCC PAVEMENT



BARE PCC PAVEMENT





MILL MACHINE AND/OR WHEEL SAW REMOVAL

AIR EQUIPMENT OR MECHANICAL SWEEPER REMOVAL OF LOOSE AND/OR UNSOUND CONCRETE

DESIGN NOTES

PARTIAL DEPTH HMA PATCHING SHALL NOT BE USED WHEN HMA OVERLAY THICKNESS (T) ON PCC PAVEMENT EXCEEDS 4 3/4 INCHES (145 mm) OR ON CRC PAVEMENT.

GENERAL NOTES

ALL VOLUME OF PARTIAL DEPTH REMOVAL SHALL BE REPLACED WITH HOT-MIX ASPHALT (HMA) AND PAID FOR AT THE CONTRACT UNIT PRICE PER TON FOR PARTIAL DEPTH PATCHING.

T = THICKNESS OF HMA OVERLAY(S). SEE EXISTING TYPICAL CROSS SECTION.

GENERAL NOTE 406H SHALL INCLUDE MIXTURE REQUIREMENTS FOR PARTIAL DEPTH PATCHING.

HMA REPLACEMENT IN RESURFACED PCC PAVEMENT LOCATIONS SHALL BE ACCORDING TO SECTION 406 OF THE STANDARD SPECIFICATIONS.

D = DEPTH OF PARTIAL DEPTH REMOVAL INTO EXISTING PCC PAVEMENT. (3" (75 mm) ± OR TO SOUND CONCRETE)

TRANSVERSE CONTRACTION JOINT SHOWN - OTHER LOCATIONS SIMILAR.

> Note: All dimensions are in INCHES (millimeters) unless otherwise shown.

DISTRICT	T 6	DETA	II NO	YYAA	2100
DISINIG	- 3	UEIA	IL NU.	. ^^44	ZIUU

RAIGRE\d0101509\xx442100.dgn		DRAWN -	REVISED -	STATE OF ILLINOIS
	PLOT SCALE = 40.000 '/ IN.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION
	PLOT DATE = 1/7/2010	DATE -	REVISED -	

REVISED - 11/06

DESIGNED -

PCC	PARTIAL	DEPTH	нот-міх	ASPHALT	PATCHING	
	CUEET NO		CUEETS	CT.		

SCALE:

F.A. RTE.		SECTION					COUNTY	TOTAL SHEETS	SHE
							CONTRACT	NO.	
FED. R	CAO	DIST.	NO.	ILLINOIS	FED.	AID	PROJECT		