



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

October 30, 2024

SUBJECT: Route FAU 5557 (East 2nd Street)
Section 17-00152-00-BT (Sterling)
Whiteside County
Contract No. 85743
Item 123
November 8, 2024 Letting
Addendum A

NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

- 1. Revised Sheets 1, 4, 7, 9, 21, 90 – 92 and 99 – 101 to the Plans.**
- 2. Added Sheet 182A to the Plans.**
- 3. Revised the Schedule of Prices.**
- 4. Revised Page ii of the Table of Contents to the Special Provisions.**
- 5. Revised Pages 24 and 34 of the Special Provisions.**
- 6. Added Pages 34A to the Special Provisions.**

Prime contractors must utilize the enclosed material when preparing their bid and must include any changes to the Schedule of Prices in their bid.

Very truly yours,

A handwritten signature in black ink, appearing to read 'Jack A. Elston'.

Jack A. Elston, P.E.
Bureau Chief, Design and Environment

TREE GRATE REMOVAL.....	22
REMOVE AND SALVAGE SIGN PANEL	23
REMOVE AND SALVAGE LIMESTONE RETENTION BLOCK WALLS.....	23
PORTLAND CEMENT CONCRETE SIDEWALK CURB.....	23
BRICK SIDEWALK	24
PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH SPECIAL.....	24
BRICK SIDEWALK REMOVAL.....	25
PEDESTRIAN RAIL (SPECIAL).....	25
PIPE HANDRAIL, SPECIAL	25
REMOVE AND RE-ERECT EXISTING HANDRAIL	26
RETAINING WALL (SPECIAL)	27
TRENCH DRAIN	27
MANHOLES, TYPE A, WITH SPECIAL FRAME AND GRATE	27
INLETS, SPECIAL	28
SANITARY MANHOLES TO BE ADJUSTED	28
SANITARY MANHOLES TO BE ADJUSTED WITH NEW TYPE 1 FRAME, CLOSED LID	28
SANITARY MANHOLES TO BE RECONSTRUCTED.....	29
SANITARY MANHOLES TO BE RECONSTRUCTED WITH NEW TYPE 1 FRAME, CLOSED LID.....	29
FENCE REMOVAL AND REINSTALLATION	30
TRAFFIC CONTROL AND PROTECTION, (SPECIAL)	30
REMOVE AND RE-ERECT EXISTING SIGN	33
HANDLE TO BE ADJUSTED	33
RELOCATE EXISTING LIGHT POLE WITH LUMINARE.....	34
CABLE SPLICE SPECIAL	34
RELOCATE EXISTING CONDUIT AND CABLES.....	34
RELOCATE EXISTING HANDHOLE.....	34A
REMOVE EXISTING UNDERGROUND CONDUIT	34A
PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH.....	34A
STORM WATER POLLUTION PREVENTION PLAN	35
LR 107-4 SPECIAL PROVISION FOR INSURANCE	43
LR 702 SPECIAL PROVISION FOR CONSTRUCTION AND MAINTENANCE SIGNS	44
LR 1030-2 SPECIAL PROVISION FOR LOCAL QUALITY ASSURANCE/ QUALITY MANAGEMENT QC/QA.....	45
IEPA LPC 663 FORM.....	47

BRICK SIDEWALK

This work shall be the construction of brick pavers in the raceway between the sidewalk and the back of curb as shown in plans. The brick pavers shall be supplied by the City of Sterling.

This work shall include the sand and concrete below the pavers per the detail shown in the plans.

Basis of payment shall be at the contract unit bid price per SQUARE FOOT for BRICK SIDEWALK and shall include all labor, materials and equipment to perform work operation.

PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH SPECIAL

This item shall be done in accordance with Section 424 of the Standard Specifications for Road and Bridge Construction and the Details included in the Plans. Subbase Granular Material, Type B 4" in thickness shall be placed under the sidewalk and shall be paid for separately as SUBBASE GRANULAR MATERIAL, TYPE B.

The Contractor shall pay special attention to the elevations and grades of the sidewalk for ADA compliance.

The Contractor shall install handicap ramps as shown on the Plans or at locations directed by the Engineer in the field. Detectable warnings, in compliance with Illinois Accessibility Codes and ADA standards, shall be installed as shown on the Plans and paid for separately as DETECTABLE WARNINGS.

Also included in these items are the following:

1. All exposed vertical surfaces poured against formwork shall be rubbed to a depth of 3" below grade to provide a smooth dense surface free from pits and irregularities. This work shall only be performed with a rubbing stone and the use of power tools and burlap sacks is strictly prohibited. This work shall be performed to the satisfaction of the Engineer.
2. All exposed, above grade surfaces that are not poured against formwork shall receive a light broom finish.
3. Joint locations shall be approved by the Engineer prior to placing concrete.
4. Sidewalk edges shall be thickened where shown on the plans.

Basis of payment shall be at the contract unit price per SQUARE FOOT for PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH, SPECIAL which price shall include all labor, materials, and equipment necessary to complete the work.

RELOCATE EXISTING LIGHT POLE WITH LUMINAIRE

This work shall be done in accordance with Sections 821, 830, and 838 of the Standard Specifications for Road and Bridge Construction and the details included in the plans and the following additions:

The work includes removing and relocating the existing light pole at Sta. 2002+84 LT. Any damage sustained to the lighting unit during removal, storing, or relocating shall be repaired, or replaced, to the satisfaction of the Engineer.

The Contractor shall verify the circuits, power source and all materials, including wire size and raceway prior to starting the work.

This item includes replacing or repairing any damage to the pole, luminaire, mounting hardware, accessories, and wiring supplied from the luminaire to the pole base, replacing all splices and fuses, and performing all operations required for completion of the work and restore the pole and luminaire to working condition.

This work shall be paid for at the contract unit price per EACH for RELOCATE EXISTING LIGHT POLE WITH LUMINAIRE and shall include labor, equipment, and materials necessary to complete the work.

The light pole foundation shall be paid for at the contract unit price per EACH for LIGHT POLE FOUNDATION, 30" DIAMETER.

Removal of the existing light pole foundation shall be paid for at the contract unit price per EACH for REMOVAL OF POLE FOUNDATION.

CABLE SPLICE SPECIAL

This work shall be done in accordance with Section 801 and 817 of the Standard Specifications for Road and Bridge Construction and the details included in the plans.

This item includes furnishing material to splice existing and proposed cables. The contractor shall install a heat shrink, waterproof sleeve to protect the splice.

This work shall be paid for at the contract unit price per EACH for CABLE SPLICE (SPECIAL) and shall include all labor and materials necessary to disconnect, remove, reconnect, and splice cables.

RELOCATE EXISTING CONDUIT AND CABLES

This work shall consist of reconnecting an existing light pole that has been relocated. The existing conduits shall be intercepted underground and extended to the new light pole location in accordance with applicable portions of Sections 810 and 873 of the Standard Specifications for Road and Bridge Construction and the details included in the plans

This work shall be paid for at the contract unit price per FOOT for RELOCATE EXISTING CONDUIT AND CABLES, which price shall include all labor, materials, and equipment necessary to complete the work described above.

RELOCATE EXISTING HANDHOLE

This work consists of the relocation of existing handholes as shown in the plans in accordance with applicable portions of Section 814 of the Standard Specifications for Road and Bridge Construction and the details included in the plans

The location of the relocated handhole shall be excavated to allow the top of the handhole to be flush with the proposed adjacent sidewalk. The relocated handholes shall be installed according to Highway Standard 814001.

This work shall be paid for at the contract unit price per EACH for RELOCATE EXISTING HANDHOLE, which price shall include all labor, materials, and equipment necessary to complete the work described above.

REMOVE EXISTING UNDERGROUND CONDUIT

This work shall consist of removing underground conduits including all cables at the locations shown on the plans. The conduit and cables shall be removed in accordance with Section 895 of the Standard Specifications for Road and Bridge Construction and the details included in the plans.

The Contractor shall protect the existing junction boxes for re-use, as shown in the plans.

The trench shall be backfilled with suitable excavated material from the trench.

This work shall be paid for at the contract unit price per FOOT for REMOVE EXISTING UNDERGROUND CONDUIT, which price shall include all labor, materials, and equipment necessary to complete the work described above.

PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH

This item shall be done in accordance with Section 424 of the Standard Specifications for Road and Bridge Construction and the Details included in the Plans. Subbase Granular Material, Type B 4" in thickness shall be placed under the sidewalk and shall be paid for separately as SUBBASE GRANULAR MATERIAL, TYPE B.

Also included in these items are the following:

5. All exposed vertical surfaces poured against formwork shall be rubbed to a depth of 3" below grade to provide a smooth dense surface free from pits and irregularities. This work shall only be performed with a rubbing stone and the use of power tools and burlap sacks is strictly prohibited. This work shall be performed to the satisfaction of the Engineer.
6. All exposed, above grade surfaces that are not poured against formwork shall receive a light broom finish.
7. Joint locations shall be approved by the Engineer prior to placing concrete.
8. Sidewalk edges shall be thickened where shown on the plans.

Basis of payment shall be at the contract unit price per SQUARE FOOT for PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH, which price shall include all labor, materials, and equipment necessary to complete the work.

