

PAVED DITCH REMOVAL SCHEDULE

LOCATION				ACTUAL LENGTH TO BE BROKEN IN PLACE	STONE RIPRAP, CLASS A3	SEEDING, CLASS 2	SEEDING, CLASS 7
UNION COUNTY		LT/RT	FEET	TON	ACRE	ACRE	
2940+81	TO	2946+10	RT	530.8	294.9	0.37	0.37
2973+07	TO	2973+26	RT	22.2	12.3	0.02	0.02
2979+50	TO	2979+83	RT	32.8	18.2	0.02	0.02
2993+80	TO	2994+35	LT	55.2	30.7	0.04	0.04
3004+06	TO	3006+00	LT	200	111.1	0.14	0.14
3013+09	TO	3019+15	LT	625	347.2	0.43	0.43
3045+69	TO	3046+04	LT	35.6	19.8	0.02	0.02
SUBTOTAL (UNION COUNTY)					835	1.1	1.1
PULASKI COUNTY							
10+66	TO	11+83	LT	115.4	64.1	0.08	0.08
21+80	TO	22+97	LT	116.9	64.9	0.08	0.08
28+88	TO	30+98	LT	210.4	116.9	0.14	0.14
31+99	TO	32+87	RT	89	49.4	0.06	0.06
39+15	TO	40+27	RT	110.9	61.6	0.08	0.08
42+46	TO	43+55	RT	108.5	60.3	0.07	0.07
SUBTOTAL (PULASKI COUNTY)					418	0.6	0.6
PROJECT TOTALS					1253	1.7	1.7

MEDIAN CROSSOVER SCHEDULE

LOCATION STATION	AREA (SQFT)	INCIDENTAL HMA SURFACING*	BITUMINOUS MATERIALS (PRIME COAT)	GRADING AND SHAPING SHOULDERS	HMA SURF REM - BT JT
		TON	GAL	UNIT	SQ YD
UNION COUNTY					
3055+75*	1183	39	12	1	19
3119+70**	622	17	6	1	
TOTALS		56	18	2	19

*INCIDENTAL HMA SURFACING TAPERS FROM 8 1/2" TO 2". AN AVERAGE THICKNESS OF 5 1/4" WAS USED FOR THIS CALCULATION.

**INCIDENTAL HMA SURFACING TAPERS FROM 8 1/2" TO 1/2". AN AVERAGE THICKNESS OF 4 1/2" WAS USED FOR THIS CALCULATION.