

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

Various Routes
OVD SIN STR REP & REPL 2008-9
Various Counties
Sheet 69 of 105
Contract Number 44973

District 4
Schedule of Overhead Sign Structure Repair & Replacement

Location No.:	4-01	State I.D. No.:	4S048U150R011.6				
County:	Knox	Route:	US 150	M.P.:	11.6	Direction:	EB
Description of Work	Unit	Quantity					
REMOVE & RE-ERECT OVERHEAD SIGN STRUCTURE-SPAN	EACH	1.00					
STRUCTURAL STEEL SUPPORT OVERHEAD SIGN STRUCTURE	EACH	2.00					
FURNISH & INSTALL SADDLE SHIM BLOCK	EACH	4.00					
FURNISH & INSTALL INTERNAL TRUSS DAMPER	EACH	1.00					
FURNISH & INSTALL SAFETY CHAIN	EACH	2.00					
OVERHEAD SIGN STRUCTURE WALKWAY	FOOT	74.00					
REPAIR HANDRAIL LOCKING PIN CONNECTION	EACH	8.00					
DISCONNECT / RECONNECT ELECTRIC SERVICE	EACH	1.00					
RELOCATE ELECTRIC SERVICE	EACH	1.00					
DRILLED SHAFT CONCRETE FOUNDATION	CU YD	12.70					
REMOVE CONCRETE FOUNDATION OVERHEAD	EACH	2.00					

Location No.:	4-04	State I.D. No.:	4S048U034L005.6				
County:	Knox	Route:	US 34	M.P.:	5.6	Direction:	WB
Description of Work	Unit	Quantity					
REMOVE & RE-ERECT OVERHEAD SIGN STRUCTURE-SPAN	EACH	1.00					
STRUCTURAL STEEL SUPPORT OVERHEAD SIGN STRUCTURE	EACH	2.00					
FURNISH & INSTALL SADDLE SHIM BLOCK	EACH	4.00					
FURNISH & INSTALL INTERNAL TRUSS DAMPER	EACH	1.00					
FURNISH & INSTALL SAFETY CHAIN	EACH	2.00					
OVERHEAD SIGN STRUCTURE WALKWAY	FOOT	77.00					
REPAIR HANDRAIL LOCKING PIN CONNECTION	EACH	8.00					
DISCONNECT / RECONNECT ELECTRIC SERVICE	EACH	1.00					
REPLACE / TIGHTEN CLIP PER SIGN	EACH	2.00					
RELOCATE ELECTRIC SERVICE	EACH	1.00					
DRILLED SHAFT CONCRETE FOUNDATION	CU YD	12.70					
REMOVE CONCRETE FOUNDATION OVERHEAD	EACH	2.00					

Location No.:	4-02	State I.D. No.:	4S048U034R005.0				
County:	Knox	Route:	US 34	M.P.:	5	Direction:	EB
Description of Work	Unit	Quantity					
REMOVE & RE-ERECT OVERHEAD SIGN STRUCTURE - SPAN	EACH	1.00					
STRUCTURAL STEEL SUPPORT OVERHEAD SIGN STRUCTURE	EACH	2.00					
FURNISH & INSTALL SADDLE SHIM BLOCK	EACH	4.00					
FURNISH & INSTALL INTERNAL TRUSS DAMPER	EACH	1.00					
FURNISH & INSTALL SAFETY CHAIN	EACH	2.00					
OVERHEAD SIGN STRUCTURE WALKWAY	FOOT	72.00					
REPAIR HANDRAIL LOCKING PIN CONNECTION	EACH	8.00					
DISCONNECT / RECONNECT ELECTRIC SERVICE	EACH	1.00					
RELOCATE ELECTRIC SERVICE	EACH	1.00					
DRILLED SHAFT CONCRETE FOUNDATION	CU YD	12.70					
REMOVE CONCRETE FOUNDATION OVERHEAD	EACH	2.00					

Location No.:	4-05	State I.D. No.:	4S048U034L008.0				
County:	Knox	Route:	US 34	M.P.:	8	Direction:	WB
Description of Work	Unit	Quantity					
REMOVE & RE-ERECT OVERHEAD SIGN STRUCTURE-SPAN	EACH	1.00					
STRUCTURAL STEEL SUPPORT OVERHEAD SIGN STRUCTURE	EACH	2.00					
FURNISH & INSTALL INTERNAL TRUSS DAMPER	EACH	1.00					
FURNISH & INSTALL SAFETY CHAIN	EACH	2.00					
OVERHEAD SIGN STRUCTURE WALKWAY	FOOT	96.00					
REPAIR HANDRAIL LOCKING PIN CONNECTION	EACH	8.00					
DISCONNECT / RECONNECT ELECTRIC SERVICE	EACH	1.00					
DRILLED SHAFT CONCRETE FOUNDATIONS	CU YD	21.50					
REMOVE CONCRETE FOUNDATION OVERHEAD	EACH	2.00					
RELOCATE ELECTRIC SERVICE	EACH	1.00					

Location No.:	4-03	State I.D. No.:	4S048U034L005.4				
County:	Knox	Route:	US 34	M.P.:	5.4	Direction:	WB
Description of Work	Unit	Quantity					
REMOVE & RE-ERECT OVERHEAD SIGN STRUCTURE-SPAN	EACH	1.00					
STRUCTURAL STEEL SUPPORT OVERHEAD SIGN STRUCTURE	EACH	1.00					
FURNISH & INSTALL SADDLE SHIM BLOCK	EACH	4.00					
FURNISH & INSTALL INTERNAL TRUSS DAMPER	EACH	1.00					
FURNISH & INSTALL SAFETY CHAIN	EACH	2.00					
OVERHEAD SIGN STRUCTURE WALKWAY	FOOT	60.00					
REPAIR HANDRAIL LOCKING PIN CONNECTION	EACH	8.00					
DISCONNECT / RECONNECT ELECTRIC SERVICE	EACH	1.00					
RELOCATE ELECTRIC SERVICE	EACH	1.00					
DRILLED SHAFT CONCRETE FOUNDATION	CU YD	12.00					
REMOVE CONCRETE FOUNDATION OVERHEAD	EACH	2.00					

Location No.:	4-06	State I.D. No.:	4C048U034L007.7				
County:	Knox	Route:	US 34	M.P.:	7.7	Direction:	WB
Description of Work	Unit	Quantity					
REMOVE OVERHEAD SIGN STRUCTURE-CANTILEVER	EACH	1.00					
REMOVE CONCRETE FOUNDATION OVERHEAD	EACH	1.00					
OVERHEAD SIGN STRUCTURE CANTILEVER, TYPE II A	FOOT	30.00					
DRILLED SHAFT CONCRETE FOUNDATION	CU YD	7.10					
REMOVE & REINSTALL SIGN PANEL	SQ FT	104.00					
REMOVE & REINSTALL WALKWAY	FOOT	18.00					
DISCONNECT / RECONNECT ELECTRIC SERVICE	EACH	1.00					
RELOCATE ELECTRIC SERVICE	EACH	1.00					
FURNISH & INSTALL HANDRAIL	FOOT	18.00					