

ROUTE NO. SECTION TOTAL SHEET NO. T.R. 167 06-01102 01-BR PIATT 15 ROAD DIST. BEMENT

CONTRACT NO. 91364



TYPICAL FABRIC FORMED CONCRETE REVETMENT MAT LINE

See Sheet 4 for Location



LAYOUT OF FILTER POINTS

GENERAL NOTES

—Abutment Cap

In placing insert points through fabric use extreme care to avoid breaking drop stitches.

Injection points shall be no more than 30 feet apart on the horizontal.

Cut off walls shall be installed at the upstream and downstream ends of the mat.

SECTION B-B See Sheet 4

BILL OF MATERIAL


Item	Unit	Quantity
Fabric Formed Concrete Revetment Mat	Sq. Yd.	173

CONCRETE REVETMENT MAT DETAILS

SECTION 06-01102-01-BR BEMENT ROAD DISTRICT PIATT COUNTY STATION 5+06.55


4440 ASH GROVE
SPRINGFIELD, IL 62711
(217) 793-8600
casinc@insightbb.com

FERR-GRAHAM & ASSOCIATES, LLC
ENGINEERING AND SCIENCE COMBULTANTS
FILE: 0602REVMAT.DGN
DATE: 05/26/06




INSTALLATION DETAIL

Locate mortar stops to accommodate mortar quantities to be injected.



TYPICAL SECTION THRU FILTER POINT MAT



F.J.S. DESIGNED CHECKED S.F.M. S.A.P. DRAWN CHECKED S.F.M.