11-17-2017 LETTING ITEM 028

FOR INDEX OF SHEETS, SEE SHEET NO. 2

Ο

0

0


0

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

PROPOSED BRIDGE MAINTENANCE

FAP ROUTE 310 (US 67/IL 100) SECTION (86) BDR-1, BJR-2 PROJECT NHPP-C2QN(008) BRIDGE DECK REPAIRS CASS COUNTY

C-96-079-17




FULL SIZE PLANS HAVE BEEN PREPARED USING STANDARD ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED.


J.U.L.I.E. JOINT UTILITY LOCATION INFORMATION FOR EXCAVATION 1–800–892–0123 OR 811


BRIDGE MAINTENANCE ENGINEER: BRANDON DUDLEY (217) 785-9290

GROSS LENGTH = 3,655 FT. = 0.69 MILE NET LENGTH = 3,655 FT. = 0.69 MILE

CONTRACT NO. 72K15







PRINTED BY THE AUTHORITY OF THE STATE OF ILLINOIS

INDEX OF SHEETS


- 1 COVER SHEET 2 INDEX OF SHEETS, GENERAL NOTES, & SIGNATURES 3 SUMMARY OF QUANTITIES 4–6 TRAFFIC CONTROL DETAILS 7 WIDTH RESTRICTION SIGNING DETAIL 8–13 BRIDGE PLANS

HIGHWAY STANDARDS

00000106
001001–02
001006
701001–02
701006–05
701201–04
701321–16
704001–08
701901-06
782006

ESTIMATE	D PATCHING SCHEDULE
	DECK SLAB
SPAN	REPAIR (PARTIAL)
	(SO YD)
1	26
2 3	29
3.	41
4	43
5	14
- 6	56
7 .	45 .
- 8	58
9	127
10	241
11	91
12	119
13	68
14	124
15	125
16	67
17	26
TOTAL	1700
- TOTAL	1300

GENERAL NOTES:



	USER NAME = dudleybm	DESIGNED -	REVISED -			JNDEX OF	CHEETS	STAND/	
	· ·	DRAWN -	REVISED -	STATE OF ILLINOIS					,
	PLOT SCALE = 100.0000 * / in.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION	N4C	ITES, SCED	ULES OF	QUANIII	TIES, & SI
	PLOT DATE = 8/23/2017	DATE -	REVISED -		SCALE:	SHEET	OF	SHEETS	STA.

STATE OF ILLINOIS MENT OF TRANSPORTATION VISION OF HIGHWAYS DISTRICT 6	
Wayst 8th 20 17 Wygungen INGINEER OF OPERATIONS	
Aug 17 ² 20_17 Manual 20_17 ENGINEER OF PROJECT IMPLEMENTATION	
AUGUST 8 20 17 AND ENGINEER OF PROGRAM DEVELOPMENT	


RDS, GENERAL ES, & SIGNATURES		SEC	SECTION			TOTAL SHEETS	SHEET NO.
		(86) SDR	-1, BJR-	2	CA\$5	13	2
					CONTRACT	NO. 72	2K15
TA. TO STA.			ILLUIOIS	FED. AI	IU PROJECT		

			[0-01288-6001		
			~	80% FED. 20% STATE		
CODE NO.	ITEM	UNIT	TOTAL QUANTITY	BRIDGE 0047 URBAN	CODE NO.	ITEM
50102400	CONCRETE REMOVAL	CU YD	14.1	14.1	X7015005	CHANGEABLE MESSAGE SIGN
50300255	CONCRETE SUPERSTRUCTURE	CU YD	15.0	15.0	X7200201	WIDTH RESTRICTION SIGNING
50300300	PROTECTIVE COAT	SQ YD	43	43	Z0016001	DECK SLAB REPAIR (FULL DEPTH, TYPE I)
50800205	REINFORCEMENT BARS, EPOXY COATED	POUND	2250	2250	Z0016002	DECK SLAB REPAIR (FULL DEPTH, TYPE II
50800515	BAR SPLICERS	EACH	60	60	Z0016200	DECK SLAB REPAIR (PARTIAL)
52000110	PREFORMED JOINT STRIP SEAL	FOOT	99	99		·
67100100	MOBILIZATION	L SUM	1	1		
70100405	TRAFFIC CONTROL AND PROTECTION, STANDARD 701321	EACH	1	1		
70100450	TRAFFIC CONTROL AND PROTECTION, STANDARD 701201	L SUM	1	1		· · · · · · · · · · · · · · · · · · ·
70106500	TEMPORARY BRIDGE TRAFFIC SIGNALS	EACH	1	1		
70400100	TEMPORARY CONCRETE BARRIER	FOOT	750	750	·	
70400200	RELOCATE TEMPORARY CONCRETE BARRIER	FOOT	750	750		
70600240	IMPACT ATTENUATORS, TEMPORARY (NON-REDIRECTIVE), TEST LEVEL 2	EACH	2	2		
70600340	IMPACT ATTENUATORS, RELOCATE (NON-REDIRECTIVE), TEST LEVEL 2	EACH	2	2		


USER NAME = dudleybm	DESIGNED -	REVISED -						
	DRAWN -	REVISED -	STATE OF ILLINOIS		SUN	MARY OF QU	JANTITI	
PLOT SCALE = 100.0000 ' / in.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION					
PLOT DATE = 8/23/2017	DATE -	REVISED -		SCALE:	SHEET C	SUMMARY OF QUANTIT		

			0-01288-600
			80% FED. 20% STATE
			BRIDGE
		TOTAL	0047
	UNIT	QUANTITY	URBAN
	CAL DAY	200	200
		200	200
	L SUM	1	1
·····.			
	SQ YD	5.	5
	SO YD	5	5
	30 10		
	SQ YD	1 300	1 300
		i	
		1	

NTITIES		SECTION	COUNTY	TOTAL SHEE SHEETS NO.		
		(86) BDR-1, BJR-2	CASS	13	3	
			CONTRACT	NO. 72	2K15	
STA. TO STA.		ILLINOIS FED.	AID PROJECT			



USER NAME = dudleybm	DESIGNED -	REVISED -		TRAFFIC CONTROL DETAIL STAGE I		TRAFFIC CONTROL DETAIL					SECTION	COUNTY	TOTAL	SHEET
	DRAWN -	REVISED -	STATE OF ILLINOIS									CASS	13	4
PLOT SCALE = 100.0000 ' / in.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION							CONTRACT	NO. 72	K15		
PLOT DATE = 8/23/2017	DATE -	REVISED -		SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT				




LOT SCALE = 100.0000 ' / in. PLOT DATE = 8/23/2017

DATE

REVISED

SCALE: SHEET OF

CONTROL DETAIL				SECTION	COUNTY	TOTAL SHEETS	SHEET NO.			
STAGE II		310	(86) BDR-1, BJR-2	CASS	13	5				
STAGE II					CONTRACT	NO. 72	2K15			
SHEETS	STA.	TO STA.		ILLINOIS FED. AID PROJECT						



PLOT DATE = 8/23/2017


DATE

REVISED


SHEET OF SHEETS

SCALE:

OL DETAIL [RTE.	SECTION			COONTI	SHEETS	NO.
& IV				(86) BDR	-1, BJR-2	2	CASS	13	6
							CONTRAC	T NO. 7	2K15
S	STA.	TO STA.	ILLINOIS FED. A				D PROJECT		




USER NAME = dudleybm	DESIGNED -	REVISED -					
	DRAWN -	REVISED -	STATE OF ILLINOIS		WIDTH	RESTRIC	CTION SIG
PLOT SCALE = 100.0000 ' / in.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION				
PLOT DATE = 8/23/2017	DATE -	REVISED -		SCALE:	SHEET	OF	SHEETS




ITEM	UNIT	QUANTITY
1/	Cu. Yd.	14.1
tructure	Cu. Yd.	15.0
	Each	60
ars, Epoxy Coated	Pound	2250
Strip Seal	Foot	99
	. Sq. Yd.	43
r (Partial)	Sq. Yd.	1300
r (Full Depth, Type I)	Sq. Yd.	5
r (Full Depth, Type II)	Sq. Yd.	5

& ELEVATION -0001		F.A.P. RTE.	SECTION		COUNTY	TOTAL SHEETS	SHEET NO.
		310	(86) BDR-1, BJ	R-2	CASS	13	8
					CONTRAC	T NO. 72	2K15
EETS STA.	TO STA.		ILLINC	IS FED, A	ID PROJECT		



ECTION	-	SPANS	9-13	3

SECTIONS			F.A.P. RTE	SEC				TOTAL SHEETS	SHEET NO.	
0001		310 (86) BDR-1, BJR-2				2	CASS	CASS 13 9		
							CONTRACT	NO. 72	2K15	
ΤS	STA.	TO STA.			ILLINOIS	FED. A	D PROJECT			





USER NAME = dudleybm	DESIGNED -	REVISED -				ΙΟΙΝ	IT DETAI
	DRAWN -	REVISED -	STATE OF ILLINOIS				
PLOT SCALE = 100.0000 ' / in.	CHECKED REVISED DEPARTMENT OF TRANSPORTATION			SNU	009-000		
PLOT DATE = 8/23/2017	DATE -	REVISED -		SCALE:	SHEET 3	OF 6	SHEETS

BILL OF MATERIAL (3 JOINTS	BILL
----------------------------	------


Bar	No.	Size	Length	Shape
a(E)	120	#5	14′-8′′	
a _I (E)	36	4'-0''		
d(E)	36	5′-2″	4	
Concrete	Removal		Cu. Yd.	14.1
Concrete	Superstru	ucture	Cu. Yd.	15.0
Bar Splic	ers	Each	60	
Reinforce Epoxy Co		Pounds	2250	

AILS 0001		F.A.P. RTE SECTION			COUNTY	TOTAL SHEETS	SHEET NO.	
		310 (86) BDR-1, BJR-2			CASS	13	10	
					CONTRACT	NO. 72	NO. 72K15	
TS STA. TO STA.			ILLINOIS	FED. A	ID PROJECT			





The pay items for Preformed Joint Strip Seal shall be to the end of the steel plate. The 6" of rubber extending past the end of the steel shall be considered incidental and and shall not be measured for payment.



conforming to Article 1006.32 of the Std. Specs., automatically end welded.

USER NAME = dudleybm	DESIGNED -	REVISED -			PREFORMED JOINT STRIP SEAL				F.A.P. RTE	SECTION	C	SUNTY g	TOTAL SHEET SHEETS NO.	
	DRAWN -	REVISED -	STATE OF ILLINOIS		SN 009-0001		310	(86) BDR-1, BJF	-2	CASS	13 11			
PLOT SCALE = 100.0000 / in	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION	21/ 003-0001					СС	NTRACT	NO. 72K15			
PLOT DATE = 8/23/2017	DATE -	REVISED -		SCALE:	SHEET 4	OF 6	SHEETS	STA.	TO STA.		ILLINOI	S FED. AID PRO	J. AID PROJECT	

Notes:

The strip seal shall be made continuous and shall have a minimum thickness of $\frac{1}{4}$ ". The configuration of the strip seal shall match the configuration of the locking edge rails. Open or "webbed" strip seal gland configurations are not permitted. The gland shall be sized for a maximum rated movement of 4 inches.

The locking edge rails depicted are configured for typical applications and are conceptual only. The actual configuration of the locking edge rails and matching strip seal may vary from manufacturer to manufacturer provided they fit the application and meet the minimum anchorage shown. Flanged edge rails, however, will not be allowed. Locking edge rails may exceed the 4¹/₂" maximum depth provided the anchorage system is revised according to the manufacturer's recommendation.


The manufacturer's recommended installation methods shall be followed.

All steel components shall be galvanized after fabrication according to Article 520.03 of the Standard Specifications.

The Maximum space between locking edge rail segments shall be $\frac{3}{16}$ " and sealed with a suitable sealant; however, any rail joint within 10' measured perpendicular to the face of the curb or parapet shall be welded as shown in the locking edge rail splice detail.

Cost of parapet sliding plates, embedded plates, and anchorage studs included with Preformed Joint Strip Seal.

34" F-shape barrier shown, 42" F-shape similar as noted. The concrete opening below the strip seal will vary based on the locking edge rail chosen by the Contractor. Deck and parapet lengths shown elsewhere in the plans are dimensioned to the concrete opening, not the joint opening, and are based on the rolled locking edge rail. If the Contractor elects to use a different locking edge rail, dimensional adjustments may be required. One exception to this would be the strip seal joint at the end of the precast bridge approach slab. For these cases the pavement connector length shall be adjusted, not the length of the bridge approach slab.




LOCKING EDGE RAIL SPLICE

The inside of the locking edge rail groove shall be free of weld residue. Rolled rail shown, welded rail similar.


<u>BILL OF MATERIAL</u>

Item	Unit	Total
Preformed Joint Strip Seal	Foot	99




- Threaded splicer bar length = min. lap length + l_2'' + thread length
- * Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Location	Bar size	No. assemblies required	Minimum Iap length
Joints	#5	60	3′ 6"



INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.
"B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.
(E) : Indicates epoxy coating.



BSD-1

6 - *8 - 1*5

JSER NAME = dudleybm DESIGNED -REVISED BAR SPLIC STATE OF ILLINOIS DRAWN REVISED SN 009-00 **DEPARTMENT OF TRANSPORTATION** LOT SCALE = 100.0000 ' / in. CHECKED REVISED REVISED SCALE: SHEET 5 OF 6 SHEET PLOT DATE = 8/23/2017 DATE

Reinforce

alternatives.

	Stage line if applicable
Stage I construction	Stage II construction
	Mechanical Coupler (E)
844444444444444444444444444444444444444	······································
rement bar _	Reinforcement bar

STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required

<u>NOTES</u>

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

All reinforcement shall be lapped and tied to the splicer bars. Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications. See approved list of bar splicer assemblies and mechanical splicers for

ERS 001		F.A.P. RTE	SECTION			COUNTY	TOTAL SHEETS	SHEET NO.	
		310	(86) BDR-1, BJR-2			CASS	13	12	
		CONTRACT NO. 72K15					2K15		
S	STA.	TO STA.			ILLINOIS	FED. A	ID PROJECT		

