FOR INDEX OF SHEETS, SEE SHEET NO. 2 FOR INDEX OF HIGHWAY STANDARDS, SEE SHEET NO. 2

FUNCTIONAL CLASSIFICATION MINOR COLLECTOR

TRAFFIC DATA **DUBOIS BOULEVARD** ADT (2018) = 1,175, ADT (2050) = 1,370 **BURLINGTON AVENUE** ADT (2018) = 600, ADT (2050) = 700

POSTED SPEED LIMIT **DUBOIS BOULEVARD = 25 MPH** BURLINGTON AVENUE = 25 MPH

DESIGN SPEED LIMIT **DUBOIS BOULEVARD = 30 MPH BURLINGTON AVENUE = 30 MPH**



Phone: 708-865-0300

STA: 1+47.00

- ♦ Civil Engineers
- Municipal Consultants
- ◆ Established 1911

SCALE: 1"= 10"

SCALE: 1"=60"

FULL SIZE PLANS HAVE BEEN PREPARED USING STANDARD

ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED.

J.U.L.LE. JOINT UTILITY LOCATION INFORMATION FOR EXCAVATION 1-800-892-0123

Contact the Metropolitan Water Reclamation District of Greater Chicago 2 days before starting work.

P (708) 588-4055

F WMOJobStart@mwrd.org

STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION

PLANS FOR PROPOSED FEDERAL AID HIGHWAY

MUN 4020(DUBOIS BOULEVARD) OGDEN AVENUE (ÚS 34) TO BURLINGTÓN AVENUE MUN 4020 (BURLINGTON AVENUE) **DUBOIS BOULEVARD TO GROVE AVENUE ROADWAY CONSTRUCTION AND RESURFACING** SECTION NO.: 20-00133-00-FP PROJECT NO.: ZLI3(141) VILLAGE OF BROOKFIELD **COOK COUNTY**

C-91-093-23 SHERIDAN (NOT TO SCALE) BEGIN PROJECT BEGIN OMISSION END PROJECT STA: 51+51.00 STA: 24+18.00 SECTION 3, TOWNSHIP 38, RANGE 12

PAU ROUTE NO. SECTION COUNTY PARTS
2072/4020 20-00133-00-FP CODK /67 ELENOIS PROJECT C-01-013-21



LOCATION OF SECTION INDICATED THUS:

STATE OF ILLINOIS ILLINOIS DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS SECONORUS 12 Course Con

TO THE BEST OF MY KNOWLEDGE AND BELIEF, THE DRAINAGE OF SURFACE WATER WILL NOT BE CHANGED BY THE PROPOSED DEVELOPMENT. IF ANY WATER WILL NOT BE CHANGED BY THE PROPOSED DEVELOPMENT. IF ANY DRAINAGE PATTERNS WILL BE CHANGED, REASONABLE PROVISIONS HAVE BEEN MADE FOR THE COLLECTION AND DIVERSION OF SUCH SURFACE WATERS IN TO THE PUBLIC AREA, OR DRAINS APPROVED FOR THE USE BY THE MUNICIPAL ENGINEER, AND THAT SUCH BURFACE WATERS ARE PLANNED FOR IN ACCORDANCE WITH GENERALLY ACCEPTED ENGINEERING PRACTICES SO AS TO REDUCE THE LIKELIHOOD OF



8-7-2023 LICENSEEXPERS: 11-30-22

> PRINTED BY THE AUTHORITY OF THE STATE OF ILLINOIS

FEDERAL AID PROGRAM DESIGN ENGINEER; CARMEN E. RAMOS,P.E.,

SCHAUMBURG,

CONTRACT NO. 61J89

GROSS LENGTH OF IMPROVEMENT = 5,004 FT = 0.948 MI NET LENGTH OF IMPROVEMENT = 4,857 FT = 0.920 MI

LOCATION MAP

DESCRIPTION TITLE SHEET, LOCATION MAP INDEX OF SHEETS, LEGEND, AND IDOT HIGHWAY STANDARDS

M.W.R.D.G.C. ROUTE OUTLET MAP

SIGNING PLAN LEGEND AND NOTES

DETECTOR LOOP REPLACEMENT PLAN

IDOT DISTRICT ONE DETAILS

STATION CROSS SECTIONS

LANDSCAPING PLAN

PAVEMENT MARKING AND SIGNING PLAN

3	GENERAL NOTES
4	M.W.R.D.G.C. GENERAL NOTES
5-13	SUMMARY OF QUANTITIES
14-15	TYPICAL SECTIONS
16	EARTHWORK QUANTITIES
17-19	ALIGNMENT, TIES, AND BENCHMARKS
20-31	PAVING PLAN AND PROFILE
32-34	ROADWAY DETAILS
35-56	MAINTENANCE OF TRAFFIC PLAN, STAGE CONSTRUCTION PLAN
57	DETOUR PLAN
58-61	EROSION CONTROL PLAN AND SWPPP
62-73	UTILITIES PLAN AND PROFILE
74-78	DRAINAGE AND UTILITIES DETAILS

79

80

81-83

84-86 87

88-96

97-107

SHEET NO.

		(TO BE USED IN CONJUNCTION V	JUNCTION WITH I.D.O.T. STANDARD 000001-08)						
EXISTING PROPOSED		DESCRIPTION	EXISTING	PROPOSED	DESCRIPTION				
Ø	ø	POWER POLE							
Δ		GAS VALVE			STORM SEWER TO BE REMOVED				
→		STREET LIGHT			STORM SEWER PIPE				
Ø	•	WATER MAIN BUFFALO BOX	——<(- <u></u>	 (COMBINATION SEWER PIPE				
\otimes	8	WATER MAIN VALVE BOX			SANITARY SEWER PIPE				
\$		SPRINKLER			UNDERDRAIN				
		WATER MAIN VALVE VAULT	Wı	W	WATER MAIN				
	_	STORM INLET	———E———		ELECTRIC LINE				
Я	A	FIRE HYDRANT	G		GAS LINE				
$igotimes_{RM}$		EXISTING STRUCTURE TO BE REMOVED	——т—		TELEPHONE LINE				
$igttimes_{_{\mathbf{F}}}$		EXISTING STRUCTURE TO BE FILLED	=====		CURB AND GUTTER				
⊗ _{RM}		TREE TO BE REMOVED			EXISTING CURB AND GUTTER TO BE REMOVED				
○		BUSH			DIRECTION OF FLOW				
	•	NEW TREE			DRAINAGE SUMMIT				
\bigcirc		TREE		Ψ	DRAINAGE SUMMIT				
		EVERGREEN TREE	XXX	627.75	WATER MAIN VALVE VAULT				
· V	TP	TREE TRUNK PROTECTION	XXXX	620.50	RIM AND TOP OF PIPE ELEVATION				
	RP	ROOT PRUNING	XXX	4' DIA. MH R:622.05 617.35 8"N	COMBINATION MANHOLE RIM AND INVERT ELEVATION				
		NON-SPECIAL WASTE DISPOSAL		4' DIA. MH	STORM SEWER MANHOLE/CATCHBASIN				
		EXISTING CONCRETE SIDEWALK TO BE REMOVED	XXX	R:622.05 617.35 8"N	RIM AND INVERT ELEVATION				
		EXISTING CONCRETE DRIVEWAY TO BE REMOVED		Α	STRUCTURE TO BE ADJUSTED				
		EADTH EVOLVATION		1C	TYPE 1 FRAME & CLOSED LID				
		EARTH EXCAVATION		1P	TYPE 1 FRAME & OPEN LID				
		PROPOSED CONCRETE PAVEMENT/SIDEWALK		RC	RECONSTRUCT EXISTING STRUCTURE				
		PROPOSED HOT MIX ASPHALT PAVING	643.90 ×	632.25 _×	GROUND ELEVATIONS				

DISTRICT ONE DETAILS

TRAFFIC CONTROL AND PROTECTION FOR		HIGHWAY STANDARDS D	RAWINGS	
SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS (TC-10)	STANDARD NO.	TITLE OR DESCRIPTION	STANDARD NO.	TITLE OR DESCRIPTION
DISTRICT ONE TYPICAL PAVEMENT MARKINGS (TC-13)	000001-08	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS	720011-01	METAL POSTS FOR SIGNS, MARKERS AND DELINEATORS
DETOUR SIGNING FOR CLOSING STATE HIGHWAYS (TC-21)	280001-07	TEMPORARY EROSION CONTROL SYSTEMS	720016-04	MAST ARM MOUNTED STREET NAME SIGNS
ARTERIAL ROAD INFORMATION SIGN (TC-22)	424001-11	PERPENDICULAR CURB RAMPS FOR SIDEWALKS	729001-01	APPLICATIONS OF TYPES A&B METAL POSTS
DRIVEWAY ENTRANCE SIGNING (TC-26)	442101-09	CLASS B PATCHES	780001-05	TYPICAL PAVEMENT MARKINGS
RAILROAD CROSSING REPAIR DETOUR SIGNING (TC-28)	542001-06	CONCRETE END SECTIONS FOR PIPE CULVERTS 15" (375 MM) THRU 84" (2100 MM) DIA		DETECTOR LOOP INSTALLATIONS
• • • • • • • • • • • • • • • • • • • •	601001-05 602601-06	PIPE UNDERDRAINS	886006-01	TYPICAL LAYOUTS FOR DETECTION LOOPS
BUTT JOINTS AND HMA TAPER DETAILS (BD-32)		PRECAST REINFORCED CONCRETE FLAT SLAB TOP		
DISTRICT ONE STANDARD TRAFFIC SIGNAL DESIGN DETAILS (TS-05)	701006-05	OFF-RD OPERATIONS, 2L, 2W, 15' (4.5M) TO 24"(600MM) FROM PAVEMENT EDGE		
DISTRICT 1 - DETECTOR LOOP INSTALLATION DETAILS (TS-07)	701011-04	OFF-RD MOVING OPERATIONS, 2L, 2W, DAY ONLY		
	701301-04	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS		
	701311-03	LANE CLOSURE, 2L, 2W, MOVING OPERATIONS-DAY ONLY		
	701501-06	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED		
	701701-10	URBAN LANE CLOSURE, MULTILANE INTERSECTION		
	701801-06	SIDEWALK, CORNER OR CROSSWALK CLOSURE		
	701901-08	TRAFFIC CONTROL DEVICES		
	720001-01	SIGN PANEL MOUNTING DETAILS		
	720006-04	SIGN PANEL ERECTION DETAILS		

	DESIGNED -	X	REVISED -
3 Roosevelt Road ster, IL, 60154-2780	DRAWN -	ECW, SFB, DMM, GD	REVISED -
one: 708-865-0300 w.ehancock.com	CHECKED -	XXX	REVISED -
w.enuncock.com	DATE -	8-7-23	REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

INDEX (EGENE Vay si		SYMBOLS, AND ARDS
SCALE: NONE	SHEET NO.	1	OF	1	SHEETS	STA.	TO STA.

F.A.U. RTE.	SECT	COUNTY	TOTAL SHEETS	SHI	
0655	20-0013	3-00-FP	соок	107	:
FIELD B	OOK NO.:	CONTRACT NO	O. 61J89		
FED. R	OAD DIST. NO. 1	. AID PROJECT			

- WHEN WORK COMMENCES, THE CONTRACTOR SHALL ASSUME THE MAINTENANCE OF ANY PAVEMENT, SHOULDERS, DRAINAGE FACILITIES, TRAFFIC CONTROL SIGNS, PAVEMENT MARKINGS, AND OTHER APPURTENANCES ON ROADWAYS WITHIN THE LIMITS OF THE CONTRACT THAT ARE TO BE USED BY THE PUBLIC DURING CONSTRUCTION AND TO RETAIN THIS MAINTENANCE RESPONSIBILITY UNTIL PROJECT COMPLETION. NEED FOR SNOW AND ICE CONTROL DURING THE CONSTRUCTION PERIOD SHALL BE
- CONTRACTOR SHALL TAKE PRECAUTION BY PRESERVING EXISTING TREES WITHIN THE RIGHT OF WAY. IF ANY DAMAGE OCCURS, TREE SHALL BE REPLACED IN KIND PER ARTICLE 201.07 REPAIR OR REPLACEMENT OF EXISTING PLANT MATERIAL REQUIREMENTS STATED HEREIN.
- THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE OR VILLAGE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE ENGINEER.
- THE CONTRACTOR SHALL MAINTAIN ACCESS FOR EMERGENCY VEHICLES AND GARBAGE TRUCKS AT ALL TIMES. IF THE GARBAGE TRUCKS ARE NOT ABLE TO HAVE ACCESS TO ALL OF THE PROPERTIES WITHIN THE PROJECT LIMITS, THEN THE CONTRACTOR SHALL PLACE ANY GARBAGE THAT IS AFFECTED IN A LOCATION WHERE THE GARBAGE TRUCKS CAN PICK IT UP. THE CONTRACTOR SHALL RETURN THE GARBAGE CANS TO THE PARKWAY OF THE RESPECTIVE PROPERTY BY THE END OF THE DAY
- 6. THE CONTRACTOR WILL BE RESPONSIBLE FOR PROVIDING WRITTEN NOTICE TO ALL RESIDENCES AND/OR PLACES OF BUSINESS IN THE WORK ZONE AT LEAST ONE (1) WORKING DAY PRIOR TO PERFORMING ANY CONSTRUCTION ACTIVITY THAT WILL ELIMINATE ACCESS TO THEIR PROPERTY. THE ITTEN NOTICE SHALL BE APPROVED BY THE ENGINEER AND COORDINATED WITH THE VILLAGE PRIOR TO THE BEGINNING OF CONSTRUCTION.
- IT IS THE CONTRACTOR'S SOLE RESPONSIBILITY TO COORDINATE WITH THE BNSF RAILROAD WHENEVER CONSTRUCTION ACTIVITY IS WITHIN 25 FEET OF THE RAILROAD ROW. THE CONTRACTOR SHALL RETAIN FLAGMEN EMPLOYED AND DESIGNATED BY THE BNSF RAILROAD TO MONITOR ON-COMING TRAIN TRAFFIC, AND ADVISE CONTRACTOR PERSONNEL WHEN ACTIVITY ON OR NEAR THE RAIL ROAD ROW MAY OCEED. THIS ITEM WILL BE PAID FOR ACCORDING TO ARTICLE 107.12 AND WILL BE REIMBURSDED ACCORDING TO ARTICLE 109.05.
- 8. BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 811 FOR FIELD LOCATIONS OF BURIED ELECTRICAL, TELEPHONE AND GAS FACILITIES. (48 HOURS NOTIFICATION IS
- THE LOCATIONS OF THE UNDERGROUND UTILITIES IF SHOWN ON THE PLANS HAVE BEEN OBTAINED BY FIELD SURVEYS AND SEARCHES OF AVAILABLE RECORDS. THE VILLAGE OF BROOKFIELD, THE ILLINOIS DEPARTMENT OF TRANSPORTATION AND/OR OTHER OFFICES AND AGENCIES ASSOCIATED WITH THE DEVELOPMENT OF THESE PLANS DO NOT GUARANTEE THEIR ACCURACY OR COMPLETENESS. THE CONTRACTOR SHALLL BE REQUIRED TO VERIFY THE EXACT LOCATION OF EACH FACILITY WITH THE UTILITY COMPANY, AND SHALL TAKE DUE CARE IN ALL PHASES OF THE CONSTRUCTION TO PROTECT ANY SUCH FACILITIES WHICH MAY BE AFFECTED BY THE WORK. ANY DAMAGE TO EXISTING UTILITIES DURING CONSTRUCTION ACTIVITIES SHALL BE REPAIRED OR REPLACED TO THE SATISFACTION OF THE
- 10. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGE OF BROOKFIELD.
- 11. ADJUSTMENTS REQUIRED BY UTILITY COMPANIES WILL BE PERFORMED BY THE COMPANY INVOLVED OR ITS CONTRACTOR, BUT WILL BE COORDINATED BY GENERAL CONTRACTOR.

THE CONTRACTOR SHALL USE EXTREME CAUTION IN THE REMOVAL OF ABANDONED EXISTING GAS LINES SINCE RESIDUAL MATERIALS CONTAINED THEREIN ARE HIGHLY EXPLOSIVE, FLAMMABLE, AND TOXIC. ONCE THE MAINS ARE ABANDONED BY THE OWNER, THE CONTRACTOR SHALL ASSUME ALL RESPONSIBILITY FOR ANY DAMAGE AND/OR INJURY OCCURRING ON THE PROJECT DUE TO HIS/HER OPERATIONS NEXT TO THE MAINS AND/OR THE METHOD OF REMOVAL OF THE ABANDONED MAINS.

CONSTRUCTION NOTES

- 1. THE SUBGRADE STABILITY BE VERIFIED BY PROOF ROLLING WITH A FULLY LOADED TANDEM-AXLE
- 2. GEOTECHNICAL FABRIC FOR GROUND STABILIZATION AND/OR AGGREGATE SUBGRADE IMPROVEMENT (CU YD) HAVE BEEN PROVIDED FOR USE AT THE LOCATIONS INDICATED FOR SOILS THAT TEND TO BE UNSTABLE AND/OR UNSUITABLE. THE ACTUAL NEED FOR REMOVAL AND REPLACEMENT WITH ABOVE ITEM WILL BE DETERMINED IN THE FIELD AT THE TIME OF CONSTRUCTION BY THE GEOTECHNICAL ENGINEER. ALL POTENTIALLY UNSTABLE SOILS SHOULD BE TESTED WITH A STATIC OR DYNAMIC CONE PENETROMETER AND TREATED IN ACCORDANCE WITH ARTICLE 301.04 OF THE SSRBC AND IDOT SUBGRADE STABILITY MANUAL. IF UNSTABLE AND/OR UNSUITABLE SOILS ARE NOT ENCOUNTERED, THEN THE QUANTITY SHALL BE DEDUCTED AND NO ADDITIONAL COMPENSATION WILL BE DUE TO THE
- ANY AGGREGATE SUBGRADE IMPROVEMENT CONTAMINATED AND/OR DAMAGED BY THE CONTRACTOR'S VEHICLES AND/OR EQUIPMENTS IS TO BE REMOVED AND REPLACED AS DIRECT BY THE ENGINEER AT CONTRACTOR EXPENSE
- 4. THE AGGREGATE GRADATION FOR THE AGGREGATE SUBGRADE IMPROVEMENT 12" LOWER LIFT SHALL
- WHEN REMOVING PAVEMENT AND/OR OTHER STRUCTURES, THE CONTRACTOR SHALL NOT USE ANY TYPE OF CONCRETE BREAKERS SUCH AS DROP HAMMERS. THAT MIGHT DAMAGE UNDERGROUND
- THE CONTRACTOR SHALL SAW CUT ASPHALT PAVEMENT AS INDICATED ON THE PLANS TO SEPARATE THE EXISTING PAVEMENT TO BE REMOVED BY APPROVED MEANS OR AN APPROVED CONCRETE SAW TO A DEPTH AS DIRECTED BY THE ENGINEER. SUITABLE GUIDELINES OR DEVICES SHALL BE USED TO ASSURE CUTTING A NEAT, STRAIGHT LINE AS SHOWN ON THE PLANS. CARE SHALL BE TAKEN BY THE CONTRACTOR AS NOT TO DAMAGE THE REMAINING PAVEMENT DIRECTLY ADJACENT TO THE PAVEMENT TO BE REMOVED. ANY DAMAGE TO THE EXISTING PAVEMENT RESULTING FROM PAVEMENT REMOVAL OPERATIONS SHALL BE REPAIRED TO THE SATISFACTION OF THE ENGINEER.
- 7. A BUTT JOINT WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT) IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.
- WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1½ INCHES (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H) OR LESS AND 1 INCH (25 MM) WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (80 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75 MM) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H)
- 9. THE CONTRACTOR WILL BE REQUIRED TO SCHEDULE THEIR OPERATIONS SO THAT NO SECTIONS OF PAVEMENT ALONG THE CENTERLINE WILL HAVE A COLD JOINT OVERNIGHT
- 10. PAVEMENT PATCHING OF UTILITY TRENCHES AS REMOVED IN STAGE I OF THE MAINTENANCE OF TRAFFIC PLAN SHALL BE PAID FOR AS 44000100 PAVEMENT REMOVAL AND 35300300 PORTLAND CEMENT BASE COURSE 8". ALL OTHER PAVEMENT PATCHES SHALL BE PAID FOR AS CLASS B
- 11. LOCATIONS OF CLASS B PATCHES ON PLANS ARE APPROXIMATE. EXACT LOCATIONS WILL BE DETERMINED IN THE FIELD BY ENGINEER. CLASS B PATCHES LOCATED WITHIN THE THROUGH LANES SHALL BE MADE ACCESSIBLE TO TRAFFIC AT THE END OF EACH WORK DAY.
- 12. PAVEMENT PATCHING SHALL BE STAGED TO MAINTAIN TWO-WAY TRAFFIC AT ALL TIMES.

UNDERGROUND NOTES

- PIPE UNDERDRAINS SHALL BE INSTALLED ACCORDING TO SECTION 601 OF THE SSRBC AND STANDARD 601001-05. TOP OF PIPE UNDERDRAINS SHALL BE PLACED MINIMUM 6" BELOW THE AGGREGATE SUBGRADE IMPROVEMENT LAYER. THE COST OF MAKING PIPE UNDERDRAIN CONNECTIONS TO DRAINAGE STRUCTURES SHALL BE INCLUDED IN THE COST OF THE PIPE UNDERDRAINS.
- BACKFILLING STORM SEWER CONSTRUCTED UNDER THE ROADWAY SPECIFIED UNDER ART. 550.07 (b, c) OF THE SSRBC WILL NOT BE ALLOWED.
- SANITARY SEWER SERVICE CONNECTION LENGTHS SHOWN ON PLAN ARE ESTIMATED. CONTRACTOR TO VERIFY IN FIELD SERVICE PIPE QUALITY AND GRADE WHEN MAKING CONNECTIONS TO EXISTING PIPE. SPECIAL ATTENTION SHOULD BE PAID TO CROSSINGS AT PURPOSED STORM SEWER PIPE. UNLESS SHOWN OTHERWISE ON PLAN, ASSUMED SANITARY SERVICE PIPE LENGTH TO COMPLETE CONNECTION IS 4.
- 4. THE TYPE OF THE FRAMES AND GRATES REQUIRED FOR ALL CATCH BASINS AND MANHOLE LISTED IN THE SUMMARY OF QUANTITIES MAY BE FOUND ON THE PLANS AT THEIR RESPECTIVE LOCATIONS. WHERE LIDS ARE CALLED FOR ON THE PLANS, THEY SHALL BE IN ACCORDANCE WITH ARTICLE 604.01 OF TH STANDARD SPECIFICATIONS AND THE TERM LID IS USED IN LIEU OF GRATE.

THE WORD "WATER", "SANITARY", OR "STORM" SHALL BE CAST INTO THE LID OF EACH RESPECTIVE MANHOLE OR VALVE VAULT.

- 5. ON ALL IMPROVEMENTS, THE FRAMES AND LIDS OF EXISTING CATCH BASINS, INLETS, MANHOLES, AND VALVE VAULTS WHICH ARE TO BE ABANDONED DUE TO CONSTRUCTION OF THIS IMPROVEMENT ARE TO REMAIN THE PROPERTY OF THE VILLAGE OF BROOKFIELD AND BE SALVAGED. THE CONTRACTOR SHALL DELIVER FRAMES AND LIDS TO THE VILLAGE OF BROOKFIELD LOCATED AT 4545 EBERLY AVE, 3ROOKFIELD. IL 60513 (708) 485-734
- THE CONTRACTOR SHALL CONDUCT OPERATIONS AS TO MAINTAIN AT ALL TIMES FLOW THROUGH EXISTING STORM AND SAN ITARY SEWER SYSTEMS. THE CONTRACTOR SHALL ALSO PROVIDE AND MAINTAIN AN EFFICIENT PUMPING PLANT IF NECESSARY AND A TEMPORARY OUTLET AND BE PREPARED AT ALL TIMES TO DISPOSE OF THE WATER COLLECTED IN A SAFE MANNER WITHOUT DAMAGE OF ANY KIND TO ADJACENT PROPERTIES. THE ENDS OF EXISTING DRAINAGE LINES THAT ARE NOT TO BE INCORPORATED INTO THE PROJECT SHALL BE SEALED AS SPECIFIED IN THE SPECIAL PROVISIONS. EXISTING STRUCTURES ARE TO BE INSPECTED BEFORE CONSTRUCTION STRATS - ANY ACCUMULATION OF MATERIAL IN THE STRUCTURE DUE TO CONSTRUCTION OPERATIONS SHALL BE REMOVED BY THE CONTRACTOR.
- ALL ABANDONED SANITARY SEWERS SHALL BE PLUGGED AT BOTH ENDS WITH AT LEAST 2 FEET LONG NON-SHRINK CONCRETE OR MORTAR PLUG. THIS WORK SHALL NOT BE PAID FOR SEPARATELY, BUT SHALL BE INCLUDED IN THE PAY ITEMS FOR REMOVING AND/OR FILLING THE VARIOUS TYPES OR

SCALE: NONE

- 1. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE APPLICABLE SECTIONS OF THE FOLLOWING,
- EXCEPT AS MODIFIED HEREIN OR ON THE PLANS:

 * STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION (LATEST EDITION), BY THE
 ILLINOIS DEPARTMENT OF TRANSPORTATION (IDOT SS) FOR ALL IMPROVEMENTS EXCEPT SANITARY
 CENTER AND MATERIAL CONSTRUCTION.
- SEWER AND WATER MAIN CONSTRUCTION;
 STANDARD SPECIFICATIONS FOR WATER AND SEWER MAIN CONSTRUCTION IN ILLINOIS, LATEST EDITION (SSWS) FOR SANITARY SEWER AND WATER MAIN CONSTRUCTION;
- * VILLAGE OF BROOKFIELD MUNICIPAL CODE; * THE METROPOLITAN WATER RECLAMATION DISTRICT OF GREATER CHICAGO (MWRD) WATERSHED
- MANAGEMENT ORDINANCE AND TECHNICAL GUIDANCE MANUAL; * IN CASE OF CONFLICT BETWEEN THE APPLICABLE ORDINANCES NOTED, THE MORE STRINGENT SHALL TAKE PRECEDENCE AND SHALL CONTROL ALL CONSTRUCTION.

- THE MWRD LOCAL SEWER SYSTEMS SECTION FIELD OFFICE MUST BE NOTIFIED AT LEAST TWO (2) WORKING DAYS PRIOR TO THE COMMENCEMENT OF ANY WORK (CALL 708-588-4055 OR SEND EMAIL NOTIFICATION WITH PROJECT NAME, LOCATION AND PERMIT NUMBER TO WMOJOBSTART@MWRD.ORG).
- 2. THE VILLAGE OF BROOKFIELD ENGINEERING DEPARTMENT AND PUBLIC MUST BE NOTIFIED AT LEAST 24 HOURS PRIOR TO THE START OF CONSTRUCTION AND PRIOR TO EACH PHASE OF WORK. CONTRACTOR SHALL DETERMINE ITEMS REQUIRING INSPECTION PRIOR TO START OF CONSTRUCTION OR EACH WORK PHASE.
- 3. THE CONTRACTOR SHALL NOTIFY ALL UTILITY COMPANIES PRIOR TO BEGINNING CONSTRUCTION FOR THE EXACT LOCATIONS OF UTILITIES AND FOR THEIR PROTECTION DURING CONSTRUCTION. IF EXISTING UTILITIES ARE ENCOUNTERED THAT CONFLICT IN LOCATION WITH NEW CONSTRUCTION, IMMEDIATELY NOTIFY THE ENGINEER SO THAT THE CONFLICT CAN BE RESOLVED. CALL J.U.L.I.E. AT 1-800-892-0123.

- ALL ELEVATIONS SHOWN ON PLANS REFERENCE THE NORTH AMERICAN VERTICAL DATUM OF 1988 (NAVD88). CONVERSION FACTOR IS 0 FT.
- 2. THE ENGINEER, IN COORDINATION WITH THE MWRD, AND THE VILLAGE OF BROOKFIELD SHALL HAVE THE AUTHORITY TO INSPECT, APPROVE, AND REJECT THE CONSTRUCTION IMPROVEMENTS.
- 3. THE CONTRACTOR(S) SHALL INDEMNIFY THE OWNER, ENGINEER, MUNICIPALITY, MWRD, AND THEIR AGENTS, ETC., FROM ALL LIABILITY INVOLVED WITH THE CONSTRUCTION, INSTALLATION, OR TESTING OF THIS WORK
- 4. THE PROPOSED IMPROVEMENTS MUST BE CONSTRUCTED IN ACCORDANCE WITH THE ENGINEERING PLANS AS APPROVED BY MWRD AND THE MUNICIPALITY UNLESS CHANGES ARE APPROVED BY MWRD, THE MUNICIPALITY, OR AUTHORIZED AGENT. THE CONSTRUCTION DETAILS, AS PRESENTED ON THE PLANS, MUST BE FOLLOWED. PROPER CONSTRUCTION TECHNIQUES MUST BE FOLLOWED ON THE IMPROVEMENTS INDICATED ON THE PLANS.
- 5. THE LOCATION OF VARIOUS UNDERGROUND UTILITIES WHICH ARE SHOWN ON THE PLANS ARE FOR INFORMATION ONLY AND REPRESENT THE BEST KNOWLEDGE OF THE ENGINEER. VERIFY LOCATIONS AND ELEVATIONS PRIOR TO BEGINNING THE CONSTRUCTION OPERATIONS.
- 6. ANY EXISTING PAVEMENT, SIDEWALK, DRIVEWAY, ETC., DAMAGED DURING CONSTRUCTION OPERATIONS AND NOT CALLED FOR TO BE REMOVED SHALL BE REPLACED AT THE EXPENSE OF THE CONTRACTOR.
- 7. MATERIAL AND COMPACTION TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE REQUIREMENTS OF THE MUNICIPALITY, MWRD, AND OWNER.
- 8. THE UNDERGROUND CONTRACTOR SHALL MAKE ALL NECESSARY ARRANGEMENTS TO NOTIFY ALL
- 9. ALL NEW AND EXISTING UTILITY STRUCTURES ON SITE AND IN AREAS DISTURBED DURING CONSTRUCTION SHALL BE ADJUSTED TO FINISH GRADE PRIOR TO FINAL INSPECTION.
- 10. RECORD DRAWINGS SHALL BE KEPT BY THE CONTRACTOR AND SUBMITTED TO THE ENGINEER AS SOON AS UNDERGROUND IMPROVEMENTS ARE COMPLETED. FINAL PAYMENTS TO THE CONTRACTOR SHALL BE HELD UNTIL THEY ARE RECEIVED. ANY CHANGES IN LENGTH, LOCATION OR ALIGNMENT SHALL BE SHOWN IN RED. ALL WYES OR BENDS SHALL BE LOCATED FROM THE DOWNSTREAM MANHOLE. ALL VALVES, B-BOXES, TEES OR BENDS SHALL BE TIED TO A FIRE HYDRANT.

D. SANITARY SEWER

- 1. THE CONTRACTOR SHALL TAKE MEASURES TO PREVENT ANY POLLUTED WATER, SUCH AS GROUND AND SURFACE WATER, FROM ENTERING THE EXISTING SANITARY SEWERS.
- A WATER-TIGHT PLUG SHALL BE INSTALLED IN THE DOWNSTREAM SEWER PIPE AT THE POINT OF SEWER CONNECTION PRIOR TO COMMENCING ANY SEWER CONSTRUCTION. THE PLUG SHALL REMAIN IN PLACE UNTIL REMOVAL IS AUTHORIZED BY THE MUNICIPALITY AND/OR MWRD AFTER THE SEWERS HAVE BEEN
- 3. DISCHARGING ANY UNPOLLUTED WATER INTO THE SANITARY SEWER SYSTEM FOR THE PURPOSE OF SEWER FLUSHING OF LINES FOR THE DEFLECTION TEST SHALL BE PROHIBITED WITHOUT PRIOR APPROVAL FROM THE MUNICIPALITY OR MWRD.
- 4. ALL SANITARY SEWER CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR WATER AND SEWER MAIN CONSTRUCTION IN ILLINOIS (LATEST EDITION).
- 5. ALL FLOOR DRAINS SHALL DISCHARGE TO THE SANITARY SEWER SYSTEM
- 6. ALL DOWNSPOUTS AND FOOTING DRAINS SHALL DISCHARGE TO THE STORM SEWER SYSTEM.
- 7. ALL SANITARY SEWER PIPE MATERIALS AND JOINTS (AND STORM SEWER PIPE MATERIALS AND JOINTS IN A COMBINED SEWER AREA) SHALL CONFORM TO THE FOLLOWING:

PIPE MATERIAL	PIPE SPECIFICATIONS	JOINT SPECIFICATIONS
VITRIFIED CLAY PIPE	ASTM C-700	ASTM C-425
REINFORCED CONCRETE SEWER PIPE	ASTM C-76	ASTM C-443
CAST IRON SOIL PIPE	ASTM A-74	ASTM C-564
DUCTILE IRON PIPE	ANSI A21.51	ANSI A21.11
POLYVINYL CHLORIDE (PVC) PIPE 6-INCH TO 15-INCH DIAMETER SDR 26	ASTM D-3034	ASTM D-3212
18-INCH TO 27-INCH DIAMETER F/DY=46	ASTM F-679	ASTM D-3212
HIGH DENSITY POLYETHYLENE (HDPE)	ASTM D-3350 ASTM D-3035	ASTM D-3261,F-2620 (HEAT FUSION ASTM D-3212,F-477 (GASKETED)
WATER MAIN QUALITY PVC	10TH D 2244	, , ,
4-INCH TO 36-INCH 4-INCH TO 12-INCH	ASTM D-2241 AWWA C900	ASTM D-3139 ASTM D-3139
14-INCH TO 48-INCH	AWWA C905	ASTM D-3139

THE FOLLOWING MATERIALS ARE ALLOWED ON A QUALIFIED BASIS SUBJECT TO DISTRICT REVIEW AND APPROVAL PRIOR TO PERMIT ISSUANCE. A SPECIAL CONDITION WILL BE ADDED TO THE PERMIT WHEN THE PIPE MATERIAL BELOW IS USED FOR SEWER CONSTRUCTION OR A CONNECTION IS MADE.

PIPE MATERIAL POLYPROPYLENE (PP) PIPE	PIPE SPECIFICATIONS	JOINT SPECIFICATIONS
12-INCH TO 24-INCH DOUBLE WALL	ASTM F-2736	D-3212, F-477
30-INCH TO 60-INCH TRIPLE WALL	ASTM F-2764	D3212, F-477

- 8. ALL SANITARY SEWER CONSTRUCTION (AND STORM SEWER CONSTRUCTION IN COMBINED SEWER AREAS), REQUIRES STONE BEDDING WITH STONE ¼ "TO 1" IN SIZE, WITH MINIMUM BEDDING THICKNESS EQUAL TO ¼ THE OUTSIDE DIAMETER OF THE SEWER PIPE, BUT NOT LESS THAN FOUR (4) INCHES NOR MORE THAN EIGHT (8) INCHES. MATERIAL SHALL BE CA-7, CA-11 OR CA-13 AND SHALL BE EXTENDED AT LEAST 12" ABOVE THE TOP OF THE PIPE WHEN USING PVC.
- 9. NON-SHEAR FLEXIBLE-TYPE COUPLINGS SHALL BE USED IN THE CONNECTION OF SEWER PIPES OF DISSIMILAR PIPE MATERIALS.
- 10. ALL MANHOLES SHALL BE PROVIDED WITH BOLTED, WATERTIGHT COVERS. SANITARY LIDS SHALL BE CONSTRUCTED WITH A CONCEALED PICKHOLE AND WATERTIGHT GASKET WITH THE WORD "SANITARY"
- 11. WHEN CONNECTING TO AN EXISTING SEWER MAIN BY MEANS OTHER THAN AN EXISTING WYE, TEE, OR
- AN EXISTING MANHOLE, ONE OF THE FOLLOWING METHODS SHALL BE USED:
 a) A CIRCULAR SAW-CUT OF SEWER MAIN BY PROPER TOOLS AND PROPER INSTALLATION OF HUBWYE SADDLE OR HUB-TEE SADDLE.
- b) REMOVE AN ENTIRE SECTION OF PIPE (BREAKING ONLY THE TOP OF ONE BELL) AND REPLACE WITH A WYE OR TEE BRANCH SECTION.
- c) WITH PIPE CUTTER, NEATLY AND ACCURATELY CUT OUT DESIRED LENGTH OF PIPE FOR INSERTION OF PROPER FITTING, USING COUPLINGS TO HOLD IT FIRMLY IN PLACE.
- 12. WHENEVER A SANITARY/COMBINED SEWER CROSSES UNDER A WATERMAIN, THE MINIMUM VERTICAL DISTANCE FROM THE TOP OF THE SEWER TO THE BOTTOM OF THE WATERMAIN SHALL BE 18 INCHES. FURTHERMORE, A MINIMUM HORIZONTAL DISTANCE OF 10 FEET BETWEEN SANITARY/COMBINED SEWERS AND WATERMAINS SHALL BE MAINTAINED UNLESS: THE SEWER IS LAID IN A SEPARATE TRENCH, KEEPING A MINIMUM 18" VERTICAL SEPARATION; OR THE SEWER IS LAID IN THE SAME TRENCH WITH THE WATERMAIN LOCATED AT THE OPPOSITE SIDE ON A BENCH OF LINDISTURBED EARTH, KEEPING A MINIMUM 18" VERTICAL SEPARATION. IF EITHER THE VERTICAL OR HORIZONTAL DISTANCES DESCRIBED CANNOT BE MAINTAINED, OR THE SEWER CROSSES ABOVE THE WATER MAIN, THE SEWER SHALL BE CONSTRUCTED TO WATER MAIN STANDARDS OR IT SHALL BE ENCASED

WATER MAIN QUALITY CARRIER PIPE WITH THE ENDS SEALED.

- 13. ALL EXISTING SEPTIC SYSTEMS SHALL BE ABANDONED. ABANDONED TANKS SHALL BE FILLED WITH GRANULAR MATERIAL OR REMOVED.
- 14. ALL SANITARY MANHOLES, (AND STORM MANHOLES IN COMBINED SEWER AREAS), SHALL HAVE A MINIMUM INSIDE DIAMETER OF 48 INCHES, AND SHALL BE CAST IN PLACE OR PRÉ-CAST REINFORCED
- 15. ALL SANITARY MANHOLES, (AND STORM MANHOLES IN COMBINED SEWER AREAS), SHALL HAVE PRECAST "RUBBER BOOTS" THAT CONFORM TO ASTM C-923 FOR ALL PIPE CONNECTIONS. PRECAST SECTIONS SHALL CONSIST OF MODIFIED GROOVE TONGUE AND RUBBER GASKET TYPE JOINTS.
- 16. ALL ABANDONED SANITARY SEWERS SHALL BE PLUGGED AT BOTH ENDS WITH AT LEAST 2 FEET LONG NON-SHRINK CONCRETE OR MORTAR PLUG.
- 17. EXCEPT FOR FOUNDATION/FOOTING DRAINS PROVIDED TO PROTECT BUILDINGS, OR PERFORATED PIPES ASSOCIATED WITH VOLUME CONTROL FACILITIES, DRAIN TILES/FIELD TILES/UNDERDRAINS/PERFORATED PIPES ARE NOT ALLOWED TO BE CONNECTED TO OR TRIBUTARY TO COMBINED SEWERS, SANITARY SEWERS, OR STORM SEWERS TRIBUTARY TO COMBINED SEWERS IN COMBINED SEWER AREAS CONSTRUCTION OF NEW FACILITIES OF THIS TYPE IS PROHIBITED; AND ALL EXISTING DRAIN TILES AND PERFORATED PIPES ENCOUNTERED WITHIN THE PROJECT AREA SHALL BE PLUGGED OR REMOVED, AND SHALL NOT BE CONNECTED TO COMBINED SEWERS, SANITARY SEWERS, OR STORM SEWERS TRIBUTARY
- 18. A BACKFLOW PREVENTER IS REQUIRED FOR ALL DETENTION BASINS TRIBUTARY TO COMBINED SEWERS REQUIRED BACKFLOW PREVENTERS SHALL BE INSPECTED AND EXERCISED ANNUALLY BY THE PROPERTY OWNER TO ENSURE PROPER OPERATION, AND ANY NECESSARY MAINTENANCES SHALL BE PERFORMED TO ENSURE FUNCTIONALITY. IN THE EVENT OF A SEWER SURCHARGE INTO AN OPEN DETENTION BASIN TRIBUTARY TO COMBINED SEWERS, THE PERMITTEE SHALL ENSURE THAT CLEAN UP AND WASH OUT OF SEWAGE TAKES PLACE WITHIN 48 HOURS OF THE STORM EVENT.

E. EROSION AND SEDIMENT CONTROL

- 1. THE CONTRACTOR SHALL INSTALL THE EROSION AND SEDIMENT CONTROL DEVICES AS SHOWN ON THE APPROVED EROSION AND SEDIMENT CONTROL PLAN
- 2. EROSION AND SEDIMENT CONTROL PRACTICES SHALL BE FUNCTIONAL PRIOR TO HYDROLOGIC DISTURBANCE OF THE SITE.
- 3. ALL DESIGN CRITERIA, SPECIFICATIONS, AND INSTALLATION OF EROSION AND SEDIMENT CONTROL PRACTICES SHALL BE IN ACCORDANCE WITH THE ILLINOIS URBAN MANUAL.
- 4. A COPY OF THE APPROVED EROSION AND SEDIMENT CONTROL PLAN SHALL BE MAINTAINED ON THE SITE AT ALL TIMES.
- 5. INSPECTIONS AND DOCUMENTATION SHALL BE PERFORMED, AT A MINIMUM:
 a) UPON COMPLETION OF INITIAL EROSION AND SEDIMENT CONTROL MEASURES, PRIOR TO ANY SOIL DISTURBANCE.
 - b) ONCE EVERY SEVEN (7) CALENDAR DAYS AND WITHIN 24 HOURS OF THE END OF A STORM EVENT WITH GREATER THAN 0.5 INCH OF RAINFALL OR LIQUID EQUIVALENT PRECIPITATION.
- 6. SOIL DISTURBANCE SHALL BE CONDUCTED IN SUCH A MANNER AS TO MINIMIZE EROSION IF STRIPPING, CLEARING, GRADING, OR LANDSCAPING ARE TO BE DONE IN PHASES, THE CO-PERMITTEE SHALL PLAN FOR APPROPRIATE SOIL FROSTON AND SEDIMENT CONTROL MEASURES.
- 7. A STABILIZED MAT OF CRUSHED STONE MEETING THE STANDARDS OF THE ILLINOIS URBAN MANUAL SHALL BE INSTALLED AT ANY POINT WHERE TRAFFIC WILL BE ENTERING OR LEAVING A CONSTRUCTION SITE. SEDIMENT OR SOIL REACHING AN IMPROVED PUBLIC RIGHT-OF-WAY, STREET, ALLEY OR PARKING AREA SHALL BE REMOVED BY SCRAPING OR STREET CLEANING AS ACCUMULATIONS WARRANT AND TRANSPORTED TO A CONTROLLED SEDIMENT DISPOSAL AREA.
- 8. CONCRETE WASHOUT FACILITIES SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE ILLINOIS URBAN MANUAL AND SHALL BE INSTALLED PRIOR TO ANY ON SITE CONSTRUCTION ACTIVITIES INVOLVING
- 9. MORTAR WASHOUT FACILITIES SHALL BE CONSTRUCTED IN ADDITION TO CONCRETE WASHOUT FACILITIES FOR ANY BRICK AND MORTAR BUILDING ENVELOPE CONSTRUCTION ACTIVITIES.
- 10. TEMPORARY DIVERSIONS SHALL BE CONSTRUCTED AS NECESSARY TO DIRECT ALL RUNOFF FROM HYDROLOGICALLY DISTURBED AREAS TO AN APPROPRIATE SEDIMENT TRAP OR BASIN. VOLUME CONTROL FACILITIES SHALL NOT BE USED AS TEMPORARY SEDIMENT BASINS.
- 11. DISTURBED AREAS OF THE SITE WHERE CONSTRUCTION ACTIVITIES HAVE TEMPORARILY OR PERMANENTLY CEASED SHALL BE STABILIZED WITH TEMPORARY OR PERMANENT MEASURES WITHIN
- 12. ALL FLOOD PROTECTION AREAS AND VOLUME CONTROL FACILITIES SHALL, AT A MINIMUM, BE PROTECTED WITH A DOUBLE-ROW OF SILT FENCE (OR EQUIVALENT).
- 13. VOLUME CONTROL FACILITIES SHALL NOT BE CONSTRUCTED UNTIL ALL OF THE CONTRIBUTING DRAINAGE AREA HAS BEEN STABILIZED.
- 14. SOIL STOCKPILES SHALL, AT A MINIMUM, BE PROTECTED WITH PERIMETER SEDIMENT CONTROLS. SOIL STOCKPILES SHALL NOT BE PLACED IN FLOOD PROTECTION AREAS OR THEIR BUFFERS.
- 15. EARTHEN EMBANKMENT SIDE SLOPES SHALL BE STABILIZED WITH APPROPRIATE EROSION CONTROL
- 16. STORM SEWERS THAT ARE OR WILL BE FUNCTIONING DURING CONSTRUCTION SHALL BE PROTECTED BY APPROPRIATE SEDIMENT CONTROL MEASURES.
- 17. THE CONTRACTOR SHALL EITHER REMOVE OR REPLACE ANY EXISTING DRAIN TILES AND INCORPORATE THEM INTO THE DRAINAGE PLAN FOR THE DEVELOPMENT. DRAIN TILES CANNOT BE TRIBUTARY TO A SANITARY OR COMBINED SEVER DRAIN TILES ALLOWED IN COMBINED SEVER AREA FOR GREEN INFRASTRUCTURE PRACTICES.
- 18. IF DEWATERING SERVICES ARE USED, ADJOINING PROPERTIES AND DISCHARGE LOCATIONS SHALL BE PROTECTED FROM EROSION AND SEDIMENTATION. DEWATERING SYSTEMS SHOULD BE INSPECTED DAILY DURING OPERATIONAL PERIODS. THE SITE INSPECTOR MUST BE PRESENT AT THE COMMENCEMENT OF DEWATERING ACTIVITIES.
- 19. THE CONTRCTOR SHALL BE RESPONSIBLE FOR TRENCH DEWATERING AND EXCAVATION FOR THE INSTALLATION OF SANITARY SEWERS, STORM SEWERS, WATERMAINS AS WELL AS THEIR SERVICES AND OTHER APPURTENANCES. ANY TRENCH DEWATERING, WHICH CONTAINS SEDIMENT SHALL PASS THROUGH A SEDIMENT SETTLING POND OR EQUALLY EFFECTIVE SEDIMENT CONTROL DEVICE.
 ALTERNATIVES MAY INCLUDE DEWATERING INTO A SUMP PIT, FILTER BAG OR EXISTING VEGETATED UPSLOPE AREA. SEDIMENT LADEN WATERS SHALL NOT BE DISCHARGE TO WATERWAYS, FLOOD PROTECTION AREAS OR THE COMBINED SEWER SYSTEM.
- 20. ALL PERMANENT EROSION CONTROL PRACTICES SHALL BE INITIATED WITHIN SEVEN (7) DAYS FOLLOWING THE COMPLETION OF SOIL DISTURBING ACTIVITIES.
- 21. ALL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE MAINTAINED AND REPAIRED AS NEEDED ON A YEAR-ROUND BASIS DURING CONSTRUCTION AND ANY PERIODS OF CONSTRUCTION SHUTDOWN UNTIL PERMANENT STABILIZATION IS ACHIEVED.
- 22. ALL TEMPORARY EROSION AND SEDIMENT CONTROL MEASURES SHALL BE REMOVED WITHIN THIRTY (30) DAYS AFTER PERMANENT SITE STABILIZATION.
- 23. THE EROSION AND SEDIMENT CONTROL MEASURES SHOWN ON THE PLANS ARE THE MINIMUM REQUIREMENTS. ADDITIONAL MEASURES MAY BE REQUIRED, AS DIRECTED BY THE ENGINEER, SITE INSPECTOR, OR MWRD.



	DESIGNE
9933 Roosevelt Road :hester, IL, 60154-2780	DRAWN
Phone: 708-865-0300	CHECKE
www.enancock.com	DATE -

	DESIGNED -	Х	REVISED -
780	DRAWN -	ECW, SFB, DMM, GD	REVISED -
300 om	CHECKED -	XXX	REVISED -
om	DATE -	8-7-23	REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

MWRDGC GENERAL NOTES (MWRD)							F.A.U. RTE.			
							0655			
							,		FIELD B	300
SCALE: NONE	SH	IEET NO.	1	OF	1	SHEETS	STA.	TO STA.	FFD R	ΩΔ

		l			
	25000	400 NI	ROGEN FERTILIZE	R NUTRIENT	
	25000	500 PH	OSPHORUS FERTIL	IZER NUTRIENT	
	25000	600 PO	TASSIUM FERTILIZ	ER NUTRIENT	
	25100	135 MU	JLCH, METHOD 4		
	I				
		DESIGNED -	x	REVISED -	
HANCOCK To get the Control of the	9933 Roosevelt Road Westchester, IL 60154-2760 Phone: 705-565-0300	DRAWN - CHECKED -	ECW, SFB, DMM, GD XXX	REVISED -	STATE
「 CINOIINECKIINO \$ a ◆ Established 1911	www.ehancock.com	DATE -	8-7-23	REVISED -	DEPARTMENT

					80% FEDERAL / 20% LOCAL		
				Total	RECONSTRUCTION	TRAINEES	
S.I,	Code No.	Item	Unit	Quantity	0004	0042	
				Quantity	URBAN	URBAN	
Х	20100110	TREE REMOVAL (6 TO 15 UNITS DIAMETER)	UNIT	66	66		
				00			
						<u> </u>	
Х	20100210	TREE REMOVAL (OVER 15 UNITS DIAMETER)	UNIT	225	225		
х	20101100	TREE TRUNK PROTECTION	EACH	41			
	20102100			71	41		
Х	20101200	TREE ROOT PRUNING	EACH	21	21		
	20200100	EARTH EXCAVATION	CUYD	5,250	5,250		
				-,	5,200		
		DESAGNAL AND DISPOSAL OF UNICHTABLE SAATERIAL	71125				
	20201200	REMOVAL AND DISPOSAL OF UNSUITABLE MATERIAL	CU YD	450	450		

	20400800	FURNISHED EXCAVATION	CU YD	200	200		
	20000455	TRENCH BACKFILL	CU YD				
·····	20800150	THE TOTAL CONTROL OF THE CONTROL OF	CO 1D	3400	3400		
	21001000	GEOTECHNICAL FABRIC FOR GROUND STABILIZATION	SQ YD	450	450		
	21101615	TOPSOIL FURNISH AND PLACE, 4"	SQYD	F750	E750		
	21101013	,		5750	5750		
					19. A.		
	21101645	TOPSOIL FURNISH AND PLACE, 12"	SQ YD	125	125		
	25000310	SEEDING, CLASS 4	ACRE	0.25	0.25		
	22000310			0.25	0.23		
				-			
	25000400	NITROGEN FERTILIZER NUTRIENT	POUND	125	125		
	25000500	PHOSPHORUS FERTILIZER NUTRIENT	POUND	125	125		
	200000		10010	125			
		DOTACCI MA FEDERAL TEDENT		+	The state of the s		
	25000600	POTASSIUM FERTILIZER NUTRIENT	POUND	125	125		
	25100135	MULCH, METHOD 4	ACRE	0.25	0.25		
				† 	- y - y - y - y - y - y - y - y - y - y		
	<u> </u>		<u> </u>				

CONSTRUCTION CODE STP FUNDS

TE OF ILLINOIS **SUMMARY OF QUANTITIES** DEPARTMENT OF TRANSPORTATION Phone: 703-83-0300 | CHECKED - XXX | DATE - 8-7-23 REVISED -SCALE: NONE SHEET ND. 1 OF 9 SHEETS STA. TO STA.

	100 U. 2023 T DIAZOR
The state of the s	
č	200
010000	7577757
A. T. Land	C Carookiela

					80% FEDERAL / 20% LOCAL RECONSTRUCTION TRAINEES		
I. Code No.	Code No.	ltem	Unit	Total	0004		
) Jint	Quantity	URBAN	0042 URBAN	
		EDOSION CONTROL DI ANIVET				UNDAN	
ŀ	25100630	EROSION CONTROL BLANKET	SQ YD	100	100		
ŀ							
+	25200110	SODDING, SALT TOLERANT	\$Q YD	5750	5750		
ł							
ŀ	25200200	SUPPLEMENTAL WATERING	UNIT	315	315		
		TEMPORARY EROSION CONTROL SEEDING					
+	28000250	TEMPORARY EROSION CONTROL SEEDING	POUND	5	5		
-	20000400	PERIMETER EROSION BARRIER					
H	28000400	- CHINE LA GROSION DANNIER	FOOT	50	50		
ŀ	28000510	INLET FILTERS	EACH				
t	20000310		LAVII	59	59		
l	28100107	STONE RIPRAP, CLASS A4	SQ YD	10	10		
\dagger	20200201	POTENTIANT, VENOVICE	30,10		10		
l	28200200	FILTER FABRIC	SQ YD	10	10		
T					~~		
T	28400100	GABIONS	CU YD	3	3	A management	
T							
	30300001	AGGREGATE SUBGRADE IMPROVEMENT	CUYD	450	450		
ľ							
	30300112	AGGREGATE SUBGRADE IMPROVEMENT 12"	SQ YD	10100	10100		
	35300300	PORTLAND CEMENT CONCRETE BASE COURSE 8"	SQ YD	1700	1700		
Ĺ							
	40201000	AGGREGATE FOR TEMPORARY ACCESS	TON	110	110		
ļ							
	40600290	BITUMINOUS MATERIALS (TACK COAT)	POUND	14,500	14,500		
1	***************************************						
ļ	40600370	LONGITUDINAL JOINT SEALANT	FOOT	5000	5000		
ļ							
1	40600400	MIXTURE FOR CRACKS, JOINTS, AND FLANGEWAYS	TON	25	25		
1							

DESIGNED - X REVISED -DRAWN - ECW, SFB, DMM, GD REVISED -CHECKED - XXX REVISED -DATE - 8-7-23 REVISED -

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

SUMMARY OF QUANTITIES SCALE: NONE SHEET NO. 2 OF 9 SHEETS STA. TO STA.

CONSTRUCTION CODE STP FUNDS

					80% FEDERAL / 20% LOCAL		
				Total	RECONSTRUCTION	TRAINEES	
	Code No.	Item	Unit	1	0004	0042	
				Quantity	URBAN	URBAN	
	40600982	HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT	SQ YD	550	550	······································	
_	40602978	HOT-MIX ASPHALT BINDER COURSE, IL-9.5, N50	TON	950	950		
	40603080	HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N50	TON	2550	2550		
	40604060	HOT-MIX ASPHALT SURFACE COURSE, IL-9.5, MIX "D", N50	TON	2750	2750		
	40800050	INCIDENTAL HOT-MIX ASPHALT SURFACING	TON	30	30		
	42000300	PORTLAND CEMENT CONCRETE PAVEMENT 8"	SQ YD	75	75		
	42000300						
	42001300	PROTECTIVE COAT	SQ YD	5250	5250		
_	42300300	PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT, 7 INCH	SQ YD	1800	1800		
-		PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH	SQ FT	- Andrews measurement area - Areas		advardatus karvansidardatas saada musikan misaka dadvarda daskida daskida karva sabida daskida daskida daskida	
-	42400200	FORTERIO CEMENT CONCRETE SIDEWALK S INCH	30,71	16500	16500		
	42400800	DETECTABLE WARNINGS	SQ FT	330	330		
-	44000100	PAVEMENT REMOVAL	SQ YD	11000	11000		
_		DRIVEWAY PAVEMENT REMOVAL	SQYD				
-	44000200	DAVEWAI FAVEWENT REMOVAL	30,10	1500	1500		
	44000500	COMBINATION CURB AND GUTTER REMOVAL	FOOT	7250	7250		
	44000600	SIDEWALK REMOVAL	SQ FT	16000	16000		
_	44200929	CLASS B PATCHES, TYPE I, 8 INCH	SQ YD	50	50		
	44200934	CLASS B PATCHES, TYPE II, 8 INCH	SQYD	100	100		
					and the second s		

			_
_	HANCOCK	<u> </u>	٠
		1 € 4	٠
	HANCOCK ENGINEERING	i ii d	٠

♦ Civil Engineers PRI Receivelt Read

Westchester, 2, 40134-7755

Municipal Consultants
Phone: 765-845-0300

♦ Established 1911

DESIGNED - X REVISED -DRAWN - ECW, SFB, DMM, GD REVISED - CHECKED - XXX REVISED -DATE - 8-7-23 REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

	SUM	M	AR	Y	OF QU	IANTII	ΓΙES
SCALE: NONE	SHEET NO.	3	OF	9	SHEETS	STA.	TO STA.

CONSTRUCTION CODE STP FUNDS

COUNTY	TOTAL	SHEETS	NO.	
0655	20-00133-00-FP	COOK	107	7
FIELD BOOK NO.:	CONTRACT NO. 61J89			
FED, ROAD DIST. NO. 1	ILLINOIS	FED. AID PROJECT		
E.H.E. PROJECT	E.H.E. PROJECT			

					80% FEDERAL / 20% LOCAL		
				Total	RECONSTRUCTION	TRAINEES	
S.I.	Code No.	Item	Unit	1	0004	0042	
				Quantity	URBAN	URBAN	
	44200942	CLASS B PATCHES, TYPE III, 8 INCH	SQ YD	150	150		
	44200342	CLASS OF ATCHES, TIFE III, O INCT	3010	130	130		
	44200944	CLASS B PATCHES, TYPE IV, 8 INCH	SQYD	225	225	A 104	
************	·····						
	44213200	SAW CUTS	FOOT	2000	2000		
	44213202	TìE BARS 1"	ЕАСН	2100	2100		
	54215448	CAST-IN-PLACE REINFORCED CONCRETE END SECTIONS 48"	EACH	1	1		
	550A2540	STORM SEWERS, RUBBER GASKET, CLASS A, TYPE 2 18"	FOOT	356	356		
	550A2560	STORM SEWERS, RUBBER GASKET, CLASS A, TYPE 2 24"	FOOT	338	338		
	550A2580	STORM SEWERS, RUBBER GASKET, CLASS A, TYPE 2 30"	FOOT	352	352		
	550A2S90	STORM SEWERS, RUBBER GASKET, CLASS A, TYPE 2 33"	FOOT	339	339		
	550A2600	STORM SEWERS, RUBBER GASKET, CLASS A, TYPE 2 36"	FOOT	395	395		
	550A2610	STORM SEWERS, RUBBER GASKET, CLASS A, TYPE 2 42"	FOOT	367	367		
	550A2620	STORM SEWERS, RUBBER GASKET, CLASS A, TYPE 2 48"	FOOT	427	427		
	55080330	STORM SEWERS, CLASS B, TYPE 2, 10"	FOOT	145	145		
х	56103300	DUCTILE IRON WATER MAIN 12"	FOOT	40	40		
х	56105200	WATER VALVES 12"	EACH	1	1		
х	56200300	WATER SERVICE LINE 1"	EACH	6	6		

HANCOCK | The second of the consultants | Page | Pa

DESIGNED - X REVISED -DRAWN - ECW, SFB, DMM, GD REVISED -CHECKED - XXX
DATE - 8-7-23 REVISED -REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

SUMMARY OF QUANTITIES SHEET NO. 4 OF 9 SHEETS STA.

SCALE: NONE

CONSTRUCTION CODE STP FUNDS

COUNTY TOTAL SHEET SHEETS NO.

0655 20-00133-00-FP COOK 107 8

FIELD BOOK NO.: CONTRACT NO. 61J89

FED, ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT

E.H.E. PROJECT NO.

w:\projects_by_wilage\prooxi		
Drawing rile: w	HANCOCK ENGINEERING	◆ Civil Enginee ◆ Municipal Co ◆ Established 1:

X

Code No.

56500600

60206905

60234200

60250400

60253000

60255800

60300305

60600605

60603800

60604100

66900200

66900530

ltem

56400510 FIRE HYDRANTS TO BE REMOVED AND REPLACED

60108204 PIPE UNDERDRAINS, TYPE 2, 4"

DOMESTIC WATER SERVICE BOXES TO BE ADJUSTED

CATCH BASINS, TYPE C, TYPE 1 FRAME, OPEN LID

60218400 MANHOLES, TYPE A, 4'-DIAMETER, TYPE 1 FRAME, CLOSED LID

CATCH BASINS TO BE ADJUSTED WITH NEW TYPE 1 FRAME, OPEN LID

MANHOLES TO BE ADJUSTED WITH NEW TYPE 1 FRAME, CLOSED LID

60265900 VALVE VAULTS TO BE ADJUSTED WITH NEW TYPE 1 FRAME, CLOSED LID

COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12

COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12 (MODIFIED)

CATCH BASINS TO BE RECONSTRUCTED WITH NEW TYPE 1 FRAME, OPEN LID

INLETS, TYPE A, TYPE 1 FRAME, OPEN LID

FRAMES AND LIDS TO BE ADJUSTED

NON-SPECIAL WASTE DISPOSAL

SOIL DISPOSAL ANALYSIS

CONCRETE CURB, TYPE B

DESIGNED -	Х	REVISED -
DRAWN -	ECW, SFB, DMM, GD	REVISED -
CHECKED -	XXX	REVISED -
DATE -	8-7-23	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SUM	M	AR	Y	OF QL	JANTI	TIES
 SHEET NO.	5	OF	9	SHEETS	STA.	TO STA

CONSTRUCTION CODE

STP FUNDS

80% FEDERAL / 20% LOCAL

TRAINEES

URBAN

RECONSTRUCTION

URBAN

12

275

2

4

12

1

27

850

6200

1400

300

1

SCALE: NONE

Total

Quantity

12

275

2

12

4

27

850

6200

1400

300

Unit

EACH

EACH

FOOT

EACH

EACH

EACH

EACH

EACH

EACH

EACH

EACH

FOOT

FOOT

FOOT

CU YD

EACH

 F.A.U. RTE.	SECT	ION		COUNTY	TOTAL	SHEET NO.
0655	20-0013	COOK	107	9		
 FIELD B	OOK NO. :			CONTRACT N	D, 61J89	
FED. R	OAD DIST. NO. 1	ILLINOIS	FED	. AID PROJECT		

					STP FU	NDS	
					80% FEDERAL		
				Total	RECONSTRUCTION	TRAINEES	
1.	Code No.	ltem	Unit	Quantity	0004	0042	
				Quarterley	URBAN	URBAN	
	66901001	REGULATED SUBSTANCES PRE-CONSTRUCTION PLAN	L SUM	1	1		
	66901003	REGULATED SUBSTANCES FINAL CONSTRUCTION REPORT	LSUM		_		
	00001000	And a state of the	r 20141	1 1	1		
			****	ļ			
<u> </u>	66901006	REGULATED SUBSTANCES MONITORING	CAL DA	13	13		
				<u> </u>			
	67100100	MOBILIZATION	LSUM	1	1		
	7040700						
	70107025	CHANGEABLE MESSAGE SIGN	CALDA	125	125		
	70300100	SHORT TERM PAVEMENT MARKING	FOOT	550	550		
	70300150	SHORT TERM PAVEMENT MARKING REMOVAL	COST				
	70500150	STORE TERMITA SCINCES PARAMETERS	SQ FT	300	300	· · · · · · · · · · · · · · · · · · ·	
〈	72000100	SIGN PANEL - TYPE 1	SQ FT	300	300		
〈	72900100	METAL POST - TYPE A	FOOT	150			
				150	150		

(72900200	METAL POST - TYPE B	FOOT	400	400	***************************************	

(78000100	THERMOPLASTIC PAVEMENT MARKING - LETTERS AND SYMBOLS	SQ FT	10	10		

(78000200	THERMOPLASTIC PAVEMENT MARKING - LINE 4"	FOOT				
	76565265	DEGRACI CASTIC FACINEAL WANKING - CINE 4	F001	5100	5100		
<u> </u>	78000400	THERMOPLASTIC PAVEMENT MARKING - LINE 6"	FOOT	1200	1200		
X	78000650	THERMOPLASTIC PAVEMENT MARKING - LINE 24"	FOOT	300	300	······································	
				300	500		
_	7000000						
<u> </u>	78009000	MODIFIED URETHANE PAVEMENT MARKING - LETTERS AND SYMBOLS	SQ FT	10	10		
х	78009004	MODIFIED URETHANE PAVEMENT MARKING - LINE 4"	FOOT	950	950		



DESIGNED - X DRAWN - ECW, SFB, DMM, GD REVISED -CHECKED - XXX
DATE - 8-7-23 REVISED -

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

SUMMARY OF QUANTITIES SCALE: NONE SHEET NO. 6 OF 9 SHEETS STA. TO STA.

CONSTRUCTION CODE

COUNTY TOTAL SHEET NO.
COOK 107 10 F.A.U. RTE. 0655 SECTION 20-00133-00-FP FIELD BOOK NO.: CONTRACT NO. 61J89
FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT
E.H.E. PROJECT NO. 125-22-25201

12:22pm
ţ
2023
8
Aug
T\05_S0Q.dwg
phase
0ve
burlington
E
12522252
,village\brookfield\

					STP FUI	
					80% FEDERAL / RECONSTRUCTION	TRAINEES
S.I.	Code No.	Item	Unīt	Total	0004	0042
				Quantity	URBAN	URBAN
Х	88600100	DETECTOR LOOP, TYPE 1	FOOT	125	125	
Х	X0325207	TELEVISION INSPECTION OF SEWER				
$\stackrel{\sim}{-}$		TELEVISION NOT SERVER	FOOT	4536	4536	
	X0325607	CDOUND CTARM CERCIANTICS				***************************************
	XU3236U7	GROUND STABILIZATION GEOSYNTHETIC	SQ YD	10100	10100	
	X0327611	REMOVE AND REINSTALL BRICK PAVER	SQ FT	450	450	
	X1200046	STORM SEWERS, CLASS B, TYPE 2, 8"	FOOT	880	880	
1						
	X1200160	CONNECTION TO EXISTING DRAINAGE STRUCTURE	EACH	6	6	TOTAL
	X2130010	EXPLORATION TRENCH, SPECIAL	FOOT	100	400	
			FOOT	100	100	
	X4021000	TERADODADY ACCESS (DDIVATE PAITO ANICE)				
	V4021000	TEMPORARY ACCESS (PRIVATE ENTRANCE)	EACH	10	10	
			······			
	X4022000	TEMPORARY ACCESS (COMMERCIAL ENTRANCE)	EACH	2	2	
	·					
	X4240800	DETECTABLE WARNINGS (SPECIAL)	SQ FT	20	20	

	X4401198	HOT-MIX ASPHALT SURFACE REMOVAL, VARIABLE DEPTH	SQ YD	9750	9750	
				3750	3730	
	X4420210	TEMPORARY PATCHING	SQ YD			
			30,15	700	700	
х	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\					
	X5610004	DUCTILE IRON WATER MAIN FITTINGS	POUND	1000	1000	
					***************************************	····
X	X5620096	WATER SERVICE LINE 1", (BORED)	EACH	5	5	
	X6020399	CONNECTION TO EXISTING MANHOLE	EACH	5	5	
	X6022805	CATCH BASINS, TYPE A, 4'-DIAMETER, TYPE 1 FRAME, OPEN LID, SPECIAL	EACH	28	28	
				40		

DESIGNED - X REVISED -DRAWN - ECW, SFB, DMM, GD REVISED -CHECKED - XXX REVISED -DATE -8-7-23 REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

SUMMARY OF QUANTITIES SCALE: NONE SHEET NO. 7 OF 9 SHEETS STA. TO STA.

CONSTRUCTION CODE

COUNTY TOTAL SHEET NO.

COOK 107 11 F.A.U. RTE. 0655 SECTION 20-00133-00-FP FIELD BOOK NO.: CONTRACT NO. 61J89
FED. ROAD DIST, NO. 1 | ILLINOIS | FED. AID PROJECT

					STP FI				
				ļ	80% FEDERAL				
				Total	RECONSTRUCTION TRAINEES				
S.I.	Code No.	ltem	Unit	Quantity	0004	0042			
				Quantity	URBAN	URBAN			
	X6023700	MANHOLES, 5'-DIAMETER, TYPE 1 FRAME, CLOSED LID, SPECIAL	EACH	4	4				
	X6023800	MANHOLES, 6'-DIAMETER, TYPE 1 FRAME, CLOSED LID, SPECIAL	EACH		_				
	70023800	MANUELS, O'DIAWLICK, TITL I PRANTE, CLOSED ED, SPECIAL	EACH	4	4				
	X7010216	TRAFFIC CONTROL AND PROTECTION, (SPECIAL)	L SUM	1	1				
Х	X7240600	REMOVE AND RE-ERECT EXISTING SIGN	EACH						
			Litteri	35	35				
				<u> </u>					
Х	XX001468	SANITARY SEWER, PVC, 18"	FOOT	210	210				
х	XX003803	SANITARY SEWER SERVICE 6"	FOOT	248	248				
^			,,,,,	240	248				
				<u> </u>					
	XX004688	BRICK PAVER SIDEWALK	SQ FT	1900	1900				

Х	XX006037	CDS UNIT	EACH	1	1				
	vvoocaca	CANUTARU ASANI (OLC. A). DIAMATTER	* 4 47.1	<u> </u>					
Х	XX006253	SANITARY MANHOLE, 4'- DIAMETER	EACH	3	3				
Х	XX006448	PVC COMBINED SEWER PIPE REPLACEMENT, 10"	FOOT	190	190				
Х	XX006449	PVC COMBINED SEWER PIPE REPLACEMENT, 12"	FOOT						
	70000445	T VC COMBINED SCAVERY FILE REPERVEDING 12	FOOT	246	246				
Х	XX006451	10" X 6" PVC SEWER SERVICE CONNECTIONS	EACH	14	14				
Х	XX006816	12" X 6" PVC SEWER SERVICE CONNECTIONS (SPECIAL)	EACH	16	16				
			{	7.0	10				
Х	XX006994	8" X 4" CATCH BASIN TRAP AND RESTRICTOR	EACH	13	13				
	XX007079	CONCRETE RIBBON	FOOT	100	100				
					200				
_				 					
Х	XX007154	18" X 6" SEWER SERVICE CONNECTIONS	EACH	12	12				
					-				

HANCOCK ENGINEERING	rellance	◆ Civ
	\$ H	♦ Esli

Civil Engineers 9933 Robusvell Road
Municipal Consultants Phone: 705-825-0200
Established 1911 www.wharcock.com

DESIGNED - X REVISED -DRAWN - ECW, SFB, DMM, GD REVISED -CHECKED - XXX REVISED -DATE -8-7-23 REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

	SUM	M	AR	Υ	OF QU	JANTII	TIES
SCALE: NONE	SHEET NO.	8	OF	9	SHEETS	STA.	TO STA.

CONSTRUCTION CODE

F.A.U.	SECTION		COUNTY	SHEETS	SHE
0655	20-00133-00-FP		COOK	107	1
FIELD B	OOK NO, :		CONTRACT N	O. 61J89	
FFO R	OAD DIST, NO. 1 ILLINOIS	FED	. AID PROJECT		

					STP FL	
					80% FEDERAL RECONSTRUCTION	
S.I.	Code No.	ltem	Unit	Total —	0004	TRAINEES 0042
• • • • • • • • • • • • • • • • • • • •				Quantity	URBAN	URBAN
	XX008159	PORTLAND CEMENT CONCRETE BAND FOR PAVER BRICKS	FOOT	70	70	
	XX008034	SEATWALL 20" HT.	FOOT	125	125	
	70000034	JENIWACE ZO TIT.	- FOG1	123	125	
Х	XX008914	RESTRAINED JOINT 12"	EACH	10	10	
	XZ127902	RETAINING WALL (SPECIAL)	SQ FT	75	75	
		A CONTROL OF THE CONT	-		,,	
	Z0004544	HOT-MIX ASPHALT DRIVEWAY PAVEMENT REMOVAL	SQYD	200	200	
	Z0018700	DRAINAGE STRUCTURE TO BE REMOVED	EACH			, , , , , , , , , , , , , , , , , , ,
			LACII	15	15	
	Z0019600	DUST CONTROL WATERING	UNIT	50	50	
	Z0030850	TEMPORARY INFORMATION SIGNING	SQFT	A may for	A 75 87	
•			3411	175	175	
*****	Z0048665	RAILROAD PROTECTIVE LIABILITY INSURANCE	L SUM	1	1	
X	XX009601	10" X 6" CATCH BASIN TRAP AND RESTRICTOR	EACH	3	3	
Х	XX009602	CHECK VALVE, 48"	EACH	1	1	
	Z0076600	TRAINEES	HOUR	500		500

	20076604	TRAINEES TRAINING PROGRAM GRADUATE	HOUR	500		500

A HAI	VICOCK ISS	• 0
♦ HAI	VCOCK \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	♦ 0

Civil Engineers Municipal Consultants Established 1911

9933 Roosevell Road Westchester, 8, 49154-2759 Phone: 768-845-0200 www.ehanaock.com

DESIGNED - X REVISED -DRAWN - ECW, SFB, DMM, GD REVISED -CHECKED - XXX REVISED -DATE -8-7-23 REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

SUMMARY OF QUANTITIES SHEET NO. 9 OF 9 SHEETS STA. TO STA.


SCALE: NONE

CONSTRUCTION CODE


F.A.U. RTE. 0655 COUNTY TOTAL SHEET NO.

COOK 107 13 SECTION 20-00133-00-FP FIELD BOOK NO. : CONTRACT NO. 61J89
FED. ROAD DIST. NO. 1 | ILLINOIS | FED. AID PROJECT

DUBOIS BOULEVARD (2' NORTH OF OGDEN AVENUE TO BURLINGTON AVENUE) (STA 1+47 TO STA 8+00)



BURLINGTON AVENUE (DUBOIS BOULEVARD TO MAPLE AVENUE) (STA 8+00 TO STA 22+71)



BURLINGTON AVENUE (MAPLE AVENUE TO SUNNYSIDE AVENUE) (STA 24+18 TO STA 37+00)

(1)

(2)

 $\langle \mathbf{3} \rangle$

 $\langle \mathbf{4} \rangle$

(5)

(6)

BORE

C-11

C-10

C-9

C-8

C-7

C-6

C-5

C-2


C-1

\(\sqrt{3}\\\\2\\\\8\\\

ITEMS TO BE REMOVED INTERMITTENT REMOVAL

BURLINGTON AVENUE (SUNNYSIDE AVENUE TO PRAIRIE AVENUE)


(STA 37+00 TO STA 44+25)




ITEMS TO BE REMOVED INTERMITTENT REMOVAL

BURLINGTON AVENUE (PRAIRIE AVENUE TO STA. 46+42)

(STA 44+25 TO STA 46+42)



BURLINGTON AVENUE (STA. 46+42 TO FOREST AVENUE) (STA 46+42 TO STA 48+00)



BURLINGTON AVENUE (FOREST AVENUE TO GROVE AVENUE)

NOTES:

THESE CORES REFLECT ONLY THE INFORMATION FOUND AT LOCATIONS LISTED. THEY DO NOT REFLECT ANY VARIATIONS WHICH MAY OCCUR BETWEEN THESE BORINGS.

TYPICAL SECTION LEGEND

EXISTING PORTLAND CEMENT CONCRETE SIDEWALK

EXISTING AGGREGATE BASE, 6"-8"

EXISTING GRASS PARKWAY

EARTH EXCAVATION, WIDENING

DUBOIS BOULEVARD

DUBOIS BOULEVARD

BURLINGTON AVENUE

EXISTING

EXISTING COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12

EXISTING PORTLAND CEMENT CONCRETE BASE COURSE, 6"-8"

EXISTING HOT-MIX ASPHALT BINDER AND SURFACE COURSE, 2"-4"

EXISTING PORTLAND CEMENT CONCRETE FINISHED PAVEMENT, 6"-8"

PAVEMENT CORE SUMMARY

1+70

5+75

7+60

16+30

25+40

28+40

32+00

34+85

38+90

42+30

47+20

51+15

STATION BITUMINOUS CONC BASE

0.00"

6.25"

6.75"

2.00"

1.75"

1.50"

2.00"

2.25"

2.50"

5.00"

3.25"

6.25"

6.75"

0.00"

0.00"

5.75"

7.00"

7.50"

6.50"

7.00"

7.50"

6.50"

6.25"

ITEMS TO BE REMOVED INTERMITTENT REMOVAL

(STA 48+00 TO STA 51+51)

◆ Municipal Consultants VEERING I & Š ◆Established 1911

stchester, IL, 60154-2780 Phone: 708-865-0300

DRAWN -CHECKED -

DESIGNED - X REVISED -ECW. SFB. DMM. GD REVISED -XXX REVISED -8-7-23 REVISED


STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

EXISTING TYPICAL SECTIONS 0655 SCALE: NONE SHEET NO. 1 OF 1 SHEETS STA.


SECTION COUNTY COOK 107 14 20-00133-00-FP CONTRACT NO. 61J89 FIELD BOOK NO. FED ROAD DIST NO 1 II I INOIS FED AID PROJECT

E.H.E. PROJECT NO. 125-22-2520

DUBOIS BOULEVARD (2' NORTH OF OGDEN AVENUE TO BURLINGTON AVENUE) (STA 1+47 TO STA 8+00)



BURLINGTON AVENUE (DUBOIS BOULEVARD TO MAPLE AVENUE) (STA 8+00 TO STA 22+71)



BURLINGTON AVENUE (MAPLE AVENUE TO SUNNYSIDE AVENUE) (STA 24+18 TO STA 37+00)

TYPICAL SECTION LEGEND

EXISTING

(1) EXISTING PORTLAND CEMENT CONCRETE SIDEWALK

EXISTING COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12

 \langle 3 angleEXISTING PORTLAND CEMENT CONCRETE BASE COURSE, 6"-8"

(4) EXISTING AGGREGATE BASE, 6"-8"

(2)

EXISTING HOT-MIX ASPHALT BINDER AND SURFACE COURSE, 2"-4"

(5)

(6) EXISTING GRASS PARKWAY

EXISTING PORTLAND CEMENT CONCRETE FINISHED PAVEMENT, 6"-8"

SCALE: NONE

PROPOSED

PROPOSED PORTLAND CEMENT CONCRETE SIDEWALK

(B) PROPOSED COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12

 $\langle c \rangle$ PROPOSED CONCRETE BARRIER CURB

PROPOSED AGGREGATE SUBGRADE IMPROVEMENT, 12"

 $\langle \mathbf{E} \rangle$ PROPOSED HOT-MIX ASPHALT BINDER AND SURFACE COURSE

PROPOSED PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT, 7"

 $\langle \mathbf{G} \rangle$ PROPOSED TIE BARS

PROPOSED CLASS 'B' PATCH

PROPOSED GROUND STABILIZATION GEOSYNTHETIC

PORTLAND CEMENT CONCRETE BASE COURSE, 8"

INTERMITTENT PLACEMENT

** INTERMITTENT PLACEMENT

BURLINGTON AVENUE

(SUNNYSIDE AVENUE TO PRAIRIE AVENUE) (STA 37+00 TO STA 44+25)

BURLINGTON AVENUE (PRAIRIE AVENUE TO STA. 46+42) (STA 44+25 TO STA 46+42)



 $\langle \mathbf{p} \rangle$

QMP MIXTURE TYPE @ Ndes **HOT-MIX ASPHALT SURFACING - BUTT JOINT** HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50, 2" (IL 9.5mm) 4% @ 50 Gyr LR 1030-2

INCIDENTAL HOT-MIX ASPHALT SURFACING - HMA DRIVEWAYS

HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50, 3" (2 LIFTS) (IL 9.5mm) 4% @ 50 Gyr

PAVEMENT RECONSTRUCTION

HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50, 2" (IL 9.5mm) 4% @ 50 Gyr. LR 1030-2 HOT-MIX ASPHALT BINDER COURSE, IL 19.0, N50, 4" 4% @ 50 Gyr. LR 1030-2

PAVEMENT RESURFACING

HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50, 2" (IL 9.5mm) LR 1030-2 HOT-MIX ASPHALT BINDER COURSE, IL-9.5, N50,1.5' 4% @ 50 Gyr LR 1030-2

TEMPORARY PATCHING


HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50,2" (IL 9.5 MM) LR 1030-2

QMP DESIGNATION: QUALITY CONTROL/ QUALITY ASSURANCE (QC/QA) PER LR1030-2.


THE UNIT WEIGHT USED TO CALCULATE ALL HMA SURFACE MIXTURE QUANTITIES IS 112 LBS/SQ YD/IN.

THE "AC TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 76-22" AND FOR NON-POLYMERIZED HMA THE "AC TYPE" SHALL BE "PG 64-22" UNLESS MODIFIED BY RECYCLED MATERIALS SPECIFICATIONS.

THE LONGITUDINAL JOINT SEALANT SHALL BE PLACED ON THE HMA BINDER COURSE: HOT-MIX ASPHALT BINDER COURSE, IL-9.5, N50, 1.5" AND HOT-MIX ASPHALT BINDER COURSE, IL 19.0, N50, 4".



BURLINGTON AVENUE (STA. 46+42 TO FOREST AVENUE) (STA 46+42 TO STA 48+00)



BURLINGTON AVENUE (STA 48+00 TO STA 52+17)

EERING | ‡ ½ → Established 1911

Municipal Consultants

estchester, IL, 60154-2780 Phone: 708-865-0300

REVISED -DRAWN -ECW. SFB. DMM. GD REVISED -CHECKED -XXX REVISED REVISED

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

PROPOSED TYPICAL SECTIONS SHEET NO. 1 OF 1 SHEETS STA.

SECTION 0655 107 15 20-00133-00-FP COOK FIELD BOOK NO. CONTRACT NO. 61J89 FED ROAD DIST NO 1 II I INOIS FED AID PROJECT

LR 1030-2

SCHEDULE OF QUANTITIES

			ARD (ODGEN AVENU			Day of	1
		CUT	NON-SPE	CIAL WASTE		FILL	
STATION	AREA (SF)	VOLUME (CF)	AREA (SF)	VOLUME (CF)	AREA (SF)	VOLUME (CF)
155	42.5		42.5		0.1	_	+
133	7607	1,652.3	46.5	1,652.3		10.3	+
196	38.1	1,032.3	38.1	4,002.0	0.4	10.5	+
200	30.1	2,043.9	30.2	0.0		13.5	
250	37.6	2,01010	0.0	- 0.0	0.1	1000	
		2,212.5		0.0		2.5	
300	50.9		0.0		0.0		
		2,427.5		0.0		0.0	
350	46.2		0.0		0.0		
		2,317.5		0.0		0,0	
400	46.5		0.0		0.0		
		2,022.5		0.0		7.5	
450	34.4		0.0		0.3		
		758.8		0.0		20.0	
475	26.3		0.0		13		
		529.2		0.0		44.1	
496	24.1		24.1		2.9		
		491.0		491.0		57.0	
516	25.0		25.0		2.8		
		1,038.7		0.0		214.2	
550	36.1		0.0		9.8		
		6,100.0		0.0		490.0	-
600	37.7		0.0		7.4		1
		6,670.0		0,0		370.0	
650	85.9		0,0		0.0		+
		4,540.0		0.0		0.0	+
700	95.7		0.0		0.0		+
		4,320.0		0.0		0.0	+
750	77.1		0.0		0.0		+
	-	2,721.3		0,0		0.0	-
785	78.4		0.0		0.0		+
BRICK	PLAZA	2,000.0		0.0		0.0	t
CI	JM	41,845.1	CF	2,143.3	CF	1,229.1	-
30	JIVI						
		1,549.8	CY	79.4	CY	45.5	(

				NUE - PRAIRIE AVENU	-11	
		UT		CIAL WASTE		ILL
STATION	AREA (SF)	VOLUME (CF)	AREA (SF)	VOLUME (CF)	AREA (SF)	VOLUME (CF)
2430	30.5		0.0	_	0.0	
2430	30.3	506.0	0.0	0.0	0.0	3.0
2450	20.1	300.0	0.0		0.3	2.0
		1,145.0		0.0		10.0
2500	25.7		0,0		0.1	
		431.0		0.0		2.6
2517	25.0		25.0		0.2	
		382.5		382.5		3.0
2532	26.0		26.0		0.2	
		480.6		0.0		2.7
2550	27.4	1 5000	0.0		0.1	
		1,597.5	-	0,0		2.5
2600	36.5	1.707.5	0.0	- 00	0.0	0.0
2650	35.4	1,797.5	0.0	0.0	0.0	0.0
2650	33,4	1,677.5	0.0	0.0	0.0	7.5
2700	31.7	1,077.5	0.0	0.0	0.3	7.5
2700	31.7	1,610.0	0.0	0.0	0.3	15,0
2750	32.7	1,010.0	0.0	0,0	0.3	15,0
2730		1,577.5	1	0.0	4.2	15.0
2800	30.4		0.0		0.3	
		1,452.5		0.0		10.0
2850	27.7		0.0		0.1	
		605.0		0.0	1	8.8
2875	20.7		0.0		0.6	
		557.5	1	0.0		10.0
2900	23.9		0.0		0.2	
		1,287.5		0.0		7.5
2950	27.6		0.0		0.1	
		1,505.0	_	0,0		5.0
3000	32.6		0.0		0.1	
anna	20.2	1,570.0		0.0	0.2	7.5
3050	30.2	1,375.0	0.0	0.0	0.2	10.0
3100	24.8	1,375.0	0.0	0.0	0.2	10.0
3100	24.0	1,112.5	0.0	0.0	0.2	22.5
3150	19.7	A,LIE.S	0.0	0,0	0.7	22.3
-	1	985.0	1	0.0	1 20	25.0
3200	19.7		0.0		0.3	
		1,082.5		0.0		10.0
3250	23.6		0.0		0.1	
		1,322.5		0.0		5.0
3300	29.3		0.0		0.1	
1		381.6		0,0		1.3
3313	29.4		0.0		0.1	
		1,230.3		0.0		3.7
3350	37.1		0.0		0.1	
		1,530.0		0.0		7.5


		3,509.2	CT		201.5	CY		125.9	1
SUI	M	94,748.3	CF		5,439.2 201.5	CF		3,399.8 125.9	1
		7.7-							
INTERSE	CTIONS	6,172.2			0.0			3,102.3	+
									1
4400	46.0	2,445.0		0.0	0.0		0.0	0.0	+
4350	51.8	2.445.0		0,0	0.0	-	0.0	0.0	+
		1,394.9	\vdash		0.0			0.0	+
4324	55.5			54.8			0.0		T
		557.0			548.0			0.0	
4314	55.9	7.22.2		54.8			0.0		1
1550	20.5	793.1		0.0	0.0		0.0	0.0	+
4300	57.4	3,137.3		0.0	0.0		0.0	0.0	+
4250	70.5	3,197.5	1	0.0	0.0		0.0	0.0	+
4250	70.5	3,652.5	-	0.0	0.0	+-+	00	0.0	+
4200	75.6	2002	-	0.0		-	0.0		+
1212	-	3,622.5			0,0			0,0	+
4150	69.3			0.0			0.0		1
		3,532.5			0,0			0.0	I
4100	72.0			0.0			0.0		1
	46.0	3,370.0		0,0	0.0			2.5	+
4050	62.8	3,245.0		0.0	910		0.1	2.0	+
1000	07.0	3,245.0		0,0	0.0	1	0.1	5.0	+
4000	67.0	2,864.4	-	0.0	0.0		0.1	4,4	+
3956	63.2	2 964 4	-	03.2	0.0	+ +	0.1	4.4	+
2056	63.2	3,404.8		63.2	3,404.8	+	0.1	5.6	+
3900	58.4	2.404.0	-	58.4	2 404 0		0.1		+
2000	50.4	4,537.5		F0.4	1,103.9	-		7.5	+
3881	57.8			57.8	-		0.1		+
		2,857.5			0.0			7.5	1
3850	55.9			0.0			0.2		1
		3,000.0			0.0			7.5	Ι
3800	64.1			0.0			0.1		
7.1		3,577.5			0.0	1 1		2.5	1
3750	79.0			0.0			0.0	-	1
3,30	166.7	5,042.5		434	0.0		0.0	0.0	1
3700	122.7	3,370.0		0.0	0.0		0.0	0.0	+
3650	36.1	3,970.0	-	0.0	0.0	1	0.0	0.0	+
2000	201	1,597.5	-	0.0	0,0	+ +	00	0,0	+
3600	27.8		-	0.0		-	0.0		+
	44.	1,132.5		-	0,0	-	157	22.5	+
3550	17.5			0.0			0.9	100	+
		985.0			0.0			25.0	+
3500	21.9			0.0			0.1		1
		1,170.0			0.0			5.0	1
3450	24.9			0.0			0.1		T
		1,325.0			0.0			7.5	T
3400	28.1			0.0			0.2		

EARTHWORK SUMMARY											
	EMBANKMENT (CY)	EARTH EXCAVATION (CY)	EXCAVATION USED AS EMBANKMENT (ADJUSTED FOR 15% SHRINKAGE)	EARTHWORK BALANCE WASTE (+), SHORTAGE (-)	NON-SPECIAL WASTE*						
DUBOIS (OGDEN-BURLINGTON)	45.5	1,549.8	52.3	1,497.5	79.4						
BURLINGTON (MAPLE-PRAIRIE)	125.9	3,509.2	144.8	3,364.4	201.5						
TOTAL	171.4	5,059.0	197.2	4,861.9	498.5						

DESIGNED -	X	REVISED -
DRAWN -	ECW, SFB, DMM, GD	REVISED -
CHECKED -	XXX	REVISED -
DATE -	8-7-23	REVISED -


STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

						RTE.	
	EARTHWORK QUANTITIES					0655	
						FIELD E	300K
SCALE:	SHEET NO. 1	OF 1	SHEETS	STA.	TO STA.	FED. R	OAD





	DATUM IS NAVD 88	
B.M. NO.	DESCRIPTION	ELEVATION
1	ARROW BOLT ON F.H. AT STA. 5+25	625.24
2	ENE BONNET BOLT ON F.H. AT STA. 8+95	624.80
3	BONNET BOLT ON F.H. AT STA. 12+30	625.19
4	WSW FLANGE BOLT ON F.H. AT STA. 15+85	623.85
5	WNW BONNET BOLT ON F.H. AT STA. 19+30	624.51
6	N BONNET BOLT ON F.H. AT STA. 22+85	625.05
7	ARROW BOLT ON F.H. AT STA. 26+20	622.65
8	ARROW BOLT ON F.H. AT STA. 29+75	621.82
9	ARROW BOLT ON F.H. AT STA. 33+20	621.65
10	ARROW BOLT ON F.H. AT STA. 36+65	622.27
11	SSE FLANGE BOLT ON F.H. AT STA. 39+85	620.98
12	WNW FLANGE BOLT ON F.H. AT STA. 44+05	620.80
13	ARROW BOLT ON F.H. AT STA. 47+60	620.41
14	ARROW BOLT ON F.H. AT STA, 51+40	617.76



HANCOCK ENGINEERING	xcellence
-----------------------	-----------

◆ Civil Engineers

◆ Municipal Consultants

◆ Established 1911


9933 Roosevelt Road Westchester, IL, 60154-2780 Phone: 708-865-0300 www.ehancock.com

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ALIGNMENT, TIES, AND BENCHMARKS

SCALE: 1"=40' SHEET NO. 1 OF 3 SHEETS STA. TO STA.

LE DOUIECT NO 12



BENCHMARKS

	DATUM IS NAVD 88	
B.M. NO.	DESCRIPTION	ELEVAT
1	ARROW BOLT ON F.H. AT STA. 5+25	625.2
2	ENE BONNET BOLT ON F.H. AT STA. 8+95	624.8
3	BONNET BOLT ON F.H. AT STA. 12+30	625.1
4	WSW FLANGE BOLT ON F.H. AT STA. 15+85	623.8
5	WNW BONNET BOLT ON F.H. AT STA. 19+30	624.5
6	N BONNET BOLT ON F.H. AT STA. 22+85	625.0
7	ARROW BOLT ON F.H. AT STA. 26+20	622.6
8	ARROW BOLT ON F.H. AT STA. 29+75	621.8
9	ARROW BOLT ON F.H. AT STA. 33+20	621.6
10	ARROW BOLT ON F.H. AT STA. 36+65	622.2
11	SSE FLANGE BOLT ON F.H. AT STA. 39+85	620.9
12	WNW FLANGE BOLT ON F.H. AT STA. 44+05	620.8
13	ARROW BOLT ON F.H. AT STA. 47+60	620.4
14	ARROW BOLT ON F.H. AT STA. 51+40	617.7


9933 Roosevelt Road Westchester, IL, 60154-2780 Phone: 708-865-0300 www.ehancock.com


DESIGNED - X REVISED -DRAWN -ECW, SFB, DMM, GD REVISED -CHECKED -XXX REVISED -8-7-23 REVISED -


STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**


ALIGNMENT, TIES, AND BENCHMARKS SCALE: 1" = 40' SHEET NO. 3 OF 3 SHEETS STA.


F.A.U. RTE. 0655 SECTION 20-00133-00-FP COOK 108 19 CONTRACT NO. 61J89 FIELD BOOK NO. : FED. ROAD DIST. NO. 1 | ILLINOIS | FED. AID PROJECT































- 1. PROVIDE 2 3/4" DIAMETER, 18" LONG EPOXY COATED SMOOTH BARS WITH PLASTIC EXPANSION CAPS AT EACH EXPANSION JOINT.
- 2. CONTRACTION JOINT 2" DEEP CONTRACTION JOINTS SHALL BE SAWED AT EQUAL SPACES (NOT EXCEEDING 15 FEET) BETWEEN NORMAL EXPANSION JOINTS, IN THE UPPER 1/3 OF CURB & GUTTERS WITHIN 24 HOURS OF PLACEMENT.

COMBINATION CONCRETE CURB & GUTTER TYPE B-6.12


HMA SURFACE COURSE, MIX D, N50, 2" VARIABLE 3" TO 8" (TO

BE DETERMINED BY THE
ENGINEER IN THE FIELD) ¾" PER F 1½" FOR DEPRESSED CURB AT DRIVEWAYS,
1/2" FOR DEPRESSED
CURB AT ADA RAMPS HMA BINDER COURSE, IL-9.5, N50, 1.5" 2" CRUSHED STONE BEDDING (INCLUDED IN COST OF THIS ITEM) EXISTING BASE COURSE FULL DEPTH SAW CUT PRIOR TO REMOVAL 6" WIDE CONCRETE WEDGE SHALL BE INSTALLED - AFTER CURB HAS BEEN POURED AND SHALL BE INCLUDED IN THIS ITEM. (INCLUDED IN COST OF THIS ITEM)


> **COMBINATION CONCRETE CURB & GUTTER TYPE B-6.12 (MODIFIED)**

1:50 MAX 1/2" (MAX.) FOR 2" CRUSHED STONE BEDDING -

CURB AND GUTTER AT A.D.A. RAMPS



PAVEMENT PATCH FOR CONCRETE BASE PAVEMENT (EXCLUDING UTILITY TRENCH PATCHES)



THE RUNNING SLOPE OF THE CURB RAMP SHALL NOT REQUIRE THE CURB LENGTH TO EXCEED 15'.


PCC BASE COURSE 8"


DEFORMED TIE BARS

4" CRUSHED STONE BEDDING

- EXISTING P.C.C. BASE COURSE. 8'

ADA RAMP





PAVEMENT PATCH FOR CONCRETE BASE PAVEMENT AT UTILITY TRENCHES

DEFORMED TIE BARS

EXISTING P.C.C. BASE COURSE, 8

TOTAL SHEET NO. SECTION COUNTY RTE. **ROADWAY DETAILS** COOK 107 32 0655 20-00133-00-FP FIFI D BOOK NO . CONTRACT NO. 61J89 SHEET NO. 1 OF 3 SHEETS STA. SCALE: NONE TO STA. FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT


◆ Municipal Consultants Phone: 708-865-0300

REVISED ECW, SFB, DMM, GD REVISED DRAWN -CHECKED -XXX REVISED DATE -8-7-23 REVISED


STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

TYPICAL CURB AND GUTTER EXPANSION JOINT


INCIDENTAL HOT-MIX ASPHALT SURFACING




BRICK PAVER CROSS WALK (CROSS SECTION)




ALLEY RETURN




TYPICAL P.C.C. SIDEWALK, DRIVEWAY, **PAVEMENT AND BASE**



BRICK PAVER PARKWAY (CROSS SECTION)



BRICK PAVER PARKWAY PATTERN



TO STA.

BRICK PAVER CROSS WALK (PLAN VIEW)

 Civil Engineers ♦ Municipal Consultants

Phone: 708-865-0300

REVISED ECW, SFB, DMM, GD REVISED DRAWN -CHECKED -XXX REVISED DATE -8-7-23 REVISED


STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

ROADWAY DETAILS SHEET NO. 2 OF 3 SHEETS STA.

SCALE: NONE


F.A.U. RTE. TOTAL SHEET NO. SECTION COUNTY 0655 COOK 107 33 20-00133-00-FP FIFI D BOOK NO · CONTRACT NO. 61J89 FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT

SEGMENTED BLOCK SEAT WALL



RETAINED SOIL SIDE

RETAINING WALL 2



CONNECTION TO EXISTING WALL

3

SEGMENTED BLOCK SEAT WALL (AERIAL)

◆ Municipal Consultants

DESIGNED -	X	REVISED -	
DRAWN -	ECW, SFB, DMM, GD	REVISED -	
CHECKED -	XXX	REVISED -	
DATE -	8-7-23	REVISED -	
			-


SCALE: NONE

			RTE.	SECTION	COUNTY	SHEETS	NO.	
ROADWAY DETAILS				0655	655 20-00133-00-FP COOK		107	34
				FIELD E	BOOK NO. :	CONTRACT N	O. 61J89	
SHEET NO. 3 OF 3	SHEETS	STA.	TO STA.	FED. R	OAD DIST. NO. 1 ILLINOIS FEE	. AID PROJECT		

SYMBOL DESCRIPTION CODE & SIZE SYMBOL DESCRIPTION CODE & SIZE	LEGEND OF SYMBOLS									
Some	SYMBOL	DESCRIPTION	CODE & SIZE	SYMBOL	DESCRIPTION	CODE & SIZE				
R2-1106P 36x18* R2-1106P 36x18* R2-1106P 36x18* R3-1 24*x24* R3-1 24*x24* R3-1 24*x30* R3-1 24*x30* R4-7a 24*x30* R4-7a 24*x30* R5-1a 36*x24* R5-1a 36*x24* R0AD CLOSED AHEAD AHEAD AHEAD R0AD CNSRTUCTION AHEAD CNSRTUCTION AHEAD R0AD CNSRTUCTION AHEAD CNSRTUC		ZONE SPEED LIMIT		(S)	STOP	30"x30"				
RA		\$250 FINE				24"x24" R3-1				
M6-1(0) 21"x15" KL KEEP LEFT R4-8a 24"X30" KL LEFT R4-8a 24"X30" KL LEFT R4-8a 24"X30" KL LEFT R4-8a 24"X30" KL LEFT R4-8a 24"X30" R5-1a 36"x24" R5-1a 36"x24" R5-1a 36"x24" R5-1a 36"x24" R5-1a	RA	-	M6-1(0) 21"x15"	KR		R4-7a				
TW W6-3(0) 36"x36" WW WRONG R5-1a 36"x24"	LA	-			→					
ROAD CLOSED AHEAD ROAD CLOSED AHEAD ROAD CONSTRUCTION AHEAD ROAD CONSTRUCTION AHEAD ROAD AHEAD ROAD AHEAD ROAD CONSTRUCTION AHEAD ROAD AHEAD ROAD AHEAD ROAD AHEAD ROAD AHEAD ROAD CLOSED AHEAD RI1-1102 24"x30" RI1-1102 24"x30" RI1-1102 24"x30" RI1-1102 24"x30" RI1-1102 15E OTHER SIDE ROAD CLOSED TO THRU TRAFFIC ROAD CLOSED THRU TRAFFIC	TW				LEFT ←	24"X30"				
RCA	\wedge		W20-3	ww	WAY					
ROAD	(RCA)	AHEAD	48"x48"	SC	CLOSED USE OTHER					
RS-1 30"X30" RS-1 TT TO THRU TRAFFIC ROAD CLOSED R11-2 48"x30" W24-R(0) 48"x48" W24-R(0) 48"x48"	RWA	ROAD		SC	CLOSED USE OTHER	R11-I102 24"x30"				
CLOSED	DNE		R5-1 30"X30"	RC TTT	TO					
KL LEFT WRA-BA W24-L(0)	RC	ROAD CLOSED	R11-2 48"x30"	$\langle \rangle$	3					
	KL ◀	LEFT		\diamondsuit	(W24-L(O) 48"x48"				


CONTRACTOR MUST NOTIFY IDOT ARTERIAL TRAFFIC CONTROL SUPERVISOR AT (847)705-4470, SEVENTY-TWO HOURS IN ADVANCE OF SETTING UP DETOUR ROUTE.

SCALE: 1" = 40'



STAGE 1A-1 CONSTRUCTION

- 1. WORK DURING THIS STAGE SHALL CONSIST OF THE REMOVAL AND REPLACEMENT OF UTILITIES AS INDICATED IN THE PROPOSED UTILITY PLANS SUCH AS PROPOSED WATER MAIN, PROPOSED STORM SEWER, AND SANITARY $\ensuremath{\mathsf{N}}$
- 2. NO OPEN EXCAVATIONS ARE TO BE LEFT OVERNIGHT. ALL TRENCHES MUST BE BACKFILLED AT THE END OF THE
- IDOT STANDARD 701301-04 SHALL BE USED TO ESTABLISH TRAFFIC CONTROL AND PROTECTION NECESSARY FOR SAW CUTTING, THE REMOVAL OF EXISTING PAVEMENT, EXCAVATION OF UTILITY IMOPROVEMENTS, AND PERFORMING ALL PROPOSED UTILITY IMPROVEMENTS AS SHOWN IN THE UTILITY PLANS AND PROFILE.
- 4. INTERSECTIONS ARE TO REMAIN OPEN AT ALL TIMES, EXCEPT DURING THE PREPARTAION, REMOVAL, AND INSTALLATION OF UTILITY IMPROVEMENTS.
- CONTRACTOR MAY KEEP ROAD CLOSED IN CONSTRUCTION WORK ZONE DURING ACTIVE CONSTRUCTION BUT SHALL MAINTAIN ACCESSIBILITY TO LOCAL TRAFFIC AT ALL OTHER TIMES.
- DRIVEWAYS ARE TO REMAIN ACCESSIBLE THROUGHOUT THE CONSTRUCTION OF THIS STAGE UNLESS A DRIVEWAY IS DISTURBED BY A UTILITY CROSSING. CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE ANY DRIVEWAY ACCESS IS DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR TO NOTIFY RESIDENT 24 HOURS BEFORE ACCESS IS DISTURBED.
- ONCE ALL WORK ASSOCIATED WITH STAGE 1A HAS BEEN COMPLETED, THE CONTRACTOR SHALL INSTALL A TEMPORARY HMA PATCH ON ANY UTILITY TRENCHES AS DIRECTED BY THE ENGINEER, INSTALLATION AND REMOVAL OF PATCH TO BE PAID UNDER PAY ITEM X4420210 TEMPORARY PATCHING.
- CONTRACTOR CANNOT REMOVE EXISTING PAVEMENT IN AREA OUTSIDE OF CONSTRUCTION LIMITS. THE EXISTING CONCRETE AND HMA MUST BE MAINTAINED THROUGHOUT THIS STAGE.



TYPICAL SECTION DURING STAGE 1A-1 CONSTRUCTION

(FOREST AVENUE TO GROVE AVENUE) (STA 48+00 TO STA 52+17)

LEGEND

CONSTRUCTION WORK ZONE

HOT-MIX SURFACE ASPHALT

DIRECTION OF TRAFFIC FLOW

PROPOSED PAVEMENT AREA WITH STANDARD PCC DRIVEWAY PAVEMENT, PCC SIDEWALK, AND CURB & GUTTER

DRUMS OR TYPE II BARRICADES

TYPE II BARRICADE OR DRUM IN TYPICAL CROSS SECTION


Westchester, IL, 60154-2780

DESIGNED -REVISED -DRAWN ECW, SFB, DMM, GD REVISED -CHECKED -REVISED XXX DATE -8-7-23 REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION


MAINTENANCE OF TRAFFIC PLAN STAGE 1A-1 CONSTRUCTION SHEET NO. 2 OF 22 SHEETS STA. SCALE: 1" = 40' TO STA.

SECTION 0655 20-00133-00-FP соок 107 CONTRACT NO. 61J89 FIELD BOOK NO. : FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT




STAGE 1A-2 CONSTRUCTION

- 1. WORK DURING THIS STAGE SHALL CONSIST OF THE REMOVAL AND REPLACEMENT OF UTILITIES AS INDICATED IN THE PROPOSED UTILITY PLANS SUCH AS PROPOSED WATER MAIN, PROPOSED STORM SEWER, AND SANITARY SEWER REPLACEMENT.
- NO OPEN EXCAVATIONS ARE TO BE LEFT OVERNIGHT. ALL TRENCHES MUST BE BACKFILLED AT THE END OF THE
- IDOT STANDARD 701301-04 SHALL BE USED TO ESTABLISH TRAFFIC CONTROL AND PROTECTION NECESSARY FOR SAW CUTTING, THE REMOVAL OF EXISTING PAVEMENT, EXCAVATION OF UTILITY IMOPROVEMENTS, AND PERFORMING ALL PROPOSED UTILITY IMPROVEMENTS AS SHOWN IN THE UTILITY PLANS AND PROFILE.
- INTERSECTIONS ARE TO REMAIN OPEN AT ALL TIMES, EXCEPT DURING THE PREPARATION, REMOVAL, AND INSTALLATION OF UTILITY IMPROVEMENTS. TWO-WAY, NORTH-SOUTH TRAFFIC TO BE MAINTAINED AT ALL TIMES AT PRAIRIE AVENUE BY USE OF SIGNAGE AND TEMPORARY PAVEMENT MARKINGS.
- CONTRACTOR MAY KEEP ROAD (BURLINGTON AVENUE) CLOSED IN CONSTRUCTION WORK ZONE DURING ACTIVE CONSTRUCTION BUT SHALL MAINTAIN ACCESSIBILITY TO LOCAL TRAFFIC AT ALL OTHER TIMES.
- THE BROOKFIELD METRA STATION AND METRA STATION PARKING ON THE NORTH PORTION OF THIS SECTION SHALL REMAIN ACCESSIBLE THROUGHOUT THE CONSTRUCTION OF THIS STAGE UNLESS DISTURBED BY A UTILITY CROSSING. CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE METRA STATION AREA IS DISTURBED TO PERFORM CONSTRUCTION WORK, CONTRACTOR SHALL RETURN ACCESS TO METRA STATION AREA IMMEDIATELY UPON COMPLETION OF UTILITY CONSTRUCTION.
- ONCE ALL WORK ASSOCIATED WITH STAGE 1A HAS BEEN COMPLETED, THE CONTRACTOR SHALL INSTALL A TEMPORARY HMA PATCH ON ANY UTILITY TRENCHES AS DIRECTED BY THE ENGINEER. INSTALLATION AND
- REMOVAL OF PATCH TO BE PAID UNDER PAY ITEM X4420210 TEMPORARY PATCHING.
 CONTRACTOR CANNOT REMOVE EXISTING PAVEMENT IN AREA OUTSIDE OF CONSTRUCTION LIMITS. THE EXISTING CONCRETE AND HMA MUST BE MAINTAINED THROUGHOUT THIS STAGE.



TYPICAL SECTION DURING STAGE 1A-2 CONSTRUCTION

PRAIRIE AVENUE



TYPICAL SECTION DURING STAGE 1A-2 CONSTRUCTION


(PRAIRIE AVENUE TO STA. 46+42)

LEGEND

CONSTRUCTION WORK ZONE DIRECTION OF TRAFFIC FLOW HOT-MIX SURFACE ASPHALT PROPOSED PAVEMENT AREA WITH STANDARD PCC DRIVEWAY PAVEMENT, PCC SIDEWALK, AND CURB & GUTTER

DRUMS OR TYPE II BARRICADES

TYPE II BARRICADE OR DRUM IN TYPICAL CROSS SECTION



TYPICAL SECTION DURING STAGE 1A-2 CONSTRUCTION

(STA. 46+42 TO FOREST AVENUE)





Westchester, IL, 60154-2780

DESIGNED -REVISED -DRAWN ECW, SFB, DMM, GD REVISED CHECKED -REVISED XXX 8-7-23 REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION MAINTENANCE OF TRAFFIC PLAN **STAGE 1A-2 CONSTRUCTION** SHEET NO. 3 OF 22 SHEETS STA.

SCALE: 1" = 40'






HANCOCK | See Section Engineers | Civil Engineers | Municipal Consultants | ENGINEERING | Established 1911

Westchester, IL, 60154-2780

DESIGNED -REVISED · DRAWN ECW, SFB, DMM, GD REVISED CHECKED -REVISED XXX 8-7-23 REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION


SCALE1"=40'



STAGE 1C CONSTRUCTION

- WORK DURING THIS STAGE SHALL CONSIST OF THE REMOVAL AND REPLACEMENT OF UTILITIES AS INDICATED IN THE PROPOSED UTILITY PLANS SUCH AS PROPOSED WATER MAIN, PROPOSED STORM SEWER, AND SANITARY SEWER REPLACEMENT.
- NO OPEN EXCAVATIONS ARE TO BE LEFT OVERNIGHT. ALL TRENCHES MUST BE BACKFILLED AT THE END OF THE DAY.
- IDOT STANDARD 701301-04 SHALL BE USED TO ESTABLISH TRAFFIC CONTROL AND PROTECTION NECESSARY FOR SAW CUTTING, THE REMOVAL OF EXISTING PAVEMENT, EXCAVATION OF UTILITY IMOPROVEMENTS, AND PERFORMING ALL PROPOSED UTILITY IMPROVEMENTS AS SHOWN IN THE UTILITY PLANS AND PROFILE.
- INTERSECTIONS TO REMAIN OPEN AT ALL TIMES, EXCEPT DURING THE PREPARATION, REMOVAL, AND
- INSTALLATION OF UTILITY IMPROVEMENTS UNLESS OTHERWISE NOTED. DRIVEWAYS TO REMAIN OPEN THOUGHOUT THE CONSTRUCTION OF THIS STAGE UNLESS A DRIVEWAY IS DISTURBED BY A UTILITY CROSSING. CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE ANY DRIVEWAYS ARE DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR TO NOTIFY RESIDENT 24 HOURS BEFORE ACCESS IS DISTURBED.
- STAGE 1C AREA WILL BE CLOSED IN INCREMENTS AS THE WORK ZONE MOVES. ROAD CLOSED AND ADDITIONAL ROAD CONSTRUCTION SIGNS TO BE MOVED AS CONSTRUCTION OPERATION MOVES DAILY. ADDITIONAL ROAD CLOSURE SIGNS WILL BE REQUIRED TO THAT SHOWN ON THE PLAN FOR MOVING WORK ZONE CLOSURES
- ACCESS TO BE MAINTAINED AT ALL TIMES TO METRA STATION PARKING LOT 1 AND METRA STATION PARKING LOT 2. THE CONTRACTOR SHALL ALSO INSTALL TEMPORARY ACCESS ENTRANCES ON THE SOUTH SIDE OF METRA STATION PARKING LOT 2 THAT ARE ACCESSIBLE FROM THE ALLEY. THESE ENTRANCES SHALL BE MAINTAINED THROUGHOUT THE DURATION OF THE PROJECT.
- ACCESS SHALL BE MAINTAINED AT ALL TIMES TO THE CONGRESS PARK METRA STATION ENTRANCE ON THE NORTH SIDE OF BURLINGTON AVENUE.
- ONCE ALL WORK ASSOCIATED WITH STAGE 1C HAS BEEN COMPLETED. THE CONTRACTOR SHALL INSTALL A TEMPORARY HMA PATCH ON ANY UTILITY TRENCHES AS DIRECTED BY THE ENGINEER. INSTALLATION AND REMOVAL OF PATCH TO BE PAID UNDER PAY ITEM X4420210 TEMPORARY PATCHING.

 10. CONTRACTOR CANNOT REMOVE EXISTING PAVEMENT IN AREA OUTSIDE OF CONSTRUCTION LIMITS. THE
- EXISTING CONCRETE AND HMA MUST BE MAINTAINED THROUGHOUT THIS STAGE.



TYPICAL SECTION DURING STAGE 1C CONSTRUCTION

(DUBOIS BOULEVARD TO MAPLE AVENUE)

LEGEND

CONSTRUCTION WORK ZONE

DIRECTION OF TRAFFIC FLOW

HOT-MIX SURFACE ASPHALT

PROPOSED PAVEMENT AREA WITH STANDARD PCC DRIVEWAY PAVEMENT, PCC SIDEWALK, AND CURB & GUTTER

DRUMS OR TYPE II BARRICADES

TO STA.

TYPE II BARRICADE OR DRUM IN TYPICAL CROSS SECTION

◆ Civil Engineers ◆ Municipal Consultants


Westchester, IL, 60154-2780

DESIGNED -REVISED -DRAWN ECW, SFB, DMM, GD REVISED CHECKED -REVISED XXX DATE -8-7-23 REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION MAINTENANCE OF TRAFFIC PLAN **STAGE 1C-2 CONSTRUCTION**


SHEET NO. 6 OF 22 SHEETS STA.

SCALE1"=40'




STAGE 2A CONSTRUCTION

- WORK DURING THIS STAGE SHALL CONSIST OF THE REMOVAL AND REPLACEMENT OF CONCRETE CURB, DRIVEWAY APRONS, SIDEWALKS, AND PAVEMENT ON THE NORTH SIDE OF BURLINGTON AVENUE AS INDICATED IN THE PROPOSED PAVING PLAN AND PROFILE. THIS WORK SHALL ALSO INCLUDE RESTORATION WORK OF DRIVEWAYS AND PAVEMENTS TO ALLOW FOR ACCESS ONCE THE WORK IS COMPLETE.
- ONCE THE CONTRACTOR STARTS REMOVALS FOR THIS STAGE, THE CONCRETE IMPROVEMENTS AND RESTORATION WORK SHALL BE COMPLETED WITHIN 14 CALENDAR DAYS LIQUIDATED DAMAGES TO APPLY AT THE FND OF 14 CALENDAR DAYS FROM START OF REMOVAL IF THE IMPROVEMENTS HAVE NOT BEEN COMPLETED AND ACCESS HAS NOT BEEN RESTORED.
- IDOT STANDARD 701301-04 SHALL BE USED TO ESTABLISH TRAFFIC CONTROL AND PROTECTION NECESSARY FOR SAW CUTTING, REMOVAL AND REPLACEMENT OF CONCRETE CURB, DRIVEWAY APRONS, SIDEWALKS, AND PAVEMENT AS SHOWN IN THE PAVING PLAN AND PROFILE.
- INTERSECTIONS ARE TO REMAIN OPEN AT ALL TIMES, EXCEPT DURING THE PREPARATION, REMOVAL, AND INSTALLATION OF UTILITY IMPROVEMENTS. TWO-WAY, NORTH-SOUTH TRAFFIC TO BE MAINTAINED AT ALL TIMES AT PRAIRIE AVENUE BY USE OF SIGNAGE AND TEMPORARY PAVEMENT MARKINGS.
- CONTRACTOR TO NOTIFY ENGINEER 48 HOURS REFORE ANY DRIVEWAY ACCESS IS DISTURRED TO PERFORM CONSTRUCTION WORK. CONTRACTOR TO NOTIFY RESIDENT 24 HOURS BEFORE ACCESS IS DISTURBED.
- TEMPORARY ROAD CLOSURES TO OCCUR DURING CONSTRUCTION FOR WORK SUCH AS CURB AND PAVEMENT REMOVAL AND REPLACEMENT.
- THE BROOKFIELD METRA STATION AND METRA STATION PARKING ON THE NORTH PORTION OF THIS SECTION SHALL REMAIN ACCESSIBLE THROUGHOUT THE CONSTRUCTION OF THIS STAGE UNLESS DISTURBED BY CURB OR PAVEMENT REMOVAL. CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE METRA STATION AREA IS DISTURBED TO PERFORM CONSTRUCTION WORK, CONTRACTOR SHALL RETURN ACCESS TO METRA STATION AREA
- IMMEDIATELY UPON COMPLETION OF CONCRETE IMPROVEMENTS. 8. CONTRACTOR CANNOT REMOVE EXISTING PAVEMENT IN AREA OUTSIDE OF CONSTRUCTION LIMITS. THE EXISTING CONCRETE AND HMA MUST BE MAINTAINED THROUGHOUT THIS STAGE.




TYPICAL SECTION DURING STAGE 2A CONSTRUCTION

PRAIRIE AVENUE




LEGEND




TYPICAL SECTION DURING STAGE 2A CONSTRUCTION

(PRAIRIE AVENUE TO STA. 46+42)



TYPICAL SECTION DURING STAGE 2A CONSTRUCTION

(STA. 46+42 TO FOREST AVENUE)



TYPICAL SECTION DURING STAGE 2A CONSTRUCTION

(FOREST AVENUE TO GROVE AVENUE) (STA 48+00 TO STA 52+17)

TO STA.

HANCOCK BANGINEERING BANGINEERIN	◆ () ◆ N
	◆ E

Civil Engineers Municipal Consultants Established 1911

3 Roosevelt Road	DESIGNED -	X	REVISED -
er, IL, 60154-2780	DRAWN -	ECW, SFB, DMM, GD	REVISED -
ne: 708-865-0300 v.ehancock.com	CHECKED -	XXX	REVISED -
v.enancock.com	DATE -	8-7-23	REVISED -


STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION


MAINTENANCE OF TRAFFIC PLAN
STAGE 2A CONSTRUCTION

SHEET NO. 7 OF 22 SHEETS STA.

SCALE: 1" = 40'

SECTION 0655 20-00133-00-FP соок 107 FIELD BOOK NO. : CONTRACT NO. 61J89





ECW, SFB, DMM, GD


REVISED

DRAWN

Westchester, IL, 60154-2780

◆ Civil Engineers

- WORK DURING THIS STAGE SHALL CONSIST OF THE REMOVAL AND REPLACEMENT OF CONCRETE CURB, DRIVEWAY
 APRONS, SIDEWALKS, AND PAVEMENT AS WELL AS IMPROVEMENTS TO THE CONGRESS PARK METRA STATION PLAZA ON THE NORTH SIDE OF BURLINGTON AVENUE AND WEST SIDE OF DUBOIS BOULEVARD AS INDICATED IN THE PROPOSED PAVING PLAN AND PROFILE. THIS WORK SHALL INCLUDE RESTORATION WORK OF DRIVEWAYS AND PAVEMENTS TO ALLOW FOR ACCESS ONCE THE WORK IS COMPLETE.
- ONCE THE CONTRACTOR STARTS REMOVALS FOR ANY AREA OF THIS STAGE. THE CONCRETE IMPROVEMENTS AND RESTORATION WORK SHALL BE COMPLETED WITHIN 14 CALENDAR DAYS. LIQUIDATED DAMAGES TO APPLY AT THE END OF 14 CALENDAR DAYS FROM START OF REMOVAL IF THE IMPROVEMENTS HAVE NOT BEEN COMPLETED AND ACCESS HAS NOT BEEN RESTORED. CONTRACTOR TO COORDINATE STAGE 2C IMPROVEMENTS WITH CONGRESS
- PARK METRA STATION WORK.
 IDOT STANDARD 701301-04 SHALL BE USED TO ESTABLISH TRAFFIC CONTROL AND PROTECTION NECESSARY FOR SAW CUTTING, REMOVAL AND REPLACEMENT OF CONCRETE CURB, DRIVEWAY APRONS, SIDEWALKS, AND PAVEMENT AS SHOWN IN THE PAVING PLAN AND PROFILE.
- INTERSECTIONS ARE TO REMAIN OPEN AT ALL TIMES, EXCEPT DURING THE PREPARATION, REMOVAL, AND INSTALLATION OF CONCRETE PAVEMENT IMPROVEMENTS
- TEMPORARY ROAD CLOSURES TO OCCUR DURING CONSTRUCTION FOR WORK SUCH AS CURB AND PAVEMENT REMOVAL AND REPLACEMENT.
- CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE ANY DRIVEWAY ACCESS IS DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR TO NOTIFY RESIDENT 24 HOURS BEFORE ACCESS IS DISTURBED.
 STAGE 2C AREA WILL BE CLOSED IN INCREMENTS AS THE WORK ZONE MOVES. ROAD CLOSED AND ADDITIONAL
- ROAD CONSTRUCTION SIGNS TO BE MOVED AS CONSTRUCTION OPERATION MOVES DAILY. ADDITIONAL ROAD CLOSURE SIGNS WILL BE REQUIRED TO THAT SHOWN ON THE PLAN FOR MOVING WORK ZONE CLOSURES.
- METRA STATION PARKING LOT 1 AND METRA STATION PARKING LOT 2 SHALL REMAIN ACCESSIBLE THROUGOUT THE CONSTRUCTION OF THIS STAGE UNLESS DISTURBED BY THE CONCRETE IMPROVEMENTS. CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE METRA STATION ACCESS IS DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR SHALL RETURN ACCESS TO METRA STATION PARKING LOTS IMMEDIATELY UPON COMPLETION OF CONCRETE IMPROVEMENTS. TEMPORARY ACCESS ENTRANCE TO METRA STATION PARKING LOT 2 TO BE MAINTAINED AND ACCESSIBLE FOR THE DURATION OF THIS STAGE.
- CONTRACTOR TO COORDINATE CONGRESS PARK METRA STATION PLAZA IMPROVEMENTS SO THAT ACCESS CAN BE MAINTAINED AT ALL TIMES TO THE METRA STATION ENTRANCE ON THE NORTH SIDE OF BURLINGTON AVENUE.
- 10. CONTRACTOR CANNOT REMOVE EXISTING PAVEMENT IN AREA OUTSIDE OF CONSTRUCTION LIMITS. THE EXISTING CONCRETE AND HMA MUST BE MAINTANINED THROUGHOUT THIS STAGE.



TYPICAL SECTION DURING STAGE 2C CONSTRUCTION

(DUBOIS BOULEVARD TO MAPLE AVENUE)

LEGEND

CONSTRUCTION WORK ZONE

DIRECTION OF TRAFFIC FLOW

PROPOSED PAVEMENT AREA WITH STANDARD PCC DRIVEWAY PAVEMENT, PCC SIDEWALK, AND CURB & GUTTER

HOT-MIX SURFACE ASPHALT

DRUMS OR TYPE II BARRICADES \circ

TO STA.

TYPE II BARRICADE OR DRUM IN TYPICAL CROSS SECTION

◆ Civil Engineers ◆ Municipal Consultants

Westchester, IL, 60154-2780

DRAWN CHECKED -XXX DATE -8-7-23


DESIGNED -REVISED · ECW, SFB, DMM, GD REVISED REVISED REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION MAINTENANCE OF TRAFFIC PLAN **STAGE 2C-2 CONSTRUCTION**

SHEET NO. 10 OF 22 SHEETS STA.


SCALE1"=40'






STAGE 3A CONSTRUCTION


- WORK DURING THIS STAGE SHALL CONSIST OF THE REMOVAL AND REPLACEMENT OF CONCRETE CURB, DRIVEWAY APRONS, SIDEWALKS, AND PAVEMENT ON THE SOUTH SIDE OF BURLINGTON AVENUE AS INDICATED IN THE PROPOSED PAVING PLAN AND PROFILE. THIS WORK SHALL ALSO INCLUDE RESTORATION WORK OF DRIVEWAYS AND PAVEMENTS TO ALLOW FOR ACCESS ONCE THE WORK IS COMPLETE.
- 2. ONCE THE CONTRACTOR STARTS REMOVALS FOR THIS STAGE, THE CONCRETE IMPROVEMENTS AND RESTORATION WORK SHALL BE COMPLETED WITHIN 14 CALENDAR DAYS, LIQUIDATED DAMAGES TO APPLY AT THE END OF 14 CALENDAR DAYS FROM START OF REMOVAL IF THE IMPROVEMENTS HAVE NOT BEEN COMPLETED AND ACCESS HAS NOT BEEN RESTORED
- 3. IDOT STANDARD 701301-04 SHALL BE USED TO ESTABLISH TRAFFIC CONTROL AND PROTECTION NECESSARY FOR SAW CUTTING, REMOVAL AND REPLACEMENT OF CONCRETE CURB, DRIVEWAY APRONS, SIDEWALKS, AND PAVEMENT AS SHOWN IN THE PAVING PLAN AND PROFILE.
- INTERSECTIONS ARE TO REMAIN OPEN AT ALL TIMES, EXCEPT DURING THE PREPARATION, REMOVAL, AND INSTALLATION OF UTILITY IMPROVEMENTS. TWO-WAY, NORTH-SOUTH TRAFFIC TO BE MAINTAINED AT ALL TIMES AT PRAIRIE AVENUE BY USE OF SIGNAGE AND TEMPORARY PAVEMENT MARKINGS.
- CONTRACTOR TO NOTIFY ENGINEER 48 HOURS REFORE ANY DRIVEWAY ACCESS IS DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR TO NOTIFY RESIDENT 24 HOURS BEFORE ACCESS IS DISTURBED.
- TEMPORARY ROAD CLOSURES TO OCCUR DURING CONSTRUCTION FOR WORK SUCH AS CURB AND PAVEMENT REMOVAL AND REPLACEMENT.
- THE BROOKFIELD METRA STATION AND METRA STATION PARKING ON THE NORTH PORTION OF THIS SECTION SHALL REMAIN ACCESSIBLE THROUGHOUT THE CONSTRUCTION OF THIS STAGE UNLESS DISTURBED BY CURB OR PAVEMENT REMOVAL. CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE METRA STATION AREA IS DISTURBED TO PERFORM CONSTRUCTION WORK, CONTRACTOR SHALL RETURN ACCESS TO METRA STATION AREA IMMEDIATELY UPON COMPLETION OF CONCRETE IMPROVEMENTS.
- 8. CONTRACTOR CANNOT REMOVE EXISTING PAVEMENT IN AREA OUTSIDE OF CONSTRUCTION LIMITS. THE EXISTING CONCRETE AND HMA MUST BE MAINTAINED THROUGHOUT THIS STAGE.



TYPICAL SECTION DURING STAGE 3A CONSTRUCTION


PRAIRIE AVENUE






TYPICAL SECTION DURING STAGE 3A CONSTRUCTION

(PRAIRIE AVENUE TO STA. 46+42)



TYPICAL SECTION DURING STAGE 3A CONSTRUCTION

(STA. 46+42 TO FOREST AVENUE)



TYPICAL SECTION DURING STAGE 3A CONSTRUCTION

(FOREST AVENUE TO GROVE AVENUE)

TO STA.



◆ Municipal Consultants


	DESIGNED -	^	KENISED -
Road 4-2780	DRAWN -	ECW, SFB, DMM, GD	REVISED -
5-0300 k.com	CHECKED -	XXX	REVISED -
k.com	DATE -	8-7-23	REVISED -

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

N					OF T		C PLAN TION
•	SHEET NO.	11	OF	22	SHEETS	STA.	TO STA

SCALE: 1" = 40'

SECTION 0655 20-00133-00-FP соок 107 CONTRACT NO. 61J89 FIELD BOOK NO. : FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT



STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION

DESIGNED -

DRAWN

DATE -

CHECKED -

Westchester, IL, 60154-2780

♦ Municipal Consultants

REVISED -

REVISED

REVISED

REVISED

ECW, SFB, DMM, GD

XXX

8-7-23

CONTRACT NO. 61J89

107

соок

SECTION

20-00133-00-FP

0655

TO STA.


FIELD BOOK NO. :

MAINTENANCE OF TRAFFIC PLAN

STAGE 3B CONSTRUCTION

SHEET NO. 12 OF 22 SHEETS STA.

SCALE: 1" = 40'



LEGEND

CONSTRUCTION WORK ZONE

DIRECTION OF TRAFFIC FLOW


HOT-MIX SURFACE ASPHALT

PROPOSED PAVEMENT AREA WITH STANDARD PCC DRIVEWAY PAVEMENT, PCC SIDEWALK, AND CURB & GUTTER

DRUMS OR TYPE II BARRICADES

TYPE III BARRICADE

TYPE II BARRICADE OR DRUM IN TYPICAL CROSS SECTION



TYPICAL SECTION DURING STAGE 3C CONSTRUCTION

(DUBOIS BOULEVARD TO MAPLE AVENUE)

TO STA.


◆ Civil Engineers ♦ Municipal Consultants Westchester, IL, 60154-2780

DESIGNED -REVISED · DRAWN ECW, SFB, DMM, GD REVISED CHECKED -XXX REVISED DATE -8-7-23 REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION MAINTENANCE OF TRAFFIC PLAN **STAGE 3C-1 CONSTRUCTION**


SHEET NO. 13 OF 22 SHEETS STA.

SCALE1"=40'



STAGE 3C CONSTRUCTION

- 1 WORK DURING THIS STAGE SHALL CONSIST OF THE REMOVAL AND REPLACEMENT OF CONCRETE CURB. DRIVEWAY APRONS, SIDEWALKS, AND PAVEMENT AS WELL AS IMPROVEMENTS TO THE CONGRESS PARK METRA STATION PLAZA ON THE SOUTH SIDE OF BURLINGTON AVENUE AND EAST SIDE OF DUBOIS BOULEVARD AS INDICATED IN THE PROPOSED PAVING PLAN AND PROFILE. THIS WORK SHALL INCLUDE RESTORATION WORK OF DRIVEWAYS AND
- PAVEMENTS TO ALLOW FOR ACCESS ONCE THE WORK IS COMPLETE.
 ONCE THE CONTRACTOR STARTS REMOVALS FOR ANY AREA OF THIS STAGE, THE CONCRETE IMPROVEMENTS AND RESTORATION WORK SHALL BE COMPLETED WITHIN 14 CALENDAR DAYS. LIQUIDATED DAMAGES TO APPLY AT THE END OF 14 CALENDAR DAYS FROM START OF REMOVAL IF THE IMPROVEMENTS HAVE NOT BEEN COMPLETED AND ACCESS HAS NOT BEEN RESTORED.
- IDOT STANDARD 701301-04 SHALL BE LISED TO ESTABLISH TRAFFIC CONTROL AND PROTECTION NECESSARY FOR SAW CUTTING, REMOVAL AND REPLACEMENT OF CONCRETE CURB, DRIVEWAY APRONS, SIDEWALKS, AND PAVEMENT AS SHOWN IN THE PAVING PLAN AND PROFILE
- INTERSECTIONS ARE TO REMAIN OPEN AT ALL TIMES, EXCEPT DURING THE PREPARATION, REMOVAL, AND
- INSTALLATION OF CONCRETE PAVEMENT IMPROVEMENTS.
 TEMPORARY ROAD CLOSURES TO OCCUR DURING CONSTRUCTION FOR WORK SUCH AS CURB AND PAVEMENT REMOVAL AND REPLACEMENT.
- CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE ANY DRIVEWAY ACCESS IS DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR TO NOTIFY RESIDENT 24 HOURS BEFORE ACCESS IS DISTURBED.
- STAGE 3C AREA WILL BE CLOSED IN INCREMENTS AS THE WORK ZONE MOVES. ROAD CLOSED AND ADDITIONAL ROAD CONSTRUCTION SIGNS TO BE MOVED AS CONSTRUCTION OPERATION MOVES DAILY. ADDITIONAL ROAD
- CLOSURE SIGNS WILL BE REQUIRED TO THAT SHOWN ON THE PLAN FOR MOVING WORK ZONE CLOSURES.
 METRA STATION PARKING LOT 1 AND METRA STATION PARKING LOT 2 SHALL REMAIN ACCESSIBLE THROUGOUT THE CONSTRUCTION OF THIS STAGE UNLESS DISTURBED BY THE CONCRETE IMPROVEMENTS. CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE METRA STATION ACCESS IS DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR SHALL RETURN ACCESS TO METRA STATION PARKING LOTS IMMEDIATELY UPON COMPLETION OF CONCRETE IMPROVEMENTS. TEMPORARY ACCESS ENTRANCE TO METRA STATION PARKING LOT 2 TO BE MAINTAINED AND ACCESSIBLE FOR THE DURATION OF THIS STAGE.
- CONTRACTOR CANNOT REMOVE EXISTING PAVEMENT IN AREA OUTSIDE OF CONSTRUCTION LIMITS. THE EXISTING CONCRETE AND HMA MUST BE MAINTANINED THROUGHOUT THIS STAGE.



TYPICAL SECTION DURING STAGE 3C CONSTRUCTION

(DUBOIS BOULEVARD TO MAPLE AVENUE)

LEGEND

CONSTRUCTION WORK ZONE DIRECTION OF TRAFFIC FLOW

HOT-MIX SURFACE ASPHALT

PROPOSED PAVEMENT AREA WITH STANDARD PCC DRIVEWAY PAVEMENT, PCC SIDEWALK, AND CURB & GUTTER DRUMS OR TYPE II BARRICADES

TYPE II BARRICADE OR DRUM IN TYPICAL CROSS SECTION



◆ Civil Engineers


Westchester, IL, 60154-2780

DESIGNED -REVISED · DRAWN ECW, SFB, DMM, GD REVISED CHECKED -REVISED XXX 8-7-23 REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION **MAINTENANCE OF TRAFFIC PLAN STAGE 3C-2 CONSTRUCTION** SHEET NO. 14 OF 22 SHEETS STA. TO STA.


SCALE1"=40'

F.A.U. RTE.	SECTION			COUNTY	TOTAL SHEETS	SHE
0655	20-0013	3-00-FP	соок	107	4	
FIELD BOOK NO. :				CONTRACT N	O. 61J89	
FED. R	OAD DIST. NO. 1	ILLINOIS	FED	. AID PROJECT		




STAGE 4A CONSTRUCTION

- WORK DURING THIS STAGE SHALL CONSIST OF THE MILLING OF PAVEMENT AND INSTALLATION OF HMA BINDER COURSE ON BURLINGTON AVENUE AS INDICATED IN THE PROPOSED PAVING PLAN AND PROFILE. PAVEMENT PATCHING MAY ALSO BE INCLUDED IN THIS STAGE ONCE THE MILLING HAS BEEN COMPLETED AND THE PAVEMENT CONDITION CAN BE ASSESSED.
- ONCE THE PAVEMENT HAS BEEN MILLED, THE CONTRACTOR SHALL INSTALL THE HMA BINDER WITHIN 7 CALENDAR DAYS. IF THE ENGINEER DETERMINES THAT PAVEMENT PATCHING IS REQUIRED, THE CONTRACTOR WILL HAVE AN ADDITIONAL 7 CALENDAR DAYS FOR A TOTAL OF 14 CALENDAR DAYS FROM PAVEMENT MILLING TO REMOVE AND REPLACE THE PAVEMENT AND INSTALL 1ST LIFT OF HMA. LIQUIDATED DAMAGES TO APPLY AT THE END OF 7 CALENDAR DAYS FROM START OF MILLING IF HMA BINDER HAS NOT BEEN INSTALLED AND NO PATCHING IS REQUIRED OR 14 CALENDAR DAYS FROM THE START OF MILLING IF HMA BINDER HAS NOT BEEN INSTALLED AND PATCHING IS
- 3. IDOT STANDARD 701501-06 SHALL BE USED TO ESTABLISH TRAFFIC CONTROL AND PROTECTION NECESSARY FOR SAW CUTTING, MILLING OF PAVEMENT, AND INSTALLATION OF HMA BINDER AS SHOWN IN THE PAVING PLAN AND PROFILE AND REMOVAL AND REPLACEMENT OF CONCRETE PAVEMENT AS NEEDED.
- INTERSECTIONS ARE TO REMAIN OPEN AT ALL TIMES, EXCEPT DURING THE PREPARATION, REMOVAL, AND INSTALLATION OF UTILITY IMPROVEMENTS. TWO-WAY, NORTH-SOUTH TRAFFIC TO BE MAINTAINED AT ALL TIMES AT PRAIRIE AVENUE BY USE OF SIGNAGE AND TEMPORARY PAVEMENT MARKINGS.
- CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE ANY DRIVEWAY ACCESS IS DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR TO NOTIFY RESIDENT 24 HOURS BEFORE ACCESS IS DISTURBED.
- TEMPORARY ROAD CLOSURES TO OCCUR DURING CONSTRUCTION FOR WORK SUCH AS PAVEMENT IMPROVEMENTS AND INSTALLATION OF HMA BINDER.
- THE BROOKFIELD METRA STATION AND METRA STATION PARKING ON THE NORTH PORTION OF THIS SECTION SHALL REMAIN ACCESSIBLE THROUGHOUT THE CONSTRUCTION OF THIS STAGE UNLESS DISTURBED BY PAVEMENT IMPROVEMENTS. CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE METRA STATION AREA IS DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR SHALL RETURN ACCESS TO METRA STATION AREA IMMEDIATELY UPON COMPLETION OF CONCRETE IMPROVEMENTS.
- ALL HMA SURFACE COURSE TO BE COMPLETED IN STAGE 5.
- CONTRACTOR CANNOT REMOVE EXISTING PAVEMENT IN AREA OUTSIDE OF CONSTRUCTION LIMITS. THE EXISTING CONCRETE AND HMA MUST BE MAINTAINED THROUGHOUT THIS STAGE UNLESS INDICATED FOR REMOVAL ON THE PAVING PLAN OR BY THE ENGINEER.




TYPICAL SECTION DURING STAGE 4A CONSTRUCTION

(PRAIRIE AVENUE TO STA. 46+42)



TYPICAL SECTION DURING STAGE 4A CONSTRUCTION

PRAIRIE AVENUE



TYPICAL SECTION DURING STAGE 4A CONSTRUCTION

(STA. 46+42 TO FOREST AVENUE)

LEGEND

CONSTRUCTION WORK ZONE DIRECTION OF TRAFFIC FLOW


HOT-MIX SURFACE ASPHALT

PROPOSED PAVEMENT AREA WITH STANDARD PCC DRIVEWAY PAVEMENT, PCC SIDEWALK, AND CURB & GUTTER

0 DRUMS OR TYPE II BARRICADES

TYPE III BARRICADE

TYPE II BARRICADE OR DRUM IN TYPICAL CROSS SECTION



TYPICAL SECTION DURING STAGE 4A CONSTRUCTION

(FOREST AVENUE TO GROVE AVENUE)

TO STA.




◆ Civil Engineers ◆ Municipal Consultants


Westchester, IL, 60154-2780

DESIGNED -REVISED · DRAWN ECW, SFB, DMM, GD REVISED CHECKED -REVISED XXX DATE -8-7-23 REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION MAINTENANCE OF TRAFFIC PLAN **STAGE 4A CONSTRUCTION** SHEET NO. 15 OF 22 SHEETS STA.

SCALE: 1" = 40'





STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION

MAINTENANCE OF TRAFFIC PLAN

STAGE 4B CONSTRUCTION

SHEET NO. 16 OF 22 SHEETS STA.

SCALE: 1" = 40'

DESIGNED -

DRAWN

DATE -

CHECKED -

Westchester, IL, 60154-2780

◆ Municipal Consultants

REVISED ·

REVISED

REVISED

REVISED

ECW, SFB, DMM, GD

XXX

8-7-23

1.E. PROJECT NO. 125-22-25201

107

соок


CONTRACT NO. 61J89

0655

TO STA.

FIELD BOOK NO.

20-00133-00-FP



METRA STATION PARKING LOT 1 AND METRA STATION PARKING LOT 2 SHALL REMAIN ACCESSIBLE THROUGOUT THE CONSTRUCTION OF THIS STAGE UNLESS DISTURBED BY THE PAVEMENT IMPROVEMENTS OR INSTALLATION OF BINDER COURSE. CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE METRA STATION ACCESS IS DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR SHALL RETURN ACCESS TO METRA STATION PARKING LOTS IMMEDIATELY UPON COMPLETION OF CONCRETE IMPROVEMENTS. TEMPORARY ACCESS ENTRANCE TO METRA STATION PARKING LOT 2 TO BE MAINTAINED AND ACCESSIBLE FOR THE DURATION OF THIS STAGE.

10. ACCESS SHALL BE MAINTAINED AT ALL TIMES TO THE CONGRESS PARK METRA STATION ENTRANCE ON THE NORTH SIDE OF BURLINGTON AVENUE

11 ALL HMA SURFACE COURSE TO BE COMPLETED IN STAGE 5

12. CONTRACTOR CANNOT REMOVE EXISTING PAVEMENT IN AREA OUTSIDE OF CONSTRUCTION LIMITS. THE EXISTING CONCRETE AND HMA MUST BE MAINTAINED THROUGHOUT THIS STAGE UNLESS INDICATED FOR REMOVAL ON THE PAVING PLAN OR BY THE ENGINEER.

CONSTRUCTION WORK ZONE (39')

TYPICAL SECTION DURING STAGE 4C CONSTRUCTION

DUBOIS BOULEVARD (2' NORTH OF OGDEN AVENUE TO BURLINGTON AVENUE)

LEGEND

CONSTRUCTION WORK ZONE DIRECTION OF TRAFFIC FLOW


HOT-MIX SURFACE ASPHALT

PROPOSED PAVEMENT AREA WITH STANDARD PCC DRIVEWAY PAVEMENT, PCC SIDEWALK, AND CURB & GUTTER

DRUMS OR TYPE II BARRICADES

TYPE III BARRICADE

TYPE II BARRICADE OR DRUM IN TYPICAL CROSS SECTION



TYPICAL SECTION DURING STAGE 4C CONSTRUCTION

(DUBOIS BOULEVARD TO MAPLE AVENUE)

◆ Civil Engineers

OGDEN AVENUE (US 34)


Westchester, IL, 60154-2780

DESIGNED -REVISED · DRAWN ECW, SFB, DMM, GD REVISED CHECKED -XXX REVISED 8-7-23 REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION MAINTENANCE OF TRAFFIC PLAN **STAGE 4C-1 CONSTRUCTION** SHEET NO. 17 OF 22 SHEETS STA. TO STA.

SCALE1"=40'


SECTION 0655 20-00133-00-FP соок 107 CONTRACT NO. 61J89 FIELD BOOK NO. FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT



STAGE 4C CONSTRUCTION

- 1. WORK DURING THIS STAGE SHALL CONSIST OF THE REMOVAL AND EXCAVATION OF PAVEMENT, PLACEMENT OF AGGREGATE STONE BASE, PAVEMENT PATCHING, AND INSTALLATION OF HMA 1ST LIFT OF HMA, AND INSTALLATION OF HMA BINDER COURSE AS SHOWN ON THE PAVING PLAN AND PROFILE. THIS WORK SHALL ALSO INCLUDE RESTORATION WORK OF PAVEMENTS TO ALLOW FOR ACCESS ONCE THE WORK IS COMPLETE.
- ONCE THE CONTRACTOR STARTS REMOVALS BETWEEN OGDEN AVENUE AND STATION 7+85, THE CONTRACTOR SHALL RESTORE ACCESS WITH A COMPLETED EXCAVATION, AGGREGATE STONE BASE, AND HMA BINDER COURSE WITHIN 14 CALENDAR DAYS. LIQUIDATED DAMAGES TO APPLY AT THE END OF 14 CALENDAR DAYS FROM THE START OF REMOVAL IF THE BINDER COURSE HAS NOT BEEN INSTALLED AND ACCESS HAS NOT BEEN RESTORED. HMA SURFACE COURSE SHALL NOT BE INCLUDED IN THE 14 CALENDAR DAYS.

 ONCE THE PAVEMENT HAS BEEN MILLED BETWEEN STATION 7+85 AND MAPLE AVENUE, THE CONTRACTOR SHALL INSTALL THE HMA BINDER WITHIN 7
- CALENDAR DAYS. IF THE ENGINEER DETERMINES THAT PAVEMENT PATCHING IS REQUIRED, THE CONTRACTOR WILL HAVE AN ADDITIONAL 7 CALENDAR DAYS FOR A TOTAL OF 14 CALENDAR DAYS FROM PAVEMENT MILLING TO REMOVE AND REPLACE THE PAVEMENT AND INSTALL THE HMA BINDER. LIQUIDATED DAMAGES TO APPLY AT THE END OF 7 CALENDAR DAYS FROM START OF MILLING IF HMA BINDER HAS NOT BEEN INSTALLED AND NO
- PATCHING IS REQUIRED OR 14 CALENDAR DAYS FROM THE START OF MILLING IF HMA BINDER HAS NOT BEEN INSTALLED AND PATCHING IS REQUIRED. IDOT STANDARD 701301-04 SHALL BE USED TO ESTABLISH TRAFFIC CONTROL AND PROTECTION NECESSARY FOR SAW CUTTING, EXCAVATION,
- PAVEMENTS IMPROVEMENTS, AND INSTALLATION OF HMA BINDER COURSE AS SHOWN IN THE PAVING PLAN AND PROFILE.
 INTERSECTIONS ARE TO REMAIN OPEN AT ALL TIMES, EXCEPT DURING THE PREPARATION, REMOVAL, AND INSTALLATION OF PAVEMENT
- IMPROVEMENTS AND INSTALLATION OF THE HMA BINDER COURSE.
 CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE ANY DRIVEWAY ACCESS IS DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR TO NOTIFY RESIDENT 24 HOURS BEFORE ACCESS IS DISTURBED.
- TEMPORARY ROAD CLOSURES TO OCCUR DURING CONSTRUCTION FOR WORK SUCH AS PAVEMENT IMPROVEMENTS AND INSTALLATION OF HMA
- STAGE 4C AREA WILL BE CLOSED IN INCREMENTS AS THE WORK ZONE MOVES, ROAD CLOSED AND ADDITIONAL ROAD CONSTRUCTION SIGNS TO BE MOVED AS CONSTRUCTION OPERATION MOVES DAILY, ADDITIONAL ROAD CLOSURE SIGNS WILL BE REQUIRED TO THAT SHOWN ON THE PLAN FOR MOVING WORK ZONE CLOSURES.
- METRA STATION PARKING LOT 1 AND METRA STATION PARKING LOT 2 SHALL REMAIN ACCESSIBLE THROUGOUT THE CONSTRUCTION OF THIS STAGE UNLESS DISTURBED BY THE PAVEMENT IMPROVEMENTS OR INSTALLATION OF BINDER COURSE. CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE METRA STATION ACCESS IS DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR SHALL RETURN ACCESS TO METRA STATION PARKING LOTS IMMEDIATELY UPON COMPLETION OF CONCRETE IMPROVEMENTS. TEMPORARY ACCESS ENTRANCE TO METRA STATION PARKING LOT 2 TO BE MAINTAINED AND ACCESSIBLE FOR THE DURATION OF THIS STAGE
- 10. ACCESS SHALL BE MAINTAINED AT ALL TIMES TO THE CONGRESS PARK METRA STATION ENTRANCE ON THE NORTH SIDE OF BURLINGTON AVENUE.
- ALL HMA SURFACE COURSE TO BE COMPLETED IN STAGE 5.
- 12. CONTRACTOR CANNOT REMOVE EXISTING PAVEMENT IN AREA OUTSIDE OF CONSTRUCTION LIMITS. THE EXISTING CONCRETE AND HMA MUST BE MAINTAINED THROUGHOUT THIS STAGE UNLESS INDICATED FOR REMOVAL ON THE PAVING PLAN OR BY THE ENGINEER.



TYPICAL SECTION DURING STAGE 4C CONSTRUCTION

(DUBOIS BOULEVARD TO MAPLE AVENUE)

LEGEND

DIRECTION OF TRAFFIC FLOW

CONSTRUCTION WORK ZONE

HOT-MIX SURFACE ASPHALT

PROPOSED PAVEMENT AREA WITH STANDARD PCC DRIVEWAY PAVEMENT, PCC SIDEWALK, AND CURB & GUTTER

DRUMS OR TYPE II BARRICADES

TYPE II BARRICADE OR DRUM IN TYPICAL CROSS SECTION

◆ Civil Engineers ◆ Municipal Consultants Westchester, IL, 60154-2780


DRAWN ECW, SFB, DMM, GD CHECKED -XXX DATE -8-7-23

DESIGNED -REVISED · REVISED REVISED REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION MAINTENANCE OF TRAFFIC PLAN **STAGE 4C-2 CONSTRUCTION** SHEET NO. 18 OF 22 SHEETS STA. TO STA.


SCALE1"=40"






STAGE 5A CONSTRUCTION


- WORK FOR THIS STAGE SHALL CONSIST OF STRUCTURE ADJUSTMENTS WITHIN THE PAVEMENT AND FINAL HMA SURFACE PLACEMENT ACCORDING TO THE PAVING PLAN AND PROFILE.
- IDOT STANDARD 701501-06 SHALL BE USED TO ESTABLISH TRAFFIC CONTROL AND PROTECTION FOR HMA SURFACE PAVING.
- INTERSECTIONS ARE TO REMAIN OPEN AT ALL TIMES, EXCEPT DURING THE PREPARATION AND PLACEMENT OF
- HMA SURFACE COURSE.
 CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE ANY DRIVEWAY ACCESS IS DISTURBED TO PERFORM
- CONSTRUCTION WORK. CONTRACTOR TO NOTIFY RESIDENT 24 HOURS BEFORE ACCESS IS DISTURBED. TEMPORARY ROAD CLOSURES TO OCCUR DURING CONSTRUCTION FOR WORK SUCH AS PAVEMENT
- IMPROVEMENTS AND INSTALLATION OF HMA SURFACE.
- THE BROOKFIELD METRA STATION AND METRA STATION PARKING ON THE NORTH PORTION OF THIS SECTION SHALL REMAIN ACCESSIBLE THROUGHOUT THE CONSTRUCTION OF THIS STAGE UNLESS DISTURBED BY HMA SURFACE PLACEMENT. CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE METRA STATION AREA IS DISTURBED TO PERFORM CONSTRUCTION WORK, CONTRACTOR SHALL RETURN ACCESS TO METRA STATION AREA IMMEDIATELY UPON COMPLETION OF HMA SURFACE COURSE INSTALLATION.
- 7. TWO-TRAFFIC, NORTH-SOUTH TRAFFIC TO BE MAINTAINED AT ALL TIMES AT PRAIRIE AVENUE BY USE OF SIGNAGE AND TEMPORARY PAVEMENT MARKINGS.



TYPICAL SECTION DURING STAGE 5A CONSTRUCTION


PRAIRIE AVENUE






TYPICAL SECTION DURING STAGE 5A CONSTRUCTION

(PRAIRIE AVENUE TO STA. 46+42)



TYPICAL SECTION DURING STAGE 5A CONSTRUCTION

(STA. 46+42 TO FOREST AVENUE)



TYPICAL SECTION DURING STAGE 5A CONSTRUCTION

(FOREST AVENUE TO GROVE AVENUE)



♣ Municipal Consultant


Westchester, IL, 60154-2780


DESIGNED -REVISED -DRAWN ECW, SFB, DMM, GD REVISED -CHECKED -REVISED XXX DATE -8-7-23 REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION


MAINTENANCE OF TRAFFIC PLAN **STAGE 5A CONSTRUCTION** SHEET NO. 19 OF 22 SHEETS STA. SCALE: 1" = 40'

SECTION 0655 20-00133-00-FP соок 107 CONTRACT NO. 61J89 FIELD BOOK NO. : FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT






◆ Civil Engineers **STATE OF ILLINOIS** DRAWN ECW, SFB, DMM, GD REVISED -Westchester, IL, 60154-2780 0655 20-00133-00-FP соок 107 Municipal Consultants **STAGE 5C-1 CONSTRUCTION** CHECKED -REVISED **DEPARTMENT OF TRANSPORTATION** XXX FIELD BOOK NO. : CONTRACT NO. 61J89 SHEET NO. 21 OF 22 SHEETS STA. DATE -8-7-23 REVISED SCALE1"=40' FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT



STAGE 5C CONSTRUCTION

- 1. WORK FOR THIS STAGE SHALL CONSIST OF STRUCTURE ADJUSTMENTS WITHIN THE PAVEMENT AND FINAL HMA
- SURFACE PLACEMENT ACCORDING TO THE PAVING PLAN AND PROFILE.
 IDOT STANDARD 701501-06 SHALL BE USED TO ESTABLISH TRAFFIC CONTROL AND PROTECTION FOR HMA SURFACE PAVING.
- 3. INTERSECTIONS ARE TO REMAIN OPEN AT ALL TIMES, EXCEPT DURING THE PREPARATION AND PLACEMENT OF HMA SURFACE COURSE.
- 4. CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE ANY DRIVEWAY ACCESS IS DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR TO NOTIFY RESIDENT 24 HOURS BEFORE ACCESS IS DISTURBED.
- 5. TEMPORARY ROAD CLOSURES TO OCCUR DURING CONSTRUCTION FOR WORK SUCH AS PAVEMENT IMPROVEMENTS AND INSTALLATION OF HMA SURFACE.
- METRA STATION PARKING LOT 1 AND METRA STATION PARKING LOT 2 SHALL REMAIN ACCESSIBLE THROUGOUT THE CONSTRUCTION OF THIS STAGE UNLESS DISTURBED BY THE PLACEMENT OF HMA SURFACE COURSE. CONTRACTOR TO NOTIFY ENGINEER 48 HOURS BEFORE METRA STATION ACCESS IS DISTURBED TO PERFORM CONSTRUCTION WORK. CONTRACTOR SHALL RETURN ACCESS TO METRA STATION PARKING LOTS IMMEDIATELY UPON COMPLETION OF CONCRETE IMPROVEMENTS. TEMPORARY ACCESS ENTRANCE TO METRA STATION PARKING LOT 2 TO BE MAINTAINED AND ACCESSIBLE FOR THE DURATION OF THIS STAGE. ONCE STAGE SC IS COMPLETE THE TEMPORARY ACCESS ENTRANCE SHALL BE REMOVED AND RESTORED TO ITS PRE-CONSTRUCTION CONDITION.
- 7. ACCESS SHALL BE MAINTAINED AT ALL TIMES TO THE CONGRESS PARK METRA STATION ENTRANCE ON THE NORTH SIDE OF BURLINGTON AVENUE.



TYPICAL SECTION DURING STAGE 5C CONSTRUCTION

(DUBOIS BOULEVARD TO MAPLE AVENUE)

LEGEND

CONSTRUCTION WORK ZONE

DIRECTION OF TRAFFIC FLOW HOT-MIX SURFACE ASPHALT

PROPOSED PAVEMENT AREA WITH STANDARD PCC DRIVEWAY PAVEMENT, PCC SIDEWALK, AND CURB & GUTTER

DRUMS OR TYPE II BARRICADES

TYPE III BARRICADE

TYPE II BARRICADE OR DRUM IN TYPICAL CROSS SECTION

HANCOCK I SERVICE ENGINEERING	+ :
	•

Civil Engineers Municipal Consultants Established 1911


Westchester, IL, 60154-2780

DESIGNED -REVISED -DRAWN ECW, SFB, DMM, GD REVISED CHECKED -REVISED XXX DATE -8-7-23 REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION **MAINTENANCE OF TRAFFIC PLAN STAGE 5C-2 CONSTRUCTION** SHEET NO. 22 OF 22 SHEETS STA. TO STA.

SCALE1"=40'

.A.U. RTE.	SECTION				COUNTY	TOTAL SHEETS	SHEE NO.
0655	20-00133-00-FP				соок	107	56
ELD BOOK NO. :				CONTRACT N	O. 61J89		
FD R	OAD DIST	NO 1	II I INOIS	FED	AID PROJECT		



TEMPORARY ACCESS LEGEND

TEMPORARY ACCESS ENTRANCE



TURN AROUND ZONE

NOTES:

- 1. ALL LOCAL DETOURS SHALL BE APPROVED BY THE ENGINEER AT LEAST 48 HOURS PRIOR TO INSTALLATION.
- 2. BURLINGTON AVE. AND DUBOIS BLVD. TO BE DETOURED.
 3. TEMPORARY ACCESS TO INTERSECTIONS AND RESIDENTIAL DRIVEWAYS TO BE MAINTAINED AT ALL TIMES UNLESS DIRECTLY IMPACTED BY CONSTRUCTON
 4. TWO-WAY TRAFFIC TO BE MAINTAINED AT ALL TIMES AT PRAIRIE AVENUE AND BURLINGTON AVENUE
- INTERSECTION.5.
 5. TEMPORARY ACCESS ENTRANCE TO METRA STATION PARKING LOT #2 TO BE INSTALLED IN STAGE 1
- AND MAINTAINED THROUGHOUT THE DURATION OF THE PROJECT



APPLICABLE):

A) AT LOCATIONS WHERE WATER DRAINS AWAY FROM THE PROJECT, INLET PROTECTION SHALL BE INSTALLED AROUND EXISTING INLETS OR CATCH BASINS.

DESCRIPTION OF STABILIZATION PRACTICES DURING CONSTRUCTION (WHERE APPLICABLE):

- 1) DURING CONSTRUCTION, AREAS OUTSIDE THE CONSTRUCTION AREA AS OUTLINED PREVIOUSLY SHALL BE PROTECTED FROM DAMAGE EFFECTS OF CONSTRUCTION. THE CONTRACTOR SHALL NOT USE THIS AREA FOR STAGING (EXCEPT AS DESIGNATED ON THE PLANS OR DIRECTED BY THE ENGINEER), PARKING VEHICLES OR CONSTRUCTION EQUIPMENT, STORAGE OF MATERIALS, OR OTHER CONSTRUCTION RELATED ACTIVITIES.
- A) WITHIN THE CONSTRUCTION ZONE, CRITICAL AREAS WHICH HAVE HIGH FLOWS OF WATER AS DETERMINED BY THE ENGINEER SHALL REMAIN UNDISTURBED UNTIL FULL SCALE CONSTRUCTION IS UNDERWAY TO PREVENT UNNECESSARY SOIL EROSION.
- B) TOP SOIL AND EARTH STOCKPILES SHALL BE TEMPORARILY SEEDED IF THEY ARE TO REMAIN UNUSED FOR MORE THAN FOURTEEN DAYS.
- C) AS THE CONTRACTOR CONSTRUCTS THE UNDERGROUND IMPROVEMENTS, THEY SHALL ADHERE TO THE FOLLOWING STEPS AS DIRECTED BY THE ENGINEER
- I. PLACE TEMPORARY EROSION CONTROL SYSTEMS AT LOCATIONS WHERE WATER LEAVES AND ENTERS THE CONSTRUCTION ZONE.
- D) THE CONTRACTOR SHALL IMMEDIATELY FOLLOW MAJOR EARTH MOVING OPERATIONS WITH FINAL GRADING EQUIPMENT. AFTER MAJOR EARTH SPREAD OPERATION HAS MOVED TO A NEW LOCATION. FINAL GRADING SHALL BE COMPLETED WITHIN FOURTEEN DAYS. IF GRADING IS NOT COMPLETED WITHIN FOURTEEN DAYS, ALL MAJOR EARTH MOVING OPERATIONS WILL BE STOPPED, AS DIRECTED BY THE ENGINEER, UNTIL DISTRIBUTED AREAS ARE FINAL GRADED AND SEEDED.
- E) EXCAVATED AREAS AND EMBANKMENT SHALL BE PERMANENTLY SEEDED WHEN FINAL GRADED. IF NOT, THEY SHALL BE TEMPORARILY SEEDED AS STATED IN THE SPECIAL PROVISION "TEMPORARY EROSION CONTROL SEEDING".
- F) CONSTRUCTION EQUIPMENT SHALL BE STORED AND FUELED ONLY AT DESIGNATED LOCATIONS. ALL NECESSARY MEASURES SHALL BE TAKEN TO CONTAIN ANY FUEL OR POLLUTION RUN-OFF IN COMPLIANCE WITH EPA WATER QUALITY REGULATIONS LEAKING EQUIPMENT OR SUPPLIES SHALL BE IMMEDIATELY REPAIRED OR REMOVED FROM THE SITE.
- G) THE RESIDENT ENGINEER SHALL INSPECT THE PROJECT DAILY DURING ACTIVITIES AND WEEKLY OR AFTER LARGE RAINS DURING THE WINTER SHUTDOWN PERIOD. THIS PROJECT SHALL ADDITIONALLY BE INSPECTED BY THE CONSTRUCTION FIELD ENGINEER ON A BIWEEKLY BASIS TO DETERMINE THAT EROSION CONTROL EFFORTS ARE IN PLACE AND EFFECTIVE AND IF OTHER CONTROL WORK IS
- H) SEDIMENT COLLECTED DURING CONSTRUCTION BY THE VARIOUS TEMPORARY EROSION CONTROL SYSTEM SHALL BE DISPOSED OF ON SITE ON A REGULAR BASIS AS DIRECTED BY THE ENGINEER. THE COST OF MAINTENANCE IS INCIDENTAL TO THE CONTRACT.
- I) THE TEMPORARY EROSION CONTROL SYSTEM SHALL BE REMOVED AS DIRECTED BY THE ENGINEER AFTER IT'S USE IS NO LONGER NEEDED OR NO LONGER FUNCTIONING

NOTES

- 1. SEE IDOT STANDARD 280001-07 FOR TEMPORARY EROSION CONTROL SYSTEMS.
- 2. THE CONTRACTOR SHALL ENSURE THAT ADJACENT PROPERTIES REMAIN PROTECTED FROM SEDIMENT DEPOSITION.
- 3. SOIL STOCKPILES SHALL BE PROTECTED WITH PERIMETER EROSION BARRIER OR OTHER EROSION PROTECTION SPECIFIED BY THE RESIDENT ENGINEER. THE COST SHALL BE INCLUDED IN THE UNIT PRICE FOR THE INDIVIDUAL SOIL MATERIALS.
- 4. WHEREVER CONSTRUCTION VEHICLE ACCESS ROUTES INTERSECT PAVED PUBLIC ROADS. PROVISIONS SHALL BE MADE TO MINIMIZE THE TRANSPORT OF SEDIMENT BY RUNOFF OR VEHICLE TRACKING ONTO THE PAVED SURFACE. THE PROVISIONS MAY INCLUDE SPRAYING VEHICLE WHEELS TO CLEAR SEDIMENT BEFORE EXITING THE CONSTRUCTION SITE OR OTHER MEASURES APPROVED BY THE ENGINEER. THE COST OF ABOVE WORK WILL BE INCLUDED IN COST OF TRAFFIC CONTROL AND PROTECTION
- 5. INLET FILTER SHALL BE INSTALLED PRIOR TO CONSTRUCTION AND SHALL BE REMOVED AFTER CONSTRUCTION IS COMPLETED. FILTERS WILL BE INSPECTED WEEKLY AND THE CONTRACTOR WILL BE NOTIFIED OF ANY CORRECTIVE MEASURES THAT WILL BE REQUIRED TO BE MADE BY THE CONTRACTOR.

DOCUMENTATION

- 1) A REPORT SUMMARIZING THE SCOPE OF INSPECTION, NAME(S) AND QUALIFICATIONS OF THE PERSONNEL MAKING THE INSPECTION, DATE(S) OF THE SECTION, MAJOR OBSERVATIONS RELATING TO THE IMPLANTATION OF THE STORM WATER POLLUTION PREVENTION PLAN, AND ACTION TAKEN IN ACCORDANCE WITH SECTION 4 B. SHALL BE MADE AND RETAINED AS PART OF THE PLAN FOR AT LEAST THREE YEARS AFTER THE DATE OF INSPECTION. THE REPORT SHALL BE SIGNED IN ACCORDANCE WITH PART VI.G. OF THE GENERAL PERMIT.
- 2) IF ANY VIOLATION OF THE PROVISIONS OF THIS PLAN IS IDENTIFIED DURING THE CONDUCT OF THE CONSTRUCTION WORK COVERED BY THIS PLAN, THE RESIDENT ENGINEER OR RESIDENT TECHNICIAN SHALL COMPLETE AND FILE AN "INCIDENT OF NONCOMPLIANCE (ION)" REPORT FOR THE IDENTIFIED VIOLATION. THE RESIDENT ENGINEER OR RESIDENT TECHNICIAN SHALL USE FORMS PROVIDED BY THE ILLINOIS ENVIRONMENTAL PROTECTION AGENCY AND SHALL INCLUDE SPECIFIC INFORMATION ON THE NONCOMPLIANCE, ACTIONS WHICH WERE TAKEN TO PREVENT ANY FURTHER CAUSES OF NONCOMPLIANCE ALL REPORTS OF NONCOMPLIANCE SHALL BE SIGNED BY A RESPONSIBLE AUTHORITY IN ACCORDANCE WITH PART VI.G. OF THE GENERAL PERMIT. THE REPORT ID NONCOMPLIANCE SHALL BE MAILED TO THE FOLLOWING ADDRESS:

ILLINOIS ENVIRONMENTAL PROTECTION AGENCY DIVISION OF WATER POLLUTION CONTROL COMPLIANCE ASSURANCE SECTION #19 POST OFFICE BOX 19276 SPRINGFIELD, IL 62794-9276

DESCRIPTION OF INTENDED SEQUENCE OF MAJOR CONSTRUCTION ACTIVITIES WHICH WILL DISTURB EARTH AND LEAD TO POSSIBLE EROSION FOR MAJOR PORTIONS OF THE **CONSTRUCTION SITE**

- 1) EXCAVATION AND REMOVAL OF EXISTING STRUCTURES AND PAVED SURFACES WILL BE COMPLETED AT LOCATIONS AS INDICATED ON THE PLANS OR DIRECTED BY THE ENGINEER
- 2) DRAINAGE STRUCTURES WILL BE INSTALLED BEFORE AND/OR DURING THE EXCAVATION AND REMOVAL OF THE EXISTING STRUCTURES TO ALLOW FOR PROPER DRAINAGE OF THE SITE.
- 3) PLACEMENT, MAINTENANCE, REMOVAL AND PROPER CLEANUP OF TEMPORARY EROSION CONTROL SUCH AS EROSION CONTROL FENCE, HAY OR STRAW BALE DITCH CHECKS, INLET PROTECTION, AND TEMPORARY SEEDING AND MULCHING.
- 4) FINAL GRADING AND PLACEMENT OF PERMANENT EROSION CONTROL SEEDING AND MULCHING.

AREA OF DISTURBED GROUND


THE TOTAL AREA DISTURBED BY CONSTRUCTION ACTIVITIES IS APPROXIMATELY 2.14 ACRES

THE FOLLOWING PLAN WAS ESTABLISHED AND INCLUDED IN THESE PLANS TO DIRECT THE CONTRACTOR IN THE PLACEMENT OF TEMPORARY EROSION CONTROL SYSTEM AND TO PROVIDE A STORM WATER POLLUTION PREVENTION PLAN FOR COMPLIANCE UNDER NPDES. THE CONTRACTOR SHALL ABIDE TO ALL REQUIREMENTS WITHIN THIS PLAN AS PART OF THE CONTRACT.

ALL DISTURBED AREAS HAVING HIGH POTENTIAL FOR EROSION, AS DETERMINED BY THE ENGINEER, SHALL BE PERMANENTLY SEEDED AS SOON AS POSSIBLE.

MAINTENANCE AFTER CONSTRUCTION (WHERE APPLICABLE):

- 1) CONSTRUCTION IS COMPLETE AFTER ACCEPTANCE IS RECEIVED AT THE FINAL INSPECTION
- 2) AREAS WILL BE INSPECTED ON A REGULAR BASIS BY THE ENGINEER AND THE VILLAGE.
- 3) MAINTENANCE CREWS WILL ALSO AID IN ANY DRAINAGE PROBLEMS
- 4) ALL MAINTENANCE WILL BE CONDUCTED AT TIMES WHEN WEATHER CONDITIONS WILL NOT CAUSE
- 5) CONTRACTORS SHALL COMPLY WITH ALL TERMS AND CONDITIONS OF IEPA NPDES PERMIT ILR 10. RESTORATION SHALL OCCUR WITHIN 7 DAYS OF DISTURBANCE
- 6) CONTRACTORS SHALL SUBMIT INSPECTION REPORTS TO THE VILLAGE AT LEAST ONCE PER SEVEN DAYS AND AFTER RAINFALL EVENTS OF HALF INCH (OR EQUIVALENT SNOW FALL).
- 7) THE CONTRACTOR IS RESPONSIBLE FOR HAVING THE SWPPP ON SITE AT ALL TIMES.
- 8) TECHNIQUES SHALL BE EMPLOYED BY THE CONTRACTOR TO PREVENT THE BLOWING OF DUST OR
- 9) DAILY REMOVAL OF SEDIMENT AND DEBRIS FROM THE STREET SHALL BE REQUIRED OF THE CONTRACTOR




LETTERS 6" MIN. HEIGHT CONCRETE 48"x24" MIN WASHOUT AREA 30-MIL POLYETHYLENE -4"y4"y6' WOOD POST OR 6' STEEL POST MIN. BARRIER WALL NATIVE SOIL -

SANDBAG ANCHOR SIGN DETAIL BARRIER WALL ANCHOR SECTION

NOTES:

- 1. MAINTAINING TEMPORARY CONCRETE FACILITIES SHALL INCLUDE REMOVING AND DISPOSING OF HARDENED CONCRETE AND/OR SLURRY AND RETURNING THE **FACILITIES TO A FUNCTIONAL CONDITION**
- 2. FACILITY SHALL BE CLEANED OR RECONSTRUCTED IN A NEW AREA ONCE

CONCRETE WASHOUT (BARRIER WALL)



INLET/CATCH BASIN PROTECTION DETAIL

(DROP-IN PROTECTION)

- 1. CLEAN OUT AFTER EVERY RAIN EVENT.
- 2. INSTALL BEFORE BEGINNING ANY WORK

◆ Civil Engineers ♣ ♦ Municipal Consultants

Westchester, IL, 60154-2780

DESIGNED -REVISED · DRAWN ECW, SFB, DMM, GD REVISED CHECKED -XXX REVISED 8-7-23 REVISED


STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION **EROSION CONTROL PLAN AND SWPPP**


SHEET NO. 1 OF 4 SHEETS STA.


SCALE: 1" = 40'

0655 соок 108 CONTRACT NO. 61J89 FIELD BOOK NO. FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT


E.H.E. PROJECT NO. 125-22-2520











H.E. PROJECT NO. 125-22-25201



































STRUCTURE ADJUSTMENT




- NOTE: 1. THRUST BLOCKS TO BE USED AT 1/16(22-1/2°) OR GREATER
- BENDS & AT ALL ENDS TO BE PLUGGED
- 2. PRECAST CONCRETE THRUST BLOCKS TO BE PLACED AGAINST FIRM, UNDISTURBED SOIL.

THRUST BLOCK






STANDARD VALVE VAULT



FIRE HYDRANT



RESTRICTED DEPTH STORM MANHOLE

DRAINAGE AND UTILITIES NOTES

THE LOCATIONS OF EXISTING DRAINAGE STRUCTURES, STORM SEWERS, COMBINED SEWERS, TELEPHONE LINES. COMMUNICATION LINES, ELECTRIC LINES, GAS MAINS, AND WATER SERVICES ARE APPROXIMATE AND THEIR SPECIFIC LOCATIONS ARE TO BE DETERMINED IN THE FIELD AT NO COMPENSATION TO THE CONTRACTOR.

COORDINATION OF ALL UTILITY WORK INVOLVED WITHIN THE CONSTRUCTION AREAS SHALL BE SUBJECT TO DISCUSSION AND CLARIFICATION AT A PRECONSTRUCTION MEETING.

WHEN EXISTING DRAINAGE FACILITIES ARE DISTURBED, THE CONTRACTOR SHALL PROVIDE AND MAINTAIN TEMPORARY OUTLETS AND CONNECTIONS FOR ALL PRIVATE OR PUBLIC DRAINAGE STRUCTURES OR SEWERS UNTIL PERMANENT CONNECTIONS TO SEWERS ARE BUILT AND IN SERVICE. THIS WORK SHALL BE PAID FOR AS TEMPORARY DRAINAGE CONNECTIONS.

IF, DURING CONSTRUCTION OPERATIONS, ANY LOOSE MATERIALS ARE DEPOSITED IN THE FLOW LINES OF GUTTERS OR DRAINAGE STRUCTURES SO THAT THE NATURAL FLOW OF WATER IS OBSTRUCTED, THE OBSTRUCTING MATERIALS SHALL BE REMOVED AT THE CLOSE OF EACH WORK DAY. AT THE CONCLUSION OF THE CONSTRUCTION OPERATIONS, ALL DRAINAGE STRUCTURES ARE TO BE FREE OF ALL DIRT, DEBRIS, AND OBSTRUCTING MATERIALS. THE WORK SPECIFIED ABOVE WILL NOT BE PAID FOR SEPARATELY, BUT SHALL BE INCLUDED IN THE COST OF PROPOSED ITEMS BEING CONSTRUCTED.

ALL COSTS INVOLVED IN CONNECTING PROPOSED STORM SEWERS AND STORM STRUCTURES TO EXISTING STORM SEWERS OR PROPOSED STORM SEWERS SHALL BE CONSIDERED INCLUDED IN THE COST OF PROPOSED

ALL PROPOSED WATER MAINS SHALL BE INSTALLED IN ACCORDANCE WITH IN THE "STANDARD SPECIFICATIONS FOR WATER AND SEWER MAIN CONSTRUCTION IN ILLINOIS", SEVENTH EDITION, DATED 2014, AND ALL REVISIONS

THE CONTRACTOR SHALL VERIFY THE TYPE OF ALL WATER MAIN HARDWARE INCLUDING VALVES. FIRE HYDRANTS, VALVE BOXES, CORPORATION STOPS, CURB STOPS, AND WATER SERVICES BOXES WITH THE UTILITY SUPERINTENDENT PRIOR TO ORDERING SUCH MATERIAL

THE TYPE OF FRAMES AND GRATES REQUIRED FOR ALL CATCH BASINS AND MANHOLES LISTED IN THE SUMMARY OF QUANTITIES MAY BE FOUND ON THE PLANS AT THEIR RESPECTIVE LOCATIONS. WHERE LIDS ARE CALLED FOR ON THE PLANS, THEY SHALL BE IN ACCORDANCE WITH ARTICLE 604.01 OF THE STANDARD SPECIFICATIONS AND THE TERM LID IS USED IN LIEU OF GRATE.

ON ALL IMPROVEMENTS. THE FRAMES AND LIDS OF EXISTING CATCH BASINS. INLETS. MANHOLES. AND VALVE VAULTS WHICH ARE TO BE ABANDONED DUE TO CONSTRUCTION OF THIS IMPROVEMENT ARE TO REMAIN THE PROPERTY OF THE VILLAGE OF BROADVIEW AND BE SALVAGED. THE CONTRACTOR IS TO DELIVER FRAMES AND LIDS TO THE VILLAGE OF BROOKFIELD PUBLIC WORKS DEPARTMENT

ANY COSTS FOR SHEETING OR SHORING REQUIRED FOR THE STORM SEWER INSTALLATION OR OTHER CONSTRUCTION ELEMENTS REQUIRING RELATIVELY DEEP EXCAVATIONS SHALL BE INCLUDED IN THE PARTICULAR PAYMENT ITEM AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED FOR ANY SUPPLEMENTAL WORK ASSOCIATED WITH THE MAINTENANCE OF TRENCH SIDES OR OTHER EXCAVATED AREAS.

ALL ABANDONED SANITARY SEWERS SHALL BE PLUGGED AT BOTH ENDS WITH AT LEAST 2 FEET LONG NON-SHRINK CONCRETE OR MORTAR PLUG. THIS WORK SHALL NOT BE PAID FOR SEPARATELY, BUT SHALL BE INCLUDED IN THE PAY ITEMS FOR REMOVING AND/OR FILLING THE VARIOUS TYPES OF STRUCTURES.

SEWER PIPE INSTALLED ON THIS PROJECT SHALL CONFORM TO THE FOLLOWING STANDARD:


TYPE OF PIPE MATERIAL STANDARD JOINT STANDARD REINFORCED CONCRETE PIPE POLYVINYLCHLORIDE PIPE, SDR 26 **ASTM D-2241 ASTM D-3139 DUCTILE IRON PIPE, CLASS 52 ASTM A-21.51** ASTM A-21.11

DUCTILE IRON PIPE SPECIFICATIONS


- ALL DUCTILE IRON PIPE WATER MAINS AND SEWER MAINS SHALL BE CLASS 52, CEMENT-LINED AND TAR-COATED, MEETING THE REQUIREMENTS OF SPECIFICATIONS ANSI/AWWA C151/A21.51 WITH "PUSH-ON" JOINTS MEETING THE REQUIREMENTS OF SPECIFICATIONS ANSI/AWWA C111/A21.11. WHERE SPECIFIED ON THE PLANS, OR IN THE SPECIFICATIONS, MECHANICAL JOINTS AND "LOCK-TYPE" JOINTS SHALL BE USED IN LIEU OF "PUSH-ON" JOINTS.
- ALL PIPE FITTINGS AND SPECIAL CASTINGS SHALL BE DUCTILE IRON CONFORMING TO ANSI/AWWA C153/A21.53 AND ANSI/AWWA C111/A21.11 SPECIFICATIONS AND SHALL MEET THE MINIMUM REQUIREMENTS OF CLASS 150 DUCTILE IRON PIPE. IF CERTAIN FITTINGS ARE NOT MANUFACTURED IN DUCTILE IRON, CAST IRON FITTINGS SHALL BE ACCEPTABLE. MECHANICAL JOINT TYPE FITTINGS SHALL BE USED.
- ALL PROPOSED DUCTILE IRON PIPE WATER MAIN AND SEWER MAIN WILL BE ENCASED WITHIN SIX (6) MIL THICK, HIGH-DENSITY POLYETHYLENE TUBING. ALL FITTINGS SHALL BE ENCASED IN A DOUBLE-LAYER OF POLYETHYLENE TUBING. THE POLYETHYLENE MATERIAL SHALL BE MANUFACTURED AND INSTALLED IN COMPLIANCE WITH ANSI/AWWA C105/A21.5.

TYPICAL SEWER AND WATER MAIN TRENCH


1 A N LOO OL / 15 % A Civil Engineers 9933 Rossevelt Road		DESIGNED -	Х	REVISED -						F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	HEET NO.
HANCOCK Mestchester, IL, 60154-2780	stchester, IL, 60154-2780 DRAWN - ECW, SFB, DMM, GD	EVISED - STATE OF ILLINOIS			DRAINAGE AND UTILITIES DETAILS				20-00133-00-FP	соок	107	74		
ENGINEERING STANDISHED 1911	Phone: 708-865-0300 www.ehancock.com	CHECKED -	XXX	REVISED -	DEPARTMENT OF TRANSPORTATION					FIELD BOOK NO. :		CONTRACT NO. 61J89		
		DATE -	8-7-23	REVISED -		SCALE: NONE	SHEET NO. 1 OF 4 SHEETS	O STA.	FED. ROA	AD DIST. NO. 1 ILLINOIS FED	. AID PROJECT			




RESTRICTED DEPTH (COMBINED) SANITARY MANHOLE




RESTRICTED DEPTH CATCH BASIN






8"X4"/10"X6" CATCH BASIN TRAP AND RESTRICTOR

(TO BE INSTALLED IN PROPOSED CATCH BASINS BETWEEN STA. 1+47 AND STA. 22+71)





HANCOCK | \$ \$ \$ \$ \times \text{Civil Engineers} \\ \text{Municipal Consul} \\ \text{Entoblished 1911} \\ \text{Established 1911}


◆ Municipal Consultants

estchester, IL, 60154-2780 Phone: 708-865-0300

DESIGNED -REVISED DRAWN -ECW, SFB, DMM, GD REVISED CHECKED -XXX REVISED -REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION **DRAINAGE AND UTILITIES DETAILS** SHEET NO. 2 OF 4 SHEETS STA.

SECTION COUNTY 0655 20-00133-00-FP соок 107 75 CONTRACT NO. 61J89 FED. ROAD DIST. NO. 1 | ILLINOIS | FED. AID PROJECT



 \bigcirc 1 \bigcirc 1 \bigcirc 1 \bigcirc 1 \bigcirc 1 (25) \bigcirc 0 $L 6 \times 4 \times \frac{1}{2}$ $(150 \times 100 \times 13)$ anchor rod with $2^{1}/_{4} \times 2^{1}/_{4} \times \frac{5}{16}$ (1)/4 (31) Ø hole in $(56 \times 56 \times 8)$ bottom leg of angle P washer RESTRAINT ANGLE DETAIL

24 typ., (600)

Restraint angle with tie plate (typ.). Omit between multiple end sections. D **PLAN**

CIP field construction. See General Notes.

36 (900) $(11/4 \times 21/2)$ $2^{1}/_{4}$ (56) (31×63) Tie P_ Slotted hole, typ. 0Ф TIE PLATE DETAIL ¢ Joint→ 1/₄ (6) Tie ₽ 13/4 (44) 16 (400) 16 (400) ─ Restraint angle typ. (25) Ø Anchor rods with $2^{1}/_{4} \times 2^{1}/_{4} \times \frac{5}{16}$ (56 × 56 × 8) \mathbb{P} washers installed in $1\frac{1}{8}$ (28) Ø formed holes in end section walls SECTION A-A

PIPE CULVERT END SECTION DIMENSIONS

		IFE COL	VENI EI	ID SECT	IOIN DIII	ILIVOIDIV	<u> </u>	
							L	
					S	lope of E	nd Sectio	n
Pipe I.D.	Α	R	S	Т	1:2	1:3	1:4	1:6
15	14	29	28	8	5′-6′′	7'-11''	10'-4''	15'-2"
(375)	(350)	(737)	(711)	(200)	(1.68 m)	(2.42 m)	(3.16 m)	(4.63 m)
18	15	33	32	8	6'-2''	8'-11''	11'-8''	17'-2''
(450)	(375)	(838)	(813)	(200)	(1.88 m)	(2.72 m)	(3.56 m)	(5.24 m)
21	15	36	34	8	6'-8''	9'-8''	12'-8''	18'-8''
(525)	(375)	(914)	(864)	(200)	(2.03 m)	(2.95 m)	(3.86 m)	(5.69 m)
24	15	39	38	8	7'-2''	10'-5''	13'-8''	20'-2''
(600)	(375)	(990)	(970)	(200)	(2.19 m)	(3.18 m)	(4.17 m)	(6.15 m)
27	15	3′-10′′	3′-6′′	8	8'-4''	12'-2''	16'-0''	23'-8''
(675)	(375)	(1.17 m)	(1.07 m)	(200)	(2.54 m)	(3.71 m)	(4.88 m)	(7.21 m)
30	16	4'-2''	3′-10′′	8	9'-0''	13'-2''	17'-4''	25'-8''
(750)	(400)	(1.27 m)	1.17 m)	(200)	(2.75 m)	(4.02 m)	(5.29 m)	(7.83 m)
33	16	4'-5''	4'-0''	8	9'-6''	13'-11''	18'-4''	27'-2''
(825)	(400)	(1.35 m)	(1.22 m)	(200)	(2.90 m)	(4.25 m)	(5.60 m)	(8.29 m)
36	16	4′-8′′	4'-4''	8	10'-0''	14'-8''	19'-4''	28'-8''
(900)	(400)	(1.42 m)	(1.32 m)	(200)	(3.05 m)	(4.47 m)	(5.90 m)	(8.74 m)
42	17	5′-3′′	5′-0′′	8	11'-2''	16'-5''	21'-8''	32'-2''
(1050)	(425)	(1.60 m)	(1.52 m)	(200)	(3.41 m)	(5.01 m)	(6.61 m)	(9.81 m)
48	17	5′-9′′	5′-6′′	8	12'-2''	17'-11''	23′-8′′	35′-2′′
(1200)	(425)	(1.75 m)	(1.68 m)	(200)	(3.71 m)	(5.46 m)	(7.22 m)	(10.73 m)
54	18	6'-4''	6'-2''	8	13'-4''	19'-8''	26′-0′′	38'-8''
(1350)	(450)	(1.93 m)	(1.88 m)	(200)	(4.07 m)	(6.00 m)	(7 . 93 m)	(11.79 m)
60	18	6′-10′′	6′-8′′	8	14'-4''	21'-2''	28'-0''	41'-8''
(1500)	(450)	(2 _• 08 m)	(2.03 m)	(200)	(4.37 m)	(6.46 m)	(8.54 m)	(12.71 m)
66	19	7′-5′′	7'-4''	8	15′-6′′	22'-11''	30′-4′′	45'-2''
(1650)	(475)	(2.26 m)	(2.24 m)	(200)	(4.73 m)	(6.99 m)	(9.26 m)	(13.78 m)
72	19	7′-11′′	7′-10′′	8	16'-6''	24'-5''	32'-4''	48'-2''
(1800)	(475)	(2.41 m)	(2.39 m)	(200)	(5 _* 03 m)	(7.45 m)	(9.87 m)	(14.70 m)
78	21	8'-6''	8′-6′′	9	17′-9′′	26'-3''	34'-9''	51'-9''
(1950)	(525)	(2.59 m)	(2.59 m)	(230)	(5.41 m)	(8.01 m)	(10.60 m)	(15.78 m)
84	21	9'-0''	9′-0′′	9	18'-9''	27′-9′′	36′-9′′	54'-9''
(2100)	(525)	(2.74 m)	(2.74 m)	(230)	(5.72 m)	(8.46 m)	(11.21 m)	(16.70 m)
						EDAL NC	TEC	

GENERAL NOTES

This Standard is for use with single pipe culverts and multi-pipe culvert installations. For multi-pipe culvert installations, place the end sections side-by-side leaving a 3 (75) space between adjacent end section walls and fill the space(s) with Class SI concrete.

The number of segments shown in elevation is for example only. The length and number of precast sections required to construct the end section shall be determined by the Contractor.

See roadway plans for slope (V:H) and pipe inside

End section may be installed up to \pm 15 degrees skewed with roadway.

 $2\frac{1}{4} \times 2\frac{1}{4} \times \frac{5}{6}$ (56 x 56 x 8) plate washers shall be provided under each nut required for the anchor rods. Holes in the walls for the culvert tie assembly may be drilled using core bits in lieu of formed holes.

See Standard 542311 for end sections having traversable pipe grate.

All slope ratios are expressed as units of vertical displacement to units of horizontal displacement

All dimensions are in inches (millimeters) unless otherwise shown.

TO STA.

ANCOCK | § § + Civil Engineers + Municipal Cons

◆ Municipal Consultants NG I ♣ 🖔 ◆Established 1911

Westchester, IL, 60154-2780 Phone: 708-865-0300 www.ehancock.com

DESIGNED - X REVISED -DRAWN -ECW, SFB, DMM, GD REVISED CHECKED -XXX REVISED -DATE . 8-7-23 REVISED -

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

(Showing end section tie details)

CONCRETE END SECTIONS FOR PIPE CULVERTS SHEET NO. 3 OF 4 SHEETS STA.


SCALE: NONE

TOTAL SHEE NO. SECTION COUNTY 0655 20-00133-00-FP соок 107 76 CONTRACT NO. 61J89 FIELD BOOK NO. FED. ROAD DIST. NO. 1 | ILLINOIS | FED. AID PROJECT

FIBERGI ASS

CDS4030-8-C DESIGN NOTES

CDS4030-8-C STANDARD CONFIGURATION IS SHOWN.



NOT TO SCALE

STRUCTURE ID						
WATER QUALITY	FLOW RAT	E (C	CFS OR L/s)		4.1 CFS	
PEAK FLOW RAT	E (CFS OR	L/s)			33.5 CFS	
RETURN PERIOD	OF PEAK F	LO۱	N (YRS)		10	
SCREEN APERTU	700)		2400			
PIPE DATA:	I.E. MATERIAL		D	IAMETER		
INLET PIPE 1	609.07		RCP		48"	
INLET PIPE 2	N/A		N/A		N/A	
OUTLET PIPE	607.07		RCP		48"	
RIM ELEVATION					615.38	
ANTI-FLOTATION	BALLAST	П	WIDTH	Т	HEIGHT	
		Ī	N/A	T	N/A	
NOTES/SPECIAL REQUIREMENTS:						

GENERAL NOTES

1. CONTECH TO PROVIDE ALL MATERIALS UNLESS NOTED OTHERWISE.

SCALE: NONE

- 2. FOR SITE SPECIFIC DRAWINGS WITH DETAILED STRUCTURE DIMENSIONS AND WEIGHT, PLEASE CONTACT YOUR CONTECH ENGINEERED SOLUTIONS LLC REPRESENTATIVE. www.ContechES.com
- 3. CDS WATER QUALITY STRUCTURE SHALL BE IN ACCORDANCE WITH ALL DESIGN DATA AND INFORMATION CONTAINED IN THIS DRAWING. CONTRACTOR TO CONFIRM STRUCTURE MEETS REQUIREMENTS OF PROJECT.
- 4. STRUCTURE SHALL MEET AASHTO HS20 LOAD RATING, ASSUMING EARTH COVER OF 0' 2', AND GROUNDWATER ELEVATION AT, OR BELOW, THE OUTLET PIPE INVERT ELEVATION. ENGINEER OF RECORD TO CONFIRM ACTUAL GROUNDWATER ELEVATION. CASTINGS SHALL MEET AASHTO M306 AND BE CAST WITH THE CONTECH LOGO.
- 5. IF REQUIRED, PVC HYDRAULIC SHEAR PLATE IS PLACED ON SHELF AT BOTTOM OF SCREEN CYLINDER. REMOVE AND REPLACE AS NECESSARY DURING MAINTENANCE CLEANING.
- 6. CDS STRUCTURE SHALL BE PRECAST CONCRETE CONFORMING TO ASTM C-478 AND AASHTO LOAD FACTOR DESIGN METHOD.

- INSTALLATION NOTES

 A. ANY SUB-BASE, BACKFILL DEPTH, AND/OR ANTI-FLOTATION PROVISIONS ARE SITE-SPECIFIC DESIGN CONSIDERATIONS AND SHALL BE SPECIFIED BY ENGINEER OF RECORD.
- CONTRACTOR TO PROVIDE EQUIPMENT WITH SUFFICIENT LIFTING AND REACH CAPACITY TO LIFT AND SET THE CDS MANHOLE STRUCTURE.
- CONTRACTOR TO INSTALL JOINT SEALANT BETWEEN ALL STRUCTURE SECTIONS AND ASSEMBLE STRUCTURE.
- CONTRACTOR TO PROVIDE, INSTALL, AND GROUT INLET AND OUTLET PIPE(S). MATCH PIPE INVERTS WITH ELEVATIONS SHOWN. ALL PIPE CENTERLINES TO MATCH PIPE OPENING CENTERLINES.
- CONTRACTOR TO TAKE APPROPRIATE MEASURES TO ASSURE UNIT IS WATER TIGHT, HOLDING WATER TO FLOWLINE INVERT MINIMUM. IT IS SUGGESTED THAT ALL JOINTS BELOW PIPE INVERTS ARE GROUTED.

Municipal Consultants NG É Š ◆Established 1911

Westchester, IL, 60154-2780 Phone: 708-865-0300 www.ehancock.com

DESIGNED - X DRAWN -ECW, SFB, DMM, GD CHECKED -XXX DATE . 8-7-23


REVISED -REVISED REVISED -REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

CDS UNIT - CDS4030-8-C STANDARD DETAIL SHEET NO. 4 OF 4 SHEETS STA.

TO STA.

SECTION COUNTY 0655 20-00133-00-FP соок 107 77 FIELD BOOK NO. CONTRACT NO. 61J89 FED. ROAD DIST. NO. 1 | ILLINOIS | FED. AID PROJECT



◆ Municipal Consultants

tchester, IL, 60154-2780 Phone: 708-865-0300


DESIGNED - X DRAWN -CHECKED -XXX 8-7-23

REVISED -REVISED -ECW. SFB. DMM. GD REVISED -REVISED

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

CHECK VALVE DETAIL SCALE: NONE SHEET NO. 1 OF 1 SHEETS STA.

F.A.U. RTE. 0655 TOTAL SHEE NO. SECTION 20-00133-00-FP соок FIELD BOOK NO. CONTRACT NO. 61J89 FED ROAD DIST NO FED AID PROJECT



Denwing file: With projects. By will and throughly 1959255 = hurlington are phase 11.104. I

SIGNING NOTES:

DESIGN: AASHTO STANDARD SPECIFICATIONS FOR STRUCTURAL

SUPPORTS FOR HIGHWAY SIGNS, LUMINAIRES, AND

TRAFFIC SIGNALS, 2013.

CONSTRUCTION: CURRENTS STANDARD SPECIFICATIONS FOR TRAFFIC

CONTROL ITEMS, AND APPLICABLE SPECIAL PROVISIONS.

LOADING: FOR 80 MPH WIND VELOCITY WITH 30% GUST FACTOR,

NORMAL TO SIGN.

SOIL PRESSURE: MINIMUM ALLOWABLE SOIL PRESSURE = 1.25 TSF.

MATERIALS: POSTS SHALL CONFORM TO THE REQUIREMENTS OF ARTICLE 1006.29, STANDARD SPECIFICATIONS FOR

ROAD AND BRIDGE CONSTRUCTION, STATE OF ILLINOIS.

HARDWARE FOR ATTACHING SIGN PANELS TO POSTS SHALL BE CADIUM OR ZINC COATED STEEL,

STAINLESS STEEL, OR ALUMINUM, AND SHALL CONFORM TO THE FOLLOWING SPECIFICATIONS: CADIUM OR ZINC

COATED STEEL: BOLTS, NUTS, AND WASHERS:

ASTM A165, TYPE NS. ZINC COATED IN ACCORDANCE WITH AASHTO M-232

OR ASTM A164, TYPE GS.

STAINLESS STEEL: BOLTS: ASTM A193, CLASS I, GRADE B8,

NUTS: ASTM A194, GRADE 8 OR 8F, WASHERS: ASTM A240, TYPE 302 OR 304.

ALUMINUM: BOLTS: ASTM B211 ALLOY 6061-T6 OR 2024-T4,

NUTS: ASTM B211 ALLOY 6061-T6 OR 6262-T9,

WASHERS: ASTM B209 ALCLAD 2024-T4.

PER 2009 MUTCD SECTION 2D.43, PARAGRAPH 03, NOTE:

STREET NAME SIGNS ARE TO BE MIXED CASE FONT.

SYMBOL

DESCRIPTION

METAL POST - TYPE A



TO STA.



Westchester, IL, 60154-2780

DESIGNED -REVISED -DRAWN -ECW, SFB, DMM, GD REVISED -CHECKED -REVISED XXX DATE -8-7-23 REVISED -

JOB-SITE SIGNING CODES AND SIZES

SIGN

CODE & SIZE

SYMBOL

SYMBOL

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

JOB-SITE SIGNING CODES AND SIZES

SIGN

CODE & SIZE

SIGNING PLAN LEGEND AND NOTES

SHEET NO. 1 OF 1 SHEETS STA.


SCALE: NTS

SECTION COUNTY 0655 20-00133-00-FP COOK 107 80 CONTRACT NO. 61J89 FIELD BOOK NO. : FED. ROAD DIST. NO. 1 | ILLINOIS | FED. AID PROJECT

NOTE:

- 1. VILLAGE MISCELLANEOUS (SPECIALTY) SIGNS ARE TO BE REMOVED BY THE CONTRACTOR PRIOR TO CONSTRUCTION. AS DESIGNATED BY ENGINEER, THE CONTRACTOR SHALL REINSTALL SIGNS AFTER COMPLETION OF PROJECT. REMOVAL AND NEW REPLACEMENT OF VILLAGE MISCELLANEOUS (SPECIALTY) SIGNS AND THEIR POSTS ARE TO BE DETERMINED BY THE ENGINEER. (COST IS TO BE INCLUDED IN THE "REMOVE AND RE-ERECT EXISTING SIGN" OR "SIGN PANEL - TYPE 1" AND "METAL POST - TYPE I" PAY ITEM)
- 2. STREET NAME SIGNS AND POSTS ARE TO BE REMOVED BY CONTRACTOR AT THE BEGINNING OF CONSTRUCTION, SAFELY STORED BY THE CONTRACTOR AND REINSTALLED BY THE CONTRACTOR AT THE COMPLETION OF THE PROJECT (COST IS TO BE INCLUDED IN THE "REMOVE AND RE-ERECT EXISTING SIGN" PAY ITEM)
- 3. ALL POSTS TO BE TYPE A UNLESS OTHERWISE NOTED.
- 4. CONTRACTOR TO VERIFY LOCATIONS OF ALL SIGNAGE.
- 5. ALL MARKINGS ARE WHITE UNLESS OTHERWISE NOTED.

ITEM DESCRIPTION	SYMBOL
THERMOPLASTIC PAVEMENT MARKING - LINE 4"	(A)
THERMOPLASTIC PAVEMENT MARKING - LINE 6"	₿
THERMOPLASTIC PAVEMENT MARKING - LINE 24"	©
THERMOPLASTIC PAVEMENT MARKING - LETTERS & SYMBOLS	0
MODIFIED URETHANE PAVEMENT MARKING TYPE 1 - LINE 4"	(
MODIFIED URETHANE PAVEMENT MARKING TYPE 1 - LETTERS AND SYMBOLS	Ē





HANCOCK | 5 8 4 Civil Engineers

Municipal Consultants

ENGINEERING | 6 00 4 Established 1911

Westchester, IL, 60154-2780

DESIGNED - X REVISED -DRAWN ECW, SFB, DMM, GD REVISED -CHECKED -REVISED XXX 8-7-23 REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

PAVEMENT MARKING AND SIGNING PLAN

TO STA.


SCALE: 1" = 40' SHEET NO. 1 OF 3 SHEETS STA.

SECTION 0655 20-00133-00-FP соок 107 CONTRACT NO. 61J89 FIELD BOOK NO. : FED. ROAD DIST. NO. 1 | ILLINOIS | FED. AID PROJECT

NOTE:

- 1. VILLAGE MISCELLANEOUS (SPECIALTY) SIGNS ARE TO BE REMOVED BY THE CONTRACTOR PRIOR TO CONSTRUCTION. AS DESIGNATED BY ENGINEER, THE CONTRACTOR SHALL REINSTALL SIGNS AFTER COMPLETION OF PROJECT. REMOVAL AND NEW REPLACEMENT OF VILLAGE MISCELLANEOUS (SPECIALTY) SIGNS AND THEIR POSTS ARE TO BE DETERMINED BY THE ENGINEER. (COST IS TO BE INCLUDED IN THE "REMOVE AND RE-ERECT EXISTING SIGN" OR "SIGN PANEL - TYPE 1" AND "METAL POST - TYPE I" PAY ITEM)
- 2. STREET NAME SIGNS AND POSTS ARE TO BE REMOVED BY CONTRACTOR AT THE BEGINNING OF CONSTRUCTION, SAFELY STORED BY THE CONTRACTOR AND REINSTALLED BY THE CONTRACTOR AT THE COMPLETION OF THE PROJECT (COST IS TO BE INCLUDED IN THE "REMOVE AND RE-ERECT EXISTING SIGN" PAY ITEM)
- 3. ALL POSTS TO BE TYPE A UNLESS OTHERWISE NOTED.
- 4. CONTRACTOR TO VERIFY LOCATIONS OF ALL SIGNAGE.
- 5. ALL MARKINGS ARE WHITE UNLESS OTHERWISE NOTED.

ITEM DESCRIPTION	SYMBOL
THERMOPLASTIC PAVEMENT MARKING - LINE 4"	A
THERMOPLASTIC PAVEMENT MARKING - LINE 6"	B
THERMOPLASTIC PAVEMENT MARKING - LINE 24"	©
THERMOPLASTIC PAVEMENT MARKING - LETTERS & SYMBOLS	0
MODIFIED URETHANE PAVEMENT MARKING TYPE 1 - LINE 4"	(E)
MODIFIED URETHANE PAVEMENT MARKING TYPE 1 - LETTERS AND SYMBOLS	(Ē)



◆ Civil Engineers

Westchester, IL, 60154-2780

DESIGNED -REVISED -DRAWN ECW, SFB, DMM, GD REVISED -CHECKED -REVISED XXX 8-7-23 REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

PAVEMENT MARKING AND SIGNING PLAN

TO STA.


SCALE: 1" = 40' SHEET NO. 2 OF 3 SHEETS STA.

SECTION 0655 20-00133-00-FP соок 107 FIELD BOOK NO. : CONTRACT NO. 61J89

NOTE:

- 1. VILLAGE MISCELLANEOUS (SPECIALTY) SIGNS ARE TO BE REMOVED BY THE CONTRACTOR PRIOR TO CONSTRUCTION. AS DESIGNATED BY ENGINEER, THE CONTRACTOR SHALL REINSTALL SIGNS AFTER COMPLETION OF PROJECT. REMOVAL AND NEW REPLACEMENT OF VILLAGE MISCELLANEOUS (SPECIALTY) SIGNS AND THEIR POSTS ARE TO BE DETERMINED BY THE ENGINEER. (COST IS TO BE INCLUDED IN THE "REMOVE AND RE-ERECT EXISTING SIGN" OR "SIGN PANEL - TYPE 1" AND "METAL POST - TYPE I" PAY ITEM)
- 2. STREET NAME SIGNS AND POSTS ARE TO BE REMOVED BY CONTRACTOR AT THE BEGINNING OF CONSTRUCTION, SAFELY STORED BY THE CONTRACTOR AND REINSTALLED BY THE CONTRACTOR AT THE COMPLETION OF THE PROJECT (COST IS TO BE INCLUDED IN THE "REMOVE AND RE-ERECT EXISTING SIGN" PAY ITEM)
- 3. ALL POSTS TO BE TYPE A UNLESS OTHERWISE NOTED.
- 4. CONTRACTOR TO VERIFY LOCATIONS OF ALL SIGNAGE.
- 5. ALL MARKINGS ARE WHITE UNLESS OTHERWISE NOTED.

ITEM DESCRIPTION	SYMBOL
THERMOPLASTIC PAVEMENT MARKING - LINE 4"	(A)
THERMOPLASTIC PAVEMENT MARKING - LINE 6"	₿
THERMOPLASTIC PAVEMENT MARKING - LINE 24"	0
THERMOPLASTIC PAVEMENT MARKING - LETTERS & SYMBOLS	o
MODIFIED URETHANE PAVEMENT MARKING TYPE 1 - LINE 4"	⑥
MODIFIED URETHANE PAVEMENT MARKING TYPE 1 - LETTERS AND SYMBOLS	Ē



Westchester, IL, 60154-2780


DESIGNED -REVISED -DRAWN ECW, SFB, DMM, GD REVISED -CHECKED -REVISED XXX 8-7-23 REVISED -

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION **PAVEMENT MARKING AND SIGNING PLAN**

TO STA.

SCALE: 1" = 40' SHEET NO. 3 OF 3 SHEETS STA.

SECTION 0655 20-00133-00-FP соок 107 CONTRACT NO. 61J89 FIELD BOOK NO. : FED. ROAD DIST. NO. 1 | ILLINOIS | FED. AID PROJECT



LANDSCAPING NOTES

SODDING:

ALL DISTURBED AREAS INDICATED ON CROSS SECTION OR LANDSCAPING PLANS TO BE SODDED, INCLUDING FERTILIZER NUTRIENTS*, AND SUPPLEMENTAL WATERING WHICH IS TO BE USED AFTER THE INITIAL WATERING (AS SPECIFIED AND AS DIRECTED BY THE ENGINEER) AT THE RATE OF 27 GALLONS PER SQUARE YARD SODDING. SODDED SLOPES WHICH ARE 2:1 OR STEEPER SHALL BE STAKED. (PROVIDE A 3" STRIP AROUND CATCH BASINS IN SEEDED AREAS).

4" TOP SOIL LAYER:

SOIL SHALL BE SPREAD AS INDICATED ON THE TYPICAL CROSS SECTIONS.

A MINIMUM OF GRADING TO BE PERMITTED WITHIN AN APPROXIMATE RADIUS OF 6' FROM ALL TREES TO BE SAVED AS DETERMINED BY THE ENGINEER.

RIPARIAN ENVIRONMENT:

IDOT CLASS 4A SEED MIXTURE TO BE USED FOR RESTORATION WITHIN RIPARIAN ENVIRONMENT

MULCH:

MULCH TO BE PLACED AROUND ALL TREES LOCATED IN AREAS THAT ARE

ALL PROPOSED TREES TO BE PLANTED BY THE VILLAGE OF BROOKFIELD AT THE COMPLETION OF THE PROJECT

ALL PROPOSED TREES SHALL FOLLOW THE FOLLOWING MINIMUM DISTANCES:

- *THREE FEET (3') FROM NEAREST MAINLINE WALK
- *THREE FEET (3') FROM NEAREST CARRIAGE WALK
 *FOUR FEET (4') FROM NEAREST FACE OF CURB
- *TEN FEET (10') FROM FIRE HYDRANTS

TREE REPLACEMENT

SYMBOL	COMMON NAME	SCIENTIFIC NAME	SIZE	QUANTITY
Α	IMPERIAL THORNLESS HONEYLOCUST	GLEDITSIA TRIACANTHOS VAR. INERMIS IMPERIAL	1-3/4" CALIPER	2
В	GREENSPIRE LITTLE LEAF LINDEN	TILIA CORDATA GREENSPIRE	2" CALIPER	2
С	AUTUMN BLAZE FREEMAN MAPLE	ACER FREEMANII	2" CALIPER	2
D	DAVID CRABAPPLE	MALUS DAVID	2-1/2" CALIPER	2
E	IVORY SILK JAPANESE TREE LILAC	SYRINGA RETICULATA IVORY SILK	2" CALIPER	2
F	DOWNY HAWTHORN	CRATAEGUS MOLLIS	2" CALIPER	2
G	COCKSPUR HAWTHORN	CRATAEGUS CRUSGALLI	2" CALIPER	2

^{*} TREE REPLACEMENT NOT PART OF PROJECT SCOPE

LEGEND OF SYMBOLS DESCRIPTION

PROPOSED SODDED PARKWAY PROPOSED CONCRETE AREA


PROPOSED HOT-MIX ASPHALT AREA

MULCH

TREE TRUNK PROTECTION TREE ROOT PRUNING

TREE MULCH DETAIL

18"




SCALE: 1" = 40'





SECTION **LANDSCAPING PLAN** 0655 20-00133-00-FP соок 107 84 CONTRACT NO. 61J89 FIELD BOOK NO. : SHEET NO. 1 OF 3 SHEETS STA. TO STA.



LANDSCAPING NOTES

SODDING:

ALL DISTURBED AREAS INDICATED ON CROSS SECTION OR LANDSCAPING PLANS TO BE SODDED, INCLUDING FERTILIZER NUTRIENTS*, AND SUPPLEMENTAL WATERING WHICH IS TO BE USED AFTER THE INITIAL WATERING (AS SPECIFIED AND AS DIRECTED BY THE ENGINEER) AT THE RATE OF 27 GALLONS PER SQUARE YARD SODDING. SODDED SLOPES WHICH ARE 2:1 OR STEEPER SHALL BE STAKED. (PROVIDE A 3" STRIP AROUND CATCH

4" TOP SOIL LAYER:

SOIL SHALL BE SPREAD AS INDICATED ON THE TYPICAL CROSS SECTIONS.

A MINIMUM OF GRADING TO BE PERMITTED WITHIN AN APPROXIMATE RADIUS OF 6' FROM ALL TREES TO BE SAVED AS DETERMINED BY THE ENGINEER.

RIPARIAN ENVIRONMENT:

IDOT CLASS 4A SEED MIXTURE TO BE USED FOR RESTORATION WITHIN RIPARIAN ENVIRONMENT

MULCH:

MULCH TO BE PLACED AROUND ALL TREES LOCATED IN AREAS THAT ARE TO BE SODDED.

PROPOSED TREES:

ALL PROPOSED TREES TO BE PLANTED BY THE VILLAGE OF BROOKFIELD AT THE COMPLETION

ALL PROPOSED TREES SHALL FOLLOW THE FOLLOWING MINIMUM DISTANCES:

*THREE FEET (3') FROM NEAREST MAINLINE WALK *THREE FEET (3') FROM NEAREST CARRIAGE WALK


*FOUR FEET (4') FROM NEAREST FACE OF CURB


*TEN FEET (10') FROM FIRE HYDRANTS

TREE REPLACEMENT

SYMBOL	COMMON NAME	SCIENTIFIC NAME	SIZE	QUANTITY
Α	IMPERIAL THORNLESS HONEYLOCUST	GLEDITSIA TRIACANTHOS VAR. INERMIS IMPERIAL	1-3/4" CALIPER	2
В	GREENSPIRE LITTLE LEAF LINDEN	TILIA CORDATA GREENSPIRE	2" CALIPER	2
С	AUTUMN BLAZE FREEMAN MAPLE	ACER FREEMANII	2" CALIPER	2
D	DAVID CRABAPPLE	MALUS DAVID	2-1/2" CALIPER	2
E	IVORY SILK JAPANESE TREE LILAC	SYRINGA RETICULATA IVORY SILK	2" CALIPER	2
F	DOWNY HAWTHORN	CRATAEGUS MOLLIS	2" CALIPER	2
G	COCKSPUR HAWTHORN	CRATAEGUS CRUSGALLI	2" CALIPER	2

* TREE REPLACEMENT NOT PART OF PROJECT SCOPE







Westchester, IL, 60154-2780

DESIGNED -REVISED -DRAWN ECW, SFB, DMM, GD REVISED -CHECKED -REVISED XXX DATE -8-7-23 REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

SCALE: 1" = 40'

SECTION **LANDSCAPING PLAN** 0655 20-00133-00-FP FIELD BOOK NO. : SHEET NO. 2 OF 3 SHEETS STA. TO STA.

107

соок

LEGEND OF SYMBOLS

SYMBOL **DESCRIPTION**

PROPOSED CONCRETE AREA

PROPOSED SODDED PARKWAY

PROPOSED HOT-MIX ASPHALT AREA

MULCH TREE TRUNK PROTECTION

TREE ROOT PRUNING

LANDSCAPING NOTES

SODDING:

ALL DISTURBED AREAS INDICATED ON CROSS SECTION OR LANDSCAPING PLANS TO BE SODDED, INCLUDING FERTILIZER NUTRIENTS*, AND SUPPLEMENTAL WATERING WHICH IS TO BE USED AFTER THE INITIAL WATERING (AS SPECIFIED AND AS DIRECTED BY THE ENGINEER) AT THE RATE OF 27 GALLONS PER SQUARE YARD SODDING. SODDED SLOPES WHICH ARE 2:1 OR STEEPER SHALL BE STAKED. (PROVIDE A 3" STRIP AROUND CATCH BASINS IN SEEDED AREAS).

4" TOP SOIL LAYER:

SOIL SHALL BE SPREAD AS INDICATED ON THE TYPICAL CROSS SECTIONS.

A MINIMUM OF GRADING TO BE PERMITTED WITHIN AN APPROXIMATE RADIUS OF 6' FROM ALL TREES TO BE SAVED AS DETERMINED BY THE ENGINEER.

RIPARIAN ENVIRONMENT:

IDOT CLASS 4A SEED MIXTURE TO BE USED FOR RESTORATION WITHIN RIPARIAN ENVIRONMENT

MULCH:

HANCOCK | 5 8 4 Civil Engineers

Municipal Consultants

ENGINEERING | 6 00 4 Established 1911

◆ Civil Engineers

MULCH TO BE PLACED AROUND ALL TREES LOCATED IN AREAS THAT ARE TO BE SODDED.

PROPOSED TREES:

ALL PROPOSED TREES TO BE PLANTED BY THE VILLAGE OF BROOKFIELD AT THE COMPLETION OF THE PROJECT

ALL PROPOSED TREES SHALL FOLLOW THE FOLLOWING MINIMUM DISTANCES:

DESIGNED -

DRAWN

CHECKED -

Westchester, IL, 60154-2780

REVISED -

REVISED

REVISED -

ECW, SFB, DMM, GD

XXX

8-7-23

*THREE FEET (3') FROM NEAREST MAINLINE WALK
*THREE FEET (3') FROM NEAREST CARRIAGE WALK
*FOUR FEET (4') FROM NEAREST FACE OF CURB
*TEN FEET (10') FROM FIRE HYDRANTS


TREE REPLACEMENT

SYMBOL	COMMON NAME	SCIENTIFIC NAME	SIZE	QUANTITY
Α	IMPERIAL THORNLESS HONEYLOCUST	GLEDITSIA TRIACANTHOS VAR. INERMIS IMPERIAL	1-3/4" CALIPER	2
В	GREENSPIRE LITTLE LEAF LINDEN	TILIA CORDATA GREENSPIRE	2" CALIPER	2
С	AUTUMN BLAZE FREEMAN MAPLE	ACER FREEMANII	2" CALIPER	2
D	DAVID CRABAPPLE	MALUS DAVID	2-1/2" CALIPER	2
E	IVORY SILK JAPANESE TREE LILAC	SYRINGA RETICULATA IVORY SILK	2" CALIPER	2
F	DOWNY HAWTHORN	CRATAEGUS MOLLIS	2" CALIPER	2
G	COCKSPUR HAWTHORN	CRATAEGUS CRUSGALLI	2" CALIPER	2


^{*} TREE REPLACEMENT NOT PART OF PROJECT SCOPE

STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION



CREEK AND RIPARIAN IMPACT									
AREA	INDICATOR	IMPACT (SF)	IMPACT (ACRE)						
TEMPORARY CREEK IMPACT		157.1	0.0036						
PERMANENT CREEK IMPACT		14.0	0.0003						
TEMPORARY RIPARIAN IMPACT		1420.0	0.0326						
PERMANENT RIPARIAN IMPACT		9.0	0.0002						




	F.A.U. RTE.	SECT	ION		COUNTY	TOTAL SHEETS	SHEET NO.
	0655	20-0013	3-00-FP		соок	107	86
	FIELD BOOK NO. :			CONTRACT NO	D. 61J89		
TO STA	FED D	OAD DICT NO. 4	II I INOIC	FFD	AID DDO IECT		


LANDSCAPING PLAN

SHEET NO. 3 OF 3 SHEETS STA.

SCALE: 1" = 40'








NOTES:

- SIDE ROAD WITH A SPEED LIMIT OF 40 MPH (60 km/h) OR LESS AS SHOWN ON THE DRAWING AND AS DIRECTED BY THE ENGINEER:
 - a) ONE "ROAD CONSTRUCTION AHEAD" SIGN 36 \times 36 (900 \times 900) WITH A FLASHER MOUNTED ON IT APPROXIMATELY 200' (60 m) IN ADVANCE OF THE MAIN ROUTE.
 - b) THE CLOSED PORTION OF THE MAIN ROUTE SHALL BE PROTECTED BY BLOCKING WITH TYPE I, TYPE II OR TYPE III BARRICADES, 1/3 OF THE CROSS SECTION OF THE CLOSED PORTION.
- 2. SIDE ROAD WITH A SPEED LIMIT GREATER THAN 40 MPH (60 km/h) AS SHOWN ON THE DRAWING AND AS DIRECTED BY THE ENGINEER:
 - a) ONE "ROAD CONSTRUCTION AHEAD" SIGN 48 x 48 (1.2 m x 1.2 m) WITH A FLASHER MOUNTED ON IT APPROXIMATELY 500" (150 m) IN ADVANCE OF THE MAIN ROUTE.
 - b) THE CLOSED PORTION OF THE MAIN ROUTE SHALL BE PROTECTED BY BLOCKING WITH TYPE III BARRICADES, 1/2 OF THE CROSS SECTION OF THE CLOSED PORTION.
- 3. CONES MAY BE SUBSTITUTED FOR BARRICADES OR DRUMS AT HALF THE SPACING DURING DAY OPERATIONS. CONES SHALL BE A MINIMUM OF 28 (710) IN HFIGHT.
- 4. WHEN THE SIDE ROAD LIES BETWEEN THE BEGINNING OF THE MAINLINE SIGNING AND THE WORK ZONE, A SINGLE HEADED ARROW (M6-1) SHALL BE USED IN LIEU OF THE DOUBLE HEADED ARROW (M6-4).

- 5. WHEN WORK IS BEING PERFORMED ON A SIDE ROAD OR DRIVEWAY, FOLLOW THE APPLICABLE STANDARD(S). THE DIRECTIONAL ARROW (M6-1 OR M6-4) SHALL BE COVERED OR REMOVED WHEN NO LONGER CONSISTENT WITH THE TRAFFIC CONTROL SET-UP.
- 6. ADVANCE WARNING SIGNS ARE TO BE OMITTED ON DRIVEWAYS UNLESS OTHERWISE SPECIFIED IN THE PLANS OR BY THE ENGINEER.
- 7. THE TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS SHALL BE INCLUDED IN THE COST OF SPECIFIED TRAFFIC CONTROL STANDARDS OR ITEMS.


All dimensions are in inches (millimeters) unless otherwise shown.

7													_
ŧ	FILE NAME =	USER NAME = footemj	DESIGNED - L.H.A.	REVISED - A. HOUSEH 10-15-96		TRAFFIC CONTROL AND PROTECTION FOR		F.A.U.	SECTION	COUNTY	TOTAL	HEET	
ź	pw:\\ILØ84EBIDINTEG.:1ll:no:s.gov:PWIDOT\Do	cuments\IDOT Offices\District 1\Projects\Dis	stb DRAWM \CADData\CADsheets\tc10.dgn	REVISED -T. RAMMACHER 01-06-00	STATE OF ILLINOIS				0655	20-00133-00-FP	соок	107	88
¥.		PLOT SCALE = 50.000 '/ in.	CHECKED -	REVISED - A. SCHUETZE 07-01-13	DEPARTMENT OF TRANSPORTATION	3	SIDE ROADS, INTERSECTIONS, AND D	DRIVEWAYS	FIELD BOOK		CONTRACT	IO. 61J89	
ذُ	Default	PLOT DATE = 9/15/2016	DATE - 06-89	REVISED - A. SCHUETZE 09-15-16		SCALE: NONE SHEET 1 OF 1 SHEETS STA. TO STA.			FED. ROAD	DIST. NO. 1 ILLINOIS FEE	. AID PROJECT		\neg



TYPICAL LANE AND EDGE LINE MARKING

MULTI-LANE DIVIDED




TYPICAL CROSSWALK MARKING

* MARKINGS SHALL BE INSTALLED PARALLEL TO THE CENTERLINE OF THE ROAD WHICH IT CROSSES

TYPICAL PAINTED MEDIAN MARKING −50′ (15 m) TO 200′ (60 m) || OVER 200' (60 m) √ 6 (150) WHITE FULL SIZE LETTERS 8' (2.4 m) AND ARROWS SHALL BE USED. \uparrow AREA = 15.6 SO. FT. (1.5 m²) **(NLY** AREA = 20.8 SO. FT. (1.9 m²) * TURN LANES IN EXCESS OF 400' (120 m) IN LENGTH MAY HAVE AN ADDITIONAL SET OF ARROW - "ONLY" INSTALLED MIDWAY BETWEEN THE OTHER TWO SETS OF TYPICAL LEFT (OR RIGHT) TURN LANE

TYPICAL TURN LANE MARKING



U-TURN

* LANE REDUCTION ARROWS REQUIRED AT SPEEDS OF 45 MPH OR GREATER OR WHEN SPECIFIED IN PLANS.

TYPE OF MARKING	WIDTH OF LINE	PATTERN	COLOR	SPACING /REMARKS
CENTERLINE ON 2 LANE PAVEMENT	4 (100)	SKIP-DASH	YELLOW	10' (3 m) LINE WITH 30' (9 m) SPACE
CENTERLINE ON MULTI-LANE UNDIVIDED PAVEMENT	2 @ 4 (100)	SOLID	YELLOW	11 (280) C-C
NO PASSING ZONE LINES: FOR ONE DIRECTION FOR BOTH DIRECTIONS	4 (100) 2 @ 4 (100)	SOLID SOLID	YELLOW	5½ (140) C-C FROM SKIP-DASH CENTERLINE 11 (280) C-C OMIT SKIP-DASH CENTERLINE BETWEEN
LANE LINES	4 (100) 5 (125) ON FREEWAYS	SKIP-DASH SKIP-DASH	WHITE WHITE	10' (3 m) LINE WITH 30' (9 m) SPACE
DOTTED LINES (EXTENSIONS OF CENTER, LANE OR TURN LANE MARKINGS)	SAME AS LINE BEING EXTENDED	SKIP-DASH	SAME AS LINE BEING EXTENDED	2' (600) LINE WITH 6' (1.8 m) SPACE
EDGE LINES	4 (100)	SOLID	YELLOW-LEFT WHITE-RIGHT	OUTLINE MEDIANS IN YELLOW
TURN LANE MARKINGS	6 (150) LINE; FULL SIZE LETTERS & SYMBOLS (8' (2.4m))	SOLID	WHITE	SEE TYPICAL TURN LANE MARKING DETAIL
TWO WAY LEFT TURN MARKING	2 & 4 (100) EACH DIRECTION 8' (2.4m) LEFT ARROW	SKIP-DASH AND SOLID IN PAIRS	YELLOW	10' (3 m) LINE WITH 30' (9 m) SPACE FOR SKIP-DASH, 5½ (140) C-C BETWEEN SOLID LINE AND SKIP-DASH LINE SEE TYPICAL TWO-WAY LEFT TURN MARKING DETAIL
CROSSWALK LINES (PEDESTRIAN) A. DIAGONALS (BIKE & EQUESTRIAN) B. LONGITUDINAL BARS (SCHOOL)	2 @ 6 (150) 12 (300) @ 45° 12 (300) @ 90°	SOLID SOLID SOLID	WHITE WHITE WHITE	NOT LESS THAN 6' (LB m) APART 2' (600) APART 2' (600) APART SEE TYPICAL CROSSWALK MARKING DETAILS.
STOP LINES	24 (600)	SOLID	WHITE	PLACE 4' (1.2 m) IN ADVANCE OF AND PARALLEL TO CROSSMALK, IF PRESENT. OTHERWISE, PLACE AT DESIRED STOPPING POINT. PARALLEL TO CROSSROAD CENTERLINE, WHERE POSSIBLE
PAINTED MEDIANS	2 @ 4 (100) WITH 12 (300) DIAGONALS @ 45° NO DIAGONALS USED FOR 4' (1,2 m) WIDE MEDIANS	SOLID	YELLOW: TWO WAY TRAFFIC WHITE: ONE WAY TRAFFIC	11 (280) C-C FOR THE DOUBLE LINE SEE TYPICAL PAINTED MEDIAN MARKING.
GORE MARKING AND CHANNELIZING LINES	8 (200) WITH 12 (300) DIAGONALS @ 45°	SOLID	WHITE	DIAGONALS: 15' (4,5 m) C-C (LESS THAN 30MPH (50 km/h)) 20' (6 m) C-C 30MPH (50 km/h) TO 45MPH (70 km/h)) 30' (9 m) C-C (OVER 45MPH (70 km/h))
RAILROAD CROSSING	24 (600) TRANSVERSE LINES; "RR" IS 6' (1.8 m) LETTERS; 16 (400) LINE FOR "X"	SOLID	WHITE	SEE STATE STANDARD 780001 AREA 0F: "R"=3.6 S0. FT. (0.33 m²) EACH "X"=54.0 S0. FT. (5.0 m²)
SHOULDER DIAGONALS (REQUIRED FOR SHOULDERS ≥ 8')	12 (300) e 45°	SOLID	WHITE - RIGHT YELLOW - LEFT	50' (15 m) C-C (LESS THAN 30MPH (50 km/h)) 75' (25 m) C-C (30 MPH (50 km/h) TO 45MPH (70 km/h) 150' (45 m) C-C (0YER 45MPH (70 km/h))
U TURN ARROW	SEE DETAIL	SOLID	WHITE	16.3 SF
2 ARROW COMBINATION LEFT AND U TURN	SEE DETAIL	SOLID	WHITE	30.4 SF

FOR FURTHER DETAILS ON PAVEMENT MARKING REFER TO STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION AND STATE STANDARD 780001.

All dimensions are in inches (millimeters) unless otherwise shown.

SECTION COUNTY DISTRICT ONE 0655 20-00133-00-FP соок 107 89 TYPICAL PAVEMENT MARKINGS FIELD BOOK NO. TC-13 CONTRACT NO. 61J89 SCALE: NONE SHEET 1 OF 1 SHEETS STA. TO STA. FED. ROAD DIST. NO. 1 ILLINOIS | FED. AID PROJECT

DESIGNED JSER NAME = footem. EVERS REVISED C. JUCIUS 09-09-09 REVISED C. JUCIUS 07-01-13 PLOT SCALE = 50.000 '/ in-CHECKED C. JUCIUS 12-21-15 REVISED 03-19-90 REVISED C. JUCIUS 04-12-16

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**


₹4' (1.2 m) OUTSIDE TO


4 (100) YELLOW LINES


(51/2 (140) C-C)

OUTSIDE OF LINES

E.H.E. PROJECT NO. 125-22-2520







NOTES:

STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION

- 1. USE BLACK LETTERING ON ORANGE BACKGROUND.
- 2. ERECT SIGNS IN ADVANCE OF THE LOCATION FOR THE "ROAD CONSTRUCTION AHEAD" SIGN AT LOCATIONS AS DIRECTED BY THE ENGINEER.
- 3. ERECT SIGN (1) WITH INSTALLED PANEL (2) ONE WEEK PRIOR TO THE START OF CONSTRUCTION.
- 4. REMOVE PANEL (2) SOON AFTER THE START OF CONSTRUCTION.
- 5. SEE SPECIAL PROVISION FOR "TEMPORARY INFORMATION SIGNING" FOR ADDITIONAL INFORMATION.
- 6. ONE SIGN ASSEMBLY EQUALS 25.70 SQ. FT. (2.3 SQ. M.)
- 7. SHALL BE PAID FOR AS TEMPORARY INFORMATION SIGNING.

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

ARTERIAL ROAD					SECTION	COUNTY	SHEETS	NO.
	INFORMATION	0655	20-00133-00-FP	соок	107	91		
INFORMATION SIGN					OOK NO. TC-22	CONTRACT N	O. 61J89	
SCALE: NONE	SHEET NO. 1 OF 1 SHEETS	STA.	TO STA.	FED. R	OAD DIST. NO. 1 ILLINOIS FI	D. AID PROJECT		

E.H.E. PROJECT NO. 125-22-25201

3.0" RADIUS, 0.5" BORDER, WHITE ON GREEN; REFLECTORIZED "DRIVEWAY" D; "ENTRANCE" D; STANDARD ARROW CUSTOM 12.0" x 5.0"

NOTES:

- 1. HALF OF THE SIGNS WILL REQUIRE A LEFT HAND FACING ARROW.
- 2. TWO SIGNS SHALL BE USED AT EACH COMMERCIAL ENTRANCE PLACED BACK-TO-BACK: ONE WITH A RIGHT HAND ARROW (SHOWN) SHALL BE PLACED ON THE NEAR RIGHT SIDE THE DRIVEWAY AND ONE WITH A LEFT HAND ARROW SHALL BE PLACED ON THE FAR LEFT SIDE OF THE DRIVEWAY.
- 3. SIGNS TO BE PAID FOR AS ITEM "TEMPORARY INFORMATION SIGNING".

 USER NAME
 = leysa
 DESIGNED
 REVISED
 C. JUCIUS 02-15-07

 DRAWN
 REVISED

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


SCALE: NONE

(5A)

6

(6A)

RAILROAD CROSSING REPAIR DETOUR SIGNING



M5-1L 21"X15"

M5-2L 21"X15"

USE SEE NOTE 4.

M4-8 24"X12"

M6-1L 21"X15"

M6-2L 21"X15"

USE SEE NOTE 4.

M4-8 24"X12"

M6-3 21"x15"

JSER NAME

PLOT DATE = 3/4/2019

M1-I100 24"X24" (STATE ROUTE)

M1-I100 24"X24" (STATE ROUTE)

DATE

REVISED

M1-4 24"X24" (US ROUTE)

FOR FREEWAY/EXPRESSWAY

M1-4 24"X24" (US ROUTE)

FOR FREEWAY/EXPRESSWAY




(17)

(18)







				<i>,</i> • • • • • • • • • • • • • • • • • • •	ABO	INE THE ROU
AME = footemj	DESIGNED -	REVISED - A. SCHUETZE 09-16		RAILROAD CROSSING REPAIR	F.A.U. RTE.	SECTION
	DRAWN -	REVISED -	STATE OF ILLINOIS	DETOUR SIGNING	0655	20-00133-00
ALE = 50.0000 ' / in.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION	DETOUR SIGNING	FIELD BO	OK NO. TC-28
		I I				

TYPE III BARRICADE

W/ FLASHING LIGHTS

SCALE: NONE

NOTES:

M1-I100 24"X24" (STATE ROUTE)

M1-4 24"X24" (US ROUTE)

USE SEE NOTE 4.

*

CLOSED

ΑT

RAILROAD

CROSSING

4'

RAILROAD

REPAIRS

BEGIN

DATE

TIME

FOR FREEWAY/EXPRESSWAY

5" LETTER MIN.

BLACK LETTERS

5" LETTER MIN.

BLACK LETTERS

ON ORANGE

BACKGROUND

ON ORANGE BACKGROUND

- 1. FOR DETOURS OF UNMARKED ROUTES, SIGNS 5 - 9A SHALL BE MODIFIED TO USE THE M4-9 SIGN
- 2. FOR DETOURS OF MARKED ROUTES, THE ORDER OF THE SIGNS SHOWN IN THE SIGN ASSEMBLIES 5 - 9A SHALL BE MODIFIED TO MATCH TYPICAL ASSEMBLY SHOWN BELOW.



- 3. ANY SIGNS THAT ARE TO BE IN PLACE FOR MORE THAN 4 DAYS MUST HAVE A VERTICAL CLEARANCE OF 7 FEET FROM TOP OF PAVEMENT TO THE BOTTOM OF THE SIGN (5 FEET IN RURAL AREAS). THESE SIGNS SHALL BE POST MOUNTED IN THE GROUND WHERE POSSIBLE PER ARTICLE 701.14 OF THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION AND HIGHWAY STANDARD 701901.
- 4. FOR FREEWAY/EXPRESSWAY USE M1-I100 36"X36" USED FOR ILLINOIS ROUTES, M1-4 36"X36" FOR U.S. ROUTES, OR ROAD NAMES SIGN WITH 6" LETTER MINIMUM BLACK LETTERS ON ORANGE BACKGROUND.
- REFER TO DISTRICT DETAIL TC-21 FOR TYPICAL SIGN LAYOUT AND SPACING



M1-I100 24"X24" USED FOR ILLINOIS ROUTES.



M1-4 24"X24" USED FOR U.S. ROUTES.



CUSTOM ROAD NAME SIGN WITH 5" MINIMUM UPPERCASE BLACK LETTERS ON ORANGE BACKGROUND.



TYPE A FLASHING LIGHT

WHEN LOWER CASE LETTERS ARE USED, AS SHOWN, THEY SHALL BE 3/4 OF THE SIZE OF THE UPPER CASE LETTERS.

FOR FREEWAY/EXPRESSWAY USE - SEE NOTE 4.



M3-1 24"X12"

M3-2 24"X12"




M3-3 24"X12" M3-4 24"X12"

CARDINAL DIRECTION SIGNS SHALL BE USED DIRECTLY ABOVE THE ROUTE MARKER.

COOK 107 93 CONTRACT NO. 61J89 SHEET 1 OF 1 SHEETS STA. FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT


E.H.E. PROJECT NO. 125-22-2520

PROPOSED PAY LIMIT OF HMA SURF. REMOVAL





(FOR BUTT JOINT AND HMA TAPER SEE DETAIL BELOW)

OPTION 2 TYPICAL TEMPORARY RAMP



TYPICAL BUTT JOINT AND HMA TAPER FOR MILLING AND RESURFACING





TYPICAL BUTT JOINT AND HMA TAPER FOR RESURFACING ONLY

** PC CONCRETE, HMA OR HMA RESURFACED PAVEMENT.

GENERAL NOTES

- A. MAINLINE ARTERIAL ROADWAYS AND MAJOR SIDE ROADS.
- A1. INTERSTATES
- B. MINOR SIDE ROADS.
- C. THE TEMP. RAMP SHALL BE CONSTRUCTED IMMEDIATELY UPON REMOVAL OF THE EXISTING HMA SURFACE.
- D. THE BUTT JOINT SHALL BE CONSTRUCTED IMMEDIATELY PRIOR TO PLACING THE PROPOSED HMA COURSES.
- E. TAPER THE TEMP. RAMP AT A RATE OF 3' 4" (1.02m) PER 1 INCH (25 mm) OF MILLING THICKNESS. * SEE TYPICAL SECTIONS FOR MILLING THICKNESS.
- F. SEE ARTICLE 406.08 AND 406.14 OF THE STANDARD SPECIFICATIONS FOR "HMA AND/OR PCC SURFACE REMOVAL, BUTT JOINT".
- *** $^{20'-0"}$ (6.1 m) PER 1 (25) RESURFACING (NOTE "A") $^{10'-0"}$ (3.0 m) PER 1 (25) RESURFACING (NOTE "B")

BASIS OF PAYMENT

- THE BUTT JOINT WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQUARE YARD (SQUARE METER)
 FOR "HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT" OR
 FOR "PORTLAND CEMENT CONCRETE SURFACE REMOVAL- BUTT JOINT".
- THE TEMPORARY RAMP AND SAW CUT SHALL BE INCLUDED IN THE UNIT COST FOR HMA OR PCC SURFACE REMOVAL-BUTT JOINT.

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.


													_
USER NAME = Lawrence.DeManche	DESIGNED - M. DE YONG	REVISED - A. ABBAS 03-21-97			BUT	T JOINT	AND		F.A.U. RTE.	SECTION	COUNTY	TOTAL SHI	ET O
	DRAWN -	REVISED - M. GOMEZ 04-06-01	STATE OF ILLINOIS						0655	20-00133-00-FP	соок	107 9	4
PLOT SCALE = 100.0000 ' / in.	CHECKED -	REVISED - R. BORO 01-01-07	DEPARTMENT OF TRANSPORTATION		HIVIA	TAPER D	HAILS		FIELD BO	OK NO. BD-32	CONTRACT N	O. 61J89	
PLOT DATE = 11/18/2022	DATE - 06-13-90	REVISED - K. SMITH 11-18-22		SCALE: NONE	SHEET 1 OF 1	SHEETS	STA.	TO STA.	FED. RO	AD DIST. NO. 1 ILLINOIS F	ED. AID PROJECT		

E.H.E. PROJECT NO. 125-22-2520


LOOP DETECTOR NOTES

- 1. EACH PAIR OF LOOP WIRES SHALL BE PLACED IN A SEPARATE EMPTY COILABLE NONMETALLIC CONDUIT FROM THE EDGE OF PAVEMENT TO THE HANDHOLE. SPACING BETWEEN THE HOLES DRILLED IN THE PAVEMENT SHALL NOT BE LESS THAN 6" (150 mm). EMPTY COILABLE NONMETALLIC CONDUIT SHALL BE INCLUDED IN THE COST OF THE LOOP WIRE.
- 2. THE NUMBER OF LOOP TURNS SHALL BE AS RECOMMENDED BY THE AMPLIFIER MANUFACTURER. ALL ADJACENT SIDES OF THE LOOPS SHALL BE INSTALLED IN SUCH A WAY THAT THE CURRENT FLOW IS IN THE SAME DIRECTION TO REINFORCE ITS MAGNETIC FIELDS FOR SMALL VEHICLE DETECTION.
- 3. EACH LOOP LEAD-IN SHALL BE IDENTIFIED AND PERMANENTLY TAGGED IN THE HANDHOLE. EACH LEAD-IN CABLE TAG SHALL INDICATE THE LOCATION OF THE LOOP, LOOP ROTATION (CLOCKWISE/COUNTERCLOCKWISE), LOOP LEAD-IN DIRECTION (IN OR OUT), LOOP CABLE NUMBER AND LOCATION IN CABINET, AND NUMBER OF TURNS IN THE DETECTOR LOOPS IN WATER PROOF INK AS INDICATED ON THE DISTRICT 1 STANDARD TRAFFIC SIGNAL DESIGN DETAIL. THE CONTRACTOR SHALL MARK LOOP LOCATIONS ON RECORD DRAWINGS AND PRESENT TO THE ENGINEER AFTER FINAL INSPECTION. LOOPS SHALL BE MARKED BY LANE AND LOOP NUMBER. SEE DETAIL BELOW.
- 4. ALL LOOP CABLE SHALL BE FASTENED WITH PLASTIC TIE WRAP TO THE HANDHOLE HOOKS.
- 5. IN ASPHALT PAVEMENT, LOOPS SHOULD BE PLACED IN THE BINDER AND DIVEHOLES MARKED AT THE CURB WITH A SAW-CUT. THE SAW-CUT SHALL BE CUT IN ACCORDANCE WITH LOCAL AND E.P.A. DUST CONTROL REQUIREMENTS. DETECTOR LOOP(S) SHALL NOT BE INSTALLED IN WET CONDITIONS AND THE SAW-CUTS MUST BE FREE OF DEBRIS AND RESIDUE SUCH AS DUST AND WATER WHICH IS TO BE ACHIEVED BY THE USE OF COMPRESSED AIR, WIRE BRUSHING AND HEAT DRYING ACCORDING TO SEALANT MANUFACTURER REQUIREMENTS. THE DETECTOR WIRE SHALL BE HELD IN PLACE BY THE USE OF FORM WEDGES. WEDGES SHALL BE SPACED NO MORE THAN 18" (450 mm) APART.
- 6. LOOP SPLICES SHALL BE SOLDERED USING A SOLDERING IRON. BLOW TORCHES OR OTHER DEVICES WHICH OXIDIZE COPPER CABLE SHALL NOT BE ALLOWED FOR SOLDERING OPERATIONS. SEE DETAIL BELOW RIGHT.
- 7. PREFORMED DETECTOR LOOPS SHALL BE USED, AS SHOWN ON THE PLANS, WHERE NEW CONCRETE PAVEMENT IS PROPOSED. THE INSTALLATION OF PREFORMED LOOPS SHALL BE IN ACCORDANCE WITH THE DISTRICT 1 SPECIFICATIONS OR AS DIRECTED BY THE ENGINEER.

LOOP LEAD-IN CABLE TAG





- A. LANE 1 IS THE LANE CLOSEST TO THE CENTERLINE OF THE ROADWAY
- B. LOOP #1 IS THE LOOP IN THE LANE CLOSEST TO THE INTERSECTION.
- C. LABEL LOOP CABLE "IN" OR LOOP CABLE "OUT".
- D. LABEL LOOP CABLE CLOCKWISE OR LOOP CABLE COUNTERCLOCKWISE.



DETECTOR LOOP WIRING SCHEMATIC

- LOOPS SHALL BE SPLICED IN SERIES.
- SAW-CUTS SHALL BE A MINIMUM WIDTH OF 5/16" (8 mm).
- SAW-CUT DEPTHS SHALL BE 3" (75 mm). IF IN CONCRETE, THE SAW-CUT DEPTH SHALL BE TO THE TOP OF THE REINFORCEMENT.
- LOOP CORNERS SHALL BE DRILLED WITH A 2" (50 mm) DIAMETER CORE.





LOOP DETECTOR SPLICE

- $\stackrel{\textstyle \frown}{\ \ \ }$ Western union splice soldered with rosin core flux. All exposed surfaces OF THE SOLDER SHALL BE SMOOTH. THE WESTERN UNION SPLICES SHALL BE STAGGERED.
- (2) WCSMW 30/100 HEAT SHRINK TUBE, MINIMUM LENGTH 3" (75 mm), UNDERWATER GRADE.
- (3) WCS 200/750 HEAT SHRINK TUBE, MINIMUM LENGHT 6" (150 mm), UNDERWATER GRADE.

SCALE: NONE

(4) NO. 14 2/C TWISTED, SHIELDED CABLE.

- (5) LOOP CONDUCTOR WITH FLEXIBLE PLASTIC TUBE.
- (6) PRE-FORMED LOOP
- XL POLYOLEFIN 2 CONDUCTOR T BREAKOUT SEALS. TYCO CBR-2 OR APPROVED EQUAL

DESIGNED DAD REVISED DAG 1-1-14 DRAWN REVISED CHECKED DAD REVISED PLOT DATE = 1/13/2014 DATE 10-28-09

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

DISTRICT ONE STANDARD TRAFFIC SIGNAL DESIGN DETAILS SHEET NO. 2 OF 7 SHEETS STA.

SECTION COUNTY 0655 20-00133-00-FP соок 108 95 FIELD BOOK NO. :TS-05 CONTRACT NO. 61J89 FED. ROAD DIST. NO. 1 | ILLINOIS | FED. AID PROJECT

 \star \star Unit duct is to be shown on plan sheets BUT SHALL NOT BE INCLUDED IN THE PAY ITEMS

SER NAME = footem

PLOT DATE = 3/4/2019

PLOT SCALE = 50.0000 ' / in


 \pm = (600 mm)

LEFT TURN LANES WITH MEDIANS

VOLUME DENSITY ("FAR OUT" DETECTION) ON SAME APPROACH

(PROTECTED / PERMITTED LEFT TURN PHASING)

HANDHOLE LOCATION MAY VARY DEPENDING ON GEOMETRICS AND DESIGN OF TRAFFIC SIGNALS. HEAVY-DUTY HANDHOLES TO BE USED WHEN THE MEDIAN IS MOUNTABLE REFER TO STANDARD 814001 TO ENSURE THAT HANDHOLE FITS IN MEDIAN.




NOTE: DUAL LEFT TURNS NOT SHOWN REFER TO

PLAN SHEET FOR DETECTOR LOOP REPLACEMENT

(900 m

LEFT TURN LANES WITHOUT MEDIANS

VOLUME DENSITY ("FAR OUT" DETECTION) ON SAME APPROACH (PROTECTED / PERMITTED LEFT TURN PHASING)



PLAN SHEET FOR DETECTOR LOOP REPLACEMENT

LANE TAPER

SCALE: NONE

ARTERIAL-VOLUME DENSITY ("FAR OUT" DETECTION) CROSS STREET-NON VOLUME DENSITY ("UPTIGHT" PRESENCE DETECTION)

ARTERIAL DO NOT INSTALL CALLING LOOP IN RIGHT TURN LANE * = (1.8m) ** = (1.5m) CROSS STREET (600mm) 11' DEPENDING ON DRIVE-WAY LOCATION. CALLING LOOPS (600mm) n ([TYP.-12' (3.6m) LANES] LOOPS ARE SAW-CUT O THE EDGE OF PAVEMENT. 1" (25 mm) UNIT DUCT IS RUN BETWEEN STRAIGHT SAW CUTS TO HEAVY-EDGE OF PAVEMENT DRIVEWAY AND HANDHOLE. DUTY HANDHOLE (TYP. FOR LOOPS OFF SET LOOPS BY IN PAVEMENT THAT TERMINATE 1' (300mm) FOR (TYP.) IN HANDHOLES STRAIGHT SAW CUTS

DETAIL 1

N.T.S.

DESIGNED

CHECKED -

R.K.F.

DRAWN

DATE

REVISED

REVISED

REVISED

REVISED

ARTERIAL-VOLUME DENSITY ("FAR OUT" DETECTION)

CROSS STREET-NON VOLUME DENSITY ("FAR OUT" DETECTION)

PAVED OR

OFFSET LOOPS BY 1' (300mm) FOR STRAIGHT SAW CUTS ARTERIAL THIS DIMENSION MAY BE ADJUSTED FOR DRIVEWAY OR OTHER OBSTRUCTIONS. WHEN ADJUSTMENT IS REQUIRED, DETECTORS WILL NORMALLY BE MOVED CLOSER TO THE INTERSECTION. |1" (25 mm UNIT DUCT CROSS STREET 15'(4.5m) MAXIMUM *6'| 9' |*6'| 9' |*6'| + - THESE DIMENSIONS DRIVEWAY WILL BE VARIABLE [6' (1.8m) MINIMUM 25' (7.6 m) MAXIMUM] A - THESE DIMENSIONS SHALL BE 5' (1.5m) FOR "FAR OUT" LOOPS 10' (3.0m) LANE WIDTHS ARE LOCATED IN TAPER OF A RIGHT TURN LANE, DIMENSION THIS LOOP TO COVER TAPER AREA. DO NOT LANE OR LEFT TURN DETAIL 2

N.T.S

NOTES:

VEHICLES LOOP DETECTORS

- * ALL LEAD IN CABLE SHALL BE TWO CONDUCTOR NO. 14 TWISTED, SHIFL DED
- * EACH DETECTOR LOOP SHALL HAVE ITS OWN SAW CUT FROM THE LOOP TO THE EDGE OF PAVEMENT OR TO A HANDHOLE IN THE **PAVEMENT**
- * EACH DETECTOR LOOP SHALL HAVE ITS OWN ONE INCH (25 mm) UNIT DUCT BETWEEN THE EDGE OF PAVEMENT AND THE FIRST HANDHOLE OR JUNCTION BOX. EACH UNIT DUCT RUN SHALL BE SHOWN ON THE PLANS BY THE DESIGNER, BUT SHALL NOT BE PAID FOR SEPARATLY. THIS ITEM IS INCIDENTAL TO THE PAY ITEM FOR DETECTOR LOOPS.
- * ONE DIMENSION OF ALL DETECTOR LOOPS SHALL BE SIX FEET (1.8 m)
- st EACH LANE OF NON-LOCKING, PRESENCE DETECTION AND EACH LANE OF A DOUBLE LEFT TURN LANE REQUIRES A SEPARATE INDUCTIVE LOOP DETECTOR AND LEAD IN CABLE.
- * WHEN NON-LOCKING, PRESENCE DETECTION IS USED, MORE THAN ONE LOOP PER LANE IS REQUIRED BEHIND THE STOP BAR (i.e. 1-1/2, 1-3/4, 2).
- * WHEN SYSTEM LOOPS ARE REQUIRED ON AN APPROACH OF AN INTERSECTION, THE LOOPS USED FOR VOLUME DENSITY AND INTERSECTION TIMING SHALL ALSO BE USED AS SYSTEM DETECTORS. EACH ONE OF THESE TYPE OF LOOPS REQUIRES A SEPARATE TWO CONDUCTOR NO. 14 TWISTED SHIELDED CABLE AND A SEPARATE INDUCTIVE LOOP DETECTOR WHEN NEW CONTROLLERS ARE UTILIZED. THE DESIGNER SHALL LABEL THESE TYPES OF LOOPS AS "INTERSECTION AND SAMPLING (SYSTEM) DETECTORS" ON THE SIGNAL LAYOUT, THE INTERCONNECT PLAN AND THE SYSTEM CABLE PLAN. WHEN AN EXISTING CONTROLLER IS UTILIZED FOR THIS TYPE OF DETECTION, THE PAY ITEM "INDUCTIVE LOOP DETECTOR WITH SYSTEM OUTPUT" SHOULD BE USED.

PLACEMENT OF DETECTORS

TO STA

THE FOLLOWING FIGURES REPRESENT THE MOST COMMON DETECTOR LOOP LOCATIONS AND SIZES. ADJUSTMENTS WILL BE NECESSARY FOR SPECIFIC GEOMETRIC CONSIDERATIONS.

LOCATIONS AND DEMENSIONS OF DETECTOR LOOPS ARE REQUIRED ON ALL SIGNAL LAYOUT PLAN SHEETS.

"FAR OUT" DETECTION REFERS TO LOCKING, PRESENCE TYPE DETECTION LOCATED IN THRU LANES, RIGHT TURN LANES, AND RIGHT TURN LANE TAPER AREAS (IF APPLICABLE), USUALLY 250' (75 m) IN ADVANCE OF STOP BARS, "UPTIGHT" DETECTION REFERS TO NON-LOCKING PRESENCE TYPE DETECTION LOCATED IN ALL LANES AND 10'-15' (3.0 m-4.5 m) BEHIND THE CROSSING STREET'S EDGE OF PAVEMENT EXTENDED.


NOTE:

ALL DETAILS AND NOTES SHOWN ARE FROM THE I.D.O.T. DISTRICT 1 TRAFFIC SIGNAL DESIGN GUIDELINES DATED JANUARY 1995

THIS DRAWING HAS BEEN PREPARED TO ASSIST THE RESIDENT ENGINEER FOR ALL ROADWAY RESURFACING OR S.M.A.R.T. PROJECTS WHERE THE DIMENSIONS ARE NOT SHOWN ON THE PLANS AND THE FINAL LOCATIONS FOR CROSSWALKS OR STOP BARS ARE NOT DETERMINED

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** DISTRICT 1 - DETECTOR LOOP INSTALLATION **DETAILS FOR ROADWAY RESURFACING** SHEET 1 OF 1 SHEETS STA.

SECTION COUNTY 0655 20-00133-00-FP COOK 108 FIELD BOOK NO. :TS-07 CONTRACT NO. 61J89 FED. ROAD DIST. NO. 1 | ILLINOIS | FED. AID PROJECT



♦ HAN ENGI

◆ Civil Engineers
 ◆ Municipal Consultants
 ◆ Established 1911
 ◆ Established 1911

 DESIGNED X
 REVISED

 DRAWN ECW, SFB, DMM, GD
 REVISED


 CHECKED XXX
 REVISED

 DATE 8-7-23
 REVISED

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


 DUBOIS CROSS SECTIONS


 SCALE: H: 1"=10", V:1"=5"
 SHEET NO. 1 OF 11 SHEETS STA. T




proming the markets_by_vinage (b) confield

PROJECT NO. 125-22-25201







HANCOCK | baseling | b

 ◆ Civil Engineers
 ◆ Municipal Consultants
 ◆ Established 1911
 ◆ Established 1911
 ◆ Westchester, IL, &0154-2780 Phone: 708-845-0300
 ◆ www.ehancock.com

 DESIGNED X
 REVISED

 DRAWN ECW, SFB, DMM, GD
 REVISED

 CHECKED XXX
 REVISED


 DATE 8-7-23
 REVISED

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BURLINGTON CROSS SECTIONS

SCALE: H:1"=10', V:1"=5' SHEET NO. 5 OF 11 SHEETS STA. TO STA

H.E. PROJECT NO. 125-22-252



9933 Roosevelt Road
Westchester, IL, 60154-2780
Phone: 708-865-0300
www.ehancock.com

 DESIGNED X
 REVISED

 DRAWN ECW, SFB, DMM, GD
 REVISED

 CHECKED XXX
 REVISED


 DATE 8-7-23
 REVISED

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BURLINGTON CROSS SECTIONS

SCALE: H: 1"=10', V:1"=5' SHEET NO. 6 OF 11 SHEETS STA. TO STA.

E. PROJECT NO. 125-22-25201




HANCOCK	uce	◆ Civil Engineers
HANCOCK ENGINEERING	<u>e</u>	◆ Municipal Cons
	Ř	◆Established 191

DESIGNED -	X	REVISED -
DRAWN -	ECW, SFB, DMM, GD	REVISED -
CHECKED -	XXX	REVISED -
DATE -	8-7-23	REVISED -

Westchester, IL, 60154-2780 Phone: 708-865-0300

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

		BURLII	10)T	NC	CROS	S SEC	TIONS
Γ	SCALE: H:1"=10', V:1"=5'	SHEET NO.	7	OF	11	SHEETS	STA.	TO STA.




◆ Municipal Consultants

REVISED -DRAWN -REVISED -ECW. SFB. DMM. GD chester, IL, 60154-2780 Phone: 708-865-0300 CHECKED -XXX REVISED -REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

BURLINGTON CROSS SECTIONS SCALE: H:1"=10', V:1"=5' SHEET NO. 8 OF 11 SHEETS STA.

F.A.U. RTE. 0655 SECTION 108 104 20-00133-00-FP соок CONTRACT NO. 61J89 FED. AID PROJECT FIELD BOOK NO. FED. ROAD DIST. NO. 1



♦ Municipal Consultants


DRAWN tchester, IL, 60154-2780 Phone: 708-865-0300 CHECKED -XXX

REVISED -REVISED -ECW. SFB. DMM. GD REVISED -REVISED

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

BURLINGTON CROSS SECTIONS SCALE: H:1"=10', V:1"=5' SHEET NO. 9 OF 11 SHEETS STA.


F.A.U. RTE. 0655 SECTION 108 105 20-00133-00-FP соок CONTRACT NO. 61J89 FIELD BOOK NO. FED ROAD DIST NO 1 FED AID PROJECT



STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BURLINGTON CROSS SECTIONS

SCALE: H:1"=10", V:1"=5" SHEET NO. 10 OF 11 SHEETS STA. TO STA.



9933 Roosevelt Road
estchester, IL, 60154-2780
Phone: 708-865-0300
www.ehancock.com

 DESIGNED X
 REVISED

 DRAWN ECW, SFB, DMM, GD
 REVISED

 CHECKED XXX
 REVISED

 DATE 8-7-23
 REVISED

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BURLINGTON CROSS SECTIONS

SCALE: H: 1"=10", V: 1"=5" | SHEET NO. 11 | OF 11 | SHEETS | STA. TO STA.