

NE1/4 of NW1/4 Sec 26 T7S-R1E

SE1/4 of NW1/4 Sec 26 T7S-R1E


Notes

1. WHERE NORTHINGS AND EASTINGS ARE NOT NOTED, THE CONSTRUCTION LIMITS SHALL FOLLOW THE EDGES OF THE EXISTING ROADS.
2. THE EXCAVATED RUBBLE PIT SHALL HAVE THE DIMENSIONS OF 270' x 150' AT ELEVATION 389 AND 135' x 96' AT THE BOTTOM ELEVATION OF 375.5.
3. ALL RUBBLE AND FOUNDATIONS NOT PLACED WITHIN THE AIR SHAFT AS RUBBLE FILL ARE TO BE PLACED WITHIN THE RUBBLE PIT. ALL VOIDS ARE TO BE FILLED WITH FINE AGGREGATE FILL MATERIAL (2,200 TON) IN ACCORDANCE WITH SECTION 501 OF THE SPECIAL PROVISIONS. THE RUBBLE SHALL THEN BE COVERED WITH A MINIMUM 3' MINE REFUSE AND 1' EARTH MATERIAL (SEE CROSS SECTIONS).

	EXISTING CONTOUR
	PROPOSED CONTOUR
	PROPOSED RUBBLE PIT CONTOUR
	PROPOSED CONSTRUCTION LIMITS
	BASELINE FOR CROSS SECTIONS
	TREE LINE
	SECTION LINE
	EDGE OF WATER
	CONTROL POINT
	BORING LOCATION (APPROX.)
	EXISTING STRUCTURE
	PROPOSED EXCELSIOR BLANKET (8' WIDTH)

Legend

Bell & Zoller #2 Mine



Date: 10/11/05

Drawn By: JLU

Checked By: