



NOTE:

1. PLACE PERIMETER EROSION BARRIER PRIOR TO ANY EARTH DISTURBING OR GRADING ACTIVITIES.
2. PLACE EMBANKMENT AND STABILIZE WITH TEMPORARY EROSION CONTROL SEEDING AS THE EMBANKMENT CONSTRUCTION PROGRESSES.
3. STABILIZE THE FINAL GRADED SLOPES WITH PERMANENT SEEDING AND EROSION CONTROL BLANKET AS SOON AS POSSIBLE. INSTALL HEAVY DUTY EROSION CONTROL BLANKET ON SLOPES STEEPER THAN 1:3 (V:H) OR AS DIRECTED BY THE ENGINEER.
4. TEMPORARY SEED ANY BARE EARTH OR DISTURBED AREAS EVERY 7 DAYS (CRITICAL LOCATIONS WITHIN 48 HOURS) IN ACCORDANCE WITH ARTICLE 280.04 OF THE STANDARD SPECIFICATIONS.
5. CONTRACTOR TO SUBMIT LOCATION OF WASHOUT BASIN FOR APPROVAL BY THE ENGINEER.

FILE NAME =	USER NAME = _USER_	DESIGNED - CGC	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	IL 2 OVER THE BNSF RAILROAD EROSION CONTROL PLANS	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
ts:\9015-phase11_11-2&11-26\civil\IL-2\CADD	Sheets\0264016-sh1-erosion.dgn	DRAWN - CGC	REVISED -			742	38VBR-1	OGLE	87	31	
	PLOT SCALE = #SCALE#	CHECKED - AKK	REVISED -			SCALE: 1"=50' SHEET NO. 31 OF 87 SHEETS STA. 504+44.50 TO STA. 511+00.00					
	PLOT DATE = 8/18/2011	DATE - 8/2/2011	REVISED -			FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT CONTRACT NO. 64D16					