

AGGREGATE (PRIME COAT)		
LOCATION	COLD-MILLED	FOG COAT
	TON	TON
DIXON CREEK - MAIN LINE		
STA. 307+06.65 TO 313+59.00	3.77	1.89
STA. 309+60.00-Bituminous Driveway	0.1	0.05
STA. 313+59.00 TO 319+54.50	3.44	1.72
STA. 315+00-Mailbox Turnout & Shoulder	0.11	0.05
STA. 319+54.50 TO 342+15.00	13.06	6.53
STA. 320+54.50-Sideroad 900N	0.53	0.26
DIXON CREEK - TOTAL	21.01	10.5
TOTAL	32	

POLYMERIZED BITUMINOUS MATERIALS (PRIME COAT)	
LOCATION	TON
EAST SHOULDER (INITIAL PLACEMENT)	
474' AGGREGATE RUN @ 0.50 GAL/SY	0.42
WOLF CREEK - TOTAL	0.42
628' AGGREGATE RUN @ 0.50 GAL/SY	0.42
DIXON CREEK - TOTAL	0.42
TOTAL	1

POLYMERIZED BITUMINOUS MATERIALS (PRIME COAT)	
LOCATION	TON
26' WIDTH GRANULAR SPECIAL - 0.50 GAL/SY FOR BINDER APPLICATION	
STA. 213+79 TO 215+83.495	1.36
SOUTH OF STRUCTURE	0
WOLF CREEK - TOTAL	1.36
STA. 344+59 TO 346+47.50	1.244
STA. 347+97.50 TO 348+68	0.408
DIXON CREEK - TOTAL	1.652
TOTAL	3

POLYMERIZED BITUMINOUS MATERIALS (PRIME COAT)	
LOCATION	TON
EAST & WEST SHOULDERS	
581.5' BINDER RUN @ 0.10 GAL/SY	0.032
172.5' AGGREGATE TUN @ 0.50 GAL/SY	0.516
WOLF CREEK - TOTAL	0.548
241' BINDER RUN @ 0.10 GAL/SY	0.032
813' AGGREGATE TUN @ 0.50 GAL/SY	0.54
DIXON CREEK - TOTAL	0.572
TOTAL	1

INCIDENTAL HOT-MIX ASPHALT SURFACING	
LOCATION	TON
ENTRANCE STA. 320+25 - 6"	37
DIXON CREEK - TOTAL	37
TOTAL	37

POLYMERIZED BITUMINOUS MATERIALS (PRIME COAT)	
LOCATION	TON
NEXT LEVEL ON BINDER @ 0.10 GAL/SY	
26' WIDTH - STA. 212+10 TO 213+00	0.104
26' WIDTH - STA. 218+00 TO 219+40	0.16
32' WIDTH - STA. 213+00 TO 215+83.50	0.404
32' WIDTH - STA. 217+06.50 TO 218+00	0.132
WOLF CREEK - TOTAL	0.8
26' WIDTH - STA. 342+15 TO 343+25	0.128
26' WIDTH - STA. 349+75 TO 351+15	0.16
32' WIDTH - STA. 343+25 TO 346+74.50	0.496
32' WIDTH - STA. 347+97.50 TO 349+75	0.252
DIXON CREEK - TOTAL	1.036
TOTAL	2

HOT-MIX ASPHALT SURFACE REMOVAL		
LOCATION	3/4"	2"
	SQ YD	SQ YD
STA. 307+36.65 TO 313+59.00	1797.9	
STA. 313+59.00 TO 315+69.00		606.67
STA. 315+69.00 TO 319+54.50		1113.67
STA. 319+54.50 TO 341+85.00	6443.67	
STA. 20+54.50 - SIDEROAD 900 N	233.33	
TOTAL	8,475	1,720

POLYMERIZED BITUMINOUS MATERIALS (PRIME COAT)	
LOCATION	TON
26' WIDTH BINDER - 0.10 GAL/SY FOR BINDER APPLICATION AT TRANSITION & VARIABLE DEPTH	
STA. 212+84.81 TO 213+79	0.132
STA. 217+06.50 TO 218+68.75	0.188
WOLF CREEK - TOTAL	0.32
STA. 342+57.50 TO 344+59	0.232
STA. 348+68 TO 350+27.27	0.184
DIXON CREEK - TOTAL	0.416
TOTAL	1

HOT-MIX ASPHALT SCHEDULE																	
LOCATION	LENGTH	HMA BASE CSE. WID., 8" PHASE I SHOULDER, LT			POLY. LEV. BINDER (MM), IL-4.75, N50		HMA SURFACE CSE., MIX "D", N 50			HMA BINDER CSE., IL.-19.0, N50 - MAINLINE				HMA SHOULDERS - LT & RT			
		PAVEMENT 26'		WOLF CREEK	DIXON CREEK	2"	1 1/2"	8"		VARIABLE THICKNESS		2"		8"		VARIABLE THICKNESS	
		WOLF CREEK	DIXON CREEK					WOLF CREEK	DIXON CREEK	WOLF CREEK	DIXON CREEK	WOLF CREEK	DIXON CREEK	WOLF CREEK	DIXON CREEK	WOLF CREEK	DIXON CREEK
FOOT	SQ YD	TON	TON	TON	TON	TON	TON	TON	TON	TON	TON	TON	TON	TON	TON	TON	
STA. 213+00 TO 216+34	334	148.4															
STA. 216+56 TO 218+00	144	64.0															
STA. 343+25 TO 347+20.33	395.33		131.8														
STA. 347+46.33 TO 349+75	228.67		76.2														
STA. 213+00 TO 215+83.495	283.495				84.7							28.2					
STA. 217+06.505 TO 218+00	93.495				28.1							9.4					
STA. 212+10 TO 213+00	90				29.1												
STA. 218+00 TO 219+40	140				45.3												
STA. 343+25 TO 346+74.50	349.5					104.4							34.8				
STA. 347+97.50 TO 349+75	177.5					52.7							17.6				
STA. 307+06.65 TO 307+36.65	30		3.65				7.34										
STA. 307+36.65 TO 313+59.00	622.35		75.69				152.28										
STA. 313+59.00 TO 315+69.00	210		25.54				51.38										
STA. 315+69.00 TO 319+54.50	385.5		46.89				94.33										
STA. 319+54.50 TO 341+85.00	2230.5		271.28				545.78										
STA. 341+85.00 TO 342+15.00	30		3.65				7.34										
STA. 342+15 TO 343+25	110					35.6											
STA. 349+75 TO 351+25	150					45.3											
STA. 213+09.81 TO 213+79	69.19									116.4						36.5	
STA. 217+06.50 TO 218+23.75	117.25									194.1						42	
STA. 213+79 TO 215+83.5	204.5								264.7					71.1			
STA. 343+03.75 TO 344+59	155.25									188.3						82.8	
STA. 348+68 TO 349+82.27	114.27									167.6						50.4	
STA. 344+59 TO 346+74.50	215.5								278.9							64.3	
STA. 347+97.50 TO 348+68	70.5								91.2							21.1	
SUB-TOTAL WOLF CREEK	212.4		187.1				264.7			310.5		37.6		71.1		78.5	
SUB-TOTAL DIXON CREEK		208	426.7		238.0	858.45		370.1		355.9		52.4		85.4		133.2	
TOTAL	420	427	1,284				1,301					458					

LOCATION	EACH	TYPE B INLET BOX, STANDARD 609006		PIPE DRAINS 12"	END SECTIONS 12"	STONE RIPRAP, CLASS A3
		OFFSET TO FACE OF CURB	ELEVATION AT TOP OF GRATE			
		FOOT	FOOT	FOOT	EACH	SQ YDS
WOLF CREEK - IL RTE. 94/116						
STA. 215+98.47 LT	1	16	621.66	37	1	1 @ 4 = 4
STA. 216+00.47 RT	1	16	621.67	37	1	1 @ 4 = 4
WOLF CREEK - TOTAL	2			74	2	8
DIXON CREEK - IL RTE. 94						
STA. 346+90.50 LT & RT	2	16	617.77	69	2	2 @ 4 = 8
STA. 347+81.50 LT & RT	2	16	617.32	64	2	2 @ 4 = 8
DIXON CREEK - TOTAL	4			133	4	16
TOTAL	6			207	6	24