

GUARDRAIL SCHEDULE							
LOCATION	GUARD-RAIL REM	TBT TYPE 6	TBT TY I SPECIAL FLARED	TBT TY I SPECIAL TANGENT	BARRIER WALL MARK	GUARD-RAIL MARK	TERMINAL MARK DIR APPLIED
	FOOT	EACH	EACH	EACH	EACH	EACH	EACH
NW QUAD	117	1	1		2	1	1
SW QUAD	154	1	1		2	1	1
NE QUAD	191	1		1	2	1	1
SE QUAD	116	1	1		2	1	1
TOTAL	578	4	3	1	8	4	4

EARTHWORK SCHEDULE				
LOCATION	EARTH EXCAVATION (CUT)	EARTHWORK ADJUSTED FOR SHRINKAGE	FILL	FURNISHED EXCAVATION
	CU YD			CU YD
DITCH WORK	322.7	242	1228.2	986.2
TOTAL	322.7			986.2

ASSUME SHRINKAGE FACTOR - 25% EARTH EXCAVATION PAY ITEMS

PAVEMENT MARKING														
LOCATION	DESCRIPTION	LENGTH	PAINT PAVEMENT MARKING LINE			TEMPORARY PAVEMENT MARKING LINE			SHORT TERM PVMT MARK	WORK ZONE PVMT MARK REMOVAL	PAVEMENT MARKING REMOVAL	RAISED REFL PVMT MARKER REMOVAL	RAISED REFL PVMT MARKER	
			4 INCH		6 INCH	4 INCH		6 INCH						
			YELLOW	WHITE	YELLOW	YELLOW	WHITE	YELLOW						
STA		FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	SQ FT	SQ FT	EACH	EACH	
964+35 TO 967+60	CENTER AND EDGE LINES	325		1300	162			650	81	98	268		4	4
967+60 TO 970+24	CENTER AND EDGE LINES	264		1056	132			528	66	79	218		3	3
964+35 TO 966+50	WB NO PASSING LINE	215	430				215				72			
STAGE CONSTRUCTION		532									324			
TOTALS			430	2356	294	215	1178	147	177	558	324	7	7	
				2786	294		1393	147	177	558	324	7	7	

NOTE: ADDITIONAL QUANTITY HAS BEEN INCLUDED TO ALLOW FOR TWO SEPARATE APPLICATIONS OF PAINT PAVEMENT MARKING LINE
NO PASSING ZONES SHALL BE REPLACED IN THE SAME LOCATIONS AS EXISTING

STAGING SCHEDULE					
LOCATION	TEMP CONC BARRIER	RELOCATE TEMP CONC BARRIER	IMPACT ATTENUATORS TEMP, NON-REDIRECTIVE TEST LEVEL 3	IMPACT ATTENUATORS RELOCATE, NON-REDIRECTIVE TEST LEVEL 3	TEMP RAMP
	FOOT	FOOT	EACH	EACH	SQ YD
STAGE I	532.0		2.0		213
STAGE II		498.0		2.0	
TOTAL	532	498	2	2	213

DRAINAGE SCHEDULE						
LOCATION	STATION	OFFSET	PIPE CULV CL D, TY 2	END SECT	PROP U.S. INVERT ELEV	PROP D.S. INVERT ELEV
			18"	18"		
	964+89	31' RT	62	1	663.41	
	965+49	46' RT		1		659.00
TOTAL			62	2		

ENTRANCE SCHEDULE						
STATION	SIDE		EXIST MAT	WIDTH	AREA	AGG SURF CSE TY B
				FOOT	SQ YD	TON
965+14	RT	PE	AGG/DIRT	12	109	1
SUBTOTAL						1

STORM SEWER EXPLORATION		
LOCATION	EXPLORATION TRENCH, SPECIAL	END SECTIONS 24" (SPECIAL)
	FOOT	EACH
SOUTHEAST QUADRANT	200	1
TOTAL	200	1

NOTE: THE END SECTION SHALL BE INSTALLED AT THE POINT WHERE THE EXISTING FLOW LINE OF THE STORM SEWER MEETS THAT OF THE PROPOSED DITCH.