

BEAM #4

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	29428.83	2.13	645.52	645.52
CL Brg. N. Abut.	29432.08	2.13	645.56	645.56
A	29442.07	2.13	645.66	645.68
B	29452.06	2.13	645.76	645.78
C	29462.05	2.13	645.85	645.87
D	29472.05	2.13	645.93	645.94
E	29482.04	2.13	646.00	646.00
F	29492.03	2.13	646.06	646.06
G	29502.02	2.13	646.11	646.10
CL Pier 1	29511.56	2.13	646.15	646.15
H	29521.55	2.13	646.19	646.21
I	29531.54	2.13	646.22	646.27
J	29541.54	2.13	646.23	646.33
K	29551.53	2.13	646.24	646.37
L	29561.52	2.13	646.25	646.40
M	29571.51	2.13	646.24	646.40
N	29581.50	2.13	646.22	646.38
O	29591.50	2.13	646.19	646.33
P	29601.49	2.13	646.15	646.25
Q	29611.48	2.13	646.10	646.17
R	29621.47	2.13	646.04	646.08
CL Pier 2	29635.00	2.13	645.95	645.95
S	29645.00	2.13	645.87	645.87
T	29655.00	2.13	645.78	645.79
U	29665.00	2.13	645.69	645.70
V	29675.00	2.13	645.58	645.61
W	29685.00	2.13	645.47	645.50
X	29695.00	2.13	645.35	645.38
Y	29705.00	2.13	645.22	645.24
CL N. Brg. Pier 3	29717.24	2.13	645.05	645.05
CL Pier 3	29718.32	2.13	645.03	645.03

BEAM #5

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	29428.83	8.38	645.79	645.79
CL Brg. N. Abut.	29432.07	8.38	645.82	645.82
A	29442.04	8.38	645.93	645.94
B	29452.01	8.38	646.02	646.05
C	29461.98	8.38	646.11	646.13
D	29471.94	8.38	646.19	646.21
E	29481.91	8.38	646.26	646.26
F	29491.88	8.38	646.32	646.32
G	29501.85	8.38	646.37	646.37
CL Pier 1	29511.56	8.38	646.41	646.41
H	29521.53	8.38	646.45	646.48
I	29531.50	8.38	646.48	646.54
J	29541.47	8.38	646.50	646.59
K	29551.43	8.38	646.51	646.64
L	29561.40	8.38	646.51	646.66
M	29571.37	8.38	646.50	646.67
N	29581.34	8.38	646.49	646.64
O	29591.31	8.38	646.43	646.57
P	29601.28	8.38	646.37	646.47
Q	29611.24	8.38	646.30	646.36
R	29621.22	8.38	646.21	646.25
CL Pier 2	29635.00	8.38	646.09	646.09
S	29645.00	8.38	645.98	645.98
T	29655.00	8.38	645.87	645.87
U	29665.00	8.38	645.75	645.76
V	29675.00	8.38	645.63	645.65
W	29685.00	8.38	645.49	645.52
X	29695.00	8.38	645.34	645.38
Y	29705.00	8.38	645.19	645.21
CL N. Brg. Pier 3	29717.24	8.38	644.99	644.99
CL Pier 3	29718.32	8.38	644.97	644.97

BEAM #6

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	29428.83	14.63	646.05	646.05
CL Brg. N. Abut.	29432.06	14.63	646.08	646.08
A	29442.01	14.63	646.19	646.20
B	29451.95	14.63	646.28	646.31
C	29461.90	14.63	646.37	646.40
D	29471.84	14.63	646.45	646.47
E	29481.79	14.63	646.52	646.53
F	29491.73	14.63	646.58	646.58
G	29501.68	14.63	646.63	646.63
CL Pier 1	29511.56	14.63	646.68	646.68
H	29521.50	14.63	646.71	646.74
I	29531.45	14.63	646.74	646.80
J	29541.39	14.63	646.76	646.85
K	29551.34	14.63	646.77	646.90
L	29561.28	14.63	646.77	646.93
M	29571.23	14.63	646.76	646.93
N	29581.17	14.63	646.75	646.91
O	29591.12	14.63	646.67	646.82
P	29601.06	14.63	646.59	646.70
Q	29611.01	14.63	646.49	646.56
R	29620.97	14.63	646.39	646.42
CL Pier 2	29635.00	14.63	646.22	646.22
S	29645.00	14.63	646.10	646.09
T	29655.00	14.63	645.96	645.96
U	29665.00	14.63	645.82	645.83
V	29675.00	14.63	645.67	645.69
W	29685.00	14.63	645.51	645.53
X	29695.00	14.63	645.33	645.36
Y	29705.00	14.63	645.15	645.17
CL N. Brg. Pier 3	29717.24	14.63	644.92	644.92
CL Pier 3	29718.32	14.63	644.89	644.89