

# SCHEDULE OF QUANTITIES

## EROSION CONTROL (SHEET 1 OF 3)

| DIRECTION   | STATION       | TO | STATION     | OFFSET       | TEMPORARY<br>DITCH CHECKS<br>28000305<br>(FOOT) | PERIMETER<br>EROSION BARRIER<br>28000400<br>(FOOT) | INLET & PIPE<br>PROTECTION<br>28000500<br>(EACH) | STONE RIPRAP<br>CLASS A 4<br>28100107<br>(SQ YD) | FILTER<br>FABRIC<br>28200200<br>(SQ YD) | STONE RIPRAP<br>CLASS A4<br>(TONS) | BEDDING<br>STONE<br>(TONS) |
|-------------|---------------|----|-------------|--------------|---|--|--|--|---|------------------------------------|----------------------------|
| LEG "A":    |               |    |             |              |   |  |  |  |   |                                    |                            |
| EB          | 33+30         |    |             | 1.75' RL     | 17.0  |  |  |  |   |                                    |                            |
| EB          | 31+00         |    |             | CL           | 10.0  |  |  |  |   |                                    |                            |
| EB          | 30+50         |    |             | 0.5' LT      | 15.0  |  |  |  |   |                                    |                            |
| EB          | 29+50         |    |             | 0.5' LT      | 15.0  |  |  |  |   |                                    |                            |
| EB          | 29+00         |    |             | CL           | 15.0  |  |  |  |   |                                    |                            |
| WB          | 32+50         |    |             | 1.0' RT      | 12.0  |  |  |  |   |                                    |                            |
| WB          | 31+50         |    |             | 1.0' RT      | 10.0  |  |  |  |   |                                    |                            |
| WB          | 28+50         |    |             | 1.0' RT      | 15.0  |  |  |  |   |                                    |                            |
| WB          | 28+00         |    |             | 3.0' RT      | 15.0  |  |  |  |   |                                    |                            |
| EB          | 28+00         |    | 26+00       | 65.0' LT     |   | 194.3  |  |  |   |                                    |                            |
| WB          | 27+50         |    |             | 2.5' RT      | 12.0  |  |  |  |   |                                    |                            |
| WB          | 27+00         |    |             | 3.0' RT      | 12.0  |  |  |  |   |                                    |                            |
| WB          | 26+00         |    |             | 4.5' RT      | 10.0  |  |  |  |   |                                    |                            |
| EB          | 26+00         |    | 25+00       | 65'-71' LT   |   | 97.2   |  |  |   |                                    |                            |
| EB          | 25+00         |    | 23+19       | 71'-68' LT   |   | 175.5  |  |  |   |                                    |                            |
| WB          | 25+00         |    |             | 6.0' RT      | 6.0   |  |  |  |   |                                    |                            |
| EB          | 23+19         |    | 23+00       | 68'-75' LT   |   | 19.7   |  |  |   |                                    |                            |
| WB          | 23+19         |    |             | 5.0' RT      |   |  | 1.0  |  |   |                                    |                            |
| EB          | 23+00         |    | 20+73       | 75'-68' LT   |   | 220.6  |  |  |   |                                    |                            |
| EB          | 19+06.39      |    |             | 3.44' LT     |   |  | 1.0  |  |   |                                    |                            |
| WB          | 23+00         |    | 21+50       | 62.0' RT     |   | 154.0  |  |  |   |                                    |                            |
| WB          | 21+50         |    | 21+05.5     | 62'-58' RT   |   | 45.9   |  |  |   |                                    |                            |
| WB          | 18+95         |    | 18+75.00 BK | 68'-70' RT   |   | 21.1   |  |  |   |                                    |                            |
| WB          | 335+55.87 AH. |    | 337+00      | 70.0' LT     |   | 144.1  |  |  |   |                                    |                            |
| EB          | 335+83        |    | 337+00      | 58.5'-60' RT |   | 116.5  |  |  |   |                                    |                            |
| EB          | 337+00        |    | 356+00      | 60.0' RT     |   | 1900.0   |  |  |   |                                    |                            |
| WB          | 337+00        |    | 338+50      | 70'-72' LT   |   | 150.0  |  |  |   |                                    |                            |
| EB          | 337+75        |    |             | 4.0' RT      |   |  | 1.0  |  |   |                                    |                            |
| WB          | 338+50        |    | 339+50      | 72.0' LT     |   | 100.0  |  |  |   |                                    |                            |
| EB          | 339+00        |    |             | 3.0' RT      |   |  | 1.0  |  |   |                                    |                            |
| WB          | 339+50        |    | 341+50      | 72'-62' LT   |   | 200.2  |  |  |   |                                    |                            |
| EB          | 339+50        |    |             | 5.0' RT      |   |  | 1.0  |  |   |                                    |                            |
| WB          | 341+50        |    | 343+00      | 62'-60' LT   |   | 150.0  |  |  |   |                                    |                            |
| EB          | 342+50        |    |             | CL           | 15.0  |  |  |  |   |                                    |                            |
| WB          | 343+00        |    | 366+00      | 60.0' LT     |   | 2310.2   |  |  |   |                                    |                            |
| EB          | 345+50        |    |             | 0.5' RT      | 15.0  |  |  |  |   |                                    |                            |
| EB          | 347+00        |    |             | 0.5' RT      | 15.0  |  |  |  |   |                                    |                            |
| EB          | 348+00        |    |             | CL           | 15.0  |  |  |  |   |                                    |                            |
| EB          | 349+00        |    |             | CL           | 15.0  |  |  |  |   |                                    |                            |
| EB          | 349+75        |    |             | CL           | 15.0  |  |  |  |   |                                    |                            |
| WB          | 350+00        |    |             | 6.0' LT      |   |  | 1.0  |  |   |                                    |                            |
| EB          | 351+00        |    |             | 1.0' RT      | 15.0  |  |  |  |   |                                    |                            |
| EB          | 351+50        |    |             | 0.75' RT     | 15.0  |  |  |  |   |                                    |                            |
| WB          | 352+50        |    |             | 4.0' LT      | 10.0  |  |  |  |   |                                    |                            |
| WB          | 353+10        |    |             | 4.0' LT      | 10.0  |  |  |  |   |                                    |                            |
| WB          | 353+62        |    |             | 1.0' LT      |   |  | 1.0  |  |   |                                    |                            |
| WB          | 353+68        |    |             | 1.0' LT      |   |  | 1.0  |  |   |                                    |                            |
| WB          | 354+50        |    |             | 0.5' LT      | 15.0  |  |  |  |   |                                    |                            |
| WB          | 355+50        |    |             | 1.0' LT      | 15.0  |  |  |  |   |                                    |                            |
| WB          | 356+50        |    |             | 3.5' LT      | 10.0  |  |  |  |   |                                    |                            |
| WB          | 357+00        |    |             | 8.0' LT      |   |  | 1.0  |  |   |                                    |                            |
| EB          | 357+00        |    |             | 64' RT       | 12.0  |  |  |  |   |                                    |                            |
| WB          | 357+50        |    |             | 4.0' LT      | 10.0  |  |  |  |   |                                    |                            |
| EB          | 358+00        |    |             | 63.0' RT     | 6.0   |  |  |  |   |                                    |                            |
| WB          | 358+50        |    |             | 4.0' LT      | 10.0  |  |  |  |   |                                    |                            |
| EB          | 359+00        |    |             | 59.0' RT     | 8.0   |  |  |  |   |                                    |                            |
| WB          | 359+50        |    |             | 0.5' LT      | 15.0  |  |  |  |   |                                    |                            |
| EB          | 360+00        |    |             | 58.0' RT     | 8.0   |  |  |  |   |                                    |                            |
| EB          | 360+50        |    |             | CL           | 15.0  |  |  |  |   |                                    |                            |
| EB          | 361+00        |    |             | 59.0' RT     | 6.0   |  |  |  |   |                                    |                            |
| EB          | 361+50        |    |             | CL           | 15.0  |  |  |  |   |                                    |                            |
| EB          | 362+00        |    |             | 61.0' RT     | 4.0   |  |  |  |   |                                    |                            |
| EB          | 362+50        |    |             | 1.0' RT      | 15.0  |  |  |  |   |                                    |                            |
| EB          | 362+75        |    |             | 63.0' RT     | 4.0   |  |  |  |   |                                    |                            |
| EB          | 363+25        |    |             | 64.0' RT     | 6.0   |  |  |  |   |                                    |                            |
| EB          | 363+75        |    |             | 65.0' RT     | 6.0   |  |  |  |   |                                    |                            |
| EB          | 364+25        |    |             | 67.0' RT     | 6.0   |  |  |  |   |                                    |                            |
| EB          | 364+75        |    |             | 70.0' RT     | 8.0   |  |  |  |   |                                    |                            |
| EB          | 365+25        |    |             | 72.0' RT     | 8.0   |  |  |  |   |                                    |                            |
| EB          | 365+58        |    |             | 72.0' RT     | 8.0   |  |  |  |   |                                    |                            |
| WB          | 366+00        |    | 366+22      | 60'-53.5' LT |   | 23.5   |  |  |   |                                    |                            |
| WB          | 366+12.5      |    |             | CL           |   |  | 1.0  |  |   |                                    |                            |
| SUB-TOTAL = |               |    |             |              | 514.0   | 6022.8   | 10.0   | 0  | 0                                       | 0                                  | 0                          |