


EXIST. CURVE 211
 PI STA. = 412+48.20
 Δ = 46° 11' 37" (RT)
 D = 6° 34' 38"
 R = 871.11'
 T = 371.50'
 L = 702.31'
 E = 75.91'
 e = 8.0%
 T.R. = N/A
 S.E. RUN = N/A
 P.C. STA. = 408+76.70
 P.T. STA. = 415+79.01

EXIST. CURVE 210
 PI STA. = 404+54.17
 Δ = 24° 23' 46" (LT)
 D = 7° 23' 35"
 R = 774.99'
 T = 167.53'
 L = 329.98'
 E = 17.90'
 e = 8.0%
 T.R. = N/A
 S.E. RUN = N/A
 P.C. STA. = 402+86.64
 P.T. STA. = 406+16.62

PAVEMENT MARKING LEGEND

- ① PR PREFORMED PLASTIC PAVEMENT MARKING, TYPE B (INLAID), LINE 5" (30' SKIP, 10' DASH, SOLID WHITE)
- ② PR MODIFIED URETHANE PAVEMENT MARKING, LINE 5" (SOLID YELLOW)
- ③ PR MODIFIED URETHANE PAVEMENT MARKING, LINE 5" (SOLID WHITE)
- ④ PR MODIFIED URETHANE PAVEMENT MARKING, LINE 6" (SOLID WHITE)
- ⑤ PR MODIFIED URETHANE PAVEMENT MARKING, LINE 5" (6' SKIP, 2' DASH)
- ⑥ PR MODIFIED URETHANE PAVEMENT MARKING, LINE 8" (SOLID WHITE)
- ⑦ PR MODIFIED URETHANE PAVEMENT MARKING, LINE 12" (SOLID WHITE)
- ⑧ PR PREFORMED PLASTIC PAVEMENT MARKING, TYPE B (INLAID), LINE 24" (SOLID WHITE)
- ⑨ PR PREFORMED PLASTIC PAVEMENT MARKING, TYPE B (INLAID), LETTERS & SYMBOLS (SOLID WHITE)
- ⑩ PR GROOVING FOR RECESSED PAVEMENT MARKING 6"
- ◁ PR RAISED REFLECTIVE PAVEMENT MARKER, WHITE (SEE STANDARD 781001-03)
- ◀ PR RAISED REFLECTIVE PAVEMENT MARKER, AMBER (SEE STANDARD 781001-03)
- I- PR DELINEATOR, TWO REFLECTORS (SEE STANDARD 635001-01)
- ├ PR DELINEATOR, SINGLE REFLECTOR (SEE STANDARD 635001-01)



design firm no. 184001036 	USER NAME = gjameson FILE NAME = D672854.pln sht 59.dgn PLOT SCALE = 100.0000 "/>	DESIGNED - CHECKED - DRAWN - CHECKED -	REVISED REVISED REVISED REVISED	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	PLAN SHEET	F.A.I. RTE. = 72 SECTION = * COUNTY = SANGAMON TOTAL SHEETS = 163 SHEET NO. = 89	CONTRACT NO. 72B54 ILLINOIS FED. AID PROJECT
	PLOT DATE = 8/25/2014	SCALE: 1" = 50' SHEET NO. 59 OF 62 SHEETS STA. 400+56.00 TO STA. 410+00.00					