

FILE NAME =	USER NAME = sparksgw	DESIGNED -	REVISED -				TVF	PICAL SECTIONS		F.A.P.	SECTION	COUNTY	TOTAL SHEET
c:\pw_work\pwidot\sparksgw\d0313568\D67;	F71-sht-typical.dgn	DRAWN -	REVISED -	STATE OF ILLINOIS	FAP 34 (IL 97)		34	(2)RS-4,(3)RS-5	MENARD	45 15			
	PLOT SCALE = 6.0000 1/ in.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION	SCALE: SHEET OF SHEETS STA. TO STA.				ILLINOIS FED. AID PROJECT				
Default	PLOT DATE = Jun-06-2014 02:14:09PM	DATE -	REVISED -										

LEGEND

(1)	EX 9-7-9 PCC PAVEMENT
(2)	EX HMA BASE COURSE WIDENING
3	EX HMA SURFACE
(4)	EX METAL JOINT WITH $\frac{1}{2}^{\prime\prime}$ DIA BAR
5	EX HMA SHOULDER
6	EX CONCRETE GUTTER
$\overline{7}$	EX PIPE UNDERDRAIN
8	EX HMA 1' SAFETY SHOULDER
\frown	
(9)	PR HMA SURFACE REMOVAL
	(VARIABLE DEPTH)
(10)	PR HMA SURFACE REMOVAL
	2 1/4"
(11)	PR LEVELING BINDER COURSE
0	(MACHINE METHOD) - ¾''
(12)	PR HMA SURFACE COURSE, $1^{1}/_{2}^{\prime\prime}$
(13)	PR HMA SHOULDER, 6″
(14)	PR AGGREGATE WEDGE SHOULDERS TYPE
(15)	PR PAVEMENT MARKING - LINE 5"
(16)	PR HMA SHOULDER, (2 1/4'')

В

NOTE:

1. WHEN THE SUPERELEVATION RATE OF PAVEMENT IS BETWEEN 0.0% AND 4.0%, THE SHOULDER SLOPE SHALL BE SLOPED AT 4.0%. WHEN THE SUPER ELEVATION RATE OF PAVEMENT EXCEEDS 4.0%, THE SHOULDER SHALL BE SLOPED SO THAT THE ALGEBRAIC DIFFERENCE BETEWEN THE PAVEMENT AND SHOULDER IS 8.0%.

2. OUTSIDE AGGREGATE SHOULDER THICKNESS HAS BEEN INCREASED FROM PAST DISTRICT 6 DESIGNS OF 1". THIS ADDITIONAL THICKNESS IS TO PROVIDE D6 OPERATIONS ADDITIONAL MATERIAL TO PULL UP FOR MAINTENANCE PURPOSES.

3. WHERE THE EARTH SHOULDER IS NOT WIDE ENOUGH FOR A 4' AGGREGATE SHOULDER, MATCH THE EARTH SHOULDER WIDTH.