

SECTION A-A (NOT MODIFIED-SHOWN AS SOLID LINES IN THE PLAN VIEW.) SECTION A-A (MODIFIED FOR DRAINAGE STRUCTURE-SHOWN AS DASHED LINE IN THE PLAN VIEW.)

GENERAL NOTES

- 1. ALL 1:10 SLOPES SHOWN ON THIS DETAIL SHALL BE CONSTRUCTED 1:10 OR FLATTER.
- 2. ANY EXISTING DRAINAGE STRUCTURES LOCATED WITHIN THE 80' (24.4m) WORKING AREA SHALL BE MODIFIED OR LEFT IN PLACE AS SHOWN ON THE PLANS. WHERE THE EXISTING DRAINAGE STRUCTURES ARE TO REMAIN IN PLACE, THE SLOPES ARE TO BE CONSTRUCTED AS SHOWN AS MODIFIED SLOPES ON THIS DETAIL AND AS DIRECTED BY THE ENGINEER.
- 3. THE SLOPES AS SHOWN ON THIS DETAIL SHALL APPLY TO BOTH ENDS OF THE BRIDGE PIERS.
- 4. ATTENUATOR BASE AND BARREL ARRAY SHALL BE INSTALLED IN ACCORDANCE WITH STATE STANDARD 643001 AND MANUFACTURER'S SPECIFICATIONS.

All slope ratios are expressed as units of vertical displacement to units of horizontal displacement (V:H) $\,$

All dimensions are in inches (millimeters) unless otherwise noted.

01-01-9	RENUM. F-3.02a, NEW REVISION BOX, REVISED	T.P.	03-15-12 REMOVED BARRELS	R.D.				RTF.	SECTION COUN	ITY TOTAL SHEET
	TITLE BOX, REVISED NOTES		08-25-15 REVISED BASE DIMENSIONS	R.D	STATE OF ILLINOIS	MEDIAN SAND MODULE IMPACT ATTENUATOR				SHEETS HO
08-02	REVISED	M.A.			DEPARTMENT OF TRANSPORTATION			•	CONT	RACT NO.
10-16-0	REVISED TO 2007 SPEC.	M.A.				NOT TO SCALE CADD STD. 65	0001-D4	ED. ROAD DIST. N	NO. ILLINOIS FED. AID PROJEC	Т