

CURB AND GUTTER SCHEDULE

LOCATION	LENGTH	COMBINATION CONCRETE CURB & GUTTER			CONCRETE MEDIAN SURFACE, 4"	STABILIZED SUB-BASE 4"	SUB-BASE GRANULAR MATERIAL, TYPE A 8"	PROTECTIVE COAT
		TYPE M-6.06 FOOT	TYPE M-6.24 FOOT	TYPE B-6.12 FOOT				
INTERSECTIONS								
TERMINAL DRIVE								
660+27.55 TO 660+77.52	49.97		69.6			28.4	28.4	22.2
661+40.94 TO 661+68.81	27.87		33.3			13.6	13.6	10.6
661+89.3				67.5		19.4	19.4	15.0
PENTECOST DRIVE								
681+11.64 TO 681+69.26	57.62			146.0		41.9	41.9	32.4
682+06.20 TO 682+66.61	60.41			98.6		28.3	28.3	21.9
REDCO DRIVE								
707+68.41 TO 708+36.59	68.18			112.0		32.1	32.1	24.9
708+92.59 TO 709+62.39	69.80			117.1		33.6	33.6	26.0
NW ISLAND								
		24.5	34.2		185	33.9	33.9	35.2
NE ISLAND								
		25.1	34.3		187	34.2	34.2	35.6
BAINBRIDGE TRAIL								
707+59.70 TO 708+31.25	71.55			103.6		29.7	29.7	23.0
709+13.12 TO 709+81.51	68.39			111.8		32.1	32.1	24.8
SW ISLAND								
		28.0	38.4		252	43.0	43.0	44.5
SE ISLAND								
		24.4	33.9		201	35.5	35.5	36.9
SUBTOTALS		102	244	757	825	406	406	353
MEDIAN								
656+65.44 TO 657+57.53	92.09	92.1	92.1		583	104.0	104.0	108.3
657+57.53 TO 660+63.47	305.94	611.9	611.9		2041	487.4	487.4	515.7
660+63.47 TO 660+99.01	35.54	35.5	35.5		83	24.3	24.3	26.0
660+99.01 TO 661+38.47	39.46	39.5	51.2		364	60.7	60.7	62.8
661+38.47 TO 661+96.16	57.69	57.7	57.7		134	39.5	39.5	42.2
661+96.16 TO 666+68.64	472.48	945.0	945.0		3151	752.6	752.6	796.4
666+68.64 TO 667+33.53	64.89	64.9	194.7		384	108.7	108.7	114.7
667+33.53 TO 675+51.95	818.42	1636.8	1636.8		2316	742.3	742.3	780.2
675+51.95 TO 676+16.80	64.85	64.9	194.6		384	108.7	108.7	114.7
676+16.80 TO 680+89.30	472.50	945.0	945.0		3152	752.7	752.7	796.4
680+89.30 TO 681+46.67	57.37	57.4	57.4		134	39.3	39.3	41.9
681+46.67 TO 681+87.30	40.63	40.6	50.6		381	62.6	62.6	64.7
681+87.30 TO 682+21.65	34.35	34.3	34.3		80	23.5	23.5	25.1
682+21.65 TO 685+27.59	305.94	611.9	611.9		2041	487.4	487.4	515.7
685+27.59 TO 686+19.59	92.00	92.0	92.0		583	103.9	103.9	108.2
SUBTOTALS		3693	5611	757	15810	3898	3898	4113
TOTALS		3795	5855	757	16635	4303	4303	4466

PERIMETER EROSION BARRIER AND INLET PROTECTION SCHEDULE

STATION TO STATION	INLET AND PIPE PROTECTION*	PERIMETER EROSION BARRIER
	EACH	FOOT
WESTBOUND		
638+37	1	
717+00 TO 725+00		800
725+00 TO 733+00		800
SUBTOTALS	1	1600
EASTBOUND		
645+85	1	
670+00 TO 674+00		400
676+90 TO 681+45		455
689+00	1	
725+00 TO 732+00		700
727+39	2	
731+06	1	
734+84	1	
SUBTOTALS	6	1555
TOTALS	7	3155

*SEE THE STORM SEWER SCHEDULE FOR ADDITIONAL QUANTITY.