



MATCHLINE STA. 18+00  
SEE SHEET NO. 6

MATCHLINE STA. 18+00  
SEE SHEET NO. 6

**NOTE:**  
 WORK ZONE SPEED LIMIT 45 MPH SIGNS REQUIRED WHEN WORKERS NOT PROTECTED BY CONCRETE BARRIER WALL  
 \* RESURFACE SHOULDER TO REMOVE RUMBLE STRIPS  
 ^ TRANSITION TAPER (SEE ROADWAY RESURFACING PLAN - SHEET 5)  
 ① BARRIER WALL/ GUARDRAIL MARKERS AT 25'. MARKERS ON RIGHT SHALL BE CRYSTAL AND MARKERS ON LEFT SHALL BE AMBER

- LEGEND:**
- ① TEMPORARY CONCRETE BARRIER
  - ☀ DIRECTION INDICATOR BARRICADE W/ STEADY BURN
  - ▲ MONO-DIRECTIONAL LIGHTS. USE TYPE II BARRICADES IN WEAVE PER TC-9
  - ☒ TYPE II BARRICADES INSTALLED & SPACED AS PER STANDARD 701411 & TC-9 W/ STEADY BURN MONO- DIRECTIONAL LIGHTS
  - ☒ TEMPORARY IMPACT ATTENUATOR
  - ▨ LATEX CONCRETE OVERLAY

FILE NAME =	USER NAME = midyja	DESIGNED -	REVISED -	<b>STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION</b>	<b>TRAFFIC STAGING PLAN</b>			F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
ct:\pw-work\PMIDOT\MDIYJA\0101558\design	.dgn	DRAWN -	REVISED -					80	99-1-B-1-2	WILL	21	5
	PLOT SCALE = 50.0000' / IN.	CHECKED -	REVISED -								CONTRACT NO. 60D66	
	PLOT DATE = 11/20/2008	DATE -	REVISED -								FED. ROAD DIST. NO. [ILLINOIS] FED. AID PROJECT	