


BORING LOGS



Illinois Department of Transportation
Division of Highways
Illinois Department of Transportation/D-2

SOIL BORING LOG

Page 1 of 1
Date 6/8/06

ROUTE FAP 599 DESCRIPTION P92-007-07 Box culvert on IL 92 over a ditch, .3 m. W. of 88th Street LOGGED BY W. Garza


SECTION (42 MFT) T-1 LOCATION Dixie Twp. - 26 NW, SEC. , TWP. 17N, RNG. 3W

COUNTY Rock Island DRILLING METHOD Hollow Stem Auger HAMMER TYPE B-53 Dierich Automatic

STRUCT. NO. Station	BORING NO. Station	Offset Ground Surface Elev.	D (ft)	B (/6")	U (tsf)	M (%)	Surface Water Elev.																																																																																																																																								
							ft	ft																																																																																																																																							
<u>081-1049</u> <u> </u>	<u>B-1</u> <u>13' E</u>	<u>13.00ft S CL</u> <u>99.60</u> ft						<u> </u> ft																																																																																																																																							
								<u>93.40</u> ft																																																																																																																																							
								Groundwater Elev.:																																																																																																																																							
								First Encounter <u>84.6</u> ft ▼																																																																																																																																							
								Upon Completion <u> </u> ft																																																																																																																																							
								After <u> </u> Hrs. <u> </u> ft																																																																																																																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Soil Description</th> <th>D (ft)</th> <th>B (/6")</th> <th>U (tsf)</th> <th>M (%)</th> </tr> </thead> <tbody> <tr> <td>MEDIUM brown SILTY CLAY LOAM</td> <td></td> <td></td> <td>0.5</td> <td>13.0</td> </tr> <tr> <td></td> <td></td> <td></td> <td>P</td> <td></td> </tr> <tr> <td>97.10</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>STIFF dark brown LOAM</td> <td>3</td> <td></td> <td></td> <td></td> </tr> <tr> <td>95.60</td> <td>5</td> <td>1.0</td> <td>24.0</td> <td></td> </tr> <tr> <td></td> <td></td> <td>B</td> <td></td> <td></td> </tr> <tr> <td>STIFF brown SILTY CLAY LOAM</td> <td>1</td> <td></td> <td></td> <td></td> </tr> <tr> <td>93.10</td> <td>3</td> <td>1.0</td> <td>22.0</td> <td></td> </tr> <tr> <td></td> <td></td> <td>B</td> <td></td> <td></td> </tr> <tr> <td>STIFF gray SILTY CLAY LOAM TILL</td> <td>1</td> <td></td> <td></td> <td></td> </tr> <tr> <td>90.60</td> <td>3</td> <td>1.6</td> <td>21.0</td> <td></td> </tr> <tr> <td></td> <td></td> <td>B</td> <td></td> <td></td> </tr> <tr> <td>VERY STIFF gray SILTY LOAM</td> <td>1</td> <td></td> <td></td> <td></td> </tr> <tr> <td>88.10</td> <td>4</td> <td>2.1</td> <td>31.0</td> <td></td> </tr> <tr> <td></td> <td></td> <td>B</td> <td></td> <td></td> </tr> <tr> <td>STIFF gray SILTY LOAM with SAND lens</td> <td>2</td> <td></td> <td></td> <td></td> </tr> <tr> <td>85.10</td> <td>7</td> <td>1.2</td> <td>23.0</td> <td></td> </tr> <tr> <td></td> <td></td> <td>B</td> <td></td> <td></td> </tr> <tr> <td>LOOSE gray clean medium SAND</td> <td>1</td> <td></td> <td></td> <td></td> </tr> <tr> <td>83.10</td> <td>7</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DENSE gray SHALE</td> <td>25</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>14</td> <td></td> <td></td> <td></td> </tr> <tr> <td>80.60</td> <td>21</td> <td></td> <td></td> <td></td> </tr> <tr> <td>End of Boring</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>									Soil Description	D (ft)	B (/6")	U (tsf)	M (%)	MEDIUM brown SILTY CLAY LOAM			0.5	13.0				P		97.10					STIFF dark brown LOAM	3				95.60	5	1.0	24.0				B			STIFF brown SILTY CLAY LOAM	1				93.10	3	1.0	22.0				B			STIFF gray SILTY CLAY LOAM TILL	1				90.60	3	1.6	21.0				B			VERY STIFF gray SILTY LOAM	1				88.10	4	2.1	31.0				B			STIFF gray SILTY LOAM with SAND lens	2				85.10	7	1.2	23.0				B			LOOSE gray clean medium SAND	1				83.10	7									DENSE gray SHALE	25					14				80.60	21				End of Boring									
Soil Description	D (ft)	B (/6")	U (tsf)	M (%)																																																																																																																																											
MEDIUM brown SILTY CLAY LOAM			0.5	13.0																																																																																																																																											
			P																																																																																																																																												
97.10																																																																																																																																															
STIFF dark brown LOAM	3																																																																																																																																														
95.60	5	1.0	24.0																																																																																																																																												
		B																																																																																																																																													
STIFF brown SILTY CLAY LOAM	1																																																																																																																																														
93.10	3	1.0	22.0																																																																																																																																												
		B																																																																																																																																													
STIFF gray SILTY CLAY LOAM TILL	1																																																																																																																																														
90.60	3	1.6	21.0																																																																																																																																												
		B																																																																																																																																													
VERY STIFF gray SILTY LOAM	1																																																																																																																																														
88.10	4	2.1	31.0																																																																																																																																												
		B																																																																																																																																													
STIFF gray SILTY LOAM with SAND lens	2																																																																																																																																														
85.10	7	1.2	23.0																																																																																																																																												
		B																																																																																																																																													
LOOSE gray clean medium SAND	1																																																																																																																																														
83.10	7																																																																																																																																														
DENSE gray SHALE	25																																																																																																																																														
	14																																																																																																																																														
80.60	21																																																																																																																																														
End of Boring																																																																																																																																															

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)



Illinois Department of Transportation
Division of Highways
Illinois Department of Transportation/D-2

SOIL BORING LOG

Page 1 of 1
Date 6/8/06

ROUTE FAP 599 DESCRIPTION P92-007-07 Box culvert on IL 92 over a ditch, .3 m. W. of 88th Street LOGGED BY W. Garza

SECTION (42 MFT) T-1 LOCATION Dixie Twp. - 26 NW, SEC. , TWP. 17N, RNG. 3W

COUNTY Rock Island DRILLING METHOD Hollow Stem Auger HAMMER TYPE B-53 Dierich Automatic

STRUCT. NO. Station	BORING NO. Station	Offset Ground Surface Elev.	D (ft)	B (/6")	U (tsf)	M (%)	Surface Water Elev.																																																																																																																																								
							ft	ft																																																																																																																																							
<u> </u> <u> </u>	<u>B-2</u> <u>22' W</u>	<u>16.00ft N CL</u> <u>99.20</u> ft						<u> </u> ft																																																																																																																																							
								<u>90.10</u> ft																																																																																																																																							
								Groundwater Elev.:																																																																																																																																							
								First Encounter <u>86.7</u> ft ▼																																																																																																																																							
								Upon Completion <u>Dry</u> ft																																																																																																																																							
								After <u> </u> Hrs. <u> </u> ft																																																																																																																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Soil Description</th> <th>D (ft)</th> <th>B (/6")</th> <th>U (tsf)</th> <th>M (%)</th> </tr> </thead> <tbody> <tr> <td>MEDIUM brown SILTY CLAY LOAM</td> <td></td> <td></td> <td>0.6</td> <td>19.0</td> </tr> <tr> <td></td> <td></td> <td></td> <td>P</td> <td></td> </tr> <tr> <td>96.70</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>VERY STIFF brown SILTY CLAY LOAM</td> <td>3</td> <td></td> <td></td> <td></td> </tr> <tr> <td>95.20</td> <td>5</td> <td>2.5</td> <td>24.0</td> <td></td> </tr> <tr> <td></td> <td></td> <td>B</td> <td></td> <td></td> </tr> <tr> <td>MEDIUM/STIFF gray SILTY LOAM with SAND lens</td> <td>2</td> <td></td> <td></td> <td></td> </tr> <tr> <td>92.70</td> <td>4</td> <td>1.0</td> <td>25.0</td> <td></td> </tr> <tr> <td></td> <td></td> <td>P</td> <td></td> <td></td> </tr> <tr> <td>SOFT gray SANDY LOAM</td> <td>1</td> <td></td> <td></td> <td></td> </tr> <tr> <td>90.20</td> <td>2</td> <td>0.3</td> <td>25.0</td> <td></td> </tr> <tr> <td></td> <td></td> <td>P</td> <td></td> <td></td> </tr> <tr> <td>MEDIUM gray SILTY LOAM with fine SAND lens</td> <td>1</td> <td></td> <td></td> <td></td> </tr> <tr> <td>87.20</td> <td>3</td> <td>0.5</td> <td>23.0</td> <td></td> </tr> <tr> <td></td> <td></td> <td>B</td> <td></td> <td></td> </tr> <tr> <td>LOOSE gray fine SAND</td> <td>2</td> <td></td> <td></td> <td></td> </tr> <tr> <td>85.20</td> <td>5</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>LOOSE gray medium SAND</td> <td>2</td> <td></td> <td></td> <td></td> </tr> <tr> <td>82.70</td> <td>5</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>VERY DENSE gray SHALE</td> <td>11</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>27</td> <td></td> <td></td> <td></td> </tr> <tr> <td>80.20</td> <td>63</td> <td></td> <td></td> <td></td> </tr> <tr> <td>End of Boring</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>									Soil Description	D (ft)	B (/6")	U (tsf)	M (%)	MEDIUM brown SILTY CLAY LOAM			0.6	19.0				P		96.70					VERY STIFF brown SILTY CLAY LOAM	3				95.20	5	2.5	24.0				B			MEDIUM/STIFF gray SILTY LOAM with SAND lens	2				92.70	4	1.0	25.0				P			SOFT gray SANDY LOAM	1				90.20	2	0.3	25.0				P			MEDIUM gray SILTY LOAM with fine SAND lens	1				87.20	3	0.5	23.0				B			LOOSE gray fine SAND	2				85.20	5									LOOSE gray medium SAND	2				82.70	5									VERY DENSE gray SHALE	11					27				80.20	63				End of Boring									
Soil Description	D (ft)	B (/6")	U (tsf)	M (%)																																																																																																																																											
MEDIUM brown SILTY CLAY LOAM			0.6	19.0																																																																																																																																											
			P																																																																																																																																												
96.70																																																																																																																																															
VERY STIFF brown SILTY CLAY LOAM	3																																																																																																																																														
95.20	5	2.5	24.0																																																																																																																																												
		B																																																																																																																																													
MEDIUM/STIFF gray SILTY LOAM with SAND lens	2																																																																																																																																														
92.70	4	1.0	25.0																																																																																																																																												
		P																																																																																																																																													
SOFT gray SANDY LOAM	1																																																																																																																																														
90.20	2	0.3	25.0																																																																																																																																												
		P																																																																																																																																													
MEDIUM gray SILTY LOAM with fine SAND lens	1																																																																																																																																														
87.20	3	0.5	23.0																																																																																																																																												
		B																																																																																																																																													
LOOSE gray fine SAND	2																																																																																																																																														
85.20	5																																																																																																																																														
LOOSE gray medium SAND	2																																																																																																																																														
82.70	5																																																																																																																																														
VERY DENSE gray SHALE	11																																																																																																																																														
	27																																																																																																																																														
80.20	63																																																																																																																																														
End of Boring																																																																																																																																															

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)