



Note: In lieu of the cast-in-place anchor device shown, the Contractor has the option of drilling and setting stainless steel anchor rods of the same diameter and grade as the specified cap screws according to Article 509.06 of the Standard Specifications. Embedment shall be according to the manufacturer's specifications.

FILE NAME =	USER NAME = teasleyck	DESIGNED - DFZ	REVISED -
c:\pwork\pwork\teasleyck\d0307638\07	4591-shr-brdetails-05800770078.dgn	DRAWN - DFZ	REVISED -
Default	PLOT SCALE = 40.0000' / in.	CHECKED - KLB	REVISED -
	PLOT DATE = 10/29/2012	DATE - 7/23/12	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

<b>HANDRAIL DETAILS</b>			
<b>SN. 058-0077 (EB) &amp; 058-0078 (WB)</b>			
SCALE:	SHEET 12 OF 15 SHEETS	STA.	TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
• 07 BRIDGE REPAIRS 2013-3		MACON	28	25
• FAI 72, FAU 7354			CONTRACT NO.	74591
ILLINOIS FED. AID PROJECT				