01-19-2024 LETTING ITEM 119

STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION


* TR 183A (1000TH AVENUE) ** D7 ENTRANCE CULVERT 2022-1

D-97-116-21

CRAWFORD LUNOIS CONTRACT NO. 74A85

PROPOSED HIGHWAY PLANS

TR 183A (1000TH AVE)
SECTION D7 ENTRANCE CULVERTS 2022-1 **CULVERT REPLACEMENTS CRAWFORD COUNTY**



STATE OF ILLINOIS SUBMITTED FERENCE March 24, 2023

LOCATION OF SECTION INDICATED THUS:-

PRINTED BY THE AUTHORITY

CONTRACT NO. 74A85

OF THE STATE OF ILLINOIS

C-97-185-21

0

0

PROJECT ENGINEER BRIAN LEWIS PROJECT MANAGER BENJAMIN J. DETERS

FOR INDEX OF SHEETS, SEE SHEET NO. 2

ADT = 450

GROSS LENGTH = 1930.00 FT. = 0.366 MILE NET LENGTH = 1930.00 FT. = 0.366 MILE

REV. - MS

INDEX OF SHEETS

SHEET NO.	DESCRIPTION
1	COVER SHEET
2	INDEX OF SHEETS / HIGHWAY STANDARDS / GENERAL NOTES
3	SUMMARY OF QUANTITIES
4	SCHEDULE OF QUANTITIES
5 - 6	PLAN SHEETS - E 1000TH AVE
7	CULVERT DETAILS
8 - 9	SINGLE CELL PRECAST BOX CULVERT TAPEREND END SECTION DETAILS
10	MEMBRANE WATERPROOFING SYSTEM / POROUS GRANULAR EMBANKEMENT DETAILS

HIGHWAY STANDARDS

STANDARD NO.	DESCRIPTION
000001 - 08	STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS
001001 - 02	AREAS OF REINFORCEMENT BARS
001006	DECIMAL OF AN INCH AND OF A FOOT
701201 - 05	LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS \geq 45 MPH
701901 - 09	TRAFFIC CONTROL DEVICES

DATE

PLOT DATE = 2/8/2023

GENERAL NOTES

THE WORK INCLUDED IN SECTION D7 ENTRANCE CULVERTS 2022-1 CONSISTS OF PIPE CULVERT AND HEADWALL REMOVAL ALONG WITH PRECAST CULVERT PLACEMENTS, RIPRAP, FURNISHED EXCAVATION, AGGREGATE SURFACE COURSE, AND ANY OTHER WORK NECESSARY TO COMPLETE THIS SECTION.

THE PROPOSED PROJECT BEGINS APPROXIMATELY 0.54 MILES AND ENDS APPROXIMATELY 0.32 MILES WEST OF N 1725TH ST. ON THE WEST END OF PALESTINE.

THE MATERIAL USED FOR AGGREGATE SURFACE COURSE, TYPE B SHALL BE CRUSHED STONE.

ANY EXISTING PRIVATELY OWNED LIGHTING WIRING OR CONDUIT DISCOVERED WITHIN THE EXISTING ENTRANCES DURING CULVERT REPLACEMENT OPERATIONS SHALL BE LOCATED AND REPAIRED BACK TO PROPER WORKING ORDER ONCE OPERATIONS FOR THAT PARTICULAR LOCATION HAVE BEEN COMPLETED.

AMEREN GAS LINES HAVE BEEN IDENTIFIED AT LOCATIONS 1 & 3 OF THIS SECTION. CARE SHALL BE TAKEN TO ENSURE THESE UTILITIES HAVE BEEN RELOCATED PRIOR TO WORK AT THESE LOCATIONS OR THAT A REPRESENTATIVE OF THESE UITILITIES HAS BEEN CONTACTED PRIOR TO THE START OF WORK TO ENSURE THESE ARE ADDRESSED APPROPRIATELY.

ANY ITEMS OR APPURTANCES EXISTING AROUND THE EXISTING STRUCTURES THAT ARE NO LONGER REQUIRED AFTER COMPLETION OF THE NEW CULVERTS SHALL BE THE PROPERTY OF THE OWNERS OF THE CORRESPONDING ENTRANCE.

THE FOLLOWING RATES OF APPLICATION HAVE BEEN USED IN THE CALCULATING PLAN QUANTITIES: AGGREGATE SHOULDERS & AGGREGATE SURFACE COURSE

USER NAME = Jessica.Hille DESIGNED REVISED **STATE OF ILLINOIS** DRAWN REVISED PLOT SCALE = 100.0000 / in. CHECKED REVISED **DEPARTMENT OF TRANSPORTATION**

REVISED

INDEX OF SHEETS, HIGHWAY STANDARDS, **AND GENERAL NOTES** OF SHEETS STA. SHEET

SCALE:

REV. - MS

	SUMMARY OF QUANTITIES			0004	RUCTION TYPE CODE	7	SUMMARY OF QUANTITIES		
CODE NO	ITEM	UNIT	TOTAL QUANTITIES	100% STATE		CODE NO	ITEM	UNIT	TOTAL QUANTITIES
									1
20400800	FURNISHED EXCAVATION	CU YD	792	792		70100450	TRAFFIC CONTROL AND PROTECTION, STANDARD	L SUM	1
20700110	POROUS GRANULAR EMBANKMENT	TON	231	231			701201		1
20700110	POROUS GRANULAR EMBANKMENT	TON	251	251		X6350108	FLEXIBLE DELINEATORS	EACH	20
28100107	STONE RIPRAP, CLASS A4	SQ YD	326	326					1
						X5810103	MEMBRANE WATERPROOFING SYSTEM FOR BURIED	SQ YD	166
28200200	FILTER FABRIC	SQ YD	326	326			STRUCTURES		
40200800	AGGREGATE SURFACE COURSE, TYPE B	TON	74	74		X2501000	SEEDING, CLASS 2 (SPECIAL)	ACRE	0.5
54001001	BOX CULVERT END SECTIONS, CULVERT NO. 1	EACH	2	2		X5015225	PIPE CULVERT REMOVAL (SPECIAL)	FOOT	98
54001001	BOX COLVERT END SECTIONS, COLVERT NO. 1	EACH	2	2		X3013223	PIPE COLVERT REMOVAL (SPECIAL)		1 90
54001002	BOX CULVERT END SECTIONS, CULVERT NO. 2	EACH	2	2					
54001003	BOX CULVERT END SECTIONS, CULVERT NO. 3	EACH	2	2					
									<u> </u>
54001004	BOX CULVERT END SECTIONS, CULVERT NO. 4	EACH	2	2					1
54001005	BOX CULVERT END SECTIONS, CULVERT NO. 5	EACH	2	2					
	BOX COLVERT END SECTIONS, COLVERT NO. 5	LACIT							
54011006	PRECAST CONCRETE BOX CULVERTS 10' X 6'	FOOT	48	48					
54011206	PRECAST CONCRETE BOX CULVERTS 12' X 6'	FOOT	116	116					
59100100	GEOCOMPOSITE WALL DRAIN	SQ YD	166	166					1
67100100	MOBILIZATION	L SUM	1	1					1
0/100100	PROBLEMION	L 30 M	"	1					1

REV. - MS

USER NAME = Jessica.Hille	DESIGNED -	REVISED -	
	DRAWN -	REVISED -	
PLOT SCALE = 100.0000 ' / in.	CHECKED -	REVISED -	
PLOT DATE = 2/8/2023	DATE -	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

	SUMMARY OF QUANTITIES							SEC	TION
								,	*
ļ							** TI	R 183A	
	SCALE:	SHEET	OF	SHEETS	STA.	TO STA.			ILLING

COUNTY TOTAL SHEET NO.

CRAWFORD 10 3 CONTRACT NO. 74A85

ILLINOIS FED. AID PROJECT

CONSTRUCTION TYPE CODE

100% STATE

1

20

166

0.5

98

USER NAME = SUSER\$	DESIGNED -	REVISED -	
	DRAWN -	REVISED -	
PLOT SCALE = SSCALES	CHECKED -	REVISED -	
PLOT DATE = SDATE\$	DATE -	REVISED -	
<u> </u>			1

SCHEDULES OF QUANTITIES SCALE: SHEET OF SHEETS STA.

COUNTY TOTAL SHEETS NO.

CRAWFORD 10 4 SECTION ** TR 183A CONTRACT NO. 74A85

STATE OF ILLINOIS
STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

	LOCATION 1	30.0	13.7	45.6	45.6				
	LOCATION 2	30.0	13.7	45.6	45.6				
	LOCATION 3	42.0	16.0	74.8	74.8				
*	LOCATION 4								
*	LOCATION 5								
TOTAL = 166.0 166.0									
	* - NOT REQUIRED, FILL HEIGHT GREATER THAN 3'								

WALL

DRAIN

(SQ YD)

GEOCOMPOSITE | MEMBRANE WATERPROOFING

SYSTEM FOR
BURIED STRUCTURES
(SQ YD)

	*	STONE	
	AREA PER	RIPRAP,	FILTER
	END SECTION	CLASS A4	FABRIC
	(SQ FT)	(SQ YD)	(SQ YD)
LOCATION 1	30.9	61.7	61.7
LOCATION 2	30.9	61.7	61.7
LOCATION 3	33.7	67.4	67.4
LOCATION 4	33.7	67.4	67.4
LOCATION 5	33.7	67.4	67.4
	TOTAL =	325.6	325.6
	ROUND TO:	326.0	326.0
* - MEASURED	IN CAD		

	AREA PER	RIPRAP,	FILTER
	END SECTION	CLASS A4	FABRIC
	(SQ FT)	(SQ YD)	(SQ YD)
LOCATION 1	30.9	61.7	61.7
LOCATION 2	30.9	61.7	61.7
LOCATION 3	33.7	67.4	67.4
LOCATION 4	33.7	67.4	67.4
LOCATION 5	33.7	67.4	67.4
•	TOTAL =	325.6	325.6
	ROUND TO:	326.0	326.0

PRECAST CONCRETE BOX CULVERTS, 10' x 6' (FOOT)

24.0

48.0

BOX CULVERT END

SECTIONS

(EACH)

2.0 2.0 2.0 2.0

2.0

FURNISHED

EXCAVATION

(CU YD)

56.9 79.1 179.7 205.3 270.4 791.4 792.0

LOCATION 1 LOCATION 2 LOCATION 3 LOCATION 4

LOCATION 5 TOTAL =

ROUND TO:

PRECAST CONCRETE BOX CULVERTS, 12' x 6' (FOOT)

SEEDING, CLASS 2 (SPECIAL)

(ACRE)

0.1 0.1 0.1 0.1 0.1 0.1 0.5

*	_	MEASI	IDED	IM	$C\Lambda\Gamma$

					AGGREGATE
	*				SURFACE COURSE,
	WIDTH	LENGTH	AREA	THICKNESS	TYPE B
	(FOOT)	(FOOT)	(SQ FT)	(FOOT)	(TON)
LOCATION 1	15.0	29.0	435	0.5	14.5
LOCATION 2	12.0	29.0	348	0.5	11.6
LOCATION 3	13.0	36.8	478.4	0.5	15.9
LOCATION 4	12.0	36.8	441.6	0.5	14.7
LOCATION 5	14.0	36.8	515.2	0.5	17.2
				TOTAL =	73.9
				BOLIND TO:	74.0


LENGTH


(F00T)

WIDTH

(FOOT)








USER NAME = SUSER\$	DESIGNED -	REVISED -	
	DRAWN -	REVISED -	
PLOT SCALE = SSCALES	CHECKED -	REVISED -	
PLOT DATE = SDATE\$	DATE -	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


SCALE:

	CHIVEDT DETAILS						SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CULVERT DETAILS						**	*	CRAWFORD	10	7
							R 183A	CONTRACT	NO. 74	4A85
	CHEET	OF	CHEETC	CTA	TO CTA			 		




Span Porous granular material

END VIEW



RESTRAINT ANGLE DETAIL



SECTION A-A

(All costs associated with furnishing and constructing the above drain detail will not be measured for payment but shall be included in the contract unit price for the associated work.)

(Sheet 1 of 2)

GENERAL NOTES

Box Culvert End Sections shall be constructed according to the requirements of Section 540 of the Standard Specifications except as modified herein. This work will be measured for payment as each, with each end of each culvert being one each. End sections will be paid for at the contract unit price per each for Box Culvert End Sections of the culvert number specified.

Typical box section dimensions, materials, and reinforcement details for Box Culvert End Sections shall be according to the requirements of ASTM C 1577 as required for

the design of the portion of the culvert within the limits of Precast Concrete Box Culverts except as modified herein.

Number of segments shown in Elevation is for example only. Length and number of precast box sections required to construct Box Culvert End Sections shall be determined by the Contractor.

See roadway plans for embankment slope (V:H).


I" Ø anchor rods for the culvert ties shall conform to the requirements of ASTM F1554, Grade 105. Structural steel for tie plate and restraint angle shall conform to the requirements of Article 1006.04 of the Standard Specifications. All components of the culvert tie detail shall be galvanized according to the requirements of AASHTO M 111 or M 232 as applicable. $2\frac{1}{4}$ " x $2\frac{1}{4}$ " x $2\frac{1}{4}$ " plate washers shall be provided under each nut required for the anchor rods. Anchor rods connecting precast sections shall be brought to a snug tight condition followed by an additional $\frac{1}{2}$ turn on one of the nuts for anchor rods installed in the walls. Match marks shall be provided on the bolt and nut to verify relative rotation between the bolt and the nut. Holes in the walls for the culvert tie assembly may be drilled using core bits in lieu of using formed holes.

All costs associated with furnishing and installing or constructing the toewall and culvert ties will not be measured for payment but shall be included in the contract unit price for Box Culvert End Sections of the culvert number specified.


Drain holes shall conform to the requirements of Article 503.11 of the Standard Specifications unless noted otherwise.

Nonwoven geotextile fabric shall conform to the requirements of Article 1080.01. The minimum weight of the fabric shall be $6\ \text{oz.}$ / sq. yd..

For end sections with traversable pipe grate systems, see grate detail sheet for required modifications.



<u>SECTION B-B</u> (Showing end section tie details)



TIE PLATE DETAIL

SCB-TES

PLAN

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SINGLE CELL PRECAST BOX CULVERT TAPERED END SECTIONS
STRUCTURE NO.


E: SHEET OF SHEETS STA. TO STA.

 F.A. RTE.
 SECTION
 COUNTY
 TOTAL SHEETS NO.

 *
 CRAWFORD
 10
 8


 ** TR 183A
 CONTRACT NO. 74A85

* D7 ENTRANCE CULVERTS 2022-1




(Design Earth Cover ≥ 2 ft) (Design Earth Cover < 2 ft)

SECTION C-C



SECTION D-D

ALTERNATE SECTION D-D



(As1m reinforcement based upon welded wire reinforcement conforming to AASHTO M 55 or M 221)

l, DIMENSION

#3 bar = 2'-0" #4 bar = 2'-8"

 $#5 \ bar = 3'-4''$ $#6 \ bar = 3'-11''$

 $2-#7 \ h \ bars (S < 8'-0")$


2-#8 h bars (5 ≥ 8'-0")

Top and bottom of headwall

Alternate Section D-D is provided to allow the Contractor the option of casting the bottom slab of the end section first followed by construction of the sidewalls using conventional forming methods Shop drawings that detail slab thickness and reinforcement layout shall be submitted to the Engineer for review and approval when using Alternate Section D-D.

The size and spacing of the v2 bars shall provide a minimum reinforcement area along each face of the walls (in.2/ft.) equal to 1.10*(As1m). v2 bars may consist of #3 thru #6 size reinforcement bars and the longitudinal spacing shall not exceed the lesser of the wall thickness or 8 inches.

Bonded construction joints shall be prepared according to Article 503.09 of the Standard Specifications.



#4 s bars at spacing = Tt (Spacing need not be less than 8") 4-h bars (See Section F-F) HEADWALL ELEVATION (Allow sidewall reinforcement to extend into end of headwall.)

TOEWALL CONSTRUCTION SEQUENCE

- 1. Perform excavation and construct toewall.
- 2. Backfill according to the applicable paragraphs of Article 502.10 of the Standard Specifications and place bedding for precast box culvert end sections.
- 3. Set precast box culvert end section.
- 4. Drill and epoxy grout reinforcement in toewall in accordance with Section 584 of the Standard Specifications.
- 5. Pressure grout voids using non-shrink grout conforming to Section 1024 of the Standard Specifications.
- The Contractor may furnish a precast or cast-in-place toewall. The Contractor shall be responsible for the strength and stability of the precast toewall during handling. Additional lifting points may be required depending upon the length of the toewall or the Contractor may need to modify the design of the toewall for the proposed handling the method.
- ** If soil conditions permit, the sides of the toewall may be poured directly against the soil. The clear cover on the sides of the toewall shall be increased to 3" by increasing the thickness of the toewall.

3" Ø corrugated PE pipe per Article 1040.04 of the Standard Specifications. Fill with non-shrink grout 6-#5 h1 bars placed as shown #4 v1 bars drilled and grouted into toewall in 9" min. deep holes at 1'-6" cts., max. #4 s1 bars at 1½" cI. 1'-0" cts., max. typ. 1'-0"

SECTION E-E

SCB-TES

2-17-2017

USER NAME = Jessica.Hille	DESIGNED -	REVISED -
	DRAWN -	REVISED -
PLOT SCALE = 100.0000 / in.	CHECKED -	REVISED -
PLOT DATE = 2/8/2023	DATE -	REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

		(She	et 2 of	2)								
IGLE CELL PRECAST BOX CULVERT TAPERED END SECTIONS						F.A. RTE	SEC ⁻	TION	COUNTY	TOTAL SHEETS	SHEET NO.	
STRUCTURE NO.						*×	*		CRAWFORD	10	9	
	STHOOTONE NO.						**	TR 183A		CONTRACT	NO. 7△	A85
	SHEET	OF	SHEETS	STA.		TO STA.	ILLINOIS FED. AID PROJECT					

* D7 ENTRANCE CULVERTS 2022-1


SECTION F-F

SCALE:

1'-0"

¾" "∆" Drip notch full length of span

MEMBRANE WATERPROOFING SYSTEM DETAILS




BOX CULVERT

Fill Height ≤ 3 ft.
For fill heights > 3 ft., omit Membrane
Waterproofing System for Buried Structures
and Geocomposite Wall Drain.

Geocomposite Wall Drain shall be according to Section 591 of the Standard Specifications, except that concrete nails shall not be used in areas where it overlaps Membrane Waterproofing System for Buried Structures.

POROUS GRANULAR EMBANKMENT DETAILS



POROUS GRANULAR EMBANKMENT SHALL EXTEND 2 FT. BEYOND THE LIMITS OF THE EXISTING AGGREGATE ENTRANCE.

THE WORK SHOWN IN THIS DETAIL SHALL BE PERFORMED IN ACCORDANCE WITH THE APPLICABLE PORTIONS OF ARTICLE 207 AND ARTICLE 540 OF THE STANDARD SPECIFICATIONS.

THIS WORK SHALL BE PAID FOR AT THE CONRACT UNIT PRICE PER CUBIC YARD OF POROUS GRANULAR EMBANKMENT.

THE AREA TO BE EXCAVATED FOR THE PROPOSED BOX CULVERT SHALL NOT BE MEASURED FOR PAYMENT. THE COST OF THE EXCAVATION SHALL BE INCLUDED IN THE COST OF PRECAST CONCRETE BOX CULVERTS AND PRECAST CONCRETE BOX CULVERT END SECTIONS.

DIMENSION:	Α	В	С	D
LOCATION 1:	10'	10"	11'-8"	9'-4"
LOCATION 2:	10 '	10"	11'-8"	9'-4"
LOCATION 3:	12'	12"	14'	10'-6"
LOCATION 4:	12'	12"	14'	10'-6"
LOCATION 5:	12'	12"	14'	10'-6"

LEGEND POROUS GRANULAR EMBANKMENT BOX CULVERT BEDDING (INCLUDED IN THE COST OF THE BOX CULVERT AND END SECTIONS)

SCALE:

BILL OF MATERIAL (5 CULVERTS)

ITEM	UNIT	TOTAL
Porous Granular Embankment	Ton	231.0
(Total All 5 Locations)		

USER NAME = Jessica.Hille	DESIGNED -	REVISED -
	DRAWN -	REVISED -
PLOT SCALE = 100.0000 / in.	CHECKED -	REVISED -
PLOT DATE = 3/9/2023	DATE -	REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

F		RANE WAT			
	SHEET	OF	SHEETS	STA.	TO STA.

F.A. RTE	SECTION			COUNTY	TOTAL SHEETS	SHEE NO.
**	*			CRAWFORD	10	10
**	TR 183A			CONTRACT	NO. 74	1A85
		TITIMOIS	EED A	ID PROJECT		