

PAVEMENT MARKING SCHEDULE						
STATION	TYPE	THERM PVT MK LINE 5"		PREF PLAS PVT MK	PREF PLAS PVT MK	PREF PLAS PVT MK
		WHITE	YELLOW	LET & SYM - WHITE	LINE 6" - WHITE	LINE 12" - WHITE
LT & RT 614+75 TO 636+84.59bk 636+86.67ah TO 646+01.90bk 46+19.90ah TO 60+20	EDGE LINE	9,050 FT				
LT & RT 614+75 TO 636+84.59bk 636+86.67ah TO 646+01.90bk 46+19.90ah TO 60+20	SKIP DASH		1,131 FT			
639+10	BIKE CROSSING				72 FT	81 FT
60+20 TO 61+65	TAPER 4 EA		580 FT			
61+65 TO 74+60.84	BI-DIR TURN LN ARROWS			219 SQ FT		
61+65 TO 74+60.84	BI-DIR TURN LN		2,994 FT			
DEDUCT FOR SIDEROADS		(267 FT)	(534 FT)			
TOTALS		8,783 FT	4,171 FT	219 SQ FT	72 FT	81 FT

NOTES:

1. STATIONS ARE APPROXIMATE.

MIXTURE REQUIREMENTS			
THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT			
MIXTURE USE(S):	B.C. S.C., SUPER, MIX D, N70	LEV. BIND. (M.M), SUPER, N70	BIT. SHOULDER, SUPER
AC/PG	PG 64-22	PG 64-22	PG 58-22
RAP %: (MAX)	10%	15%	15%
DESIGN AIR VOIDS:	4.0% @ N DESIGN = 70	4.0% @ N DESIGN = 70	2.0% @ N DESIGN = 30
MIXTURE COMP:	IL 9.5 OR 12.5	IL 9.5	B.A.M.
FRICTION AGG:	MIX "D"	N/A	N/A

SCHEDULES
FAP 315 (U.S. 136)
SECTION 28RS-6, 29RS-5
HANCOCK COUNTY