



NOTE:
The 1/8" TFE sheet shall be bonded directly to the top steel plate with a two-component, medium viscosity epoxy resin, conforming to the requirements of the Federal Specification MMM-A-134, Type I. The bond agent shall be applied on the full area of the contact surfaces.
Bonding of 1/8" TFE sheet during vulcanizing process will be permitted provided the process and method of adjusting assembly height is approved by the Engineer.

DESIGNED: [Signature]
CHECKED: [Signature]
DRAWN: [Signature]
CHECKED: [Signature]

BILL OF MATERIAL CONCRETE FLOOR ALTERNATE		
DESCRIPTION	UNIT	QUANTITY
Slip Stringer Span Removal and Replacement	Each	6
Elastomeric Bearing Assembly Type III	Each	24

BILL OF MATERIAL STEEL GRID FLOOR ALTERNATE		
DESCRIPTION	UNIT	QUANTITY
Slip Stringer Span Removal and Replacement	Each	6
Elastomeric Bearing Assembly Type III	Each	24

BRIDGE NO. 1
STRUCTURE 002-0005
FOR INFORMATION ONLY

SLIP STRINGER SPAN DETAILS
F.A.U.S. Rte. 9811 (U.S. 60 & 62)
S.B.I. 150 SECTION 138D-BR
ALEXANDER CO., IL. MISSISSIPPI CO., MO.
STATION 28+13.08