GENEAL NOTES

- 1. Reinforcement bars shall conform to the requirements of ASTM A 706 Gr. 60.
- 2. Reinforcement bars designated (E) shall be epoxy coated.
- 3. Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid
- 4. Layout of slope protection system may be varied to suit ground conditions in the field as directed by the Engineer.
- 5. The Contractor shall make allowance for the deflection of forms, shrinkage and settlement of falsework, in addition to allowance for dead load deflection. Forms for deck slab shall be removed prior to placement of bridge approach
- 6. Existing reinforcement shall be cleaned and incorporated into the new construction. Cost included with Concrete Removal.
- 7. Work in the waterway shall be timed to take place during low flow conditions.
- 8. Work may not be performed in the water except for the placement of the materials necessary for de-watering.

SUGGESTED SEQUENCE OF CONSTRUCTION

- 1. Install Temporary Soil Retention System at both abutments.
- 2. Excavate behind existing abutment to elevation for Stage I proposed abutment placement.
- 3. Install Stage I drilled shafts at both abutments.
- 4. Stage I partial removal of abutments. (See Sheet S-14)
- 5. Form and pour abutments and tie walls between existing and proposed abutments.


- 6. Stage I Removal of deck.
- 7. Place riprap between existing and proposed abutments proposed drainage.
- 8. Form and pour deck and approach slab.
- 9. Repeat, steps 2 8 for stage II.

INDEX OF SHEETS

- General Plan
- S-2 General Notes, Bill of Materials and Index of Sheets
- S-3 Stage Construction
- 5-4 Temporary Concrete Barrier for Stage Construction
- S-5 Top of Slab Elevations
- S-6 Top of South Approach Slab Elevations
- S-7' Top of North Approach Slab Elevations
- S-8 Superstructure Plan and Cross Section Concrete Bridge Railing Sidewalk Mounted 5-9
- S-10 Superstructure Details
- S-11 Bridge Approach Slab Details 1
- S-12 Bridge Approach Slab Details 2
- S-13 Abutment Details
- S-14 Abutment Removal
- S-15 Bar Splicer Assembly and Mechanical Splicer Details
- S-16 Soil Boring Log I
- S-17 Soil Boring Log II

STATION 36+54 BUILT 20__ BY STATE OF ILLINOIS F.A.U. RT. 2742 SEC. 3222-W-BR LOADING HS20-44 STR. NO. 016-2818

NAME PLATE



SECTION A-A

See sheet S-1 for section location Bedding and Filter Fabric included with cost of Gabions

Packfill with Paraus Cranular Embankment

abutment into the creek. Cost for coring through abutment

included in the Cost of Pipe Underdrains for Structures.

| posed abutments and | | Const. joint | Geocomposite wall drain | Backfill with Porous Granular Embankment (Special) by Bridge Contractor after superstructure is in place. |
|--|--|---|----------------------------|--|
| Excavation between pr abutment and existing paid for as Structure 16" thick Stone Riprap Class A4, typical between abutment and exist, ab | abutment is Excavation en prop. utment wall | 13 N:th) Rt 1/5 13 N:th) Rt 1/5 17-0" 1/-9" 1/-9" typ. 6" Bedding Filter Fabric Drilled Shaft | **4'' \$ Per pipe drain | Excavation for placing Porous Granular Embankment (Special) is paid for as Structure Excavation chnical Fabric for Darains age Aggregate |
| EXISI | . Abutment ——— | | | drainage system components shall extend to 2'-0" from |
| | | SECTION THRU A | | e end of each abutment. The pipes shall be sloped toward a center of the bridge and be outletted thru the existing |

(Horiz. dim. @ Rt. L's)

TOTAL BILL OF MATERIAL

| ITEM | UNIT | SUB | SUPER | TOTAL |
|--|-------|--------|--------|--------|
| Stone Riprap, Class A4 | Sq Yd | 289 | | 289 |
| Filter Fabric | Sq Yd | 289 | | 289 |
| Gabions | Cu Yd | 16 | | 16 |
| Removal Of Existing Superstructures | Each | | 1 | 1 |
| Concrete Removal | Cu Yd | 3.0 | | 3.0 |
| Structure Excavation | Cu Yd | 246 | | 246 |
| Concrete Structures | Cu Yd | 87.0 | | 87.0 |
| Rubbed Finish | Sq Ft | | 917 | 917 |
| Concrete Superstructure | Cu Yd | | 347.5 | 347.5 |
| Bridge Deck Grooving | Sq Yd | | 423 | 423 |
| Protective Coat | Sq Yd | | 695 | 695 |
| Reinforcement Bars | Pound | 10,040 | | 10,040 |
| Reinforcement Bars, Epoxy Coated | Pound | 13,830 | 83,950 | 97,780 |
| Bar Splicers | Each | 102 | 192 | 294 |
| Name Plates | Each | | 1 | 1 |
| Drilled Shaft In Soil | Cu Yd | 56.6 | | 56.6 |
| Geocomposite Wall Drain | Sq Yd | 44 | | 44 |
| Concrete Bridge Rail, Sidewalk Mounted | Foot | | 121 | 121 |
| Porous Granular Embankment, Special | Cu Yd | 86 | | 86 |
| Pipe Underdrains For Structures 4" | Foot | 136 | | 136 |
| Temporary Soil Retention System | Sq Ft | 152 | | 152 |

* Special Provision

| | USER NAME = rdanley | DESIGNED | BWS | REVISED | - | |
|----|----------------------------|----------|-----|---------|---|--|
| е. | | CHECKED | AMK | REVISED | _ | |
| | PLOT SCALE = 0:1 ':" / in. | DRAWN | RD | REVISED | | |
| | PLOT DATE = 10/25/2011 | CHECKED | DL | REVISED | • | |

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

COUNTY TOTAL SHEE NO. SECTION GENERAL NOTES, BILL OF MATERIAL AND INDEX OF SHEETS COOK 51 27 2742 3222-W-BR STRUCTURE NO. 016-2818 CONTRACT NO. 62116 SHEET NO. S-2 OF S-17 SHEETS ILLINOIS FED. AID PROJECT