

DRAINAGE STRUCTURE TABLE

DRAINAGE STRUCTURE TABLE

NO.	STATION	OFFSET	STRUCTURE TYPE					STR DIA (FT)	FRAME TYPE	RIM ELEV	INVERT N	INVERT S	INVERT W	INVERT E	INVERT	INVERT	NO.	STATION	OFFSET	STRUCTURE TYPE					STR DIA (FT)	FRAME TYPE	RIM ELEV	INVERT N	INVERT S	INVERT W	INVERT E	INVERT	INVERT
			JC'	MH	CB	INL	FLAT SLAB													Sump ²	JC'	MH	CB	INL									
100	10+52.68	31.88' RT		A				7	T1F CL	694.56			687.76 W		688.76NW	687.76 SE	213	22+10.00	12.0' LT					4	T11V F&G	690.20					685.20 E		
101	11+00.00	18.0' LT			A			4	T11V F&G	695.36			690.35 E				214	22+50.00	12.0' RT					4	T11V F&G	689.69				683.95 W			
102	11+00.00	18.0' RT			A			4	T11V F&G	695.36			690.35 W				216	22+75.00	18.0' RT					4	T11V F&G	688.91				684.70 W			
104	11+50.00	18.0' RT				B			T11V F&G	695.05	689.90 N						217	22+75.00	12.0' LT					4	T11V F&G	689.59	684.55 N			684.55 E			
105	11+50.00	18.0' LT				B			T11V F&G	695.05	690.05 N						218	24+00.00	12.0' RT					4	T11V F&G	690.80				685.80 W			
106	11+60.48	18.0' RT			A		x	4	T11V F&G	695.04		689.75 S	689.75 W	690.20 E			219	22+90.00	12.0' LT				B	4	T11V F&G	689.57		684.70 S					
107	11+60.48	18.0' LT			A			4	T11V F&G	695.04		689.90 S		689.90 E			220	24+78.70	12.0' RT				A	4	T11V F&G	692.71				687.70 W			
109	12+20.00	18.0' LT			A			4	T11V F&G	695.37				690.35 E			221	23+81.05	25.3' LT				B	4	T11V F&G	689.94					685.75NE		
110	12+65.00	18.0' RT			A			4	T11V F&G	696.05			691.05 W	691.05 E			222	19+80.00	33.6' RT				A	4	T8G	696.90				692.45 W			
111	12+65.00	18.0' LT			A			4	T11V F&G	696.05				691.05 E			223	24+00.00	13.7' LT				A	4	T11V F&G	690.77				685.55 E	685.55SW		
112	13+35.00	18.0' RT			A			4	T11V F&G	697.82			691.80 W		691.80 NE		224	21+80.00	35.7' RT				A	4	T8G	690.00					686.20SW		
113	13+35.00	18.0' LT			A		x	4	T11V F&G	697.82				693.25 E	693.25NW		225	24+78.70	12.0' LT				A	4	T11V F&G	692.71				688.50 W	687.90 E		
115	14+25.00	18.0' LT			A			6	T11V F&G	700.26				695.25 E	695.25 SW		226	25+50.00	32.7' RT				C	4	T8G	692.83				685.25 W			
117	14+00.00	37.4' LT				A			T8G	698.60					695.60NE		227	25+50.00	12.0' LT				A	4	T11V F&G	693.89				688.85 E			
118	14+75.00	33.3' RT				A			T8G	699.97					695.80SSW		228	18+75.00	34.4' RT				A	4	T8G	698.90				694.60 W			
119	15+50.00	36.4' LT				C			T8G	701.55				698.55 E			229	18+45.00	34.3' LT				C	4	T8G	699.30				696.00 E			
120	14+25.00	18.0' RT				A		4	T11V F&G	700.26			695.25 W		695.25 NNE		230	20+90.00	34.3' RT				A	4	T8G	692.20				688.30 W			
122	15+50.00	33.6' RT				C			T8G	700.72			698.45 W				231	20+60.00	34.0' LT				A	4	T8G	693.30	687.15 N						
124	11+60.48	37.1' RT				A			T8G	693.87			690.40 W				240	17+70.00	6.0' RT			A	4	T1F CL	702.33	695.20 N			697.00 W	695.75 E			
126	12+65.00	37.8' RT				A			T8G	681.50			691.50 W				242	18+75.00	6.0' RT			A	4	T1F CL	700.42	693.10 N	693.10 S	694.25 W	694.25 E				
128	10+75.00	18.9' RT		A (R)*				8	T1F CL	695.55					688.84NW	688.84 SE	244	19+80.00	6.0' RT			A	7	T1F CL	697.36	684.12 N	691.00 S	692.00 W	692.10 E				
130	11+00.00	6.0' RT		A				6	T1F CL	695.60	688.92 N		690.10 W	690.20 E	688.92 SE		246	20+90.00	6.0' RT			A	7	T1F CL	693.60	684.01 N	684.01 S	686.40 W	687.65 E				
132	11+60.48	6.0' RT		A				6	T1F CL	695.28	689.10 N	689.10 S	689.65 W	689.60 E			248	21+70.00	6.0' RT			A	7	T1F CL	691.13	683.93 N	683.93 S	685.80 W	685.40 E				
134	12+20.00	6.0' RT		A				6	T1F CL	695.61	689.28 N	689.28 S	690.10 W	690.20 E			250	22+75.00	6.0' RT			A	6	T1F CL	689.71	683.83 N	683.83 S	684.35 W	684.55 E				
136	12+65.00	6.0' RT		A				6	T1F CL	696.29	689.42 N	689.42 S	690.80 W	690.90 E			254	23+00.00	6.0' RT			A	7	T1F CL	689.70	683.80 N	283.80 S	686.39 W	683.80 E				
138	13+35.00	6.0' RT		A			x	5	T1F CL	698.06	689.63 N	689.63 S	693.00 W	691.65 E			256	23+00.00	18.0' RT			A (R)*	6	T1F CL	689.41				683.79 W	683.79 E			
140	14+25.00	6.0' RT		A				5	T1F CL	700.50	696.00 N	689.90 S	695.00 W	695.10 E			258	24+00.00	6.0' RT			A	7	T1F CL	690.92	683.90 N	683.90 S	685.35 W	685.70 E				
142	15+50.00	6.0' RT		A				5	T1F CL	702.60		697.00 S	698.10 W	698.15 E			260	24+78.70	6.0' RT			A	7	T1F CL	692.83	683.98 N	683.98 S	687.70 W	687.60 E				
201	17+70.00	12.0' LT			A			4	T11V F&G	702.21				697.20 E			262	25+50.00	6.0' RT			A	7	T1F CL	694.01		684.05 S	688.65 W	684.95 E				
202	17+70.00	12.0' RT			A			4	T11V F&G	702.21			695.85 W	695.85 E			264	23+04.15	219.1' RT			A	4	T1F CL	685.32	682.50 N	682.50 S	682.29 W	682.29 E				
203	18+75.00	12.0' LT			A			4	T11V F&G	700.30				694.45 E			301	27+50.00	12.0' LT			A	4	T11V F&G	693.55				688.55 E				
204	18+75.00	12.0' RT			A			4	T11V F&G	700.30			694.35 W	694.35 E			302	27+50.00	12.0' RT			A	4	T11V F&G	693.55				688.55 W				
205	19+80.00	12.0' LT			A			4	T11V F&G	697.24				692.20 E			303	28+25.00	29.7' LT			C	4	T8G	690.63				686.45 E				
206	19+80.00	12.0' RT			A			4	T11V F&G	697.24			692.20 W	692.20 E			304	29+30.00	12.0' RT			A	4	T11V F&G	689.22				684.20 W				
207	20+90.00	12.0' LT			A			4	T11V F&G	693.48			686.60 W	686.60 E			305	29+30.00	12.0' LT			A	4	T11V F&G	689.22				683.20 E	683.20NW			
208	20+90.00	12.0' RT			A			4	T11V F&G	693.48			687.75 W	688.05 E			306	30+35.00	12.0' RT			A	4	T11V F&G	686.38				681.35 W				
209	20+90.00	33.1' LT				B			T8G	691.04		686.85 S		686.85 E			307	30+85.00	12.0' LT			A	4	T11V F&G	685.21				678.95 W	678.95 E			
210	21+70.00	12.0' RT			A			4	T11V F&G	691.01			685.50 W		685.90NE		308	30+53.00	54.2' RT			A	4	T11V F&G	684.64	680.40 N				680.40SE			
211	21+70.00	12.0' LT			A			4	T11V F&G	691.01				686.00 E			309	31+55.00	12.0' LT			A	4	T11V F&G	684.21				679.20 E				
212	17+70.00	35.1' RT				A			T8G	700.30			696.10 W				310	30+42.80	93.2' RT			A	4	T8G	683.00					680.80NW			

A (R)* MANHOLE, TYPE A WITH RESTRICTOR REQUIRES TWO FRAMES AND LIDS
 JC' JUNCTION CHAMBER
 Sump² DISTANCE FROM INVERT OF OUTLET TO BOTTOM OF STRUCTURE (INCH)



REVISIONS	
NAME	DATE

VILLAGE OF VILLA PARK, ILLINOIS
DRAINAGE STRUCTURE SCHEDULE
SOUTH VILLA AVENUE
SHEET 1 OF 4

SCALE: NONE
 DATE: 11-NOV-2004
 DRAWN BY: E.D.
 CHECKED BY: J.T.G.