TRAFFIC SIGNAL LEGEND

DRAWN - BCK REVISED -			DEPARTMENT OF TRANSPORTATION			SCALE: NO	STANDARD TRAFFIC SIGNAL DESIGN DETAILS NE SHEET NO. 6 OF 6 SHEETS STA. TO STA	FED. ROAL	2010-133-I TS-05 DIST. NO. 1 ILLINOIS FE	WILL 54 CONTRACT NO. 60 D. AID PROJECT		
ILE NAME =	USER NAME = qureshiya	DESIGNED - DAG/BCK REVISED - DRAWN - BCK REVISED -			CTATE	STATE OF ILLINOIS			DISTRICT ONE	F.A.P. RTE.	SECTION	COUNTY TOTAL SHEETS
WIRELESS ACCESS POINT		R			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)		1	(1)	CROSSBUCK		<u></u> → 1	
WIRELESS DETECTOR SENSOR		1R(W) 1	W	W	ALL DETECTOR LOOP CABLE TO BE SHIELDED)=)		CROSSING GATE		202 >	X0 X -
PAN, TILT, ZOOM CAMERA		PZI	PIZM	PTZ	DENOTES NUMBER OF CONDUCTORS, ELECTRIC CABLE NO. 14, UNLESS NOTED OTHERWISE,		-5-		FLASHING SIGNAL		X0 X	X⊖X
		D			RADIO REPEATER	RERR	ERR	RR	RAILROAD CANTILEVER MAST ARM		XOX X X	XOX
IDEO DETECTION ZONE		r^.h		<u></u>	RADIO INTERCONNECT	## * 0	##+0	-	RAILROAD CONTROL CABINET			
IDEO DETECTION CAMERA		-R [V]1	<u> </u>	⊙		. D		★ D	DATE DOAD CONTROL CAPINET		EXISTING	PROPOSED
MICROWAVE VEHICLE SENSOR		R MD	M	M∎	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		(€) C (3 €) D	₽ C			EVICTING	DDODOCED
PREFORMED DETECTOR LOOP			P	P	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID		X	秀	RAILROAD	SYMBO	LS	
DETECTOR LOOP, TYPE I											<u>.</u>	
"NO RIGHT TURN"		R			12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETECTOR		. PS	PS
ILLUMINATED SIGN					12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		ÓW W		PREFORMED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR		PIS	PIS
ILLUMINATED SIGN "NO LEFT TURN"		R	•	9				"P"	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETE	CTOR	ÎPPÎ	
ACCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR		R APS	⊚APS	APS O O O O O O O O O O O O O			(P"	◆ Y ◆ G	EXISTING PREFORMED INTERSECTION LOOP DETECTOR			
PEDESTRIAN PUSHBUTTON DETECTOR		n (⊚)	(a)	©	"P" INDICATES PROGRAMMED HEAD			G	EXISTING INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETE	CTOR	(<u>P</u>)	
S DENOTES SOLAR POWER) PEDESTRIAN SIGNAL HEAD		-0	-1		SIGNAL FACE WITH BACKPLATE.		R	R	SAMPLING (SYSTEM) DETECTOR		[8]	S
		· ·					<u>E</u>		(SYSTEM) DETECTOR		IS	IS
FLASHER INSTALLATION		R O-D∕″F″	○-▷"F".	← —"F"			◆ ∀	∢ Y ∢ G	INTERSECTION & SAMPLING		, grand	
IGNAL HEAD OPTICALLY PROC		R >′′P′′		- ▶ "P"	SIGNAL FACE			G	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF O		
NUMBERS INDICATE THE CONS SIGNAL HEAD WITH BACKPLATE		R +▷	+(>>	+			R	R	AND POLE WITH LUMINAIRE AND FOUNDATION TO BE REMOVED	FUNE		
SIGNAL HEAD CONSTRUCTION S		-		2	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY	RMF		
SIGNAL HEAD		R -	>	-			R		ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
SUY WIRE	, IVI — IVI	R	>	>	ABANDON ITEM 12" (300mm) TRAFFIC SIGNAL SECTION	A	R	R	FOUNDATION TO BE REMOVED	0		
EMPORARY WOOD POLE (CLASS 5 OR ETTER) 45 FOOT (13.7m) MINIMUM		R⊗	\otimes	. •	RELOCATE ITEM	RL			STEEL MAST ARM POLE AND	RMF		
SIGNAL POST	Z CAMENA	R O	0	•	REMOVE ITEM	R			CONTROLLER CABINET AND FOUNDATION TO BE REMOVED	RCF		
STEEL COMBINATION MAST AR ASSEMBLY AND POLE WITH PT		P PTZ[j]	Q	PTZ	INTERSECTION ITEM		I	IP	(H) HANDHOLE, (P) POST, (M) MAST ARM, OR (S) SERVICE		Cull → o	^C ∥⊢•
STEEL COMBINATION MAST AR ASSEMBLY AND POLE WITH LU		^R O→X	0-14	• *	COILABLE NONMETALLIC CONDUIT (EMPTY) SYSTEM ITEM		S	CNC S	GROUND ROD AT (C) CONTROLLER,		C a	C.
ALUMINUM MAST ARM ASSEMBLY AND POLE		R			COMMON TRENCH			СТ	(NUMBER OF FIBERS & TYPE TO BE NOTED ON PLANS)			
TEEL MAST ARM ASSEMBLY AND POLE		R 0	0	• .	TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE	R			NO. 62.5/125, MM12F SM12F FIBER OPTIC CABLE NO. 62.5/125,			
TELEPHONE CONNECTION (P) POLE OR (G) GROUND MOUN	NT .	R	P	P	IN TRENCH (T) OR PUSHED (P)		Jacobs, volater Andreas, advals in Press, Sentence, a		FIBER OPTIC CABLE		—(24F)—	—(24F)—
SERVICE INSTALLATION, P) POLE OR (G) GROUND MOUN	VT		- <u>-</u> -	- P	JUNCTION BOX GALVANIZED STEEL CONDUIT				FIBER OPTIC CABLE NO. 62.5/125, MM12F		——————————————————————————————————————	
NINTERRUPTIBLE POWER SUPPLY		UPS	EUPS	UPS	DOUBLE HANDHOLE	R (0)			COPPER INTERCONNECT CABLE, NO. 18 3 PAIR TWISTED, SHIELDED		<u> </u>	6
MASTER MASTER CONTROLLER		R	[EMMC]	MMC	HEAVY DUTY HANDHOLE	H	Н	H	VENDOR CABLE FOR CAMERA			
MASTER CONTROLLER		CC "	EMC	MC	HANDHOLE							
RAILROAD CONTROL CABINET COMMUNICATIONS CABINET		R	æ æ Ecc	B ►√R C C	CONFIRMATION BEACON	R _{O()}	o - ()	•-•	COAXIAL CABLE			C
CONTROLLER CABINET		R			EMERGENCY VEHICLE LIGHT DETECTOR	, e	\bowtie	. ◄	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE			1
TEM					ITEM	R			ELECTRIC CARLE IN CONDUIT TRACER			