

**BEAM 5**

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abut.	1264+03.62	11.25	600.92	600.92
☉ S. Abut.	1264+04.91	11.25	600.93	600.93
A	1264+14.91	11.25	600.93	600.95
B	1264+24.91	11.25	600.94	600.98
C	1264+34.91	11.25	600.94	600.99
D	1264+44.91	11.25	600.95	600.99
E	1264+54.91	11.25	600.96	600.98
☉ S. Brg. Pier 1	1264+66.37	11.25	600.97	600.97
☉ Pier 1	1264+67.37	11.25	600.97	600.97
☉ N. Brg. Pier 1	1264+68.37	11.25	600.97	600.97
F	1264+78.37	11.25	600.97	601.00
G	1264+88.37	11.25	600.98	601.03
H	1264+98.37	11.25	600.99	601.05
I	1265+08.37	11.25	600.99	601.05
J	1265+18.37	11.25	601.00	601.04
K	1265+28.37	11.25	601.01	601.03
☉ S. Brg. Pier 2	1265+35.37	11.25	601.01	601.01
☉ Pier 2	1265+36.37	11.25	601.01	601.01
☉ N. Brg. Pier 2	1265+37.37	11.25	601.01	601.01
L	1265+47.37	11.25	601.01	601.03
M	1265+57.37	11.25	601.00	601.04
N	1265+67.37	11.25	600.99	601.03
O	1265+77.37	11.25	600.97	601.01
P	1265+87.37	11.25	600.94	600.97
☉ N. Abut.	1265+98.83	11.25	600.91	600.91
Bk. N. Abut.	1266+00.12	11.25	600.90	600.90

**BEAM 6**

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abut.	1264+01.61	18.75	600.77	600.77
☉ S. Abut.	1264+02.90	18.75	600.77	600.77
A	1264+12.90	18.75	600.78	600.80
B	1264+22.90	18.75	600.78	600.82
C	1264+32.90	18.75	600.79	600.84
D	1264+42.90	18.75	600.80	600.84
E	1264+52.90	18.75	600.80	600.83
☉ S. Brg. Pier 1	1264+64.36	18.75	600.81	600.81
☉ Pier 1	1264+65.36	18.75	600.81	600.81
☉ N. Brg. Pier 1	1264+66.36	18.75	600.81	600.81
F	1264+76.36	18.75	600.82	600.85
G	1264+86.36	18.75	600.83	600.88
H	1264+96.36	18.75	600.83	600.89
I	1265+06.36	18.75	600.84	600.90
J	1265+16.36	18.75	600.85	600.89
K	1265+26.36	18.75	600.85	600.87
☉ S. Brg. Pier 2	1265+33.36	18.75	600.86	600.86
☉ Pier 2	1265+34.36	18.75	600.86	600.86
☉ N. Brg. Pier 2	1265+35.36	18.75	600.86	600.86
L	1265+45.36	18.75	600.86	600.88
M	1265+55.36	18.75	600.85	600.89
N	1265+65.36	18.75	600.84	600.89
O	1265+75.36	18.75	600.82	600.86
P	1265+85.36	18.75	600.80	600.82
☉ N. Abut.	1265+96.82	18.75	600.76	600.76
Bk. N. Abut.	1265+98.11	18.75	600.76	600.76

11/22/2018 10:06:51 AM G:\ENR\08-0719-144\_02\_Bridges\_Phase 2\102\104\Structure\Sh.N\1717176\_64125\_0802\_TopSlab.Elev2.dgn



PLOT DATE = 11/22/2018

DESIGNED - MWS	REVISED -
CHECKED - JNH	REVISED -
DRAWN - MWS	REVISED -
CHECKED - BJM	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**TOP OF SLAB ELEVATIONS  
STRUCTURE NO. 037-0176**

SHEET NO. 9 OF 29 SHEETS

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
638	129BR-4	HENRY	93	30
CONTRACT NO. 64D25				
ILLINOIS FED. AID PROJECT				