| F.A.P. | SECTION | COUNTY | SHEETS | NO. | | TOTAL | SHEETS | NO. | TOTAL | S STA. N/A TO STA. N/A FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT CONTRACT NO. 70514 PR & SIX POINTS ROAD 2.4 m 2.45 m 2.45 m 2.4 m STEEL PLATE BEAM GUARDRAIL, TYPE A -PROFILE GRADE 1.5% (TYP.) - PORTLAND CEMENT CONCRETE SHOULDERS-150MM PORTLAND CEMENT
CONCRETE PAVEMENT 230MM (JOINTED) SUB-BASE GRANULAR MATERIAL, TYPE A 300MM 7) PROPOSED TYPICAL SECTION SIX POINTS ROAD STA. 0+635.000 TO STA. 0+673.930 HMA = HOT MIX ASPHALT PR & SIX POINTS ROAD 2.4 m 2.45 m 2.45 m STEEL PLATE BEAM GUARDRAIL, TYPE A -- PROFILE GRADE 1.5% VAR. 150--(TYP.) - HMA SHOULDER, 200MM HMA SHOULDER, 200MM POLYMER HMA CONCRETE SURFACE COURSE, 600 ---MIX "E", N90, (90,82 Kg/sq m) POLYMER HMA CONCRETE BINDER COURSE, IL-19.0, N90, (136.23 Kg/sq m) ILLINOIS DEPARTMENT OF TRANSPORTATION • SEE CROSS SECTIONS FOR GORE AREA -HMA BASE COURSE, 290MM PROPOSED TYPICAL SECTIONS (8) PROPOSED TYPICAL SECTION SIX POINTS ROAD - SUB-BASE GRANULAR MATERIAL, SIX POINTS ROAD SHEET 4 OF 4 TYPE A 300MM ALL DIMENSIONS ARE IN MM UNLESS OTHERWISE NOTED. STA. 0+673.930 TO STA. 0+693.159 DATE 05-27-09 CHECKED BY PMH SIX POINTS ROAD, PROPOSED TYPICAL SECTIONS