

BILL OF MATERIALS ITEM HANDHOLE HEAVY-DUTY HANDHOLE DOUBLE HANDHOLE FULL-ACTUATED CONTROLLER AND TYPE IV CABINET, SPECIAL TRANSCEIVER - FIBER OPTIC TRAFFIC SIGNAL BACKPLATE, LOUVERED, FORMED PLASTIC INDUCTIVE LOOP DETECTOR PEDESTRIAN PUSH-BUTTON TEMPORARY TRAFFIC SIGNAL INSTALLATION REMOVE EXISTING HANDHOLE REMOVE EXISTING CONCRETE FOUNDATION REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT SIGN PANEL TYPE I SIGN PANEL TYPE II CONDUIT IN TRENCH, 50MM DIA., PVC CONDUIT IN TRENCH, 65MM DIA., PVC CONDUIT IN TRENCH, 100MM DIA. PVC CONDUIT PUSHED, SOMM DIA., GALVANIZED STEEL CONDUIT PUSHED, 75MM DIA., GALVANIZED STEEL CONDUIT PUSHED, 100MM DIA., GALVANIZED STEEL TRENCH AND BACKFILL FOR ELECTRICAL WORK ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 30 ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 50 ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 70 ELECTRIC CABLE IN CONDUIT, LEAD-IN, NO. 14 1 PAIR ELECTRIC CABLE IN CONDUIT, SERVICE, NO. 6 2 C TRAFFIC SIGNAL POST, GALVANIZED STEEL 3.65 METER TRAFFIC SIGNAL POST, GALVANIZED STEEL 4.85 METER STEEL COMBINATION MAST ARM ASSEMBLY AND POLE, 11.58 METER STEEL COMBINATION MAST ARM ASSEMBLY AND POLE, 12.80 METER STEEL COMBINATION MAST ARM ASSEMBLY AND POLE, 13.41 METER 12" (300mm) PEDESTRIAN SIGNAL SECTION CONCRETE FOUNDATION. TYPE A CONCRETE FOUNDATION, TYPE D CONCRETE FOUNDATION, TYPE E, 600MM DIAMETER CONCRETE FOUNDATION, TYPE E, 750MM DIAMETER DETECTOR LOOP, TYPE I ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C FIBER OPTIC CABLE IN CONDUIT, NO. 62.5/125 MM12F & SM12F ELECTRIC CABLE IN CONDUIT, GROUNDING NO. 6 1C SERVICE INSTALLATION. TYPE A LIGHT POLE, WOOD, 10.67 M, CLASS 3 SIGNAL HEAD, LED, 1-FACE, 3-SECTION, MAST ARM MOUNTED SIGNAL HEAD, LED, 1-FACE, 3-SECTION, BRACKET MOUNTED SIGNAL HEAD, LED, 1-FACE, 5-SECTION, MAST ARM MOUNTED SIGNAL HEAD, LED, 1-FACE, 4-SECTION, MAST ARM MOUNTED SIGNAL HEAD, LED, 2-FACE, 1-3 SECTION, 1-5 SECTION, BRACKET MOUNTED SIGNAL HEAD, LED. 2-FACE, 3-SECTION, BRACKET MOUNTED LIGHT DETECTOR LIGHT DETECTOR AMPLIFIER ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 20 3C TWISTED SHIELDED PEDESTRIAN SIGNAL HEAD, LED, 1-FACE, BRACKET MOUNTED W/CDT STEEL MAST ARM ASSEMBLY AND POLE. 6.09 METER

\*\* 100% COST TO CITY OF BLOOMINGTON FIRE DEPARTMENT

MORRIS AVENUE & SIX POINT ROAD SCHEDULE OF QUANTITIES. CABLE PLAN AND PHASE DESIGNATION DIAGRAM DRAWN BY: RV DESIGNED BY: AS CHECKED BY: MSA SCALE: NONE

DATE: MARCH, 2009

AMES Engineering, Inc. Consulting Engineers 1341 Warren Avenue Downers Grove, IL 60515

-5--2-SIX POINT RD. OL A 99 PHASE DESIGNATION DIAGRAM PHASE LETTER 3 Α ≃

NOTE: LIGHTING CABLE SHALL CONSIST OF 2-#6 (XLP-TYPE USE) 1-#8 (XLP-TYPE USE) AND SHALL BE INSTALLED IN THE SEPARATE LIGHTING CONDUIT AS SHOWN ON THE PLAN SHEET. SEE BILL OF MATERIALS FOR LIGHTING.

2-#6; 1-#8 (TYP)

6 4 2 5

- 2 × 30mm

65 mm 74 x 5c

(7)

1 x 7c

1 × 3c 8 × 2c

100 mm 3 x 5c

CABLE PLAN

NOT TO SCALE

1 x 7c

2 x 2c

1 x 5c

4 x 5c 75 mm 6 x 2c

50 mm 2 x 3c

2 x 30mm

R Y

G

Ç ≺ P

11 x 7c

1 x 2c

3×30mm

3x30mm

CABLE PLAN LEGEND:

CONTROLLER

MANDHOLE.

- SERVICE INSTALLATION

H HEAVY DUTY HANDHOLE

DOUBLE HANDHOLE

× 30mm O MAST ARM OR SIGNAL POST

R RED BALL SECTION

CONDUIT SIZE

50 mm 3 x 2c

YELLOW LEFT TURN ARROW

SIGNAL HEAD BACKPLATE

---(5)--- NUMBER OF CONDUCTORS IN CABLE

- NUMBER OF CABLES IN CONDUIT

IN EACH CABLE

PEDESTRIAN PUSHBUTTON

EMERGENCY VEHICLE LIGHT

DETECTOR LOOP

DETECTOR

- NUMBER OF CONDUCTORS

65 mm 1 x 5c 1 x 3c

LEGEND: - DUAL ENTRY PHASE - SINGLE ENTRY PHASE PEDESTRIAN PHASE OL OVERLAP • NUMBER REFERS TO ASSOCIATED PHASE REFER TO STANDARD EASTBOUND AND WESTBOUND SHALL BE SPLIT PHASED

2 x 5c

1 x 3c 1 x 2c 65 mm

2 x 2c 50 mm

**\$7** 4\$ 3

-(5)-- (c > ∪

- O - 2 > 0 9

1 × 7c 65 mm

2 x 5c

3 x 7c

3 x 3c 100 mm

-1 × 30mm 26 × 2c

( 0 7 7 8 4 7 9

50 mm 2 × 5c

50 mm 1 × 2c (#6)

3 x 7c

SIX POINT RD