

| PAVEMENT MARKING SCHEDULE | | | |
|---------------------------|-----------|----------------------|-----------|
| STATION | TYPE | PAINT PVT MK LINE 5" | |
| | | WHITE | YELLOW |
| LT & RT 66+50 TO 88+32 | EDGE LINE | 4,364 FT | |
| RT 66+50 TO 68+16 | NO PASS | | 166 FT |
| LT 66+50 TO 75+74 | NO PASS | | 924 FT |
| RT 78+90 TO 88+32 | NO PASS | | 942 FT |
| 68+16 TO 88+32 | SKIP DASH | | 510 FT |
| | | | |
| LT & RT 134+63 TO 191+57 | EDGE LINE | 11,388 FT | |
| LT 134+63 TO 144+78 | NO PASS | | 1,015 FT |
| RT 164+60 TO 191+57 | NO PASS | | 2,697 FT |
| LT 174+70 TO 191+57 | NO PASS | | 1,687 FT |
| 134+63 TO 174+70 | SKIP DASH | | 1,000 FT |
| LT & RT 191+57 TO 197+50 | NO PASS | | 1,194 FT |
| | | | |
| | | | |
| TOTALS | | 15,752 FT | 10,135 FT |

| CONCRETE GUTTER, TYPE A | | | | |
|-------------------------|--------------------------|------------|-----------|-------------------------|
| STATION | CLASS SI CONCRETE OUTLET | | | CLASS SI GUTTER, TYPE A |
| | INLET | ENTRANCE | OUTLET | |
| RT 80+50 TO 80+86 | | | 6.8 CU YD | |
| RT 80+86 TO 82+85 | | | | 199 FT |
| RT 82+85 TO 83+15 | | 5.0 CU YD | | |
| RT 83+15 TO 86+03 | | | | 288 FT |
| RT 86+03 TO 86+15 | 0.9 CU YD | | | |
| | | | | |
| | | | | |
| TOTALS | | 12.7 CU YD | | 487 FT |

| HOT-MIX ASPHALT SHOULDERS, 8" | |
|-------------------------------|-----------|
| STATION | |
| RT 80+00 TO 86+15 | 137 SQ YD |
| | |
| | |
| TOTALS | 170.0 TON |

| SAW CUTS | |
|-------------------|------------|
| STATION | |
| RT 80+00 TO 86+15 | 615 LIN FT |
| | |
| | |
| TOTALS | 615 LIN FT |

| AGGREGATE SHOULDERS, TYPE B | |
|-----------------------------|-----------|
| STATION | |
| LT & RT 66+50 TO 74+50 | 30.3 TON |
| LT 79+00 TO 82+50 | 6.6 TON |
| RT 70+00 TO 80+00 | 1.9 TON |
| LT & RT 143+85 TO 171+75 | 105.8 TON |
| LT 176+50 TO 183+44 | 13.2 TON |
| RT 177+32 TO 183+44 | 11.6 TON |
| | |
| | |
| TOTALS | 170.0 TON |

| MIXTURE REQUIREMENTS | | | |
|--|------------------------|----------------------|----------------------|
| THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT | | | |
| MIXTURE USE(S): | H.M.A S.C., MIX C, N50 | PAVEMENT PATCHING | H.M.A SHOULDERS, 8" |
| AC/PG | PG 64-22 | PG 64-22 | PG 58-22 |
| DESIGN AIR VOIDS: | 4.0% @ N DESIGN = 50 | 4.0% @ N DESIGN = 50 | 2.0% @ N DESIGN = 30 |
| MIXTURE COMP: | IL 9.5 OR 12.5 | IL 19.0 | IL 19.0 |
| FRICITION AGG: | MIX "C" | N/A | N/A |

NOTES:
STATIONS ARE APPROXIMATE.

SCHEDULES
SBI 96 (WARSAW SPUR)
SECTION 123 RS-6
HANCOCK COUNTY