

**GENERAL NOTES**

- FOR STABILIZATION, ALL TYPE III BARRICADES SHALL REQUIRE A MINIMUM OF FOUR SANDBAGS PER BARRICADE.
- WHERE SECTION OR SUBSECTION MONUMENTS ARE ENCOUNTERED, THE ENGINEER SHALL BE NOTIFIED BEFORE SUCH MONUMENTS ARE REMOVED. THE CONTRACTOR SHALL PROTECT AND CAREFULLY PRESERVE ALL MONUMENTS UNTIL AN AUTHORIZED SURVEYOR OR AGENT HAS WITNESSED OR OTHERWISE REFERENCED THEIR LOCATION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR HAVING AN AUTHORIZED SURVEYOR REESTABLISH ANY SECTION OR SUBSECTION MONUMENTS DESTROYED BY HIS/HER OPERATIONS.
- THE FOLLOWING RATES OF APPLICATION HAVE BEEN USED TO CALCULATE THE PLAN QUANTITIES:
 

AGG WEDGE SHOULDERS	1.60 TONS / CU YD
BITUMINOUS MATERIALS (PRIME COAT)	0.05 LBS / SQ FT (MILLED/AGED)
	0.025 LBS / SQ FT (FOG COAT BTW LIFTS)
	0.25 LBS / SQ FT (AGG BASE)
HMA RESURFACING	112 LBS / SQ YD / IN
SHORT TERM PAVEMENT MARKING	4 FT / 40 FT OF APPLICATION
AGG BASE COURSE, TYPE A	2.05 TONS / CU YD
- THE CONTRACTOR SHALL NOTIFY THE DISTRICT 6 BUREAU OF OPERATIONS THREE WEEKS PRIOR TO IMPLEMENTING ANY TRAFFIC CONTROL.

**INDEX OF SHEETS**

- COVER SHEET
- GENERAL NOTES
- 3-4 SUMMARY OF QUANTITIES
- TYPICAL SECTION
- 6-8 SCHEDULES OF QUANTITIES
- 9-16 PLANS
- MORRISONVILLE INTERSECTION WITH DETAIL
- TRAFFIC SIGNING DETAIL

**COMMITMENTS**

NONE

**HIGHWAY STANDARDS**

- 000001-08 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
- 001006 DECIMAL OF AN INCH AND OF A FOOT
- 442201-03 CLASS C AND D PATCHES
- 701001-02 OFF-ROAD OPERATIONS, 2L, 2W, MORE THAN 15' (4.5m) AWAY
- 701006-05 OFF-ROAD OPERATIONS, 2L, 2W, 15' (4.5m) TO 24" (600mm) FROM PAVEMENT EDGE
- 701201-05 LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS >= 45 MPH
- 701301-04 LANE CLOSURE, 2L, 2W, SHORT SHORT TIME OPERATIONS
- 701306-04 LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS, DAY ONLY, FOR SPEEDS >= 45 MPH
- 701311-03 LANE CLOSURE, 2L, 2W, MOVING OPERATIONS, DAY ONLY
- 701901-08 TRAFFIC CONTROL DEVICES
- 780001-05 TYPICAL PAVEMENT MARKINGS
- BLR 21-9 TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES FOR CONSTRUCTION ON RURAL LOCAL HIGHWAYS

**MIXTURE TABLES**

	HMA BINDER COURSE	HMA SURFACE COURSE	PATCHING	INCIDENTAL HMA
Mixture Use(S):	HMA BINDER COURSE	HMA SURFACE COURSE	PATCHING	INCIDENTAL HMA
PG Grade:	PG 64-22	PG 64-22	PG 64-22	PG 64-22
Design Air Voids:	4.0% @ N50	4.0% @ N50	4.0% @ N50	4.0% @ N50
Mixture Composition:	IL-9.5FG	IL-9.5	IL-9.5	IL-9.5
Friction Aggregate:	N/A	Mix "C"	Mix "C"	Mix "C"
Quality Management:	QCP	QCP	QC/QA	QC/QA
Mixture Sublot Size:	1000 TONS	1000 TONS	N/A	N/A
Material Transfer Device:	No	Yes	No	No

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
DISTRICT 6**

---

EXAMINED October 4 2021  
*[Signature]*  
ENGINEER OF OPERATIONS

---

EXAMINED October 7 2021  
*[Signature]*  
ENGINEER OF PROJECT IMPLEMENTATION

---

EXAMINED October 7 2021  
*[Signature]*  
ENGINEER OF PROGRAM DEVELOPMENT

△ REVISED 1-4-2022  
REV. - MS

MODEL: D:\default...  
FILE: M:\...  
PROJECT: ...