

SCHEDULE OF PARTIAL DEPTH PATCHING (CONT'D)

STATION	DIRECTION	LENGTH (FOOT)	WIDTH (FOOT)	PARTIAL DEPTH REMOVAL	PARTIAL DEPTH PATCHING
				8 1/2" 44022051 (SQ YD)	X4421000 (TONS)
340+35.00	WB	10	12	13.3	6.3
341+13.00	WB	10	12	13.3	6.3
341+45.00	EB	10	12	13.3	6.3
341+96.00	EB	20	12	26.7	12.7
341+96.00	WB	20	12	26.7	12.7
342+68.00	EB	20	12	26.7	12.7
347+45.00	EB	6	12	8.0	3.8
347+45.00	WB	6	12	8.0	3.8
347+74.00	EB	6	12	8.0	3.8
348+47.00	EB	6	12	8.0	3.8
348+47.00	WB	6	12	8.0	3.8
350+46.00	EB	6	12	8.0	3.8
350+46.00	WB	6	12	8.0	3.8
350+95.00	WB	6	12	8.0	3.8
354+43.00	EB	15	12	20.0	9.5
354+43.00	WB	15	12	20.0	9.5
364+50.00	EB	20	12	26.7	12.7
365+50.00	WB	20	12	26.7	12.7
365+06.00	WB	20	12	26.7	12.7
365+81.00	WB	6	12	8.0	3.8
366+41.00	WB	15	12	20.0	9.5
371+44.00	EB	15	12	20.0	9.5
371+44.00	WB	15	12	20.0	9.5
372+04.00	EB	25	12	33.3	15.9
372+04.00	WB	25	12	33.3	15.9
373+01.00	WB	6	12	8.0	3.8
378+49.00	EB	10	12	13.3	6.3
378+49.00	WB	10	12	13.3	6.3
389+62.00	WB	8	12	10.7	5.1
390+12.00	EB	15	12	20.0	9.5
SUB-TOTAL =				504.0	239.9